

ACN 143 194 165 Level 2, 22 Mount Street, Perth, WA 6000 PO Box 7054, Cloisters Square, Perth, WA 6850 Ph: (08) 6188 8181 Fax: (08) 6188 8182 ragusaminerals.com.au

21st November 2022 ASX ANNOUNCEMENT

NT LITHIUM PROJECT UPDATE

PHASE 1 EXPLORATION DRILLING PROGRAM COMPLETED

HIGHLIGHTS

- Phase 1 exploration drilling program completed identifying significant pegmatite intercepts from geological logging works
- Select pegmatite drill samples delivered to laboratory for lithium analysis testing
- Pegmatite intercepted in 12 out of 18 drillholes

Ragusa Minerals Limited (ASX: **RAS**) ("**Ragusa**" or "**Company**") is pleased to advise that it has recently completed its first phase exploration drilling program at the Company's NT Lithium Project ("**Project**") – located in the highly prospective Litchfield Pegmatite Belt in Northern Territory, approximately 120km south of Darwin.

The Company completed a total of 18 reverse circulation drillholes comprising a total of 1505 metres drilled – with 12 drillholes intersecting pegmatite. From the geological logging works conducted on site, a total of 226 drill samples were selected for laboratory analysis testing.

Ragusa Chair, Jerko Zuvela said "The Company is pleased to have conducted our maiden exploration drilling program at our strategic and highly prospective NT Lithium Project. We are very encouraged by the preliminary drilling observations at our priority targets, noting the scale of the pegmatite zones encountered within our project area. We look forward to receiving the lithium assay results in coming weeks.

The completion of the initial exploration program is another positive step that puts Ragusa in a strong position to rapidly accelerate the development of our project within a proven high-quality lithium district in a Tier 1 jurisdiction close to major infrastructure at a time of record lithium prices."

Whilst the Company awaits the lithium sample assay results from the laboratory, the Company's geological staff identified additional samples containing visually significant levels of graphite in the hangingwall and footwall zones either side of some of the pegmatites. The Company will further review these samples prior to compiling and considering for laboratory analysis testing.

Due to some targeted drill sites not being accessible during the phase 1 works program, the Company is preparing the remaining priority sites for drilling works during the next dry season. The Company will also consider conducting diamond drilling operations (subject to drill rig access).

The Company will also consider conducting geophysical surveying works in the priority target areas to assist with planning the next phase exploration drilling works.

The maiden exploration drilling program targeted lithium bearing pegmatites beneath the weathering profile (evident at the Core Lithium Project located to the north). Upon receipt of all drill sample results,

ASX RAS

HOLE_ID	EASTING	NORTHING	AZIMUTH	DIP	TOTAL DEPTH (m)	PEG (m) (from)	PEG (m) (to)
22RC01	694991	8508396	91	-60	90		
22RC07	692595	8507643	65	-60	66	16	43
22RC08	692620	8507647	65	-60	19	0	19
22RC09	693268	8504768	61	-85	60	13	15
22RC016	692063	8504051	72	-60	78	44	57
22RC017	693160	8502073	64	-72	96	69	88
22RC018	692500	8502662	64	-70	120		
22RC023	692562	8507623	62	-60	114		
22RC024	693412	8504560	255	-55	64	49	64
22RC025	693426	8504562	254	-65	138	120	132
22RC026	692717	8502590	243	-65	150	74	93
22RC027	692117	8504178	250	-60	162		
22RC028	692050	8504050	72	-74	24		
22RC029	692728	8507662	265	-60	108	15	21
22RC030	692671	8507651	251	-60	120	1	17
22RC031	693285	8504773	61	-60	36	14	27
22RC032	691757	8504833	243	-60	30		
22RC033	691758	8504840	41	-60	30	3	19

and in combination with other geological data gained, the Company will review all data to determine if an exploration target (or targets) can be delineated (subject to analysis results).

Table 1. NT Lithium Project – Drillhole Details



Figure 1. NT Lithium Project – Drillhole Location Map

ASX RAS



Figure 2. NT "Supergroup" Lithium Project Location

ENDS

This announcement has been authorised by Jerko Zuvela, the Company's Chair

For more information on Ragusa Minerals Limited and to subscribe for regular updates, please visit our website <u>www.ragusaminerals.com.au</u> or contact us at <u>admin@ragusaminerals.com.au</u> or Twitter <u>@Ragusa_Minerals</u>.

For further information:

Jerko Zuvela Chair

T | +61 8 6188 8181
E | admin@ragusaminerals.com.au
W | www.ragusaminerals.com.au

Ragusa confirms that it is not aware of any new information or data that materially affects the information included in the original market announcement and, in the case of Mineral Resources or Ore Reserves, that all material assumptions and technical parameters underpinning the estimates in the relevant market announcement continue to apply and have not materially changed. Ragusa confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcement.

Forward Looking Statements: Statements regarding plans with respect to the Company's mineral properties are forward looking statements. There can be no assurance that the Company's plans for development of its mineral properties will proceed as expected. There can be no assurance that the Company will be able to confirm the presence of mineral deposits, that any mineralisation will prove to be economic or that a mine will successfully be developed on any of the Company's mineral properties.

Competent Person's Statement

The information contained in this ASX release relating to Exploration Results has been reviewed by Mr Olaf Frederickson. Mr Frederickson is a Member of the Australasian Institute of Mining and Metallurgy and has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Mr Frederickson is an Executive Director of Ragusa Minerals Ltd and consents to the inclusion in this announcement of this information in the form and context in which it appears.

ABOUT RAGUSA MINERALS LIMITED

Ragusa Minerals Limited (ASX: RAS) is an Australian company with an interest in the following projects – NT Lithium Project (including Litchfield and Daly River Lithium Projects) in Northern Territory, Monte Cristo Gold Project in Alaska, Burracoppin Halloysite Project in Western Australia, and Lonely Mine Gold Project in Zimbabwe.

The Company has an experienced board and management team with a history of exploration, operational and corporate success.

Ragusa leverages the team's energy, technical and commercial acumen to execute the Company's mission - to maximize shareholder value through focussed, data-driven, risk-weighted exploration and development of our assets.

JORC Code, 2012 Edition – Table 1 report template

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine 	 RC chip sampling every 1m downhole. Entire sample collected from base of cyclone into a green plastic bag with a 2kg split diverted from cyclone underflow to a calico sample bag for assay.

ASX RAS

Criteria	JORC Code explanation	Commentary
	nodules) may warrant disclosure of detailed information.	
Drilling techniques	 Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- sampling bit or other type, whether core is oriented and if so, by what method, etc). 	RC drilling with face sampling bit.
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	All sample collected from cyclone underflow.
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	Chip samples logged on 1m intervals.
Sub- sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled 	 No sub sampling or sample preparation completed.
Quality of assay data and laboratory	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. 	No assay results received as yet.

ASX RAS

Criteria	JORC Code explanation	Commentary
tests	 For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	• N/A
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 Drill collars located with handheld GPS. Down-hole single shot camera used for downhole surveys every 30m.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 Reconnaissance drilling with single holes testing pegmatite fertility. Data not suitable for resource estimation in its own right.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	 Drillholes are not necessarily perpendicular to the mineralized body. True thickness not known at this stage.
Sample security	The measures taken to ensure sample security.	Samples collected by geologist and delivered directly to lab for assay
Audits or reviews	 The results of any audits or reviews of sampling techniques and data. 	No audits.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 NT Lithium Project held by May Drilling Pty Ltd under group reporting status, with label of GR370 Individual tenements are: EL30521, EL28462, EL29731, EL32671 All tenements are granted and in good standing. Ragusa has the right to enter into joint venture agreement over the tenure package to earn an initial 90% with expenditure in the ground and up to 100% with some additional conditions.
Exploration done by other parties	 Acknowledgment and appraisal of exploration by other parties. 	 Prior exploration limited to chip sampling, soil sampling and geophysics was conducted by PNX Metals and Monax. May Drilling has completed 5 RC drillholes and 4 diamond drillholes since grant of tenure.
Geology	 Deposit type, geological setting and style of mineralisation. 	 Pegmatite intrusions into a pelitic metasedimentary host.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	Drillhole locations included in table within body of announcement.
Data aggregatio n methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. 	 No data aggregation methods used.
	Where aggregate intercepts incorporate	

ASX RAS

Criteria	JORC Code explanation	Commentary
	 short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	
Relationshi p between mineralisati on widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	 Intercepts are not true width. Not enough information obtained to establish true widths.
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	 Plan of drillhole locations within body of announcement.
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	All information reported.
Other substantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	• N/A
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 Phase 1 drilling program completed. Diamond drilling works to be determined. Possible geophysical surveying for future targeting.