



[www.kglresources.com.au](http://www.kglresources.com.au)

17 November 2014

## Further Jervois Drilling Results

### Highlights

More high-grade intersections have been generated by the in-fill and extensional resource drilling at Jervois.

Mineralisation intercepted at Reward includes:

- 4m @ 3.87% Cu, 30.6g/t Ag, 0.66g/t Au from 10 m (RC Hole JOC265)

In-fill drilling at Bellbird continues to intercept good copper grades including:

- 9m @ 3.36% Cu, 17.9g/t Ag, 0.16g/t Au from 89 m (RC Hole JOC182)

At the Central Bellbird area good grades of both gold and copper continue to be intercepted:

- 3m @ 1.52% Cu, 9.7g/t Ag, 0.56g/t Au from 20 m and  
3m @ 6.05% Cu, 24.7g/t Ag, 2.09g/t Au from 24 m (RC Hole JOC287)
- 5m @ 2.65% Cu, 20.6g/t Ag, 0.57g/t Au from 37 m (RC Hole JOC288)

Drilling at Green Parrot continues to intersect zones of high-grade mineralisation:

- 2m @ 4.79% Cu, 2.09% Pb, 4.14% Zn, 125.4g/t Ag, 0.05g/t Au from 68 m (RC Hole JOC221)
- 3m @ 2.31% Cu, 8.61% Pb, 1.72% Zn, 159.3g/t Ag, 0.05g/t Au from 99 m (RC Hole JOC222)
- 1m @ 4.9% Cu, 2.32% Pb, 0.46% Zn, 387g/t Ag, 0.02g/t Au from 127 m (RC Hole JOC223)

At Morley significant results include:

- 7m @ 1.24% Cu, 27.1g/t Ag, 0.09g/t Au from 46 m and  
4m @ 1.64% Cu, 12.7g/t Ag, 0.07g/t Au from 59 m (RC hole JOC195)
- 2m @ 1.93% Cu, 14.5g/t Ag, 0.03g/t Au from 64 m (RC Hole JOC196)

RC Drilling has now concluded for this field season. It is anticipated that assay results from the remainder of the RC drilling will be received and announced over the next few weeks.

Diamond drilling to enable further metallurgical test-work on the shallow transitional material is planned to commence later this week. This program consists of 8 PQ holes into Marshall, Reward, Green Parrot and Bellbird to help further optimise recoveries from the transition zone material.

## **Background**

In May-June 2014 KGL completed a 177 hole reverse circulation program at Jervois for 9,653m. The drilling program was designed to improve delineation of shallow mineralisation and to improve interpretation of the oxidation boundaries within the regolith profile prior to a resource update. The new resource was subsequently used for a pit optimisation that forms part of the preliminary feasibility study. The drilling returned high-grade shallow copper intersections that were better than anticipated because of supergene enrichment at the base of oxidation. Following the pit optimisation the current phase of shallow drilling was designed with the aim of converting all Inferred resources within the Marshall-Reward, Bellbird and Morley pits to the Indicated category and test for extensions beyond the pit designs.




Figure 1 Green Parrot Cross-Section




Figure 2 Bellbird Cross-Section




Figure 3 Plan of Jervois tenement and drill hole collar locations




Figure 4 Plan of Jervois tenement and drill hole collar locations




Figure 5 Plan of drilling at Bellbird




Figure 6 Plan of drilling at Marshall, Reward and Morley

Table 1 Table of significant results

Hole ID	Easting (m)	Northing (m)	RL (m)	Dip	Azimuth	BOX <sup>4</sup> (m)	Total Depth (m)	From (m)	To (m)	Interval (m)	ETW <sup>2</sup> (m)	Cu %	Pb %	Zn %	Ag g/t	Au g/t
JOC182	627331	7490679	363	-56	267	37	114	35	37	2	1.7	1.05	0.01	0.02	7.6	0.03
								45	46	1	0.9	1.83	0	0.02	5.3	0.04
								48	49	1	0.9	1.19	0.01	0.02	2.2	0.04
								66	72	6	5.3	1.04	0.01	0.02	4	0.09
								74	75	1	0.9	0.66	0	0.02	0.9	0.03
								86	88	2	1.8	0.63	0	0.02	2.9	0.03
								89	98	9	8.2	3.36	0.04	0.03	17.9	0.16
JOC195	630519	7495640	362	-61	88	38	90	37	40	3	1.6	0.55	0.01	1.68	7.3	0.04
								46	53	7	3.6	1.24	0.08	0.1	27.1	0.09
								54	55	1	0.5	0.59	0.01	0.05	1.8	0.02
								59	63	4	2.1	1.64	0.01	0.04	12.7	0.07
JOC196	630511	7495560	358	-61	87	33	115	64	66	2	1.2	1.93	0.05	0.02	14.5	0.03
								69	70	1	0.6	0.69	0.01	0.03	5.2	0.03
JOC197	630692	7495675	364	-58	97	-	12	1	2	1	0.5	1.26	0	0.01	0.7	0.02
JOC199	630529	7495480	357	-61	89	15	60	30	31	1	0.5	0.97	0	0.03	3.6	0.03
								41	42	1	0.5	0.5	0	0.05	2.8	0.01
								43	44	1	0.5	3.67	0.02	0.07	16.5	0.05
JOC200	630511	7495480	356	-62	90	27	95	58	59	1	0.6	0.58	0	0.02	1.2	0.02
JOC201	630491	7495480	355	-61	91	50	130	83	84	1	0.7	0.58	0	0.02	1.7	0.01
JOC203	630539	7495391	358	-46	90	20	36	6	7	1	0.8	1.05	0	0.05	1.1	0.01
JOC214	630273	7494480	361	-60	92	47	54	31	32	1	0.6	0.56	0.41	0.45	7.6	0.01
JOC215	630128	7494019	354	-66	83	1	132	94	95	1	0.4	0.49	0.36	0.26	28.2	0.01
								106	107	1	0.4	0.85	0.1	0.15	67.3	0.01
JOC216	630067	7493700	347	-62	87	5	198	166	169	3	1.5	0.45	0.1	3.04	34.9	0.27
								176	177	1	0.5	1.03	0.06	0.08	72.7	0.43
								178	179	1	0.5	1.02	0.15	0.24	81	0.49
JOC217	630100	7493620	345	-56	89	2	138	65	66	1	0.6	0	0.07	2.9	2.5	0.01
								78	80	2	1.2	0.54	1.36	0.66	58	0.12

Hole ID	Easting (m)	Northing (m)	RL (m)	Dip	Azimuth	BOX <sup>1</sup> (m)	Total Depth (m)	From (m)	To (m)	Interval (m)	ETW <sup>2</sup> (m)	Cu %	Pb %	Zn %	Ag g/t	Au g/t
JOC219	630209	7493850	351	-70	272	28	84	19	21	2	0.7	0.02	0.01	1.51	1.2	0
								58	60	2	0.8	0.53	0.57	0.1	32.6	0.29
JOC220	630155	7493898	345	-51	90	3	96	26	30	4	2.5	1.06	0	0.2	60.5	0.25
								61	64	3	1.9	1.33	15.15	11.71	551.3	0.07
								64	66	2	1.3	0.07	0.86	0.56	31.1	0.01
JOC221	630154	7493898	344	-66	88	1	126	32	33	1	0.4	0.32	1.53	0.7	41.7	0.02
								68	70	2	0.7	4.79	2.09	4.14	125.4	0.05
JOC222	630145	7493849	345	-62	88	11	132	99	102	3	1.5	2.31	8.61	1.72	159.3	0.05
								102	104	2	1.0	0.54	1.6	0.57	36.4	0.01
JOC223	630105	7493860	349	-55	91	1	150	127	128	1	0.6	4.9	2.32	0.46	387	0.02
								128	132	4	2.5	0.66	0.64	0.46	54.8	0.02
JOC224	629893	7492715	338	-51	109	>36	36	3	4	1	0.6	0.61	0.01	0.02	1.3	0.02
JOC233	627667	7490345	375	-72	235	50	66	50	54	4	1.6	0.03	0.02	1.86	0	0
JOC234	627629	7490366	377	-74	223	39	60	43	45	2	0.7	1.07	0.29	2.87	17.4	0.02
JOC252	630529	7495560	358	-62	89	20	60	3	4	1	0.6	1.06	0	0.05	0.9	0.03
JOC254	630520	7495522	357	-61	86	21	72	48	50	2	1.0	1.76	0.02	0.02	5.2	0.04
JOC262	630686	7495242	356	-61	261	47	54	21	22	1	0.5	2.22	0.38	0.25	135	0.17
								38	40	2	1.0	0.99	0.15	0.04	18.5	0.24
JOC263	630351	7495200	357	-57	94	>30	30	9	10	1	0.5	0.64	0.14	0.3	5.6	0.24
JOC264	630339	7495201	356	-56	96	>48	48	28	29	1	0.6	0.67	0.02	0.28	3.2	0.07
								34	35	1	0.6	1.53	0.34	0.05	32.5	0.26
JOC265	630354	7495172	359	-46	132	>24	24	10	14	4	2.8	3.87	0.1	0.2	30.6	0.66
JOC278	630270	7494395	359	-61	92	35	48	11	14	3	1.5	0.8	0.03	0.24	3.6	0.03
								17	19	2	1.0	0.6	0.13	0.78	12	0.04
JOC286	627239	7491320	358	-55	267	31	72	50	51	1	0.9	1.71	0.02	0.05	5.5	0.45
JOC287	627214	7491240	358	-60	267	40	42	20	23	3	2.3	1.52	0.01	0.03	9.7	0.56
								24	27	3	2.3	6.05	0.03	0.05	24.7	2.09
JOC288	627229	7491240	357	-61	268	34	54	37	42	5	4.2	2.65	0.03	0.05	20.6	0.57

<sup>1</sup>Base of Oxidisation down hole depth <sup>2</sup>Estimated true width



**For further information contact:**

Mr Simon Milroy  
Managing Director  
Phone: (07) 3071 9003

**About KGL Resources**

KGL Resources Limited is an Australian mineral exploration company focussed on increasing the high grade Resource at the Jervois Copper-Silver-Gold Project in the Northern Territory and developing it into a multi-metal mine.

**Competent Person Statement**

The following drill holes were originally reported on the date indicated and using the JORC code specified in the table. Results reported under JORC 2004 have not been updated to comply with JORC 2012 on the basis that the information has not materially changed since it was last reported.

Hole		Date originally Reported	JORC Reported Under
RJ	194	31/08/2011	2004
KJC	020	24/02/2014	2012
JOC	177	14/08/2014	2012
JOC	176	14/08/2014	2012
RJ	003	06/08/2012	2004

The Jervois Exploration data in this report is based on information compiled by Martin Bennett, who is a member of the Australian Institute of Geoscientists and a full time employee of KGL Resources Limited.

Mr. Bennett has sufficient experience which is relevant to the style of the mineralisation and the type of deposit under consideration and to the activity to which he is undertaking, to qualify as a Competent Person as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Mr. Bennett has consented to the inclusion of this information in the form and context in which it appears in this report.

# 1 JORC CODE, 2012 EDITION – TABLE 1

## 1.1 Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> <li>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</li> <li>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</li> <li>Aspects of the determination of mineralisation that are Material to the Public Report.</li> <li>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</li> </ul>	<ul style="list-style-type: none"> <li>Diamond drilling and reverse circulation (RC) drilling were used to obtain samples for geological logging and assaying.</li> <li>RC drill holes are sampled at 1m intervals and split using a cone splitter attached to the cyclone to generate a split of ~3kg.</li> <li>Diamond core was quartered with a diamond saw and generally sampled at 1m intervals with shorter samples at geological contacts.</li> <li>RC samples are routinely scanned with a Niton XRF. Samples assaying greater than 0.1% Cu, Pb or Zn are submitted for analysis at a commercial laboratory.</li> </ul>
Drilling techniques	<ul style="list-style-type: none"> <li>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</li> </ul>	<ul style="list-style-type: none"> <li>RC Drilling was conducted using a reverse circulation rig with a 5.25" face-sampling bit. Diamond drilling was either in NQ2 or HQ3 drill diameters.</li> </ul>
Drill sample recovery	<ul style="list-style-type: none"> <li>Method of recording and assessing core and chip sample recoveries and results assessed.</li> <li>Measures taken to maximise sample recovery and ensure representative nature of the samples.</li> <li>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</li> </ul>	<ul style="list-style-type: none"> <li>RC samples were not weighed on a regular basis but no sample recovery issues were encountered during the drilling program.</li> <li>Overweight samples (&gt;3kg) were re-split with portable riffle splitter</li> </ul>
Logging	<ul style="list-style-type: none"> <li>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</li> <li>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</li> <li>The total length and percentage of the relevant intersections logged.</li> </ul>	<ul style="list-style-type: none"> <li>All RC and diamond core samples are geologically logged. Core samples are also orientated and logged for geotechnical information.</li> </ul>
Sub-sampling techniques and sample preparation	<ul style="list-style-type: none"> <li>If core, whether cut or sawn and whether quarter, half or all core taken.</li> <li>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</li> <li>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</li> <li>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</li> <li>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</li> <li>Whether sample sizes are appropriate to the grain size of the material being sampled.</li> </ul>	<ul style="list-style-type: none"> <li>RC drill holes are sampled at 1m intervals and split using a cone splitter attached to the cyclone to generate a split of ~3kg.</li> <li>Diamond core was quartered with a diamond saw and generally sampled at 1m intervals with shorter samples at geological contacts.</li> <li>RC sample splits (~3kg) are pulverized to 85% passing 75 microns.</li> <li>Diamond core samples are crushed to 70% passing 2mm and then pulverized to 85% passing 75 microns.</li> </ul>
Quality of assay data and laboratory tests	<ul style="list-style-type: none"> <li>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</li> <li>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times,</li> </ul>	<ul style="list-style-type: none"> <li>The QAQC data includes standards, duplicates and laboratory checks. In ore zones Standards are added at a ratio of 1:10 and duplicates and blanks 1:20.</li> <li>Basemetal samples are assayed using a four acid digest with an ICP AES finish.</li> </ul>

Criteria	JORC Code explanation	Commentary
	<p><i>calibrations factors applied and their derivation, etc.</i></p> <ul style="list-style-type: none"> <li>• <i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i></li> </ul>	<p>Gold samples are assayed by Aqua Regia with an ICP MS finish. Samples over 1ppm Au are re-assayed by Fire Assay with an AAS finish.</p> <ul style="list-style-type: none"> <li>• An umpire laboratory is used to check ~1% of samples analysed.</li> </ul>
Verification of sampling and assaying	<ul style="list-style-type: none"> <li>• <i>The verification of significant intersections by either independent or alternative company personnel.</i></li> <li>• <i>The use of twinned holes.</i></li> <li>• <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i></li> <li>• <i>Discuss any adjustment to assay data.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Data is validated on entry into the Dashed database.</li> <li>• Further validation is conducted when data is imported into Vulcan</li> </ul>
Location of data points	<ul style="list-style-type: none"> <li>• <i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i></li> <li>• <i>Specification of the grid system used.</i></li> <li>• <i>Quality and adequacy of topographic control.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Surface collar surveys were picked up using a Trimble DGPS.</li> <li>• Downhole surveys were taken during drilling with a Ranger or Reflex survey tool every 30m with checks conducted with a Gyrosmart gyro and Azimuth Aligner.</li> <li>• All drilling is conducted on the MGA 94 Zone 53 grid. All downhole magnetic surveys were converted to MGA 94 grid.</li> </ul>
Data spacing and distribution	<ul style="list-style-type: none"> <li>• <i>Data spacing for reporting of Exploration Results.</i></li> <li>• <i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i></li> <li>• <i>Whether sample compositing has been applied.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Drilling for Inferred resources has been conducted at a spacing of 50m along strike and 80m within the plane of the mineralized zone. Closer spaced drilling was used for Indicated resources.</li> <li>• Shallow oxide RC drilling was conducted on 80m spaced traverses with holes 10m apart</li> </ul>
Orientation of data in relation to geological structure	<ul style="list-style-type: none"> <li>• <i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i></li> <li>• <i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Holes were drilled perpendicular to the strike of the mineralization a default angle of -60 degrees but holes vary from -45 to -80.</li> </ul>
Sample security	<ul style="list-style-type: none"> <li>• <i>The measures taken to ensure sample security.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Samples were stored in sealed polyweave bags on site and transported to the laboratory at regular intervals by KGL staff.</li> </ul>
Audits or reviews	<ul style="list-style-type: none"> <li>• <i>The results of any audits or reviews of sampling techniques and data.</i></li> </ul>	<ul style="list-style-type: none"> <li>• The sampling techniques are regularly reviewed.</li> </ul>

## 1.2 Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<ul style="list-style-type: none"> <li>• <i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i></li> <li>• <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i></li> </ul>	<ul style="list-style-type: none"> <li>• The Jervois project is within E25429 100% owned by Jinka Minerals and operated by Kentor Minerals (NT), both wholly owned subsidiaries of KGL Resources.</li> <li>• The Jervois project is covered by Mineral Claims and an Exploration licence owned by KGL Resources subsidiary Jinka Minerals.</li> </ul>
Exploration done by other parties	<ul style="list-style-type: none"> <li>• <i>Acknowledgment and appraisal of exploration by other parties.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Previous exploration has primarily been conducted by Reward Minerals, MIM and Plenty River.</li> </ul>
Geology	<ul style="list-style-type: none"> <li>• <i>Deposit type, geological setting and style of mineralisation.</i></li> </ul>	<ul style="list-style-type: none"> <li>• EL25429 lies on the Huckitta 1: 250 000 map sheet (SF 53-11). The tenement is located mainly within the Palaeo-Proterozoic Bonya Schist on the northeastern boundary of the Arunta</li> </ul>

Criteria	JORC Code explanation	Commentary
		<p>Orogenic Domain. The Arunta Orogenic Domain in the north western part of the tenement is overlain unconformably by Neo-Proterozoic sediments of the Georgina Basin.</p> <ul style="list-style-type: none"> <li>The copper-lead-zinc mineralisation is interpreted to be stratabound in nature, probably relating to the discharge of base metal-rich fluids in association with volcanism or metamorphism or dewatering of the underlying rocks at a particular time in the geological history of the area.</li> </ul>
Drill hole Information	<ul style="list-style-type: none"> <li>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: <ul style="list-style-type: none"> <li>easting and northing of the drill hole collar</li> <li>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</li> <li>dip and azimuth of the hole</li> <li>down hole length and interception depth</li> <li>hole length.</li> </ul> </li> <li>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</li> </ul>	<ul style="list-style-type: none"> <li>Refer Table 1</li> </ul>
Data aggregation methods	<ul style="list-style-type: none"> <li>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</li> <li>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</li> <li>The assumptions used for any reporting of metal equivalent values should be clearly stated.</li> </ul>	<ul style="list-style-type: none"> <li>Refer Table 1</li> </ul>
Relationship between mineralisation widths and intercept lengths	<ul style="list-style-type: none"> <li>These relationships are particularly important in the reporting of Exploration Results.</li> <li>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</li> <li>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</li> </ul>	<ul style="list-style-type: none"> <li>Refer Table 1</li> </ul>
Diagrams	<ul style="list-style-type: none"> <li>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</li> </ul>	<ul style="list-style-type: none"> <li>Refer Figures 1, 2 &amp; 3</li> </ul>
Balanced reporting	<ul style="list-style-type: none"> <li>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</li> </ul>	<ul style="list-style-type: none"> <li>Refer Table 1</li> </ul>
Other substantive exploration data	<ul style="list-style-type: none"> <li>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</li> </ul>	<ul style="list-style-type: none"> <li>Outcrop mapping of exploration targets using Real time DGPS.</li> </ul>
Further work	<ul style="list-style-type: none"> <li>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</li> <li>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</li> </ul>	<ul style="list-style-type: none"> <li>Refer Figure 3</li> </ul>