BASS METALS LTD. (ASX: BSM) ABN: 31 109 933 995 Phone: +61 (0) 7 3063 3233

WEBSITE: WWW.BASSMETALS.COM.AU POST: PO BOX 15048 BRISBANE QLD 4000

ASX Announcement 7 July 2021

GRAPHITE EXPLORATION UPDATE

Bass Metals Limited (ASX:BSM) (the **Company** or **Bass**) is pleased to provide investors with an update on further exploration success at the Company's wholly owned Graphmada Mining Complex, located in eastern Madagascar.

Bass is seeking to expand its current Mineral Resource¹ of 20.2mt @ 4.0% TGC and is well placed to increase its established resource base to support both expanded production and its Advanced Materials strategy.

HIGHLIGHTS

- Bass has completed furth a further 140 shallow auger holes drilled, to an average depth of 12m from surface.
- At Ambatofafana-West additional augering confirmed at least 1 graphite zone over a strike length of approx. 600m and widths of approx. 100-450m and open-ended North-South. Weighted averages up to 11.5m @ 5.9% FC (incl. 4.0m @ 9.8% FC) were obtained.
- At Ambatofafana-East augering to date confirmed at least 3 graphite zones over strike lengths of approx. 250-450m and widths of approx. 50-100m and open-ended North-South. Weighted averages up to 11.5m @ 5.2% FC (incl. 6.0m @ 7.5% FC) were obtained. Further auger results to the north and south are still pending.
- 1 'wildcat' drill hole located further to the north-west of Ambatofafana yielded a weighted average up to 11.5m @ 9.6% FC (incl. 4.5m @ 14.8% FC). This area appears to be a part of the Mahela-South graphite zone and will need further investigation and augering.

¹ ASX Announcement "Increase in Graphite Mineral Resource" released 16 March 2021.

KEY INTERCEPTS

- 11.5m @ 9.6% FC (incl. 4.5m @ 14.8% FC)
- 9.0m @ 6.6% FC (incl. 4.0m @ 9.6% FC)
- 11.5m @ 5.9% FC (incl. 4.0m @ 9.8% FC)
- 10.5m @ 5.6% FC (incl. 8.0m @ 6.8% FC)
- 11.5m @ 5.6% FC
- 2.5m @ 9.6% FC
- 11.0m @ 4.7% FC (incl. 9.0m @ 5.4% FC)
- 11.5m @ 4.4% FC (incl. 3.0m @ 7.0% FC)
- 11.5m @ 5.2% FC (incl. 6.0m @ 7.5% FC)
- 3.0m @ 5.5% FC
- 5.0m @ 5.3% FC



Exploration continues to target easily mineable at surface graphite mineralisation.

CURRENT MINERAL RESOURCES & EXPLORATION TARGET

In 2019 the Company, with an extensive data set of historical exploration, announced a brownfields **Exploration Target estimate of 86-146 Million tonnes between 4-6% Total Graphitic Carbon (TGC)**, in accordance with the JORC Code (2012)².

This Exploration Target is in addition to an already substantial regolith hosted large flake graphite **Mineral Resource1¹** of **20.2 Mt @ at 4% TGC**, estimated in accordance with the JORC Code (2012).

Mineral Resources for Graphmada Mining Complex

Total	Tonnes (Mt)	TGC (%)	Contained Graphite (kt)
Measured	2.9	4.2	121
Indicated	3.3	4.3	143
Inferred	14.0	3.9	550
Total	20.2	4.0	815

Important Notes:


An Exploration Target is a statement or estimate of the exploration potential of a mineral deposit in a defined geological setting where the statement or estimate, quoted as a range of tonnes and a range of grade, relates to mineralization for which there has been insufficient exploration to estimate a Mineral Resource. The potential quantity and grade of the Exploration Target is conceptual in nature, there has been insufficient exploration to estimate an additional Mineral Resource and it is uncertain if further exploration will result in the estimation of an additional Mineral Resource.

The Company confirms that it is not aware of any new information or data that materially affects the information in the relevant ASX releases and the form and context of the announcement has not materially changed. The Company confirms that the form and context in which the Competent Persons findings are presented have not been materially modified from the original market announcements.

² ASX Announcement "Significant Exploration Program to commence at Graphmada" released 3 June 2019.

AMBATOFAFANA

Ambatofafana is at the southernmost end of the Company's permits at Graphmada. The prospect is divided into two known mineralization zones, Ambatofafana West and Ambatofafana East. The Company has yet to test the possible mineralization between Ambatofafana West and Mahela, or the mineralization between Ambatofafana and Mahefedok.



Ambatofafana and the current Mineral Resource (JORC 2012) at Graphmada.


Results

The Company's drilled 140 shallow auger holes to an average depth of 12m from surface at the Ambatofafana Prospect for a total of 1,647 metres drilled. The results of which continue to demonstrate the regolith hosted graphite mineralization footprint at Graphmada is extensive, both laterally and in width.


Key intercepts from recent drilling include:

Collar ID	x	Y	Azi.	Incl.	Total Depth	Weighted Average %FC
BSMA588	288,008	7,901,766	0	-90	12.0	11.5m @ 9.6% FC (incl. 4.5m @ 14.8% FC)
BSMA557	289,130	7,901,040	0	-90	10.0	9.0m @ 6.6% FC (incl. 4.0m @ 9.6% FC)
BSMA585	288,046	7,901,231	0	-90	12.0	11.5m @ 5.9% FC (incl. 4.0m @ 9.8% FC)
BSMA508	289,159	7,901,140	0	-90	12.0	10.5m @ 5.6% FC (incl. 8.0m @ 6.8% FC)
BSMA597	288,401	7,900,940	0	-90	12.0	11.5m @ 5.6% FC
BSMA582	288,106	7,901,230	0	-90	10.5	2.5m @ 9.6% FC
BSMA598	288,420	7,900,940	0	-90	12.0	11.0m @ 4.7% FC (incl. 9.0m @ 5.4% FC)
BSMA599	288,441	7,900,940	0	-90	12.0	11.5m @ 4.4% FC (incl. 3.0m @ 7.0% FC)
BSMA639	288,959	7,901,140	0	-90	12.0	11.5m @ 5.2% FC (incl. 6.0m @ 7.5% FC)
BSMA600	288,461	7,900,940	0	-90	12.0	3.0m @ 5.5% FC
BSMA621	288,576	7,901,140	0	-90	12.0	5.0m @ 5.3% FC

Please refer to tables provided as appendices for further information.



Ambatofafana collar locations with intercept grades.



Ambatofafana drill section.

TIM MCMANUS CEO

"Bass, via successive drilling programs, has seen the overall Mineral Resource at Graphmada grow from 5.4~Mt @ 4.1% TGC to 20.2~Mt @ 4.0% TGC.

From Stage 1 mining of this Mineral Resource, the Company produced premium quality concentrates which were sold globally into various markets without penalty or rejection.

The Company looks forward to updating the market further as the team aims to continue the growth of the Company's Mineral Resources to support large scale mining and processing operations (Stage 2) while in parallel developing advanced materials utilizing Graphmada concentrates."

For more information, please contact:

Rick Anthon Peter Wright

Chairman Executive Director

Phone: (07) 3063 3233

Email: InvestorRelations@bassmetals.com.au

www.bassmetals.com.au

This announcement has been approved by the Chairman for release.

Disclaimer

This document has been prepared by Bass Metals Limited (the "Company"). It should not be considered as an invitation or offer to subscribe for or purchase any securities in the Company or as an inducement to make an invitation or offer with respect to those securities. No agreement to subscribe for securities in the Company will be entered into on the basis of this document.

This document is provided on the basis that neither the Company nor its officers, shareholders, related bodies corporate, partners, affiliates, employees, representatives and advisers make any representation or warranty (express or implied) as to the accuracy, reliability, relevance or completeness of the material contained in the document and nothing contained in the document is, or may be relied upon as a promise, representation or warranty, whether as to the past or the future. The Company hereby excludes all warranties that can be excluded by law.

Forward Looking Statements

This announcement contains certain 'forward-looking statements' within the meaning of the securities laws of applicable jurisdictions. Forward-looking statements can generally be identified by the use of forward-looking words such as 'may,' 'should,' 'expect,' 'anticipate,' 'estimate,' 'scheduled' or 'continue' or the negative version of them or comparable terminology.

Any forecasts or other forward-looking statements contained in this announcement are subject to known and unknown risks and uncertainties and may involve significant elements of subjective judgment and assumptions as to future events which may or may not be correct. There are usually differences between forecast and actual results because events and actual circumstances frequently do not occur as forecast and these differences may be material.

Bass Metals does not give any representation, assurance or guarantee that the occurrence of the events expressed or implied in any forward-looking statements in this announcement will actually occur and you are cautioned not to place undue reliance on forward-looking statements. The information in this document does not take into account the objectives, financial situation or particular needs of any person. Nothing contained in this document constitutes investment, legal, tax or other advice.

Important information

This announcement does not constitute an offer to sell, or a solicitation of an offer to buy, securities in the United States, or in any other jurisdiction in which such an offer would be illegal. The securities referred to in this document have not been and will not be registered under the United States Securities Act of 1933 (the 'US Securities Act'), or under the securities laws of any state or other jurisdiction of the United States and may not be offered or sold, directly or indirectly, within the United States, unless the securities have been registered under the US Securities Act or an exemption from the registration requirements of the US Securities Act is available.

This document may not be distributed or released in the United States.

Competent Person Statement

The information in this document that relates to Exploration Results, Exploration Targets and Mineral Resources is based on information compiled by Tim McManus, a Competent Person who is a member of the Australasian Institute of Mining and Metallurgy and a full-time employee of the Company.

Tim McManus has sufficient experience that is relevant to the style of mineralization and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves.

Tim McManus consents to the inclusion of the information in this document in the form and context in which it appears.

JORC CODE, 2012 EDITION - TABLE 1

Discussion and results within this appendix relate to exploration activities at the Graphmada Mining Complex.

Section 1 Sampling Techniques and Data

Criteria	Commentary			
Sampling techniques	Auger samples were collected and included composite samples of the graphite bearing host rocks. Visual estimation of graphite percentages and flake sizes have been used to define mineralization before the return of assays. The samples were solar-dried, manually crushed, split twice through a 50/50 riffle splitter to obtain a representative sub-sample, weighing between 100-150g that was sent to the Bass Metals in-house laboratory for Fixed Carbon analysis.			
Drilling techniques	Drilling was vertical (-90 °) with the aim to achieve an average depth of 10-12m.			
Drill sample recovery	Not applicable			
Logging	Samples were all geologically logged and photographed, and geological recording of relevant data was captured on Bass Metals logging templates. All data was codified to a set company code system as per sampling and logging procedures which are in place. All logging included lithological features, estimates of graphite percentages, and flake sizes which is quantitative and is recorded on the logging sheets. Photographs have been taken as a qualitative check on logging when the need arises.			
Sub-sampling techniques and sample preparation	Samples were solar-dried, crushed, and split twice using a 50:50 riffle splitter. The crushing and splitting equipment were cleaned according to best practice procedures before every run. Each sample was manually crushed to nominal -2mm and approximately 100-150g sub-samples were collected and sent to the Bass Metals inhouse laboratory in Madagascar. The in-house laboratory then pulverized such that 80% of the sample is -75 micron or less in size. consultant will analyze all blanks, standards, and duplicates to maintain QAQC standards.			
Quality of assay data and laboratory tests	Samples are currently being analyzed at the Bass Metals in-house laboratory for a preliminary evaluation of the carbon grade. The Muffle Furnace method was used to determine Loss on Ignition (LoI), Volatile Matter (VM), and Fixed Carbon (FC). LoI Test: a crucible is placed on an electronic balance, primarily zeroed and the weight recorded. 1 gram +- 0.01 of the sample are added, the weight of the crucible + sample are recorded. The crucible is placed in the Muffle Furnace at 950°C +-25°C for 8 hours continuously. After the crucible is removed and cooled, the ash + crucible is then weighed and recorded. The LoI % is calculated as follows: LOI % = (1 - Weight of ash Weight of original sample) × 100 VM Test: a crucible is placed on an electronic balance, primarily zeroed and the weight recorded. 2 grams +- 0.01 of the sample are added, the weight of the crucible + sample is recorded. The crucible is placed in the Muffle Furnace at 950°C +- 25°C for 7 minutes. After the crucible is removed and cooled, the ash + crucible is then weighed and recorded. VM % is calculated as follows: V M % = (1 - Weight of ash Weight of original sample) × 100 FC % of the sample is calculated as follows: FC % = (LOI % - VM %) Certified graphite standards (GC-09 and GC-10) and silica blanks (AMIS0439) were inserted with the samples. An external, independent consultant has certified the results.			
Verification of sampling and assaying	All work was completed by Bass Metals personnel. Significant mineralization intersections were verified by an external consultant and by internal peer review. No twinned holes were drilled as this was reconnaissance drilling. All data was collected initially on paper log sheets by Bass Metals personnel. This data was hand entered into spreadsheets and validated by an external consultant. All paper log sheets were scanned, and electronic spreadsheets stored together with the photographs of the geological features logged. The master collar and assay database with all photographs are backed-up via cloud storage.			

	No adjustments were made to the data.
Location of data points	DGPS's were used to locate collar locations, and final location coordinates were completed with estimated positional errors between 15 and 30 centimetres. The WGS84 UTM Zone 39S projection system was used.
Data spacing and distribution	The purpose of the auger locations was to confirm the presence of graphitic units within the project area. The data collected is insufficient to determine a Mineral Resource and is considered preliminary exploration results only. Sample compositing has not been applied.
Orientation of data in relation to geological structure	Not applicable.
Sample security	Samples were stored in a secure storage area at the Bass Metals sample storage facility. Samples bags were sealed as soon as sampling was completed and stored securely until dispatch to the Company's laboratory facility at Graphmada.
Audits or reviews	The sampling techniques and data are reviewed by an external consultant and internally peer reviewed. It is considered by the Company that industry best practice methods have been implemented by the Company at all stages of exploration.

Section 2 Reporting of Exploration Results

The criteria listed in the preceding section also apply to this section.

Criteria	Commentary
Mineral tenement and land tenure status	Exploitation permit no PE 26670 is located in the Toamasina Province of Madagascar and held by the Malagasy company, Graphmada SARL which is a wholly owned subsidiary of the ASX listed company, Bass Metals Ltd. Permit no PE 26670 was granted on 21/01/2008 and is valid for 40 years. The permit is in good standing, and all statuary approvals are in place to conduct exploration and exploitation activities throughout this permit area, including mining.
Exploration done by other parties	Not applicable as the mineralization is a virgin discovery by Bass Metals and has had no previous work completed by other Parties.
Geology	Crystalline "hard rock" flake graphite deposits occur in graphitic gneisses within Neoproterozoic metasedimentary type rocks and include accessory minerals of biotite (± sillimanite/kyanite, ± garnet). Due to the tropical climate and because graphite is comparatively inert, weathering of the "hard rock" graphitic gneiss units further concentrates the graphite to form residual regolith-hosted accumulations within the weathered profile. Regolith refers to weathered material that occurs above unweathered bedrock. Two primary subdivisions are the pedolith (PED) and the saprolith (SAP). Secondary subdivisions of the pedolith, from the surface downwards, include soil (SL), ferruginous zone (FZ), and the mottled zone (MZ). Secondary subdivisions of the saprolith, include saprolite (SP) and saprock (SR).
Drill hole Information	A summary of all information material to the understanding of the exploration results including a tabulation of visually logged data is supplied in the above announcement.
Data aggregation methods	Samples are currently being assayed for in-situ Fixed Carbon (FC) grades by the in- house Graphmada laboratory. No Metal Equivalents have been stated.
Relationship between mineralization widths and intercept lengths	The mineralization is hosted within a weathered regolith profile and the main mineralized lenses/horizons are suspected to dip towards the west at between 30° and 45°. The samples, taken vertically, are reported as true width and tables have been annotated in the above announcement.
Diagrams	This information has been accurately represented in the announcement and contains all relevant information required for the reader to understand the nature of the graphitic mineralization.
Balanced reporting	The summary table of all the auger sample results is contained within the announcement.
Other substantive exploration data	Not applicable.
Further work	A systematic exploration program will be planned, including further auger and pitting with sampling, to be followed by a potential drilling and sampling program for grade estimation, flake size distribution, and metallurgical testing.