



PENNY SOUTH DRILLING UPDATE

- Two weeks into the 6-week drill programme with almost 6 holes completed for 1218m of RC drilling over the priority structural targets.
- Another 12 structural target holes remain to be completed over the next 4 weeks.
- Trace levels of sulphides have been logged in five of the holes in ultramafic schists, basalts, amphibolites and granodiorites.

Aurum Resources is pleased to announce that the Penny South drilling programme is a third of the way through the 18 structural target holes in a similar structural and geological setting to Penny West and Penny North (Ramelius ASX:RMS) gold deposits lying immediately to the North. A total of 5 of the 18 planned holes have been completed, with the 6th hole almost completed (Table 1) intersecting mafic and ultramafic schists, basalts (including dolerite) and granodiorites (hanging wall) with selvages of amphibolite of various thicknesses. While no visible gold has been identified, trace levels of sulphides and quartz veining (from stringers to sheets) have been logged from the drill cuttings. Trace levels of sulphides (<1%), predominately pyrite and galena, were visible in 1m interval drill chips from holes APSRC0028, APSRC0029, APSRC0030, APSRC0032 and APRC0033.




Photo 1: Drilling at hole APSRC0033 (RHRC007) at Penny South





Photo 2: Chip tray from hole APSRC0033 depth 80-100m showing sulphides in a basaltic unit



Map 1: Structural interpretation on magnetic image showing the collar positions. The inset shows the image area for Map 2 which also labels collar ID numbers. Note the major north-south shear zone (magnetic low) traverses the length of the image and is referred to as the Penny West Shear Zone. The Penny West pit sits in a northwest striking fault and associated shear that splays off this major north-south feature. The northern holes (Map 2 area) have a similar structural setting to the Penny West deposit.





Map 2: Planned collar positions with the RHRC collar based on structural interpretation and the MHRC based on geology and historical intersections. Holes drilled in this update are RHRC001-005.

		Easting	Northing				<u>Target</u>	Drilled	
<u>ID</u>	Hole No.	(MGAz50)	(MGAz50)	Elevation	<u>Azimuth</u>	<u>Dip</u>	Depth (m)	Depth (m)	Comment
RHRC001	APSRC0027	676553	6805952	501	270	-60	200	204	Test strong NW structure
RHRC002	APSRC0028	676701	6805952	500	270	-60	200	210	Test strong NW structure
RHRC003	APSRC0029	676653	6805849	499	270	-60	200	185.5	Test NW structure with offsets in PWSZ
RHRC004	APSRC0030	676801	6805851	500	270	-60	200	198	Test NW structure with offsets in PWSZ
RHRC005	APSRC0031	676602	6805748	496	270	-60	200	55	Test NW structure with offsets in PWSZ
RHRC005	APSRC0032	676599	6805747	496	270	-60	200	198	Test NW structure with offsets in PWSZ
RHRC006	APSRC0033	676750	6805750	492	270	-60	200	168	Test NW structure with offsets in PWSZ
RHRC007		676900	6805750	491	270	-60	200		Test NW structure with offsets in PWSZ
RHRC008		676700	6805500	488	270	-60	200		Test NW structure/PWSZ adjacent to 5.56 ppm Au hit in APSRC015
RHRC009		676720	6805450	487	270	-60	200		Test NW structure/PWSZ adjacent to 5.56 ppm Au hit in APSRC015
RHRC010		676750	6805400	486	270	-60	200		Test NW structure/PWSZ adjacent to 5.56 ppm Au hit in APSRC015
RHRC011		676950	6805170	486	270	-60	200		Testing gap zone between main Nth and Sth zones. NW trending structure
RHRC012		676950	6805110	486	270	-60	200		Testing gap zone between main Nth and Sth zones. NW trending structure
RHRC013		676950	6804700	486	270	-60	200		Testing adjacent to 6.67 ppm Au hit in APSRC026
RHRC014		676950	6804600	486	270	-60	200		Testing adjacent to 6.67 ppm Au hit in APSRC026
RHRC015		676900	6804500	486	270	-60	200		Testing adjacent to 62.55 pm Au hit in 95PSRC0673
RHRC016		676970	6804450	486	270	-60	250		Testing possible down plunge to 62.55 pm Au hit in 95PSRC0673
RHRC017		676950	6804370	486	270	-60	250		Testing extension to 5.2 ppm Au hit in APSRC005
RHRC018		676850	6804200	488	270	-60	200		Testing extension to 3.36 ppm Au hit in APSRC006
Total								1218.5	

Table 1: List of collars based on structural interpretation, note PWSZ is the abbreviation for the Penny West Shear Zone (the major north -south shear zone shown in Map 1). The table's black text is for the completed holes, while the information in green applies to holes that are still to be drilled and the hole in red is still ongoing.



These holes were drilled with 127mm (5") wide percussion hammer. Note a second hole was drilled at RHRC005, as the first (ASPRC0031) was abandoned after the top of the hole blew out. The collar positions for the completed holes were GPS averaged to give greater accuracy.

References to the historical holes have been previously reported by Aldoro (ASX:ARN 28/5/20) and Gold Mines of Australia (DMIRS open file reports).

Drill Hole Summaries

Hole APSRC0027 (RHRC001).

FROM	то	LITHOLOGY	SULPHIDES
0	7	overburden	
7	10	upper saprolite	
10		basalt	
17	22	mafic schist	
22	44	ultramafic schist	
44	47	granodiorite	
47	52	ultramafic schist	
52	74	granodiorite	
74	76	amphibolite	
76	104	ultramafic schist	
104	111	granodiorite	
111	114	ultramafic schist	
114	116	mafic schist	
116	120	ultramafic schist	
120	125	basalt	
125	129	mafic schist	
129	132	basalt	
132	135	mafic schist	
134	140	basalt	
140	143	mafic schist	
143	144	ultramafic talc chlorite	
144	150	basalt	
		granodiorite	
160	168	mafic schist	
168	181	granodiorite	
181	183	vein quartz	
184	186	granodiorite	
186	187	vein quartz	
187	204	granodiorite	





Hole APSRC0028 (RHRC002)

FROM	ТО	LITHOLOGY	SULPHIDES
0	17	overburden	
17	20	upper saprolite	
20	26	lower saprolite	
26	41	basalt	
41	45	volcanoclastic	
45	47	basalt	
47	57	ultramafic	
57	60	basalt	
60	63	diorite	
63	149	pyroxenite?	63, 73, 75, 94, 96, 99, 101-105, 123, 135, 138, 148-149
149	173	granodiorite	
173	188	amphibolite	174-183, 186-187
188	191	vein quartz	
191	192	mafic schist	
192	194	granodiorite	
194	196	mafic schist	195
196	204	quartz porphyry	197-198
204	205	vein quartz	
205	209	ultramafic schist	
209	210	vein quartz	

Hole APSRC0029 (RHRC003)

FROM	то	LITHOLOGY	SULPHIDES
0	12	overburden	
12	25	upper saprolite	
25	32	lower saprolite	
32	45	dolerite	
45	57	basalt	
57	58	vein quartz	
58	62	basalt	
62	65	felsic schist	
65	72	quartz porphyry	
72	73	mafic schist	
73	78	basalt	74-75
78	79	vein quartz	
79	80	basalt	
80	88	granodiorite	
88	115	mafic schist	103, 105-106, 110-111
115	121	vein quartz	
121	130	ultramafic schist	
130	139	granodiorite	133-134, 138
139	147	ultramafic schist	
147	155	amphibolite	
155	161	granodiorite	
161	170	amphibolite	162
170	185.5	granodiorite	



Hole APSRC0030 (RHRC004)

FROM	то	LITHOLOGY	SULPHIDES
0	18	overburden	
18	32	upper saprolite	
32	55	lower saprolite	
55	58	ultramafic schist	
58	60	ultramafic talc chlorite schist	
60	103	gabbro	71, 74-79, 86,90,94,100-103
103	108	ultramafic schist	103-103, 105-107
108	174	basalt	111-114, 119, 123, 128-130, 132-134, 136, 138-167, 169-170, 172, 174
174	180	amphibolite	179
180	187	basalt	181-182, 184, 186
187	190	amphibolite	
190	198	basalt	191-194

Hole APSRC0031 (RHRC005)

FROM	то	LITHOLOGY	SULPHIDES
0	13	overburden	
13	42	upper saprolite	
42	54	lower saprolite	
		Abandoned hole	

Hole APSRC0032 (RHRC005)

FROM	то	LITHOLOGY	SULPHIDES
0	13	overburden	
13	46	upper saprolite	
46	51	lower saprolite	
51	60	felsic granitoid	
60	134	granodiorite	
134	136	amphibolite	
136	168	granodiorite	
168	171	amphibolite	159-160
171	181	granodiorite	
181	183	amphibolite	
183	186	granodiorite	
186	189	vein quartz	
189	195	granodiorite	
195	196	amphibolite	197
196	198	granodiorite	

Hole APSRC0033 (RHRC006) – drilling ongoing

FROM	то	LITHOLOGY	SULPHIDES
0	15	Overburden	
15	20	Upper saprolite	
20	50	Lower saprolite	
50	54	Basalt	
54	63	Metasediment	
63	108	Basalt	73-100, 102-104, 106-108
108	111	Mafic schist	109, 111
111	118	Basalt	112-118
118	121	Mafic schist	121
121	158	Basalt	122-123, 127-128, 135, 137-138, 145-146, 157
158	168	Amphibolite	
			Hole ongoing






Figure 1: Aurum Resources Limited project locations.

END

Background

Penny South Project. The project sits on the same shear structure that the high-grade Penny West (1990's open pit 121,000t at 21.8g/t for 85,000oz) and the more recently discovered adjacent Penny North (2020 – underground 569,000t at 16.8g/t for 306,800oz). Penny West lies just 510m north of Aurum's Penny South licence and the Penny West N-S Shear continues through the licence for a strike length of 2.5km. High grade mineralisation is associated with the sheared contacts between mafic and granodiorite(felsic) rocks and quartz veining (often associated with sulphides). Similar contacts are seen in Penny South and drilling to date has produced some hits, 2m at 33.89g/t from 38m (historic hole 95PSR0673), 4m at 2.1g/t from 92m (APSRC015 ARN: 28/05/2020) highlighting the potential of the area. The high-grade mineralisation at Penny West and Penny North are narrow high-grade zones so targeting has to be highly focused. While the Penny south area has been extensive drilled with 652 holes, these are generally shallow, with the average around 40m, so if a Penny North deposit, where the mineralisation starts at 80m and continues to 320m, was in the area it would likely be missed. So, the focus has been combining high resolution ground magnetics available drilling information for a detailed structural interpretation. Aurum contracted Richard Hill, who worked on the Penny North deposit for Spectrum, and Margie Hawke (Hazina Geoscience) to define targets along the AURUM RESOURCES LIMITED | ACN 17 650 477 286 | +61.8 6559 1792



structurally complex shear system. Ramelius Resources (**ASX:RMS**), to the North, have released a JORC Mineral Resource and ore reserve for enlarging the Penny West pit and planned a decline to Penny North from the open pit with **620,000t at 15.0g/t for 300,000oz** .(2g/t cut off)

About Aurum Resources Limited

Aurum Resources Ltd is an ASX-listed (**ASX:AUE**) mineral exploration and development company. Aurum has a collection of gold focused projects from early-stage reconnaissance to advanced exploration projects all located in Western Australia. The Company's flagship project is the Penny South Project, highly prospective for gold mineralisation and located adjacent to and on the same structure as Ramelius's Penny West & Penny North gold mine. The Company's other projects include the Ryans Find, another high prospective project adjacent to known gold deposits and the Unaly Hill South gold target.

Competent Persons Statement

The information in this announcement that relates to exploration data and results derived from open file reports and information supplied by Aldoro Resources Limited (ASX: ARN and has been previously released) and prepared in accordance with the 2012 Edition of the Australian Code for reporting of Exploration Results, Mineral Resources and Ore Reserves (JORC). The data was reviewed and compiled by Mr Mark Mitchell, an employee with Aurum Resources Ltd. Mr Mitchell is a Registered Professional Geoscientist (No.10049) with the Australian Institute of Geoscientists and has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Mitchell consents to the inclusion in the release of the statements based on his information in the form and context in which it appears.

This Announcement has been approved for release by the Board of Aurum Resources Ltd

Disclaimer

Some of the statements appearing in this announcement may be in the nature of forward-looking statements. You should be aware that such statements are only predictions and are subject to inherent risks and uncertainties. Those risks and uncertainties include factors and risks specific to the industries in which Aurum operates and proposes to operate as well as general economic conditions, prevailing exchange rates and interest rates and conditions in the financial markets, among other things. Actual events or results may differ materially from the events or results expressed or implied in any forward-looking statement. No forward-looking statement is a guarantee or representation as to future performance or any other future matters, which will be influenced by several factors and subject to various uncertainties and contingencies, many of which will be outside Aurum's control. Aurum does not undertake any obligation to update publicly or release any revisions to these forward-looking statements to reflect events or circumstances after today's date or to reflect the occurrence of unanticipated events. No representation or warranty, express or implied, is made as to the fairness, accuracy, completeness or correctness of the information, opinions or conclusions contained in this announcement. To the maximum extent permitted by law, none of Aurum, its directors, employees, advisors, or agents, nor any other person, accepts any liability for any loss arising from the use of the information contained in this announcement. You are cautioned not to place undue reliance on any forward-looking statement. The forward-looking statements in this announcement reflect views held only as at the date of this announcement.



This announcement is not an offer, invitation or recommendation to subscribe for, or purchase securities by Aurum. Nor does this announcement constitute investment or financial product advice (nor tax, accounting, or legal advice) and is not intended to be used for the basis of making an investment decision. Investors should obtain their own advice before making any investment decision.





JORC Code, 2012 Edition – Table 1

Section 1 Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	 Reverse circulation drilling used to collect individual 1 metre samples downhole Cyclone sample splitter used to collect 2 representative samples per metre where one sample was composited with other samples over a 4m interval, while the other sample was kept for individual analysis when required. Composite samples will be pulverized to obtain a homogenised sample from which a 50g sample will be used for fire assay for gold and another 50g charge for trace element analysis. A quality control/quality assurance system comprising three OEAS gold standards and blank sand was used at random intervals to evaluate the assay process.
Drilling techniques	 Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc). 	 Reverse Circulation using a Schramm T450 universal rig and a rock face sampling hammer with 127mm diameter (5"). The holes were orientated by compass and clinometer (rig). A gyro probe was sent down the hole at the end of each hole and orientation data recorded every 30m.



Criteria	JORC Code explanation	Commentary
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 Sample recoveries assessed qualitatively, no routine weighing or other assessment processes. Standard drilling techniques used to maximise sample recovery with cone splitter on cyclone used to collect 2 individual splits (calico bags) and the remainder into a green plastic bag. No relationship established as samples have not been analysed yet.
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	 The 1 metre detailed logs provide fair geological descriptions but lacks geotechnical information so the level of information collected to date would not support Mineral Resource estimation It also lacks mining studies and metallurgical studies. The logging is qualitative but not quantative The RC chips have been logged on a 1 metre basis.
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	 No core collected only RC chips The RC chips were collected using a cone splitter system attached to the bottom of the cyclone. Samples varied from dry to wet, depending on the presence of the water table and the 6m rod changes. The cone splitter used on the cyclone is considered an appropriate technique for reducing bias in the sample collection. The quality control procedure for the first split sample is to take a level scoop from each of the 4 one metre splits for a composite sample. The second spilt will be retained whole for 1m analysis where required. Sample control duplicates were collected at various regular intervals at around every 40 samples. These will be analysed, and results compared their counterparts. Initially the first spilt is combined to form 4m composites for analysis, the second split is retained and may be used for individual 1m analysis It is not known whether grain size is a consideration in the subsampling technique as no size screening has been conducted.



Criteria	JORC Code explanation	Commentary
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 The samples are still in the field and have not been consigned to the laboratory. No geophysical tools used It is unknown what control procedures were adopted
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	 No verification techniques have been adopted as the samples are yet to be consigned to the laboratory. No twinned holes were drilled, however an abandoned hole 3m from the final hole will be compared for the 55m overlap. Logging in the field is conducted using logging software on a tablet and will be transferred to a sever and backed up in raw format to preserve the original dataset. No samples have been consigned to the laboratory to date.
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 The hole collars were located using a Garmin 66st and a compass was used to locate guidance pegs for the drill rig azimuth. At the completion of the hole an averaged reading (5-10minutes) was taken with the GPS to record the position. Down hole dip and azimuth were recorded using a gyro at 50m intervals. The datum used GDA94 zone 50 The topographic control is limited to that provided by the handheld GPS averaged reading.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and 	 The drill hole placement was not on a regular grid as the holes were targeted interpreted structural features in the capacity of exploration drilling, not resource constraining. The holes are exploration in nature and not defining a resource which



Criteria	JORC Code explanation	Commentary
	classifications applied.Whether sample compositing has been applied.	 is yet to be discovered. Sample compositing has not been applied as the drilling is still in exploration phase.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	 The holes are drilled at 270 azimuth which is approximately perpendicular to the strike of the lithology which steeply dips to the east. There is no quantitative information regarding the orientation of mineralised structures and the relationship between drilling orientation and the orientation of key mineralised structures is not known No sampling bias is considered to have been introduced however there is currently insufficient information to confirm this.
Sample security	The measures taken to ensure sample security.	Samples were bagged and secured by contractor field staff • Samples will be transported directly to the analytical laboratory by Company staff
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	No sampling techniques or data have been independently audited.

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 Tenement E57/1045 (4 graticular blocks) is currently held by Altilium Metals Limited and is 100% owned and operated by Aurum Resources Limited The licence is in the process of being transferred to Aurum Resources Limited.



Criteria	JORC Code explanation	Commentary
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	 Gold Mines of Australia (GMA) undertook extensive exploration in the period 1989 -1996 with extensive soil sampling returning disappointing results and angled RAB drilling generating some encouraging results in the regolith. Two anomalous intercepts of 2 m @33.98g/t Au (95PSR0673;38-40m) and 1 m @ 1.04 g/t Au (PSR0100;28-29m) were tested by very limited RC drilling however the majority regolith anomalies were untested. Lach Drummond Resources (2002-2004); Follow-up aircore drilling of the GMA generated regolith anomalies with better results including 6m @ 1.27 g/t Au (PWAC062; 29-35m) and 1m @ 1.04 g/t Au (PWAC092; 33-34m) Beacon Minerals (2014-15); 34 angled aircore holes totaling 1820m were undertaken to test the historical regolith anomalies. Results were moderate with follow up RC drilling proposed for significant aircore results. Aldoro Resources (2016-2021) Conducted a detailed ground magnetic survey and interpreted in conjunction with lithological information contained within historic drill logs and incorporating the Penny West and Penny North mineralisation styles. The interpretation identified 7 targets based on structural interpretation and historical mineralisation. Aircore drilling successfully highlighted the inferred extension of the Penny West Shear and granodiorite-mafic contact, with two target areas showing coincident factors of sulphidic quartz veining. RC drilling at the Southern Target within the tenement area identified a mineralised structure over 400m of strike with gold intersections of up to 6.7g/t Au. A 2021 review of all the exploration activity across the tenement found that the drilling had not been deep enough to intersect the structures and contacts hosting the mineralisation.



Criteria	JORC Code explanation	Commentary
Geology	Deposit type, geological setting and style of mineralisation.	 The Penny South Project is located at the southern end of the Youanmi greenstone belt, dominated by metamorphosed mafic extrusives and intrusives, minor BIF, intrusive felsic porphyries and some felsic volcanic rocks. The Youanmi intrusive complex is made up of layered mafic and ultramafic rocks and occurs to the immediate west of the main greenstone sequence. Anomalous gold occurs in a favourable structural setting close to the Youanmi Fault, a major structure known to host or control gold mineralisation in the district
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	 See the tables attached after this section which provide collar, geology and assay information. Drill hole information is not considered material at this stage as no assay results are yet known. Exclusion of this information does not detract from the understanding that the announcement is brief update on drilling progress with a few visual observations the significance of which will be determined once assay results are known.
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	 No data aggregation methods have been adopted as no analytical data is being reported as the samples have not been sent to the laboratory.



Criteria	JORC Code explanation	Commentary
Relationship between mineralisatio n widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	 No relationship between mineralisation width and intercept lengths have been established as no analytical data is being reported as the samples have not been sent to the laboratory
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	 No detailed maps or sections are presented as no analytical data is being reported as the samples have not been sent to the laboratory
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	 No grades or widths are tabled as no analytical data is being reported as the samples have not been sent to the laboratory.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	No other substantive exploration data is available at this stage.
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 The further work programme involves the completion of the RC drill programme and the analytical results of the programme will dictate the direction of addition exploration. Analytical results are required before any diagrams can be constructed
Cut-off parameters	The basis of the adopted cut-off grade(s) or quality parameters applied.	No cut-off parameters are required at this stage of early exploration.



Criteria	JORC Code explanation	Commentary
Mining factors or assumptions	 Assumptions made regarding possible mining methods, minimum mining dimensions and internal (or, if applicable, external) mining dilution. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential mining methods, but the assumptions made regarding mining methods and parameters when estimating Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the mining assumptions made. 	 No mining factors or assumptions have been considered for this exploration stage as these are considered outside the scope at this level of exploration.
Metallurgical factors or assumptions	The basis for assumptions or predictions regarding metallurgical amenability. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential metallurgical methods, but the assumptions regarding metallurgical treatment processes and parameters made when reporting Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the metallurgical assumptions made.	 No metallurgical factors or assumptions have been considered at this stage as these are considered outside the scope of this stage of exploration
Environmen- tal factors or assumptions	 Assumptions made regarding possible waste and process residue disposal options. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider the potential environmental impacts of the mining and processing operation. While at this stage the determination of potential environmental impacts, particularly for a greenfields project, may not always be well advanced, the status of early consideration of these potential environmental impacts should be reported. Where these aspects have not been considered this should be reported with an explanation of the environmental assumptions made. 	 No environmental factors or assumptions have been considered for this exploration stage as these are considered outside the scope of this stage of exploration.
Bulk density	Whether assumed or determined. If assumed, the basis for the assumptions. If determined, the method used, whether wet or dry, the frequency of the measurements, the nature, size and representativeness of the samples.	 No bulk density sampling has been considered at this stage of exploration



Criteria	JORC Code explanation	Commentary
	 The bulk density for bulk material must have been measured by methods that adequately account for void spaces (vugs, porosity, etc), moisture and differences between rock and alteration zones within the deposit. Discuss assumptions for bulk density estimates used in the evaluation process of the different materials. 	
Classification	 The basis for the classification of the Mineral Resources into varying confidence categories. Whether appropriate account has been taken of all relevant factors (ie relative confidence in tonnage/grade estimations, reliability of input data, confidence in continuity of geology and metal values, quality, quantity and distribution of the data). Whether the result appropriately reflects the Competent Person's view of the deposit. 	No Mineral resource is considered, the project is purely an exploration play.
Audits or reviews	The results of any audits or reviews of Mineral Resource estimates.	No Mineral Resource defined
Discussion of relative accuracy/confidence	 Where appropriate a statement of the relative accuracy and confidence level in the Mineral Resource estimate using an approach or procedure deemed appropriate by the Competent Person. For example, the application of statistical or geostatistical procedures to quantify the relative accuracy of the resource within stated confidence limits, or, if such an approach is not deemed appropriate, a qualitative discussion of the factors that could affect the relative accuracy and confidence of the estimate. The statement should specify whether it relates to global or local estimates, and, if local, state the relevant tonnages, which should be relevant to technical and economic evaluation. Documentation should include assumptions made and the procedures used. These statements of relative accuracy and confidence of the estimate should be compared with production data, where available. 	No Mineral Resource defined



Criteria	JORC Code explanation	Commentary
Study status	 The type and level of study undertaken to enable Mineral Resources to be converted to Ore Reserves. The Code requires that a study to at least Pre-Feasibility Study level has been undertaken to convert Mineral Resources to Ore Reserves. Such studies will have been carried out and will have determined a mine plan that is technically achievable and economically viable, and that material Modifying Factors have been considered. 	No Mineral Resource defined
Cut-off parameters	The basis of the cut-off grade(s) or quality parameters applied.	No Mineral Resource defined
Mining factors or assumptions	 The method and assumptions used as reported in the Pre-Feasibility or Feasibility Study to convert the Mineral Resource to an Ore Reserve (i.e. either by application of appropriate factors by optimisation or by preliminary or detailed design). The choice, nature and appropriateness of the selected mining method(s) and other mining parameters including associated design issues such as pre-strip, access, etc. The assumptions made regarding geotechnical parameters (eg pit slopes, stope sizes, etc), grade control and pre-production drilling. The major assumptions made and Mineral Resource model used for pit and stope optimisation (if appropriate). The mining dilution factors used. Any minimum mining widths used. The manner in which Inferred Mineral Resources are utilised in mining studies and the sensitivity of the outcome to their inclusion. The infrastructure requirements of the selected mining methods. 	No Mineral Resource defined
Metallurgical factors or assumptions	 The metallurgical process proposed and the appropriateness of that process to the style of mineralisation. Whether the metallurgical process is well-tested technology or novel in nature. 	No Mineral Resource defined



Criteria	JORC Code explanation	Commentary
	 The nature, amount and representativeness of metallurgical test work undertaken, the nature of the metallurgical domaining applied and the corresponding metallurgical recovery factors applied. Any assumptions or allowances made for deleterious elements. The existence of any bulk sample or pilot scale test work and the degree to which such samples are considered representative of the orebody as a whole. For minerals that are defined by a specification, has the ore reserve estimation been based on the appropriate mineralogy to meet the specifications? 	
Environmen- tal	The status of studies of potential environmental impacts of the mining and processing operation. Details of waste rock characterisation and the consideration of potential sites, status of design options considered and, where applicable, the status of approvals for process residue storage and waste dumps should be reported.	No Mineral Resource defined
Infrastructure	 The existence of appropriate infrastructure: availability of land for plant development, power, water, transportation (particularly for bulk commodities), labour, accommodation; or the ease with which the infrastructure can be provided, or accessed. 	No Mineral Resource defined
Costs	 The derivation of, or assumptions made, regarding projected capital costs in the study. The methodology used to estimate operating costs. Allowances made for the content of deleterious elements. The source of exchange rates used in the study. Derivation of transportation charges. The basis for forecasting or source of treatment and refining charges, penalties for failure to meet specification, etc. The allowances made for royalties payable, both Government and private. 	No Mineral Resource defined



Criteria	JORC Code explanation	Commentary
Revenue factors	 The derivation of, or assumptions made regarding revenue factors including head grade, metal or commodity price(s) exchange rates, transportation and treatment charges, penalties, net smelter returns, etc. The derivation of assumptions made of metal or commodity price(s), for the principal metals, minerals and co-products. 	No Mineral Resource defined
Market assessment	 The demand, supply and stock situation for the particular commodity, consumption trends and factors likely to affect supply and demand into the future. A customer and competitor analysis along with the identification of likely market windows for the product. Price and volume forecasts and the basis for these forecasts. For industrial minerals the customer specification, testing and acceptance requirements prior to a supply contract. 	No Mineral Resource defined
Economic	 The inputs to the economic analysis to produce the net present value (NPV) in the study, the source and confidence of these economic inputs including estimated inflation, discount rate, etc. NPV ranges and sensitivity to variations in the significant assumptions and inputs. 	No Mineral Resource defined
Social	The status of agreements with key stakeholders and matters leading to social licence to operate.	No Mineral Resource defined
Other	 To the extent relevant, the impact of the following on the project and/or on the estimation and classification of the Ore Reserves: Any identified material naturally occurring risks. The status of material legal agreements and marketing arrangements. The status of governmental agreements and approvals critical to the viability of the project, such as mineral tenement status, and government and statutory approvals. There must be reasonable grounds to expect that all necessary Government approvals will be received within the timeframes anticipated in the Pre-Feasibility or Feasibility study. Highlight and discuss the materiality of any 	No Mineral Resource defined



Criteria	JORC Code explanation	Commentary
Classification	unresolved matter that is dependent on a third party on which extraction of the reserve is contingent. The basis for the classification of the Ore Reserves into varying	No Mineral Resource defined
Classification	 The basis for the classification of the Gre Reserves into varying confidence categories. Whether the result appropriately reflects the Competent Person's view of the deposit. The proportion of Probable Ore Reserves that have been derived from Measured Mineral Resources (if any). 	TWO MINISTRA PRESCUENCE CONTINUES
Audits or reviews	The results of any audits or reviews of Ore Reserve estimates.	No Mineral Resource defined
Discussion of relative accuracy/confidence	 Where appropriate a statement of the relative accuracy and confidence level in the Ore Reserve estimate using an approach or procedure deemed appropriate by the Competent Person. For example, the application of statistical or geostatistical procedures to quantify the relative accuracy of the reserve within stated confidence limits, or, if such an approach is not deemed appropriate, a qualitative discussion of the factors which could affect the relative accuracy and confidence of the estimate. The statement should specify whether it relates to global or local estimates, and, if local, state the relevant tonnages, which should be relevant to technical and economic evaluation. Documentation should include assumptions made and the procedures used. Accuracy and confidence discussions should extend to specific discussions of any applied Modifying Factors that may have a material impact on Ore Reserve viability, or for which there are remaining areas of uncertainty at the current study stage. It is recognised that this may not be possible or appropriate in all circumstances. These statements of relative accuracy and confidence of the estimate should be compared with production data, where available. 	No Mineral Resource defined