

HIGHEST GRADE DRILL INTERCEPT TO DATE AT ROOT PROJECT: 4.06% Li₂O

HIGHLIGHTS

- **Exceptional high-grade drill success at McCombe deposit, Root Project.**
- **Assays received for a further five holes from the Phase 1 diamond program including:**
 - RL-22-0013: **8.0m @ 1.72% Li₂O** from 64.0m (incl. **2.0m @ 4.06% Li₂O** from 64.6m)
 - RL-22-0014: **8.4m @ 1.32% Li₂O** from 102.0m (incl. **1.0m @ 3.91% Li₂O** from 103.6m)
 - RL-22-0015: **13.4m @ 1.24% Li₂O** from 28.9m (incl. **1.0m @ 3.16% Li₂O** from 29.3m)
 - RL-22-0016A: **6.3m @ 1.52% Li₂O** from 66.3m (incl. **1.0m @ 2.38% Li₂O** from 70.7m)
- **31 holes have been drilled to date at McCombe with two diamond drill rigs operating 24/7**
- **Phase 1 definition drilling completed for 22 holes, assays pending for 8 holes**
- **Phase 2 extensional drilling in progress with strong visual spodumene logged in pegmatite intercepts; 9 holes completed, assays pending**
- **McCombe potentially joining with the Morrison pegmatite system to form a structure over several kilometres long**
- **Grab sample from new spodumene outcrop discovery at Root Bay prospect assayed 2.39% Li₂O**
- **GT1 opting to begin environmental baseline surveys and permitting process**
- **Maiden Root Mineral Resource estimate on track for Q1 2023**

Green Technology Metals Limited (**ASX: GT1**)(**GT1** or the **Company**), a Canadian-focused multi-asset lithium business, is pleased to announce further high-grade lithium assay results from its 100%-owned Root Project, located approximately 200km west of its flagship Seymour Project in Ontario, Canada. Drilling at Root is initially focussed on the McCombe LCT pegmatite system, targeting rapid delineation of a maiden Mineral Resource estimate for this deposit.

“Recent assay returns have confirmed that McCombe is higher grade than originally interpreted based on historical data. The Root Project as a whole is also developing into a much larger complex, with McCombe potentially joining with Morrison to form a structure over several kilometres long, and recent spodumene discoveries at Root Bay confirming it extends east and west along a magnetic high.”

- *GT1 Chief Executive Officer, Luke Cox*



McCombe Deposit (Root Project)

The McCombe LCT (Lithium-Caesium-Tantalum) pegmatite is currently the most advanced prospect at the Root Project. Historical drilling completed by previous owners from 1950 to 2016 intersected numerous pegmatites, generally dipping to the south and striking east-west. Phase 1 and Phase 2 drilling by GT1 has now demonstrated McCombe to be a much simpler mineralised system: one major pegmatite averaging 10m thickness (ranging 2m to 19m), striking east-west with shallow dip approximately 30 degrees to the south, and a second pegmatite striking northeast with similar thickness.




Figure 1: Plan view of McCombe interpreted pegmatite, thickness, and grades.

The average grades, spodumene crystal size and crystal mass returned in the recent drilling at McCombe correlate well with the historic down dip continuity drill hole completed in 2016, which intercepted **67m @ 1.75% Li₂O** (see GT1 ASX release dated 8 November 2021, *Prospectus*). A second similar pegmatite has been intersected at the mid-point of the main pegmatite striking northeast and dipping to the southeast, with further targeted drilling set to extend this pegmatite to its natural limits.

Phase 1 drilling at McCombe has been completed, comprised of twenty-two (22) resource definition diamond holes. Assays have been returned for fourteen (14) holes all intersected thick and continuous high grade spodumene pegmatites from surface (refer to ASX announcement: All holes have intersected spodumene bearing pegmatite, 28 October 2022) with the recent holes returning the highest-grade intercept to date, **2m @ 4.06% Li₂O** (RL-22-0013) within a broader 8m pegmatite intercept averaging 1.72% Li₂O from 64m downhole. Assays are still pending for the last eight (8) holes (see Figures 1 and 2) and are expected to be received in the coming weeks.

Phase 2 extensional diamond drilling at McCombe is in progress, with two drill rigs operating around-the-clock. The Phase 2 program has delivered significant expansion of the McCombe deposit already, with strong visual spodumene logged in robust extensional pegmatite intercepts (see Table 1 and Figures 1 and 2). To date, nine (9) holes of the Phase 2

program have been completed, with all assays pending. Estimation of a maiden Root Mineral Resource remains on track for Q1 2023.




Figure 2: Section map (A-B) looking east, highlighting the start of the second pegmatite to the northeast

Table 1: McCombe drilling results – Phases 1 and 2 (Vis Est.% = Visual estimate of Spodumene mineral abundance*)

Hole	Easting	Northing	RL	Dip	Azi	Depth	From	To	Interval	Vis Est. %	Li ₂ O
RL-22-001	590,698	5,643,629	397	-59	358	60	11.8	24.2	12.4		1.77
RL-22-002	590,700	5,643,575	394	-62	0	72	42.2	57.5	15.3		1.20
RL-22-003	590,699	5,643,517	394	-58	358	102	72.0	83.5	11.5		2.03
RL-22-004	590,698	5,643,482	397	-61	357	144	80.5	87.4	7.0		1.41
RL-22-005	590,699	5,643,421	396	-60	359	147	90.8	100.7	9.9		0.25
RL-22-006	590,800	5,643,604	399	-59	360	120	21.7	31.2	9.5		1.54
RL-22-007	590,799	5,643,549	393	-61	359	117	64.9	74.7	9.8		1.51
RL-22-008	590,801	5,643,505	392	-61	359	162	71.5	80.3	8.8		1.81
RL-22-009	590,799	5,643,441	395	-61	2	186	91.7	99.4	7.7		0.54
RL-22-010	590,792	5,643,405	395	-61	358	150	107.8	114.7	6.9		0.80
RL-22-013	590,906	5,643,649	397	-60	360	132	64.0	72.0	8.0		1.72
RL-22-014	590,900	5,643,602	397	-60	360	129	102.0	110.4	8.4		1.32
RL-22-015	590,962	5,643,691	392	-60	360	93	28.9	42.3	13.4		1.24
RL-22-016A	590,894	5,643,540	394	-61	3	156	67.3	73.6	6.3		1.44
RL-22-017	590,957	5,643,575	396	-60	360	120	53.8	60.0	6.2	15	
RL-22-018	591,011	5,643,702	390	-61	1	90	51.8	64.4	12.6	15	
RL-22-019	591,006	5,643,574	397	-60	2	120	23.1	26.7	3.5	10	
RL-22-020	590,901	5,643,508	389	-60	360	150	78.0	82.8	4.8	15	
RL-22-021	590,999	5,643,481	397	-60	360	181	111.3	118.7	7.4	15	
RL-22-022	590,650	5,643,525	394	-59	0	152	47.4	61.4	14.0	20	
RL-22-023	590,700	5,643,625	397	-61	2	189	12.4	25.5	13.1	15	
RL-22-024	590,900	5,643,425	388	-60	2	150	85.6	93.0	7.4	15	
RL-22-025	590,850	5,643,600	396	-60	360	141	30.1	37.8	7.7	15	
RL-22-027	590,850	5,643,651	397	-59	358	108	3.4	15.6	12.3	15	
RL-22-029	590,850	5,643,475	392	-60	360	227	106.4	112.3	5.9	15	
RL-22-033	590,599	5,643,489	395	-58	4	162	2.8	8.0	5.2	10	
RL-22-035	590,643	5,643,487	397	-59	0	162	66.5	79.2	12.7	10	
RL-22-037	590,596	5,643,419	392	-60	-	180	40.1	43.8	3.8	10	
RL-22-038	591,045	5,643,706	390	-60	-	141	81.5	90.0	8.4	10	
RL-22-040	591,058	5,643,675	389	-60	360	120	94.0	103.0	9.0	10	
RL-22-041	590,633	5,643,399	397	-59	359	201	94.2	113.7	19.5	10	

* In relation to the disclosure of visual mineralisation, the Company cautions that visual estimates of mineral abundance should never be considered a proxy or substitute for laboratory analysis. Laboratory assay results are required to determine the widths and grade of the visible mineralisation reported in preliminary geological logging. The Company will update the market when laboratory analytical results become available. The reported intersections are down hole measurements and are not necessarily true width. Descriptions of the mineral amounts seen and logged in the core are qualitative, visual estimates only (they are listed in order of abundance of estimated combined percentages).



Figure 3: RL-22-003 – Whole NQ diamond core showing high density spodumene crystal laths, 11.5m @ 2.03% Li₂O

Substantial further targets at Morrison and Root Bay

The **Morrison** LCT spodumene pegmatites, located approximately 1km east of McCombe, were explored by Consolidated Morrison Explorations Ltd in the mid to late 1950's. The pegmatites strike east-west and dip about 30 degrees towards the south. Outcrop of the pegmatite is about 200m long and tested by trenching, but historical drilling has also proved the strike of the pegmatite to be at least 1.6km.

The Morrison pegmatites are open along-strike and down-dip.

The **Root Bay** LCT spodumene pegmatite has no historical drilling, however a channel sample returned 14m @ 1.67% Li₂O including 3m at 2.24% Li₂O (see GT1 ASX release dated 8 November 2021, *Prospectus*). Field exploration mapping completed by GT1 in September and October 2022 has located additional spodumene occurrences approximately 300m west along a magnetic and topographic ridge running east-west with a **grab sample returning 2.39% Li₂O** (see Figure 4). The initial geological model (hypothesis) has the pegmatites cross-cutting the magnetic high, north-south in a potential stacked system.

Exploration drilling programs are in planning to progressively test these two target areas over the next 12 months, building upon the recent success at McCombe.




Figure 4: New spodumene discoveries located at Root Bay (Sample 1109951, location easting 600500 northing 5642000)

This ASX release has been approved for release by the Board.

KEY CONTACTS

Investors

Luke Cox

Chief Executive Officer

info@greentm.com.au

+61 8 6557 6825

Media

Jacinta Martino

Investor Relations and Media

ir@greentm.com.au

+61 430 147 046

Green Technology Metals (ASX:GT1)

GT1 is a North American focussed lithium exploration and development business. The Company's 100% owned Ontario Lithium Projects comprise high-grade, hard rock spodumene assets (Seymour, Root and Wisa) and lithium exploration claims (Allison and Solstice) located on highly prospective Archean Greenstone tenure in north-west Ontario, Canada.

All sites are proximate to excellent existing infrastructure (including hydro power generation and transmission facilities), readily accessible by road, and with nearby rail delivering transport optionality.

Seymour has an existing Mineral Resource estimate of 9.9 Mt @ 1.04% Li₂O (comprised of 5.2 Mt at 1.29% Li₂O Indicated and 4.7 Mt at 0.76% Li₂O Inferred).¹ Accelerated, targeted exploration across all three projects delivers outstanding potential to grow resources rapidly and substantially.



¹ For full details of the Seymour Mineral Resource estimate, see GT1 ASX release dated 23 June 2022, *Interim Seymour Mineral Resource Doubles to 9.9Mt*. The Company confirms that it is not aware of any new information or data that materially affects the information in that release and that the material assumptions and technical parameters underpinning this estimate continue to apply and have not materially changed.

APPENDIX A: IMPORTANT NOTICES

Competent Person's Statements

Information in this report relating to Exploration Results is based on information reviewed by Mr Luke Cox (Fellow AusIMM). Mr Cox has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined by the 2012 Edition of the Australasian Code for reporting of Exploration Results, Mineral Resources and Ore Reserves. Mr Cox consents to the inclusion of the data in the form and context in which it appears in this release. Mr Cox is the Chief Executive Officer of the Company and holds securities in the Company.

No new information

Except where explicitly stated, this announcement contains references to prior exploration results, all of which have been cross-referenced to previous market announcements made by the Company. The Company confirms that it is not aware of any new information or data that materially affects the information included in the relevant market announcements.

The information in this report relating to the Mineral Resource estimate for the Seymour Project is extracted from the Company's ASX announcement dated 23 June 2022. GT1 confirms that it is not aware of any new information or data that materially affects the information included in the original announcement and that all material assumptions and technical parameters underpinning the Mineral Resource estimate continue to apply.

Forward Looking Statements

Certain information in this document refers to the intentions of Green Technology Metals Limited (ASX: GT1), however these are not intended to be forecasts, forward looking statements or statements about the future matters for the purposes of the Corporations Act or any other applicable law. Statements regarding plans with respect to GT1's projects are forward looking statements and can generally be identified by the use of words such as 'project', 'foresee', 'plan', 'expect', 'aim', 'intend', 'anticipate', 'believe', 'estimate', 'may', 'should', 'will' or similar expressions. There can be no assurance that the GT1's plans for its projects will proceed as expected and there can be no assurance of future events which are subject to risk, uncertainties and other actions that may cause GT1's actual results, performance or achievements to differ from those referred to in this document. While the information contained in this document has been prepared in good faith, there can be given no assurance or guarantee that the occurrence of these events referred to in the document will occur as contemplated. Accordingly, to the maximum extent permitted by law, GT1 and any of its affiliates and their directors, officers, employees, agents and advisors disclaim any liability whether direct or indirect, express or limited, contractual, tortious, statutory or otherwise, in respect of, the accuracy, reliability or completeness of the information in this document, or likelihood of fulfilment of any forward-looking statement or any event or results expressed or implied in any forward-looking statement; and do not make any representation or warranty, express or implied, as to the accuracy, reliability or completeness of the information in this document, or likelihood of fulfilment of any forward-looking statement or any event or results expressed or implied in any forward-looking statement; and disclaim all responsibility and liability for these forward-looking statements (including, without limitation, liability for negligence).

APPENDIX B: JORC CODE, 2012 EDITION – Table 1 Report

Section 1 Sampling Techniques and Data


Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual 	<p>The McCombe deposit at the Root project is a new discovery and, as such, has not been historically sampled.</p> <p>An excavator has exposed and enlarged the outcrop area to make it amenable to mapping and sampling.</p> <p>GT1 commenced a diamond drilling on September 3, 2022 at the McCombe prospect with 31 holes completed to date and more planned.</p> <p>Diamond Drilling</p> <ul style="list-style-type: none"> Diamond drilling was used to obtain nominally 1m downhole samples of core. NQ core samples were ½ cored using a diamond saw with ½ the core placed in numbered sample bags for assaying and the other half retained in sequence in the core tray. ½ core samples were approximately 3.0kg in weight with a minimum weight of 500grams. Core was cut down the apex of the core and the same downhole side of the core selected for assaying to reduce potential sampling bias. <p>Channel Samples</p> <ul style="list-style-type: none"> Preparation prior to obtaining the channel samples including grid and geo-references and marking of the pegmatite structures. Samples were cut across the pegmatite with a diamond saw perpendicular to strike. Average 1 metre samples are obtained, logged, removed and bagged and secured in accordance with QAQC procedures. Sampling continued past the Spodumene -Pegmatite zone, even if it is truncated by Mafic Volcanic a later intrusion. Samples were then transported directly to the laboratory for analysis accompanied with the log and instruction forms. Bagging of the samples was supervised by a geologist to ensure there are no numbering mix-ups. One tag from a triple tag book was inserted in the sample bag. <p>Grab Samples</p> <ul style="list-style-type: none"> Preparation prior to obtaining the grab sample including logging location with D/GPS, geological setting and rock identification and mineralogy Samples were then transported directly to the laboratory for analysis accompanied with the log and instruction forms. Bagging of the samples was supervised by a geologist to ensure there are no numbering mix-ups. One tag from a triple tag book was inserted in the sample bag.

Criteria	JORC Code explanation	Commentary
	<p><i>commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i></p>	
Drilling techniques	<ul style="list-style-type: none"> • <i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i> 	<ul style="list-style-type: none"> • Tri-cone drilling was undertaken through the thin overburden prior to NQ2 diamond drilling through the primary rock using a standard tube.
Drill sample recovery	<ul style="list-style-type: none"> • <i>Method of recording and assessing core and chip sample recoveries and results assessed.</i> • <i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i> • <i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i> 	<ul style="list-style-type: none"> • No core was recovered through the overburden tri-coned section of the hole (top 5m of the hole) • Core recovery through the primary rock and mineralised pegmatite zones was 98%. Country rock, mainly meta basalts showed high, 96% recoveries. • The core has not been assayed yet so no correlation between grade and recovery can be made at this time. Recovery was determined by measuring the recovered metres in the core trays against the drillers core block depths for each run.
Logging	<ul style="list-style-type: none"> • <i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and</i> 	<ul style="list-style-type: none"> • Each sample was logged for lithology, minerals, grain size and texture as well as alteration, sulphide content, and any structures. • Logging is qualitative in nature. • Samples are representative of an interval or length. • Sampling will be undertaken for the entire cross strike length of the intersected pegmatite unit at nominal 1m intervals with breaks at geological contacts. Sampling extended into the country mafic rock.


Criteria	JORC Code explanation	Commentary
	<p><i>metallurgical studies.</i></p> <ul style="list-style-type: none"> • Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. • The total length and percentage of the relevant intersections logged. 	
Sub-sampling techniques and sample preparation	<ul style="list-style-type: none"> • If core, whether cut or sawn and whether quarter, half or all core taken. • If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. • For all sample types, the nature, quality and appropriateness of the sample preparation technique. • Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. • Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. • Whether sample sizes are appropriate to the grain size of the material being sampled. 	<ul style="list-style-type: none"> • Each ½ core sample was dried, crushed to entirety to 90% -10 mesh, riffle split (up to 5 kg) and then pulverized with hardened steel (250 g sample to 95% -150 mesh)(includes cleaner sand). • Blanks and Certified Reference samples will be inserted in each batch submitted to the laboratory at a rate of approximately 1:20. • The sample preparation process is considered representative of the whole core sample.
Quality of assay data and	<ul style="list-style-type: none"> • The nature, quality and appropriateness of the assaying and 	<ul style="list-style-type: none"> • Actlabs inserted internal standards, blanks and pulp duplicates within each sample batch as part of their own internal monitoring of quality control. • GT1 inserted certified lithium standards and blanks into each batch submitted to Actlabs to

Criteria	JORC Code explanation	Commentary																																																																																																																																								
laboratory tests	<p>laboratory procedures used and whether the technique is considered partial or total.</p> <ul style="list-style-type: none"> For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	<p>monitor precision and bias performance at a rate of 1:20.</p> <ul style="list-style-type: none"> The major element oxides and trace elements including Rb, Cs, Nb, Ta and Be were analysed by FUS-ICP and FUS-MS (4Litho-Pegmatite Special) analytical codes which uses a lithium metaborate tetraborate fusion with analysis by ICP and ICPMS. QAQC results to date do not indicate any significant issues with the assay <div data-bbox="574 436 1430 886" data-label="Figure"> <p>Oreas_751_Li</p> <table border="1"> <caption>Data for Oreas_751_Li</caption> <thead> <tr> <th>Assay</th> <th>Assays Loaded</th> <th>Expected</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4687</td> <td>4675</td> </tr> <tr> <td>2</td> <td>4687</td> <td>4675</td> </tr> <tr> <td>3</td> <td>4600</td> <td>4675</td> </tr> </tbody> </table> </div> <div data-bbox="574 892 1224 1165" data-label="Table"> <table border="1"> <thead> <tr> <th colspan="2">Summary Statistics</th> <th colspan="2">3SD</th> </tr> <tr> <th>No of samples</th> <th></th> <th>3 Min Cert</th> <th>Max Cert</th> </tr> </thead> <tbody> <tr> <td>Certified Value</td> <td>4,675</td> <td>4,165</td> <td>5,185</td> </tr> <tr> <td>Actual Mean</td> <td>4,687</td> <td>4,600</td> <td>4,730</td> </tr> <tr> <td>Abs Difference</td> <td>11</td> <td></td> <td></td> </tr> <tr> <td>Rel. Difference</td> <td>0%</td> <td></td> <td></td> </tr> <tr> <td>Records Outside 2SD</td> <td>0</td> <td>0% Fail Rate</td> <td></td> </tr> <tr> <td>Records Outside 3SD</td> <td>0</td> <td>0% Fail Rate</td> <td></td> </tr> </tbody> </table> </div> <div data-bbox="574 1171 1419 1619" data-label="Figure"> <p>Oreas_753_Li</p> <table border="1"> <caption>Data for Oreas_753_Li</caption> <thead> <tr> <th>Assay</th> <th>Assays Loaded</th> <th>Expected</th> </tr> </thead> <tbody> <tr><td>1</td><td>9317</td><td>9489</td></tr> <tr><td>2</td><td>9317</td><td>9489</td></tr> <tr><td>3</td><td>9317</td><td>9489</td></tr> <tr><td>4</td><td>9317</td><td>9489</td></tr> <tr><td>5</td><td>9317</td><td>9489</td></tr> <tr><td>6</td><td>9317</td><td>9489</td></tr> <tr><td>7</td><td>9317</td><td>9489</td></tr> <tr><td>8</td><td>9317</td><td>9489</td></tr> <tr><td>9</td><td>9317</td><td>9489</td></tr> <tr><td>10</td><td>9317</td><td>9489</td></tr> <tr><td>11</td><td>9317</td><td>9489</td></tr> <tr><td>12</td><td>9317</td><td>9489</td></tr> <tr><td>13</td><td>9317</td><td>9489</td></tr> <tr><td>14</td><td>9317</td><td>9489</td></tr> <tr><td>15</td><td>9317</td><td>9489</td></tr> <tr><td>16</td><td>9317</td><td>9489</td></tr> <tr><td>17</td><td>9317</td><td>9489</td></tr> <tr><td>18</td><td>9317</td><td>9489</td></tr> <tr><td>19</td><td>9317</td><td>9489</td></tr> </tbody> </table> </div> <div data-bbox="537 1633 1110 1879" data-label="Table"> <table border="1"> <thead> <tr> <th colspan="2">Summary Statistics</th> <th colspan="2">3SD</th> </tr> <tr> <th>No of samples</th> <th></th> <th>19 Min Cert</th> <th>Max Cert</th> </tr> </thead> <tbody> <tr> <td>Certified Value</td> <td>10,179</td> <td>9,489</td> <td>10,869</td> </tr> <tr> <td>Actual Mean</td> <td>9,317</td> <td>15</td> <td>10,400</td> </tr> <tr> <td>Abs Difference</td> <td>861</td> <td></td> <td></td> </tr> <tr> <td>Rel. Difference</td> <td>8%</td> <td></td> <td></td> </tr> <tr> <td>Records Outside 2SD</td> <td>3</td> <td>100% Fail Rate</td> <td></td> </tr> <tr> <td>Records Outside 3SD</td> <td>3</td> <td>100% Fail Rate</td> <td></td> </tr> </tbody> </table> </div>	Assay	Assays Loaded	Expected	1	4687	4675	2	4687	4675	3	4600	4675	Summary Statistics		3SD		No of samples		3 Min Cert	Max Cert	Certified Value	4,675	4,165	5,185	Actual Mean	4,687	4,600	4,730	Abs Difference	11			Rel. Difference	0%			Records Outside 2SD	0	0% Fail Rate		Records Outside 3SD	0	0% Fail Rate		Assay	Assays Loaded	Expected	1	9317	9489	2	9317	9489	3	9317	9489	4	9317	9489	5	9317	9489	6	9317	9489	7	9317	9489	8	9317	9489	9	9317	9489	10	9317	9489	11	9317	9489	12	9317	9489	13	9317	9489	14	9317	9489	15	9317	9489	16	9317	9489	17	9317	9489	18	9317	9489	19	9317	9489	Summary Statistics		3SD		No of samples		19 Min Cert	Max Cert	Certified Value	10,179	9,489	10,869	Actual Mean	9,317	15	10,400	Abs Difference	861			Rel. Difference	8%			Records Outside 2SD	3	100% Fail Rate		Records Outside 3SD	3	100% Fail Rate	
Assay	Assays Loaded	Expected																																																																																																																																								
1	4687	4675																																																																																																																																								
2	4687	4675																																																																																																																																								
3	4600	4675																																																																																																																																								
Summary Statistics		3SD																																																																																																																																								
No of samples		3 Min Cert	Max Cert																																																																																																																																							
Certified Value	4,675	4,165	5,185																																																																																																																																							
Actual Mean	4,687	4,600	4,730																																																																																																																																							
Abs Difference	11																																																																																																																																									
Rel. Difference	0%																																																																																																																																									
Records Outside 2SD	0	0% Fail Rate																																																																																																																																								
Records Outside 3SD	0	0% Fail Rate																																																																																																																																								
Assay	Assays Loaded	Expected																																																																																																																																								
1	9317	9489																																																																																																																																								
2	9317	9489																																																																																																																																								
3	9317	9489																																																																																																																																								
4	9317	9489																																																																																																																																								
5	9317	9489																																																																																																																																								
6	9317	9489																																																																																																																																								
7	9317	9489																																																																																																																																								
8	9317	9489																																																																																																																																								
9	9317	9489																																																																																																																																								
10	9317	9489																																																																																																																																								
11	9317	9489																																																																																																																																								
12	9317	9489																																																																																																																																								
13	9317	9489																																																																																																																																								
14	9317	9489																																																																																																																																								
15	9317	9489																																																																																																																																								
16	9317	9489																																																																																																																																								
17	9317	9489																																																																																																																																								
18	9317	9489																																																																																																																																								
19	9317	9489																																																																																																																																								
Summary Statistics		3SD																																																																																																																																								
No of samples		19 Min Cert	Max Cert																																																																																																																																							
Certified Value	10,179	9,489	10,869																																																																																																																																							
Actual Mean	9,317	15	10,400																																																																																																																																							
Abs Difference	861																																																																																																																																									
Rel. Difference	8%																																																																																																																																									
Records Outside 2SD	3	100% Fail Rate																																																																																																																																								
Records Outside 3SD	3	100% Fail Rate																																																																																																																																								


Criteria	JORC Code explanation	Commentary
----------	-----------------------	------------



Summary Statistics	3SD		
No of samples	19	Min Cert	Max Cert
Certified Value	-	-	-
Actual Mean	763	-	14,400
Abs Difference	763		



Summary Statistics	
No of duplicates	38
Mean Original	2,648
Mean Duplicate	2,646
Abs Difference	2
Rel. Difference	0%

Criteria	JORC Code explanation	Commentary
Verification of sampling and assaying	<ul style="list-style-type: none"> The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	<ul style="list-style-type: none"> Most of the holes in the McCombe program to date are drilled close to existing historic drilling from the 1950's. Whilst the historic drilling suggests some spatial issues with the holes collar locations, the current drilling largely supports the existence of significant pegmatite and Li₂O intersections at McCombe. Historic drilling data could not be verified and QAQC was likely not included in the testing regime at the time. <ul style="list-style-type: none"> The laboratory assay results have been sourced directly from the laboratory and the laboratory file directly imported directly into GT1's SQL database. All north seeking gyroscope surveys are uploaded directly from the survey tool output file and visually validated. Geological logs and supporting data are uploaded directly to the database using custom built importers to ensure no chance of typographical errors. No adjustment to laboratory assay data was made other than conversion of Li ppm to Li₂O using a factor of 2.153
Location of data points	<ul style="list-style-type: none"> Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	<ul style="list-style-type: none"> A GPS reading was taken for each sample location using UTM NAD83 Zone15 (for Seymour); waypoint averaging or dGPS was performed when possible. GT1 undertook a Lidar survey of the Root area in 2022 (+/- 0.15m) which underpins the local topographic surface. GT1 has used continuous measurement north seeking gyroscope tools with readings retained every 5m downhole. 
Data spacing and distribution	<ul style="list-style-type: none"> Data spacing for reporting of Exploration Results. Whether the data spacing and 	<ul style="list-style-type: none"> NA - insufficient drilling has been undertaken to estimate the degree of geological and grade continuity to support a Mineral Resource or Ore Reserve.

Criteria	JORC Code explanation	Commentary
	<p>distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</p> <ul style="list-style-type: none"> Whether sample compositing has been applied. 	
Orientation of data in relation to geological structure	<ul style="list-style-type: none"> Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	<ul style="list-style-type: none"> The current drilling program is drilled to achieve as close to a representative intersection of the pegmatites as possible which dip moderately to the south. Holes are orientated approximately north and 60 degrees inclination. Grab and trench samples were taken where outcrop was available. All attempts were made to ensure trench samples represented traverses across strike of the pegmatite.
Sample security	<ul style="list-style-type: none"> The measures taken to ensure sample security. 	<ul style="list-style-type: none"> All core and samples were supervised and secured in a locked vehicle, warehouse, or container until delivered to Actlabs in Thunder Bay for cutting, preparation and analysis.
Audits or reviews	<ul style="list-style-type: none"> The results of any audits or reviews of sampling techniques and data. 	<ul style="list-style-type: none"> NA

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<ul style="list-style-type: none"> Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical 	<ul style="list-style-type: none"> Green Technology Metals (ASX:GT1) holds a 100% interest in the Ontario Lithium Projects (Seymour, Root and Wisa). Root Lithium Asset consist of 249 single and boundary cell claims (Exploration


Criteria	JORC Code explanation	Commentary
	<p><i>sites, wilderness or national park and environmental settings.</i></p> <ul style="list-style-type: none"> <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i> 	<p>Licences), 33 patent claims and 3 mining licence of occupation claims (total 285 claims) with a total claim area of approximately 5,376ha.</p> <ul style="list-style-type: none"> All Cell Claims are in good standing An Active Exploration Permit for 3 years exist over the Root Lithium Assets, including the McCombe Deposit, Morrison Prospect and Root Bay Prospect. There is an Early Exploration Agreement with Slate Falls Nation and Lac Seul First Nation, who are supportive of GT1 exploration activities.
<p><i>Exploration done by other parties</i></p>	<ul style="list-style-type: none"> <i>Acknowledgment and appraisal of exploration by other parties.</i> 	<ul style="list-style-type: none"> Regional exploration for lithium deposits commenced in the 1950's. In 1955-1956 Capital Lithium Mines Ltd. geologically mapped and sampled dikes near the McCombe Deposit with the highest recorded channel sample of 1.52m at 3.06%Li₂O. 7 drill holes (1,042.26m total) within the McCombe Deposit and Root Lake Prospect yielding low lithium assays. According to Mulligan (1965), Capital Lithium Mines Ltd. reported to Mulligan that they drilled at least 55 holes totalling 10469.88m in 1956. They delineated 4 pegmatite zones and announced a non-compliant NI 41-101 reserve calculation of 2.297 million tons at 1.3% Li₂O. However, none of that information is available on the government database. In 1956, Consolidated Morrison Explorations Ltd drilled 16 holes (1890m total) at the Morrison prospect recording 3.96m at 2.63% Li₂O. In 1956, Three Brothers Mining Exploration southwest of the McCombe Deposit that did not intersect pegmatite In 1957, Geo-Technical Development Company Limited on behalf of Continental Mining Exploration conducted a magnetometer survey and an electromagnetic check survey on the eastern claims of the Root Lithium Project to locate pyrrhotite mineralization In 1977, Northwest Geophysics Limited on behalf of Noranda Exploration Company Ltd. conducted an electromagnetic and magnetometer survey for sulphide conductors on a small package of

Criteria	JORC Code explanation	Commentary
		<p>claims east of the Morrison Prospect. Noranda also conducted a mapping and sampling program over the same area, mapped a new pegmatite dike and sampled a graphitic schist assaying 0.03% Cu and 0.15% Zn.</p> <ul style="list-style-type: none"> • In 1998, Harold A. Watts prospected, trenched and sampled spodumene-bearing pegmatites with the Morrison Prospect assaying up to 5.91% Li₂O. In 2002 stripped and blasted 2 more spodumene-bearing pegmatites near the Morrison prospect. • In 2005, Landore Resources Canada Inc. created a reconnaissance survey, mapping and sampling project mostly within the McCombe Deposit, but also in the Morrison and Root Lake Prospects. Highest sample was 3.69% Li₂O with the McCombe Deposit. • In 2008, Rockex Ltd. on behalf of Robert Allan Ross stripped and trenched 40 trenches for iron, gold and base metals associated with oxide iron formation. All Fe assays were above 25% (up to 47.5% Fe). 3 gold zones were discovered with assays up to 4.0g/t Au in Zone A (Root Bay Gold Prospect), 1.3%g/t Au over 0.5m in Trench 9, 0.19% Cu-Zn over 8m and up to 0.14% Li₂O in Zone B. Best assays of samples collected north-east area of Root Bay had up to 394ppm Zn, 389ppm Cu, 185ppm Ni, 102ppm Co and 57.0ppm Mo. • In 2009, Golden Dory Resources along with Harold A. Watts conducted a due diligence sampling program to validate historic data from the Morrison Prospect. Highest grab sample was 5.10% Li₂O and a channel sample of 5m at 4.44% Li₂O. • In 2011, Geo Data Solutions GDS Inc. on behalf of Rockex Ltd. flew a high-resolution helicopter borne aeromagnetic survey intersecting a small portion of the south-central claims owned by GM1. • In 2012, Stares Contracting on behalf of Golden Dory Resources Corporation conducted a ground magnetic survey near the Morrison Prospect to look for magnetic

Criteria	JORC Code explanation	Commentary
		<p>contrasts between pegmatites and metasedimentary units. They also conducted a prospecting (lithium) and soil sampling (gold) program at the Rook Lake Prospect and east of the Morrison Prospect. Highest Li assays within GM1 claims was 0.0037% Li₂O and a gold soil assay of 52ppb Au.</p> <ul style="list-style-type: none"> In 2016, Ardiden Ltd. conducted a drilled 7 diamond drill holes (469m total) within the McCombe deposit. Highest assay was 1m at 3.8% Li₂O. A hole drilled down dip intersected 70m at 1.7% Li₂O. An outcrop sampling within the Morrison and Root Bay Prospects yielded 0.04% Li₂O. Channel sample within the Morrison Prospect had 5m at 2.09% Li₂O and within the Root Bay Prospect, 14m at 1.67% Li₂O. In 2021, KBM Resources Group on behalf of Kenorland Minerals North America Ltd. conducted an 800km² aerial LIDAR acquisition survey over their South Uchi Property which intersects a very small portion of the patented claims held by GM1, just west of the McCombe Deposit.
Geology	<ul style="list-style-type: none"> <i>Deposit type, geological setting and style of mineralisation.</i> 	<ul style="list-style-type: none"> Regional Geology: The Root Lithium Asset is located within the Uchi Domain, predominately metavolcanic units interwoven with granitoid batholiths and English River Terrane, a highly metamorphosed to migmatized, clastic and chemical metasedimentary rock with abundant granitoid batholiths. They are part of the Superior craton, interpreted to be the amalgamation of Archean aged microcontinents and accretionary events. The boundary between the Uchi Domain and the English River Terrane is defined by the Sydney Lake – Lake St. Joseph fault, an east west trending, steeply dipping brittle ductile shear zone over 450km along strike and 1 – 3m wide. Several S-Type, peraluminous granitic plutons host rare-element mineralization near the Uchi Domain and English River subprovince boundary. These pegmatites include the Root Lake Pegmatite Group, Jubilee Lake Pegmatite Group, Sandy Creek Pegmatite and East Pashkokogan Lake Lithium Pegmatite. Local Geology: The Root Lithium Asset contains most of the pegmatites within the Root Lake Pegmatite Group including the McCombe Pegmatite, Morrison

Criteria	JORC Code explanation	Commentary
		<p>Prospect, Root Lake Prospect and Root Bay Prospect. The McCombe Pegmatite and Morrison Prospect are hosted in predominately mafic metavolcanic rock of the Uchi Domain. The Root Lake and Root Bay Prospects are hosted in predominately metasedimentary rocks of the English River Terrane. On the eastern end of the Root Lithium Asset there is a gold showing (Root Bay Gold Prospect) hosted in or proximal to silicate, carbonate, sulphide, and oxide iron formations of the English River Terrane.</p> <ul style="list-style-type: none"> • Ore Geology: The McCombe Pegmatite is internally zoned. These zones are classified by the tourmaline discontinuous zone along the pegmatite contact, white feldspar-rich wall zone, tourmaline-bearing, equigranular to porphyritic potassium feldspar sodic apalite zone, tourmaline-bearing, porphyritic potassium feldspar spodumene pegmatite zone and lepidolite-rich pods and seams (Breaks et al., 2003). Both the McCombe and Morrison pegmatites have been classified as complex-type, spodumene-subtype (Černý 1991a classification) based on the abundance of spodumene, highly evolved potassium feldspar chemistry and presence of petalite, mircolite, lepidolite and lithium-calcium liddicoatite (Breaks et al., 2003).
<p><i>Drill hole Information</i></p>	<ul style="list-style-type: none"> • <i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> <ul style="list-style-type: none"> ○ <i>easting and northing of the drill hole collar</i> ○ <i>elevation or RL (Reduced Level - elevation above sea level in metres) of the drill hole collar</i> ○ <i>dip and azimuth of the hole</i> ○ <i>down hole length and interception depth</i> ○ <i>hole length.</i> • <i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i> 	<ul style="list-style-type: none"> • McCombe lies within the western edge of the Root project and hosts a non-JORC compliant Mineral Resource based on 1950's drilling. • The deposit is being re-drilled to modern industry standards sampling NQ diamond core. Collar locations are noted below and all coordinates are in North American Datum 1983 (NAD83) Zone 15:

Criteria	JORC Code explanation	Commentary																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
		<table border="1"> <thead> <tr> <th>Hole</th> <th>Easting</th> <th>Northing</th> <th>RL</th> <th>Dip</th> <th>Azi</th> <th>Depth</th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr><td>RL-22-001</td><td>590,698</td><td>5,643,629</td><td>397</td><td>-59</td><td>358</td><td>60</td><td>11.8</td><td>24.2</td></tr> <tr><td>RL-22-002</td><td>590,700</td><td>5,643,575</td><td>394</td><td>-62</td><td>0</td><td>72</td><td>42.2</td><td>57.5</td></tr> <tr><td>RL-22-003</td><td>590,699</td><td>5,643,517</td><td>394</td><td>-58</td><td>358</td><td>102</td><td>72.0</td><td>83.5</td></tr> <tr><td>RL-22-004</td><td>590,698</td><td>5,643,482</td><td>397</td><td>-61</td><td>357</td><td>144</td><td>80.5</td><td>87.4</td></tr> <tr><td>RL-22-005</td><td>590,699</td><td>5,643,421</td><td>396</td><td>-60</td><td>359</td><td>147</td><td>90.8</td><td>100.7</td></tr> <tr><td>RL-22-006</td><td>590,800</td><td>5,643,604</td><td>399</td><td>-59</td><td>360</td><td>120</td><td>21.7</td><td>31.2</td></tr> <tr><td>RL-22-007</td><td>590,799</td><td>5,643,549</td><td>393</td><td>-61</td><td>359</td><td>117</td><td>64.9</td><td>74.7</td></tr> <tr><td>RL-22-008</td><td>590,801</td><td>5,643,505</td><td>392</td><td>-61</td><td>359</td><td>162</td><td>71.5</td><td>80.3</td></tr> <tr><td>RL-22-009</td><td>590,799</td><td>5,643,441</td><td>395</td><td>-61</td><td>2</td><td>186</td><td>91.7</td><td>99.4</td></tr> <tr><td>RL-22-010</td><td>590,792</td><td>5,643,405</td><td>395</td><td>-61</td><td>358</td><td>150</td><td>107.8</td><td>114.7</td></tr> <tr><td>RL-22-013</td><td>590,906</td><td>5,643,649</td><td>397</td><td>-60</td><td>360</td><td>132</td><td>64.0</td><td>72.0</td></tr> <tr><td>RL-22-014</td><td>590,900</td><td>5,643,602</td><td>397</td><td>-60</td><td>360</td><td>129</td><td>102.0</td><td>110.4</td></tr> <tr><td>RL-22-015</td><td>590,962</td><td>5,643,691</td><td>392</td><td>-60</td><td>360</td><td>93</td><td>28.9</td><td>42.3</td></tr> <tr><td>RL-22-016A</td><td>590,894</td><td>5,643,540</td><td>394</td><td>-61</td><td>3</td><td>156</td><td>67.3</td><td>73.6</td></tr> <tr><td>RL-22-017</td><td>590,957</td><td>5,643,575</td><td>396</td><td>-60</td><td>360</td><td>120</td><td>53.8</td><td>60.0</td></tr> <tr><td>RL-22-018</td><td>591,011</td><td>5,643,702</td><td>390</td><td>-61</td><td>1</td><td>90</td><td>51.8</td><td>64.4</td></tr> <tr><td>RL-22-019</td><td>591,006</td><td>5,643,574</td><td>397</td><td>-60</td><td>2</td><td>120</td><td>23.1</td><td>26.7</td></tr> <tr><td>RL-22-020</td><td>590,901</td><td>5,643,508</td><td>389</td><td>-60</td><td>360</td><td>150</td><td>78.0</td><td>82.8</td></tr> <tr><td>RL-22-021</td><td>590,999</td><td>5,643,481</td><td>397</td><td>-60</td><td>360</td><td>181</td><td>111.3</td><td>118.7</td></tr> <tr><td>RL-22-022</td><td>590,650</td><td>5,643,525</td><td>394</td><td>-59</td><td>0</td><td>152</td><td>47.4</td><td>61.4</td></tr> <tr><td>RL-22-023</td><td>590,700</td><td>5,643,625</td><td>397</td><td>-61</td><td>2</td><td>189</td><td>12.4</td><td>25.5</td></tr> <tr><td>RL-22-024</td><td>590,900</td><td>5,643,425</td><td>388</td><td>-60</td><td>2</td><td>150</td><td>85.6</td><td>93.0</td></tr> <tr><td>RL-22-025</td><td>590,850</td><td>5,643,600</td><td>396</td><td>-60</td><td>360</td><td>141</td><td>30.1</td><td>37.8</td></tr> <tr><td>RL-22-027</td><td>590,850</td><td>5,643,651</td><td>397</td><td>-59</td><td>358</td><td>108</td><td>3.4</td><td>15.6</td></tr> <tr><td>RL-22-029</td><td>590,850</td><td>5,643,475</td><td>392</td><td>-60</td><td>360</td><td>227</td><td>106.4</td><td>112.3</td></tr> <tr><td>RL-22-033</td><td>590,599</td><td>5,643,489</td><td>395</td><td>-58</td><td>4</td><td>162</td><td>2.8</td><td>8.0</td></tr> <tr><td>RL-22-035</td><td>590,643</td><td>5,643,487</td><td>397</td><td>-59</td><td>0</td><td>162</td><td>66.5</td><td>79.2</td></tr> <tr><td>RL-22-037</td><td>590,596</td><td>5,643,419</td><td>392</td><td>-60</td><td>-</td><td>180</td><td>40.1</td><td>43.8</td></tr> <tr><td>RL-22-038</td><td>591,045</td><td>5,643,706</td><td>390</td><td>-60</td><td>-</td><td>141</td><td>81.5</td><td>90.0</td></tr> <tr><td>RL-22-040</td><td>591,058</td><td>5,643,675</td><td>389</td><td>-60</td><td>360</td><td>120</td><td>94.0</td><td>103.0</td></tr> <tr><td>RL-22-041</td><td>590,633</td><td>5,643,399</td><td>397</td><td>-59</td><td>359</td><td>201</td><td>94.2</td><td>113.7</td></tr> </tbody> </table> <p> <ul style="list-style-type: none"> McCombe downhole pegmatites are summarised below. The downhole intervals of the McCombe pegmatites are approximate to true widths. </p> <table border="1"> <thead> <tr> <th>Hole</th> <th>From</th> <th>To</th> <th>Interval</th> <th>Vis Est. %</th> <th>Li₂O</th> </tr> </thead> <tbody> <tr><td>RL-22-001</td><td>11.8</td><td>24.2</td><td>12.4</td><td></td><td>1.77</td></tr> <tr><td>RL-22-002</td><td>42.2</td><td>57.5</td><td>15.3</td><td></td><td>1.20</td></tr> <tr><td>RL-22-003</td><td>72.0</td><td>83.5</td><td>11.5</td><td></td><td>2.03</td></tr> <tr><td>RL-22-004</td><td>80.5</td><td>87.4</td><td>7.0</td><td></td><td>1.41</td></tr> <tr><td>RL-22-005</td><td>90.8</td><td>100.7</td><td>9.9</td><td></td><td>0.25</td></tr> <tr><td>RL-22-006</td><td>21.7</td><td>31.2</td><td>9.5</td><td></td><td>1.54</td></tr> <tr><td>RL-22-007</td><td>64.9</td><td>74.7</td><td>9.8</td><td></td><td>1.51</td></tr> <tr><td>RL-22-008</td><td>71.5</td><td>80.3</td><td>8.8</td><td></td><td>1.81</td></tr> <tr><td>RL-22-009</td><td>91.7</td><td>99.4</td><td>7.7</td><td></td><td>0.54</td></tr> <tr><td>RL-22-010</td><td>107.8</td><td>114.7</td><td>6.9</td><td></td><td>0.80</td></tr> <tr><td>RL-22-013</td><td>64.0</td><td>72.0</td><td>8.0</td><td></td><td>1.72</td></tr> <tr><td>RL-22-014</td><td>102.0</td><td>110.4</td><td>8.4</td><td></td><td>1.32</td></tr> <tr><td>RL-22-015</td><td>28.9</td><td>42.3</td><td>13.4</td><td></td><td>1.24</td></tr> <tr><td>RL-22-016A</td><td>67.3</td><td>73.6</td><td>6.3</td><td></td><td>1.44</td></tr> <tr><td>RL-22-017</td><td>53.8</td><td>60.0</td><td>6.2</td><td>15</td><td></td></tr> <tr><td>RL-22-018</td><td>51.8</td><td>64.4</td><td>12.6</td><td>15</td><td></td></tr> <tr><td>RL-22-019</td><td>23.1</td><td>26.7</td><td>3.5</td><td>10</td><td></td></tr> <tr><td>RL-22-020</td><td>78.0</td><td>82.8</td><td>4.8</td><td>15</td><td></td></tr> <tr><td>RL-22-021</td><td>111.3</td><td>118.7</td><td>7.4</td><td>15</td><td></td></tr> <tr><td>RL-22-022</td><td>47.4</td><td>61.4</td><td>14.0</td><td>20</td><td></td></tr> <tr><td>RL-22-023</td><td>12.4</td><td>25.5</td><td>13.1</td><td>15</td><td></td></tr> <tr><td>RL-22-024</td><td>85.6</td><td>93.0</td><td>7.4</td><td>15</td><td></td></tr> <tr><td>RL-22-025</td><td>30.1</td><td>37.8</td><td>7.7</td><td>15</td><td></td></tr> <tr><td>RL-22-027</td><td>3.4</td><td>15.6</td><td>12.3</td><td>15</td><td></td></tr> <tr><td>RL-22-029</td><td>106.4</td><td>112.3</td><td>5.9</td><td>15</td><td></td></tr> <tr><td>RL-22-033</td><td>2.8</td><td>8.0</td><td>5.2</td><td>10</td><td></td></tr> <tr><td>RL-22-035</td><td>66.5</td><td>79.2</td><td>12.7</td><td>10</td><td></td></tr> <tr><td>RL-22-037</td><td>40.1</td><td>43.8</td><td>3.8</td><td>10</td><td></td></tr> <tr><td>RL-22-038</td><td>81.5</td><td>90.0</td><td>8.4</td><td>10</td><td></td></tr> <tr><td>RL-22-040</td><td>94.0</td><td>103.0</td><td>9.0</td><td>10</td><td></td></tr> <tr><td>RL-22-041</td><td>94.2</td><td>113.7</td><td>19.5</td><td>10</td><td></td></tr> </tbody> </table>	Hole	Easting	Northing	RL	Dip	Azi	Depth	From	To	RL-22-001	590,698	5,643,629	397	-59	358	60	11.8	24.2	RL-22-002	590,700	5,643,575	394	-62	0	72	42.2	57.5	RL-22-003	590,699	5,643,517	394	-58	358	102	72.0	83.5	RL-22-004	590,698	5,643,482	397	-61	357	144	80.5	87.4	RL-22-005	590,699	5,643,421	396	-60	359	147	90.8	100.7	RL-22-006	590,800	5,643,604	399	-59	360	120	21.7	31.2	RL-22-007	590,799	5,643,549	393	-61	359	117	64.9	74.7	RL-22-008	590,801	5,643,505	392	-61	359	162	71.5	80.3	RL-22-009	590,799	5,643,441	395	-61	2	186	91.7	99.4	RL-22-010	590,792	5,643,405	395	-61	358	150	107.8	114.7	RL-22-013	590,906	5,643,649	397	-60	360	132	64.0	72.0	RL-22-014	590,900	5,643,602	397	-60	360	129	102.0	110.4	RL-22-015	590,962	5,643,691	392	-60	360	93	28.9	42.3	RL-22-016A	590,894	5,643,540	394	-61	3	156	67.3	73.6	RL-22-017	590,957	5,643,575	396	-60	360	120	53.8	60.0	RL-22-018	591,011	5,643,702	390	-61	1	90	51.8	64.4	RL-22-019	591,006	5,643,574	397	-60	2	120	23.1	26.7	RL-22-020	590,901	5,643,508	389	-60	360	150	78.0	82.8	RL-22-021	590,999	5,643,481	397	-60	360	181	111.3	118.7	RL-22-022	590,650	5,643,525	394	-59	0	152	47.4	61.4	RL-22-023	590,700	5,643,625	397	-61	2	189	12.4	25.5	RL-22-024	590,900	5,643,425	388	-60	2	150	85.6	93.0	RL-22-025	590,850	5,643,600	396	-60	360	141	30.1	37.8	RL-22-027	590,850	5,643,651	397	-59	358	108	3.4	15.6	RL-22-029	590,850	5,643,475	392	-60	360	227	106.4	112.3	RL-22-033	590,599	5,643,489	395	-58	4	162	2.8	8.0	RL-22-035	590,643	5,643,487	397	-59	0	162	66.5	79.2	RL-22-037	590,596	5,643,419	392	-60	-	180	40.1	43.8	RL-22-038	591,045	5,643,706	390	-60	-	141	81.5	90.0	RL-22-040	591,058	5,643,675	389	-60	360	120	94.0	103.0	RL-22-041	590,633	5,643,399	397	-59	359	201	94.2	113.7	Hole	From	To	Interval	Vis Est. %	Li ₂ O	RL-22-001	11.8	24.2	12.4		1.77	RL-22-002	42.2	57.5	15.3		1.20	RL-22-003	72.0	83.5	11.5		2.03	RL-22-004	80.5	87.4	7.0		1.41	RL-22-005	90.8	100.7	9.9		0.25	RL-22-006	21.7	31.2	9.5		1.54	RL-22-007	64.9	74.7	9.8		1.51	RL-22-008	71.5	80.3	8.8		1.81	RL-22-009	91.7	99.4	7.7		0.54	RL-22-010	107.8	114.7	6.9		0.80	RL-22-013	64.0	72.0	8.0		1.72	RL-22-014	102.0	110.4	8.4		1.32	RL-22-015	28.9	42.3	13.4		1.24	RL-22-016A	67.3	73.6	6.3		1.44	RL-22-017	53.8	60.0	6.2	15		RL-22-018	51.8	64.4	12.6	15		RL-22-019	23.1	26.7	3.5	10		RL-22-020	78.0	82.8	4.8	15		RL-22-021	111.3	118.7	7.4	15		RL-22-022	47.4	61.4	14.0	20		RL-22-023	12.4	25.5	13.1	15		RL-22-024	85.6	93.0	7.4	15		RL-22-025	30.1	37.8	7.7	15		RL-22-027	3.4	15.6	12.3	15		RL-22-029	106.4	112.3	5.9	15		RL-22-033	2.8	8.0	5.2	10		RL-22-035	66.5	79.2	12.7	10		RL-22-037	40.1	43.8	3.8	10		RL-22-038	81.5	90.0	8.4	10		RL-22-040	94.0	103.0	9.0	10		RL-22-041	94.2	113.7	19.5	10	
Hole	Easting	Northing	RL	Dip	Azi	Depth	From	To																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-001	590,698	5,643,629	397	-59	358	60	11.8	24.2																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-002	590,700	5,643,575	394	-62	0	72	42.2	57.5																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-003	590,699	5,643,517	394	-58	358	102	72.0	83.5																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-004	590,698	5,643,482	397	-61	357	144	80.5	87.4																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-005	590,699	5,643,421	396	-60	359	147	90.8	100.7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-006	590,800	5,643,604	399	-59	360	120	21.7	31.2																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-007	590,799	5,643,549	393	-61	359	117	64.9	74.7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-008	590,801	5,643,505	392	-61	359	162	71.5	80.3																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-009	590,799	5,643,441	395	-61	2	186	91.7	99.4																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-010	590,792	5,643,405	395	-61	358	150	107.8	114.7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-013	590,906	5,643,649	397	-60	360	132	64.0	72.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-014	590,900	5,643,602	397	-60	360	129	102.0	110.4																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-015	590,962	5,643,691	392	-60	360	93	28.9	42.3																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-016A	590,894	5,643,540	394	-61	3	156	67.3	73.6																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-017	590,957	5,643,575	396	-60	360	120	53.8	60.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-018	591,011	5,643,702	390	-61	1	90	51.8	64.4																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-019	591,006	5,643,574	397	-60	2	120	23.1	26.7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-020	590,901	5,643,508	389	-60	360	150	78.0	82.8																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-021	590,999	5,643,481	397	-60	360	181	111.3	118.7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-022	590,650	5,643,525	394	-59	0	152	47.4	61.4																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-023	590,700	5,643,625	397	-61	2	189	12.4	25.5																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-024	590,900	5,643,425	388	-60	2	150	85.6	93.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-025	590,850	5,643,600	396	-60	360	141	30.1	37.8																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-027	590,850	5,643,651	397	-59	358	108	3.4	15.6																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-029	590,850	5,643,475	392	-60	360	227	106.4	112.3																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-033	590,599	5,643,489	395	-58	4	162	2.8	8.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-035	590,643	5,643,487	397	-59	0	162	66.5	79.2																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-037	590,596	5,643,419	392	-60	-	180	40.1	43.8																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-038	591,045	5,643,706	390	-60	-	141	81.5	90.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-040	591,058	5,643,675	389	-60	360	120	94.0	103.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
RL-22-041	590,633	5,643,399	397	-59	359	201	94.2	113.7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
Hole	From	To	Interval	Vis Est. %	Li ₂ O																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-001	11.8	24.2	12.4		1.77																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-002	42.2	57.5	15.3		1.20																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-003	72.0	83.5	11.5		2.03																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-004	80.5	87.4	7.0		1.41																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-005	90.8	100.7	9.9		0.25																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-006	21.7	31.2	9.5		1.54																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-007	64.9	74.7	9.8		1.51																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-008	71.5	80.3	8.8		1.81																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-009	91.7	99.4	7.7		0.54																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-010	107.8	114.7	6.9		0.80																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-013	64.0	72.0	8.0		1.72																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-014	102.0	110.4	8.4		1.32																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-015	28.9	42.3	13.4		1.24																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-016A	67.3	73.6	6.3		1.44																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
RL-22-017	53.8	60.0	6.2	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-018	51.8	64.4	12.6	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-019	23.1	26.7	3.5	10																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-020	78.0	82.8	4.8	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-021	111.3	118.7	7.4	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-022	47.4	61.4	14.0	20																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-023	12.4	25.5	13.1	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-024	85.6	93.0	7.4	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-025	30.1	37.8	7.7	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-027	3.4	15.6	12.3	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-029	106.4	112.3	5.9	15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-033	2.8	8.0	5.2	10																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-035	66.5	79.2	12.7	10																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-037	40.1	43.8	3.8	10																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-038	81.5	90.0	8.4	10																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-040	94.0	103.0	9.0	10																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
RL-22-041	94.2	113.7	19.5	10																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
Data aggregation methods	<ul style="list-style-type: none"> In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the 	<ul style="list-style-type: none"> Length weighted Li₂O averages are used across the downhole length of intersected pegmatites Grade cut-offs have not been incorporated. No metal equivalent values are quoted. 																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																

Criteria	JORC Code explanation	Commentary
	<p><i>procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i></p> <ul style="list-style-type: none"> The assumptions used for any reporting of metal equivalent values should be clearly stated. 	
Relationship between mineralisation widths and intercept lengths	<ul style="list-style-type: none"> These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	<ul style="list-style-type: none"> Holes drilled by GT1 attempt to pierce the mineralised pegmatite approximately perpendicular to strike, and therefore, the downhole intercepts reported are approximately equivalent to the true width of the mineralisation. Trenches are representative widths of the exposed pegmatite outcrop. Some exposure may not be a complete representation of the total pegmatite width due to recent glacial deposit cover limiting the available material to be sampled.
Diagrams	<ul style="list-style-type: none"> Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	<ul style="list-style-type: none"> The appropriate maps are included in the announcement.
Balanced reporting	<ul style="list-style-type: none"> Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	<ul style="list-style-type: none"> Pegmatite downhole interval summary with associated assay results are listed in Appendix C
Other substantive exploration data	<ul style="list-style-type: none"> Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples - size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	<ul style="list-style-type: none"> GT1 completed a high resolution Heliborne Magnetic geophysical survey over the property in July 2022. The survey was undertaken by Propsectair using their Robinson R-44 and EC120B helicopters. Survey details, 1,201 line-km, 50m line spacing, direction 179 degrees to crosscut pegmatite strike, 50m altitude. Control lines were flown perpendicular to these lines at 500m spacing. Images have been received Total Magnetics.  <ul style="list-style-type: none"> Interpretation is currently being completed by Southern Geoscience
Further work	<ul style="list-style-type: none"> The nature and scale of planned further 	

Criteria	JORC Code explanation	Commentary
	<p><i>work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i></p> <ul style="list-style-type: none"> <i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i> 	<ul style="list-style-type: none"> Further extensional drilling is currently being carried out at McCombe testing strike extents over 500m in length and downdip extensions up to 300m from the current outcrop.

References

Breaks, F.W., Selway, J.B. and Tindle, A.G., (2003) Fertile peraluminous granites and related rare element mineralization in pegmatites, Superior province, northwest and northeast Ontario: Operation Treasure Hunt. Ontario Geological Survey, Open File Report 6099, 179 p.

Černý, P. (1991a) Rare-element granitic pegmatites, part I. Anatomy and internal evolution of pegmatite deposits; Geoscience Canada, v.18, p.49-67.

Appendix C Downhole Interval Summary

HOLEID	FROM	TO	INTERVAL	Li2O_ppm	Ta2O5_ppm	LITH
RL-16-01A	0.00	5.00	5.00			Overburden
RL-16-01A	5.00	25.20	20.20			Extrusive
RL-16-01A	25.20	33.90	8.70	12,515	99	Pegmatite
RL-16-01A	33.90	75.00	41.10			Extrusive
RL-16-02	0.00	6.00	6.00			Overburden
RL-16-02	6.00	10.00	4.00			Extrusive
RL-16-02	10.00	21.40	11.40	10,640	102	Pegmatite
RL-16-02	21.40	26.50	5.10			Extrusive
RL-16-03	0.00	6.00	6.00			Overburden
RL-16-03	6.00	52.50	46.50			Extrusive
RL-16-03	52.50	61.50	9.00	12,485	81	Pegmatite
RL-16-03	61.50	72.00	10.50			Extrusive
RL-16-04	0.00	2.00	2.00			Overburden
RL-16-04	2.00	18.00	16.00			Extrusive
RL-16-04	18.00	32.00	14.00	10,533	92	Pegmatite
RL-16-04	32.00	41.00	9.00			Extrusive
RL-16-05	0.00	6.00	6.00			Overburden
RL-16-05	6.00	68.40	62.40			Extrusive
RL-16-05	68.40	76.10	7.70	10,346	113	Pegmatite
RL-16-05	76.10	80.00	3.90			Extrusive
RL-16-07	0.00	4.00	4.00			Overburden
RL-16-07	4.00	28.00	24.00			Extrusive
RL-16-07	28.00	35.30	7.30	2,049	133	Pegmatite
RL-16-07	35.30	41.00	5.70			Extrusive
RL-16-07	41.00	46.10	5.10	11,391	70	Pegmatite
RL-16-07	46.10	54.00	7.90			Extrusive
RL-22-001	0.00	2.28	2.28			Overburden
RL-22-001	2.28	11.84	9.56			Sediment
RL-22-001	11.84	24.22	12.38	17,687	71	Pegmatite
RL-22-001	24.22	60.00	35.78			Sediment
RL-22-002	0.00	11.30	11.30			Overburden
RL-22-002	11.30	42.20	30.90			Sediment
RL-22-002	42.20	57.52	15.32	12,022	104	Pegmatite
RL-22-002	57.52	72.00	14.48			Sediment
RL-22-003	0.00	5.70	5.70			Overburden
RL-22-003	5.70	72.00	66.30			Sediment
RL-22-003	72.00	83.47	11.47	20,350	113	Pegmatite
RL-22-003	83.47	102.00	18.53			Sediment
RL-22-004	0.00	3.00	3.00			Overburden
RL-22-004	3.00	12.28	9.28			Sediment
RL-22-004	12.28	17.75	5.47			Mafic

HOLEID	FROM	TO	INTERVAL	Li2O_ppm	Ta2O5_ppm	LITH
RL-22-004	17.75	80.27	62.52			Sediment
RL-22-004	80.27	80.47	0.20			Mafic
RL-22-004	80.47	87.44	6.97	14,139	79	Pegmatite
RL-22-004	87.44	144.00	56.56			Sediment
RL-22-005	0.00	3.50	3.50			Overburden
RL-22-005	3.50	90.79	87.29			Sediment
RL-22-005	90.79	100.72	9.93	2,462	130	Pegmatite
RL-22-005	100.72	106.45	5.73			Sediment
RL-22-005	106.45	135.81	29.36			Mafic
RL-22-005	135.81	136.70	0.89	279	46	Pegmatite
RL-22-005	136.70	147.00	10.30			Mafic
RL-22-006	0.00	5.00	5.00			Overburden
RL-22-006	5.00	21.70	16.70			Sediment
RL-22-006	21.70	31.20	9.50	15,360	107	Pegmatite
RL-22-006	31.20	72.75	41.55			Sediment
RL-22-006	72.75	75.49	2.74	1,545	106	Pegmatite
RL-22-006	75.49	120.00	44.51			Sediment
RL-22-007	0.00	5.00	5.00			Overburden
RL-22-007	5.00	64.90	59.90			Sediment
RL-22-007	64.90	74.67	9.77	15,122	87	Pegmatite
RL-22-007	74.67	117.00	42.33			Sediment
RL-22-008	0.00	15.80	15.80			Overburden
RL-22-008	15.80	71.50	55.70			Sediment
RL-22-008	71.50	80.25	8.75	18,050	109	Pegmatite
RL-22-008	80.25	87.28	7.03			Sediment
RL-22-008	87.28	87.33	0.05	-	-	Pegmatite
RL-22-008	87.33	91.28	3.95			Sediment
RL-22-008	91.28	92.13	0.85	2,504	82	Pegmatite
RL-22-008	92.13	162.00	69.87			Sediment
RL-22-009	0.00	1.15	1.15			Overburden
RL-22-009	1.15	33.00	31.85			Sediment
RL-22-009	33.00	84.40	51.40			Mafic
RL-22-009	84.40	91.74	7.34			Sediment
RL-22-009	91.74	99.42	7.68	5,346	170	Pegmatite
RL-22-009	99.42	123.00	23.58			Sediment
RL-22-009	123.00	130.47	7.47			Mafic
RL-22-009	130.47	186.00	55.53			Sediment
RL-22-010	0.00	9.00	9.00			Overburden
RL-22-010	9.00	107.76	98.76			Mafic
RL-22-010	107.76	114.65	6.89	7,947	119	Pegmatite
RL-22-010	114.65	135.05	20.40			Mafic
RL-22-010	135.05	135.68	0.63	254	199	Pegmatite
RL-22-010	135.68	150.00	14.32			Mafic

HOLEID	FROM	TO	INTERVAL	Li2O_ppm	Ta2O5_ppm	LITH
RL-22-011	0.00	9.00	9.00			Overburden
RL-22-011	9.00	97.12	88.12			Mafic
RL-22-011	97.12	130.58	33.46			Sediment
RL-22-011	130.58	132.40	1.82	417	161	Pegmatite
RL-22-011	132.40	180.00	47.60			Sediment
RL-22-012	0.00	0.30	0.30			Overburden
RL-22-012	0.30	111.00	110.70			Mafic
RL-22-013	0.00	5.20	5.20			Overburden
RL-22-013	5.20	64.00	58.80			Sediment
RL-22-013	64.00	72.00	8.00	17,213	131	Pegmatite
RL-22-013	72.00	132.00	60.00			Sediment
RL-22-014	0.00	3.85	3.85			Overburden
RL-22-014	3.85	36.20	32.35			Sediment
RL-22-014	36.20	38.90	2.70	11,297	89	Pegmatite
RL-22-014	38.90	55.47	16.57			Sediment
RL-22-014	55.47	75.00	19.53			Mafic
RL-22-014	75.00	102.00	27.00			Sediment
RL-22-014	102.00	110.40	8.40	13,181	112	Pegmatite
RL-22-014	110.40	129.00	18.60			Sediment
RL-22-015	0.00	10.85	10.85			Overburden
RL-22-015	10.85	28.90	18.05			Sediment
RL-22-015	28.90	42.25	13.35	12,233	109	Pegmatite
RL-22-015	42.25	92.00	49.75			Sediment
RL-22-015	92.00	93.00	1.00			
RL-22-016A	0.00	8.10	8.10			Overburden
RL-22-016A	8.10	67.30	59.20			Sediment
RL-22-016A	67.30	73.60	6.30	14,405	73	Pegmatite
RL-22-016A	73.60	126.00	52.40			Sediment
RL-22-016A	126.00	130.15	4.15	3,195	-	Pegmatite
RL-22-016A	130.15	156.00	25.85			Mafic