

More significant copper-gold intersected at Mynt

Results from initial diamond core drilling confirm that continuous sulphide-related mineralisation extends to 200m below surface.

HIGHLIGHTS

- First diamond core hole drilled at the **Mynt prospect**, part of the 100%-owned Moora Project in WA, intersects strong copper-gold mineralisation:
 - ✓ **MRRD0088** **36m @ 1.0% Cu and 0.4g/t Au from 194 – 230m*, including:**
 - **18m @ 1.6% Cu and 0.8g/t Au from 194 – 212m**
- The latest intersection is located ~90m down-dip of MRRD0089 (see ASX release dated 27th February 2023), which returned the following results:
 - ✓ **MRRD0089** **21m @ 1.3% Cu and 0.4g/t Au from 119 – 140m*, including:**
 - **5m @ 2.4% Cu and 0.8g/t Au from 121 – 126m and**
 - **4m @ 2.3% Cu and 0.7g/t Au from 129 – 133m**
- The intersections reported above are hosted by a mineralised shoot where drilling has intersected continuous sulphide-related copper-gold mineralisation on multiple drill sections over ~140m strike with the system still open down-plunge.
- Drilling at Mynt indicates the potential for multiple copper-gold mineralised shoots.
- Assays pending for a further 12 RC holes and four diamond core holes drilled in the Mynt area to follow up results reported earlier this year (see ASX releases dated 27th February and 22nd March 2023).
- Cash position (~\$21.1M at 31 December 2022) ensures that Minerals 260 can maintain exploration momentum at Moora and its newly acquired Gascoyne projects.

Minerals 260 Limited (ASX:MI6, “Minerals 260” or “Company”) is pleased to advise that diamond core drilling has confirmed the down-dip continuity of sulphide-related copper-gold mineralisation previously reported for the Mynt prospect, part of its Moora Project in WA.

The 100%-owned Moora Project, which is located ~150km north-east of Perth in the Julimar Mineral Province of SW Western Australia (**Figure 1**), forms part of a contiguous, 1,000km² land package which includes the adjacent Koojan JV, where the Company is in joint venture with Lachlan Star Limited (ASX: LSA) and has earned an initial 30% equity with the right to increase this to 51%.

Drilling at Mynt since the beginning of the year has intersected multiple copper-gold zones (**Figure 2**), with the latest result hosted by a steeply plunging shoot (**Figures 3 and 4**), up to 140m long and which is open at depth.

Similar mineralisation has been intersected ~700m to the west in hole MRRDC0105 (**Figure 2**/see ASX release dated 22nd March 2023) and 200m to the east in hole MRRD0137 (**Figure 4**/assays pending). Given the limited deeper RC drilling in the Mynt area, there is good potential to discover further mineralised shoots.

Follow-up drilling will be planned at Mynt once all pending assays have been received and processed.

* True width uncertain due to limited geological data; however, at this stage estimated to be 70-80% of down-hole width

In addition to MRRD0088, assays have been received for 24 other RC holes (MRRC0108, 0109, 0111, and 116 - 0136).

Significant results from these holes include:

- ✓ MRRC0108 20m @ 0.8g/t Au from 1 – 21m, including:
 - 8m @ 1.3g/t Au from 3 - 11m

- ✓ MRRC0109 22m @ 0.5g/t Au from 2 – 24m, including:
 - 2m @ 2.4g/t Au from 17 - 19m

- ✓ MRRC0124 5m @ 0.7g/t Au and 0.2% Cu from 62 – 67m, including:
 - 1m @ 2.7g/t Au and 0.2% Cu from 62 – 67m

MRRC0108 and MRRC0109 were drilled at the Angepena prospect, located ~1.5km south-west of Mynt, with the mineralisation encountered hosted by strongly oxidised, lateritic bedrock.

MRRC0124, which also reported strongly anomalous cobalt (4m @ 0.05% Co from 63 – 67m) and zinc (1m @ 5.7% from 91 – 92m), was drilled into a previously untested target located 3.5km south-southeast of Mynt (**Figure 5**) near the western margin of the Moora Gravity Anomaly (MGA).

All the significant mineralised zones discovered by Minerals 260 at Moora are spatially related to the MGA (**Figure 5**), indicating that it is an important control on mineralisation and a priority for future exploration.

Drill statistics including significant assays are listed in Appendix 1.

Management Comments

Minerals 260 Managing Director David Richards said: *“Assays from the first diamond hole at Mynt supports our view that there is potential to delineate a significant resource at this rapidly emerging prospect. Our drilling across the broader project continues to return significant assays for a range of metals, highlighting the metal fertility of the Moora region”.*

“Drilling has been temporarily suspended due to the onset of the seeding season and we will now take the time to carefully review all datasets before planning the next phase of work. Once this review is completed, we will re-engage with landowners to discuss accessing key areas for follow up drilling.”

“We’re also excited about commencing work on our new Gascoyne projects¹ in late April/early May 2023, where other explorers² in the immediate region continue to report promising lithium and rare earth results”.

This announcement has been authorised for release by the Managing Director, David Richards.

1: See Minerals 260 Limited ASX releases dated 7th and 27th March 2023

2: See Red Dirt Limited, Kingfisher Mining Limited and Dreadnought Resources Limited ASX announcements dated 3rd April 2023.

Competent Person Statement

The Information in this report that relates to new Exploration Results is based on and fairly represents information and supporting documentation prepared by Mr David Richards, who is a Competent Person and a member of the Australasian Institute of Geoscientists (AIG). Mr Richards is a full-time employee of the company. Mr Richards has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activities being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Richards consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

The Information in this Report that relates to other Exploration Results for the Moora and Koojan Projects is extracted from Minerals 260 Limited ASX announcements titled:

- "Significant new copper-gold zone discovered at Mynt" released on 22nd March 2023
- "Mynt prospect continues to grow with significant new copper-gold intercept" released on 27 February 2023;
- "Multiple zones of gold mineralisation intersected in initial follow-up drilling at Moora" released on 3 February 2022;
- "Wide copper-gold zone confirmed at Moora" released on 4 March 2022;
- "Second significant copper-gold zone discovered at Moora" released on 19 April 2022;
- "Outstanding new intercept of 13m @ 3.3g/t gold at Moora" released on 11 July 2022;
- "New intercept of 16m @ 2.8g/t Au confirms scale and potential of Angepena gold prospect at Moora" released on 27 September 2022;
- "Significant bedrock palladium-platinum intersected for the first time at Moora ahead of major new drilling program" released on 4 November 2022; and
- "Second phase of drilling to commence at the Mynt copper-gold prospect – Moora Project, WA" released on 3 February 2023

which are available on www.minerals260.com.au.

The Company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcements and that all material assumptions and technical parameters underpinning the estimates or production targets or forecast financial information derived from a production target (as applicable) in the relevant market announcements continue to apply and have not materially changed. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcements.

Forward Looking Statement

This announcement contains forward-looking statements which involve a number of risks and uncertainties. These forward-looking statements are expressed in good faith and believed to have a reasonable basis. These statements reflect current expectations, intentions or strategies regarding the future and assumptions based on currently available information. Should one or more of the risks or uncertainties materialise, or should underlying assumptions prove incorrect, actual results may vary from the expectations, intentions and strategies described in this announcement. No obligation is assumed to update forward looking statements if these beliefs, opinions and estimates should change or to reflect other future developments.

For further information please contact:

David Richards
Managing Director
T: +61 8 6556 6020
info@minerals260.com.au

Investor Relations:

Nicholas Read
Read Corporate
T: +61 8 9388 1474
nicholas@readcorporate.com.au




Figure 1: Moora and Koojan JV Projects: Regional magnetic image and location plan.

Minerals 260

ASX RELEASE | 3rd April 2023 | ASX:MI6




Figure 2: Mynt Prospect: Magnetic image (TMI1VD NE shade) showing drill holes and better intersections.




Figure 3: Mynt Prospect – Cross section – see Figures 2 and 4 for location.




Figure 4: Mynt Prospect – Long section – see Figure 2 for location.




Figure 5: Moora Project – Gravity image showing Moora Gravity Anomaly and mineralised prospects

Appendix 1 – Moora Project– RC Drill Hole Statistics

Hole_ID	East	North	RL	Depth (m)	Dip	Azimuth	From (m)	To (m)	Significant Intercepts			
									Gold (>0.1g/t)		Copper (>0.1%)	
									Interval (m)	Grade (g/t)	Interval (m)	Grade (%)
MRRC0001	422190	6599839	300	246	-59	39	198	241	43*	1.8		
							inc. 18m @ 3.9g/t Au from 211m and 2m @ 21.2g/t Au from 222m					
MRRC0002	422355	6600014	300	224	-60	225	No significant assays					
MRRC0003	422620	6599527	300	102	-59	353	No significant assays					
MRRC0004	423456	6600628	300	150	-59	360	0	20			20	0.1
MRRC0005	423446	6600764	300	117	-60	180	24	32			8	0.2
MRRC0006	423448	6600425	300	120	-60	360	No significant assays					
MRRC0007	423451	6600374	300	120	-59	360	48	56	8	0.9	8	0.1
							inc. 2m @ 2.8g/t Au and 0.1% Cu from 48m					
MRRC0008	424047	6600425	300	123	-60	358	27	37	10	1.2		
							inc. 2m @ 3.6g/t Au from 34m					
							92	95	3	0.3	3	0.2
MRRC0009	424050	6600374	300	123	-60	356	10	12	2	0.8	2	0.3
							19	20	1	1.3		
							32	34	2	0.6		
							37	49	12	0.7	12	0.3
							inc. 6m @ 1.1g/t Au and 0.4% Cu from 41m					
MRRC0010	424052	6600325	300	117	-60	360	22	25	3	0.3		
MRRC0011	424250	6600525	300	117	-60	178	No significant assays					
MRRC0012	424450	6600325	300	117	-60	359	No significant assays					
MRRC0013	424450	6600475	300	150	-60	178	114	117	3	0.3	3	0.9
							inc. 2m @ 0.3g/t Au and 1.3% Cu from 115m					
							133	138	5	0.4	5	0.6
							inc. 1m @ 0.9g/t Au and 1.2% Cu from 135m					
MRRC0014	424450	6600475	300	120	-60	358	60	62	2	0.8	2	0.3
MRRC0015	422158	6600089	307	84	-60	215	Hole Abandoned					
MRRC0016	422127	6600042	305	150	-57	213	1	12	11	0.3	11	0.1
							inc. 1m @ 1.3g/t Au and 0.2% Cu from 11m					
							61	66	5	0.4	5	0.8
							inc. 3m @ 0.5g/t Au and 1.1% Cu from 61m					
							79	88	9	0.2	9	0.1
							92	96	4	1.4	4	0.2
							inc. 2m @ 2.1g/t Au and 0.3% Cu from 93m					
							101	116	15	0.6	15	0.1
							inc. 1m @ 1.5g/t Au from 103m					
inc. 2m @ 1.3g/t Au and 0.1% Cu from 106m												
MRRC0017	422165	6600088	308	150	-58	214	147	149	2	8.7		
inc. 1m @ 16.4g/t Au from 147m												
MRRC0018	422087	6599992	304	180	-51	217	0	6	6	0.7		
							inc. 2m @ 1.6g/t Au from 1m					
							10	20	10	0.7		
inc. 4m @ 1.3g/t Au from 13m												
MRRC0019	422078	6600147	301	150	-55	213	No significant assays					
MRRC0020	422046	6600097	300	30	-55	212	Hole Abandoned					
MRRC0021	422043	6600094	300	150	-60	213	13	16	3	0.5	3	0.1
							40	48	8	0.3		
							inc. 1m @ 1.2g/t Au from 40m					
							120	128	8	0.5		
							inc. 1m @ 1.2g/t Au from 126m					
145	150	5	0.7									
inc. 2m @ 1.2g/t Au from 147m												

Appendix 1 (cont.)– Moora Project– RC Drill Hole Statistics

Hole_ID	East	North	RL	Depth (m)	Dip	Azimuth	From (m)	To (m)	Significant Intercepts			
									Gold (>0.1g/t)		Copper (>0.1%)	
									Interval (m)	Grade (g/t)	Interval (m)	Grade (%)
MRRC0022	422010	6600047	300	150	-58	211	3	12	9	2.8		
							inc. 5m @ 4.7g/t Au from 3m					
							30	43	13	1.3		
							inc. 4m @ 3.5g/t Au from 32m					
							46	52	6	0.2		
						79	96	20	0.3			
						inc. 4m @ 1.0g/t Au from 76m						
MRRC0023	421975	6600001	300	150	-56	212	No significant assays					
MRRC0024	421890	6600059	300	150	-56	220	28	48	2	0.1		
							50	57	7	0.4		
						inc. 1m @ 1.0g/t Au from 56m						
MRRC0025	421923	6600109	300	150	-60	213	116	125	9	0.2		
MRRC0026	421958	6600159	300	96	-61	212	No significant assays					
MRRC0027	422500	6599700	314	150	-60	216						
MRRC0028	422535	6599758	317	150	-61	215	40	46	6	0.4		
MRRC0029	422570	6599798	318	150	-59	221	28	32	4	0.2		
							124	128	4	0.3		
MRRC0030	422580	6599641	318	156	-60	213	91	96	5	0.6	5	0.3
						inc. 2m @ 1.1g/t Au and 0.6% Cu from 92m						
MRRC0031	422618	6599697	320	150	-61	214	No significant assays					
MRRC0032	422653	6599747	320	150	-61	212	20	24	4	0.3		
MRRC0033	422662	6599588	320	150	-61	213	No significant assays					
MRRC0034	422697	6599637	321	150	-62	211	2	20	18	0.2		
MRRC0035	422733	6599689	320	150	-61	212	No significant assays					
MRRC0036	422045	6599920	298	150	-60	215						
MRRC0037	425696	6598176	339	192	-72	359	138	139	1	0.3	1	0.4
							143	144	1	0.1	1	0.8
							148	152	4	0	4	0.3
MRRC0038	425701	6598319	338	42	-77	180	Hole Abandoned					
MRRC0039	425697	6598313	338	162	-60	180	72	84	12	2	12	1.4
							inc. 6m @ 3.5g/t Au and 2.5% Cu from 74m					
							140	152			12	0.2
MRRC0040	423400	6600601	313	186	-61	42	99	123	24	0.7	24	1.9
						inc. 14m @ 1.1g/t Au and 2.9% Cu from 100m						
MRRC0041	427897	6594698	298	234	-60	270	106	111			5	0.6
						inc. 2m @ 1.3% Cu from 108m						
MRRC0042	425691	6598269	343	120	-60	180	2	6	4	0.6		
							inc. 1m @ 1.1g/t Au from 3m					
							10	16	6	0.3		
							21	37	16	0.2		
							52	58	6	0.1		
						102	103	1	1.2	1	0.3	
						127	140	13	3.3	13	0.2	
MRRC0043	425691	6598355	339	210	-61	178	inc. 1m @ 16.7g/t Au and 1.6% Cu from 130m and					
						inc. 1m @ 16.9g/t Au and 0.4% Cu from 137m						
MRRC0044	425774	6598274	340	150	-60	211	No significant assays					
MRRC0045	425796	6598309	338	120	-60	212	5	11	6	0.5		
							inc. 1m @ 1.2g/t Au from 7m					
MRRC0046	425600	6598351	343	210	-60	215	No significant assays					
MRRC0047	425618	6598382	340	126	-59	215						
MRRC0048	425789	6598355	336	204	-59	177	5	9	4	0.3		

Appendix 1 (cont.)– Moora Project– RC Drill Hole Statistics

Hole_ID	East	North	RL	Depth (m)	Dip	Azimuth	From (m)	To (m)	Significant Intercepts									
									Gold (>0.1g/t)		Copper (>0.1%)							
									Interval (m)	Grade (g/t)	Interval (m)	Grade (%)						
MRRC0049	425692	6598394	338	203	-60	177	1	6	5	0.2								
							26	35			9	0.1						
							117	118	1	0.4	0.1	0.2						
							154	155	1	0.4	1	0.2						
MRRC0050	425797	6598331	337	192	-60	180	193	196	3	0.2								
							3	9	6	0.2								
							25	26	1	0.5								
MRRD0051	425681	6598334	341	259	-60	215	36	40	4	0.3	4	0.1						
							52	70			18	0.3						
							inc. 2m @ 1.2% Cu from 52m and											
							inc. 1m @ 0.7% Cu from 56m											
							123	128	5	0.2	5	0.1						
							132	140	8	0.2	8	0.1						
							152	180	28	0.2	28	0.3						
MRRC0052	421981	6599971	298	180	-60	31	207	210	3	1.2								
							inc. 1m @ 3.5g/t Au and 0.3% Cu from 209m											
							56	64	8	0.3								
							84	92	8	0.2								
MRRC0053	422086	6599961	304	107	-60	32	152	156	4	0.2								
							0	3	3	0.4								
							28	40	12	0.4								
							inc. 2m @ 1.2g/t Au from 34m											
							44	56	12	0.2								
							inc. 1m @ 1.0g/t Au from 44m											
							71	78	7	0.2								
MRRC0054	422153	6599978	298	72	-60	37	82	89	7	0.3								
							103	107	4	0.6								
							0	2	2	0.3								
							14	16	2	0.2								
							20	22	2	0.3								
							24	27	3	0.2								
MRRC0055	427767	6593687	351	252	-59.9	232	48	64	16	2.8								
							inc. 2m @ 9.8g/t Au from 50m											
							inc. 3m @ 6.6g/t Au from 54m											
							178	179			1	0.2						
							182	187			5	0.3						
MRRC0056	427890	6593761	337	180	-59	240	202	205			3	0.1						
							209	210			1	0.4						
MRRC0057	428030	6593971	323	204	-60.5	49	No significant assays											
MRRC0058	427729	6593637	353	252	-61	239	156	160	4	0.2	4	0.1						
MRRC0059	427574	6593544	360	210	-60	220	No significant assays											
MRRC0060	412800	6592931	291	67	-60	240												
MRRC0060A	412768	6592945	294	174	-61	235												
MRRC0061	412525	6593625	305	150	-61	235												
MRRC0062	411881	6593661	304	228	-61	237												
MRRC0063	411648	6593941	306	186	-60	237												
MRRC0064	411580	6593899	305	150	-61	237						82	84			2	0.2	
MRRC0065	411419	6593723	299	204	-60	246	No significant assays											
MRRC0066	412267	6592851	297	183	-60	238												
MRRC0067	412700	6592900	298	150	-61	242												

Appendix 1 (cont.)– Moora Project– RC Drill Hole Statistics

Hole_ID	East	North	RL	Depth (m)	Dip	Azimuth	From (m)	To (m)	Significant Intercepts			
									Gold (>0.1g/t)		Copper (>0.1%)	
									Interval (m)	Grade (g/t)	Interval (m)	Grade (%)
MRRC0068	411848	6610121	247	150	-60	87						
MRRC0069	411682	6610090	246	122	-60	79						
MRRC0070	413038	6594431	323	150	-60	236						
MRRC0071	413100	6594465	325	150	-60	239						
MRRC0072	413170	6594509	324	150	-60	236						
MRRC0073	413239	6594547	319	145	-59	238						
MRRC0074	411529	6593852	302	150	-60	237						
MRRC0075	412319	6592370	289	174	-60	239						
MRRC0076	412214	6592815	295	150	-61	235						
MRRC0077	411941	6593701	305	120	-61	234						
MRRC0078	417001	6604501	292	160	-60	264						
MRRC0079	417056	6603822	316	252	-60	270						
MRRC0080	411762	6610105	246	150	-60	82						
MRRC0081	411923	6610129	244	150	-61	81						
MRRC0082	411576	6610075	245	150	-61	82						
MRRC0083	411775	6609583	251	150	-61	78						
MRRC0084	411639	6609559	253	150	-61	84						
MRRC0085	411862	6609587	249	150	-61	76						
MRRC0086	411940	6609601	251	150	-60	80						
MRRC0087	423826	6600083	318	114	-60	179	49	65			16	0.2
							92	95			3	0.3
							194	230	36	0.4	36	1
							inc. 18m @ 0.8g/t Au and 1.6% Cu from 194m (inc. 11m @ 1.2g/t Au and 2.2% Cu from 195m)					
							233	239.6	6.65	0.1	6.65	0.1
							119	140	21	0.4	21	1.3
							inc. 5m @ 0.8g/t Au and 2.4% Cu from 121m and inc. 4m @ 0.7g/t Au and 2.3% Cu from 129m					
							145	150	5	0.1	5	0.1
MRRD0088	423357	6600560	314	280	-61	43						
MRRC0089	423430	6600575	316	168	-60	49						
MRRC0090	417116	6604004	308	180	-60	269						
MRRC0091	408717	6592370	226	150	-60	218						
MRRC0092	408177	6591904	219	150	-60	220						
MRRC0093	408269	6592006	221	150	-60	223						
MRRC0094	408317	6592066	217	150	-60	225						
MRRC0095	408668	6592316	224	133	-60	219						
MRRC0096	416879	6584001	281	150	-60	269						
MRRC0097	416795	6584008	278	150	-61	270						
MRRC0098	415875	6583752	254	150	-61	269						
MRRC0099	415943	6583748	253	150	-61	266						
MRRC0100	423372	6600630	313	222	-60	49	118	129	11	0.6	11	1.5
							inc. 5m @ 0.8g/t Au and 2.0% Cu from 122m and No significant assays					
MRRC0101	423069	6600288	319	168	-60	48						
MRRD0102	423304	6600510	314	397.1	-60	41						
							Assays Pending					
MRRC0103	423523	6600380	313	186	-61	43	13	23			10	0.2
							28	31	3	0.3		
							34	36	2	1.1		
							65	66	1	2.7	1	0.4
							112	116	4	0.3		
MRRC0104	423062	6600979	311	180	-61	46	120	124			4	0.6
							inc. 1m @ 1.7% Cu from 121m					
							44	46	2	0.3		
							69	71	2	0.3		
MRRC0105	422665	6600714	312	162	-61	40	124	135	11	1.3	11	1.4
							inc. 3m @ 4.2g/t Au and 2.8% Cu from 128m					

Appendix 1 (cont.)– Moora Project– RC Drill Hole Statistics

Hole_ID	East	North	RL	Depth (m)	Dip	Azimuth	From (m)	To (m)	Significant Intercepts			
									Gold (>0.1g/t)		Copper (>0.1%)	
									Interval (m)	Grade (g/t)	Interval (m)	Grade (%)
MRRC0106	422651	6601100	303	180	-60	357	No significant assays					
MRRC0107	421936	6600032	294	150	-60	36	No significant assays					
MRRC0108	422079	6600028	302	180	-61	33	1	21	20	0.8	20	0.1
							inc. 8m @ 1.3g/t Au and 0.1% Cu from 3m and inc. 1m @ 1.5g/t Au and 0.1% Cu from 16m					
MRRC0109	422114	6600012	304	75	-60	32	2	24	22	0.5	22	0.2
							inc. 1m @ 1.2g/t Au and 0.4% Cu from 12m and inc. 2m @ 2.4g/t Au and 0.5% Cu from 17m					
MRRC0110	416018	6583752	256	150	-60	271	No significant assays					
MRRC0111	428595	6595858	280	36	-90	174	No significant assays					
MRRC0112	423243	6600787	311	178	-60	44	No significant assays					
MRRC0113	426931	6598013	312	202	-61	269	69	70			1	0.4
MRRC0114	426609	6594335	324	220	-60	268	205	206			1	0.2
MRRC0115	427522	6593340	351	172	-61	176	No significant assays					
MRRC0116	427055	6594358	356	132	-60	90	No significant assays					
MRRC0117	427692	6592920	328	204	-61	217	No significant assays					
MRRC0118	426949	6597954	312	102	-61	269	No significant assays					
MRRC0119	424123	6597998	326	180	-62	267	No significant assays					
MRRC0120	422113	6599708	299	150	-60	213	1	4	3	0.1		
MRRC0121	422069	6599645	295	150	-60	219	No significant assays					
MRRC0122	423484	6600576	317	204	-60	48	84	88	4	0.1	4	0.3
MRRC0123	424835	6597153	324	150	-61	267	No significant assays					
MRRC0124	424702	6597163	318	150	-60	87	62	67	5	0.7	5	0.2
							inc. 1m @ 2.7g/t Au and 0.2% Cu from 62m					
MRRC0125	423787	6600097	317	42	-60	177	Hole Abandoned					
MRRC0126	423872	6600086	316	180	-60	175	129	130	1	0.3		
							106	108	2	0.8		
MRRC0127	423465	6600338	319	240	-61	41	inc. 1m @ 1.5g/t Au from 106m					
							71	81	10	0.3		
MRRC0128	421692	6600181	300	198	-59	211	No significant assays					
MRRC0129	421739	6600012	300	200	-60	210	No significant assays					
MRRC0130	429395	6592910	284	126	-61	211	No significant assays					
MRRC0131	429320	6592767	285	144	-59	27	No significant assays					
MRRC0132	429452	6592771	282	96	-60	178	No significant assays					
MRRC0133	429435	6592647	286	138	-59	359	No significant assays					
MRRC0134	409025	6592452	225	150	-60	219	No significant assays					
MRRC0135	429453	6592648	228	150	-61	227	No significant assays					
MRRC0136	423299	6600828	312	200	-60	46	No significant assays					
MRRC0137	423639	6600471	321	208	-61	43	No significant assays					
MRRC0138	423669	6600524	320	154	-60	45	No significant assays					
MRRC0139	423616	6600530	322	196	-61	45	No significant assays					
MRRC0140	423365	6600686	312	124	-60	46	No significant assays					
MRRC0141	422699	6600742	313	130	-60	46	No significant assays					
MRRC0142	423387	6600541	315	150	-61	45	No significant assays					
MRRC0143	423455	6600605	316	190	-61	45	No significant assays					
MRRC0144	422710	6600696	313	118	-61	44	No significant assays					
MRRC0145	423464	6600556	317	196	-61	45	No significant assays					
MRRC0146	423881	6600083	315	160	-60	235	Assays Pending					
MRRC0147	423535	6600509	320	180	-60	45	Assays Pending					
MRRC0148	423691	6600492	322	150	-60	45	Assays Pending					

* True thicknesses: unless otherwise indicated 75-80% for holes drilled towards SW, 20-30% for holes drilled towards NE

* True thicknesses: **MRRC0039** and **MRRC0043** ~75% of downhole intersection

* True thicknesses: **MRRC0040** 85-90% of downhole intersection

Appendix 2 – Moora Project– Diamond Core Drill Hole Statistics

Hole_ID	East	North	RL	Depth (m)	Dip	Azimuth	From (m)	To (m)	Significant Intercepts		
									Interval (m)	Au >0.1 (g/t)	Cu >0.1%
MRDD0001	422286	6599923	308	142	-61	215	100	115	15	0.7	-
									inc. 9m @ 1.1g/t Au from 100m and 3m @ 2.7g/t from 102m		
MRDD0002	422311	6599963	310	217	-60	212	172	189	17	0.4	-
									inc. 3m @ 1.0g/t Au from 172m		
MRDD0003	422196	6599984	308	228	-60	215	1	3.1	2.1	0.3	-
							16	19	3	0.3	0.2
							29	33	4	1.3	0.1
									inc. 1m @ 4.6g/t Au and 0.1% Cu from 32m		
							64	66.45	2.45	5.6	-
									inc. 1.45m @ 9.4g/t Au from 65m		
							110	111.83	1.83	3.1	0.3
									inc. 1.0m @ 5.5g/t Au and 0.3% Cu from 110m		
							124	130	6	1.1	-
		inc. 1.1m @ 5.3g/t Au from 128m									
133	137.32	4.32	2.7	-							
		inc. 1.61m @ 6.5g/t Au from 135.04m									
MRDD0004	422222	6600010	310	271	-60	215	158	159	1	0.3	0.9
							61	62	1	0.8	-
									15	0.5	0.2
							104	119	inc. 1m @ 2.2g/t Au and 0.3% Cu from 104m		
									inc. 1m @ 1.2g/t Au and 0.5% Cu from 117m		
							129	142	13	0.4	0.3
									inc. 1m @ 2.4g/t Au and 1.5% Cu from 140m		
							162	164	2	0.4	1.6
							187	189	2	0.4	0.3
201	202	1	0.2	0.7							
209	210	1	0.5	0.7							
211	212	1	0.9	-							
MRDD0005	422376	6599861	311	163	-60	216	48	52.6	4.6	0.8	0.5
									inc. 0.6m @ 5.0g/t Au and 2.7% Cu from 51m		
MRDD0006	422391	6599900	314	180	-60	214	107.84	110	2.16	0.2	0.4
									10.1	0.4	0.3
MRDD0007	422470	6599835	319	240	-60	213	137.9	148	inc. 0.55m @ 1.0g/t Au and 1.3% Cu from 51m		
									inc. 1m @ 1.4g/t Au and 1.1% Cu from 51m		
MRDD0008	422276	6600087	315	420	-55	216	206	211	5	0.3	0.1
							312	314	2	0.5	0.2
MRDD0009	422504	6599880	321	265	-59	215	49.33	50	0.77	0.2	0.6
							59	69	10	0.3	0.1
							186	187	1	0.1	1.5
							200	213	13	0.3	0.5
		inc. 1.27m @ 0.3g/t Au and 1.4% Cu from 51m									
MRDD0010	422453	6599797	316	159	-59	215	No Significant Assays				
MRDD0011	425694	6598310	339	228	-61	179	2	8.15	6.15	0.3	
							28	36	8	0.2	
							68.5	77	8.5	3.1	
									inc. 2.9m @ 7.2g/t Au and 0.3% Cu from 70.9m		
212	215	3	0.4								
MRDD0012	423826	6600081	318	202	-60	180	Assays Pending				
MRDD0013	423426	6600572	316	271	-60	49					

Appendix 3 – Moora– JORC Code 2012 Table 1 Criteria

The table below summarises the assessment and reporting criteria used for the Moora Project and reflects the guidelines in Table 1 of *The Australasian Code for the Reporting of Exploration Results, Mineral Resources and Ore Reserves* (the JORC Code, 2012).

Section 1 Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
Sampling techniques	<p><i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i></p> <hr/> <p><i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i></p> <p><i>Aspects of the determination of mineralisation that are Material to the Public Report.</i></p> <p><i>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i></p>	<p>Sub-surface samples have been collected by aircore (AC), reverse circulation (RC) and diamond core drilling techniques (see below).</p> <p>Drillholes are oriented perpendicular to the interpreted strike of the mineralised trend except where limited access necessitates otherwise.</p> <p>Soil samples collected from 0.1 -1m depth with 200-500g, - 2mm material collected for assay.</p> <hr/> <p>AC and RC samples are collected by the metre from the drill rig cyclone in calico bags and a bulk sample in plastic mining bags.</p> <p>4m composite samples collected via spear sampling of 1m bulk samples.</p> <p>1m samples retained for future analyses if 4m composites return anomalous assays.</p> <p>Samples typically dry.</p> <p>Cyclones regularly cleaned to remove hung-up clays and avoid cross-sample contamination.</p> <p>Diamond core sampled in intervals of ~1m (up to 2m) where possible, otherwise intervals less than 1 m selected based on geological boundaries.</p> <p>Entire sample pulverised.</p> <p>Mixed 4 acid digest.</p> <p>Samples assayed at Bureau Veritas in Perth, WA</p> <p>Au, Pt, Pd (FA003),</p> <p>Cr, Fe, Mg, S, Ti (MA101)</p> <p>As, Bi, Co, Cu, Ni, Te, Zn (MA102)</p>
Drilling techniques	<p><i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i></p>	<p>Drilling techniques used:</p> <ul style="list-style-type: none"> ○ Aircore – standard 3.5" aircore drill bit. ○ Reverse Circulation (RC/5.5") with a face sampling hammer ○ NQ2 Diamond Core, standard tube <p>Diamond core holes drilled directly from surface or from bottom of RC pre-collars. Core orientation provided by an ACT REFLEX (ACT II RD) tool.</p>
Drill sample recovery	<p><i>Method of recording and assessing core and chip sample recoveries and results assessed.</i></p> <hr/> <p><i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i></p>	<p>Sample recoveries for AC and RC drilling are visually estimated and recorded for each metre.</p> <p>For diamond core the recovery is measured and recorded for every metre.</p> <hr/> <p>AC and RC drill collars are sealed to prevent sample loss and holes are normally drilled dry to prevent poor recoveries and contamination caused by water ingress. Wet intervals are noted in case of unusual results.</p>

Criteria	JORC Code explanation	Commentary
		For diamond core loss, core blocks inserted in sections where core loss has occurred. This has then been written on the block and recorded during the logging process and with detailed photography of dry and wet core.
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	None noted.
Logging	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	All AC and RC drillholes are logged on 1 m intervals and the following observations recorded: Recovery, quality (i.e. degree of contamination), wet/dry, hardness, colour, grain size, texture, mineralogy, lithology, structure type and intensity, vein type and %, and alteration assemblage. Diamond core is logged in its entirety as per detailed geological description listed above. Geotechnical logging completed for the entire hole.
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i>	Logging is quantitative, based on visual field estimates
	<i>The total length and percentage of the relevant intersections logged.</i>	All holes are logged from start to finish.
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	Half core submitted for assaying following sawing with diamond core blade. Remaining half core stored as a library sample. Density measurements, if required, will be taken on half core samples using the Archimedes method.
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	Non-core samples are collected as 1 metre samples and then composited to 4m by tube/spear sampling. Samples are typically dry.
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	Sample preparation follows industry best practice standards and is conducted by internationally recognised laboratories, i.e. Oven drying, jaw crushing and pulverising so that 85% passes -75microns.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	Duplicates, standards and blanks inserted approximately every 25 samples. Review of lab standards
	<i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i>	Measures taken for drill samples include: <ul style="list-style-type: none"> regular cleaning of cyclones and sampling equipment to prevent contamination; statistical comparison of duplicate, standards and blanks Statistical comparison of anomalous composite assays versus average of follow up 1m assays.
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	Entire sample submitted for assay. The drill sample size (2-3kg) submitted to laboratory is consistent with industry standards.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i>	Assay and laboratory procedures have been selected following a review of techniques provided by internationally certified laboratories. Samples are submitted for multi-element analyses by Bureau Veritas fire assay and aqua-regia techniques following mixed-acid digest.

Criteria	JORC Code explanation	Commentary
		The assay techniques used are total.
	<i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i>	An Olympus Vanta M Series Handheld XRF (pXRF) machine was used to assist geologists with mineral and lithology identification, in particular observed sulphides. A read time of 30 seconds was utilised, 15 second each for the first and second beams. The pXRF calibration was checked daily against a known standard. PXRF readings are only used to assist with sampling and logging and are not reported.
	<i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established</i>	Regular insertion of blanks, standards and duplicates every 25 samples. Lab standards checked for accuracy and precision.
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Intersections peer reviewed in house.
	<i>The use of twinned holes.</i>	None drilled.
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	All field data is manually collected, entered into excel spreadsheets, validated and loaded into an Access database. Electronic data is stored on the Perth server. Data is exported from Access for processing by different software packages. All electronic data is routinely backed up. No hard copy data is retained.
	<i>Discuss any adjustment to assay data.</i>	None required
Location of data points	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	All samples collected are located using a handheld GPS.
	<i>Specification of the grid system used</i>	The grid system used is GDA94 Zone 50
	<i>Quality and adequacy of topographic control.</i>	Nominal RLs based on regional topographic datasets are used initially; however, these will be updated if DGPS coordinates are collected.
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	Drilling Angepena – Holes ~50m apart on lines ~100m apart. Other targets - Variable due to first pass testing of geochemical or geophysical anomalies See diagrams in report.
	<i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	Soils First pass sampling collected on 200x200m, 400x400m and 800x800m grid spacing with density of sampling dependent on perceived prospectivity. Infill sampling collected on 50m x50m, 100m x 50m and 200x50m grids depending complexity of anomaly.
	<i>Whether sample compositing has been applied.</i>	MRE not being prepared. AC and RC drill samples collected as 4m composites which are composited from 1 m intervals. 1 m samples submitted for assay where composite or pXRF results are considered significant.

Criteria	JORC Code explanation	Commentary
Orientation of data in relation to geological structure	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	Drilling is typically oriented perpendicular to the interpreted strike of geology and no bias is envisaged.
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	None observed.
Sample security	<i>The measures taken to ensure sample security.</i>	Senior company personnel supervise all sampling and transport to assay laboratory in Perth.
Audits or reviews	<i>The results of any audits or reviews of sampling techniques and data.</i>	None completed.

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i>	<p>The Moora Project comprises 3 granted exploration licences (E70/5217, E70/5286 and E70/5287). The tenement package forms a contiguous, 467km² area located ~150km NNE of Perth, Western Australia.</p> <p>All ELs are held by ERL (Aust) Pty Ltd, a wholly owned subsidiary of Minerals 260 Limited (MI6).</p> <p>MI6 has agreed to pay Armada Exploration Services:</p> <ul style="list-style-type: none"> \$1,000,000 cash; and a 0.5% NSR <p>if it discovers an economic mineral deposit and makes a decision to mine within the above tenements.</p> <p>The Koojan JV Project area totals ~550km² and comprises five granted Exploration Licences (ELs 70/5312, 70/5337, 70/5429, 70/5450 and 70/5515), and one application for a Prospecting Licence (PL 70/1743).</p> <p>All tenements are 100%-owned by Coobaloo Minerals Pty Ltd, which is owned 75% by Lachlan Star Limited (ASX: LSA) and 25% by private group Wavetime Nominees Pty Ltd.</p> <p>Minerals 260 (MI6) through its wholly owned subsidiary, ERL (Aust) Pty Ltd, has earned 30% equity in the Koojan JV by spending \$1,500,000 on in-ground exploration and has the right to increase this 51% equity if it spends \$4,000,000 within 5 years of Agreement execution.</p> <p>MI6 manages exploration on the JV - a JV committee will be established to Wavetime will be 25% free-carried until completion of a BFS after which it will have the right to contribute pro-rata or convert to a 2% NSR.</p> <p>The Moora and Koojan Projects are largely underlain by freehold properties used for broad acre cropping and livestock rearing. MI6 and Coobaloo have negotiated access agreements the properties where fieldwork has been completed and is in discussions with other landowners.</p> <p>ERL and Coobaloo have signed Heritage Agreements with the South West Aboriginal Land and Sea Council Aboriginal Council who act on behalf of the Yued Agreement Group.</p>
	<i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i>	All tenements are in good standing.

Criteria	JORC Code explanation	Commentary
Exploration done by other parties	<i>Acknowledgment and appraisal of exploration by other parties.</i>	<p>Previous exploration for magmatic Ni-Cu-PGE sulphide mineralisation has been carried out over the central part of the Moora Project area by Poseidon NL (1968), Palladium Resources (1999 – 2001) and Washington Resources (2004 – 2009).</p> <p>This work included geophysical surveys, surface geochemistry and shallow drilling. Anomalous Ni+Cu+PGE+Au was defined within the shallow, weathered regolith.</p> <p>There has been no drill testing of the primary, unoxidised bedrock prior to M16 commencing work.</p>
Geology	<i>Deposit type, geological setting and style of mineralisation.</i>	<p>The Moora Project area is located within the >3Ga age Western Gneiss Terrain of the Archaean Yilgarn Craton of southwest Western Australia.</p> <p>The prospective mafic/ultramafic bodies lie within the highly deformed Jimperding Metamorphic Belt which locally comprises high grade metamorphic rocks of quartz feldspar composition with some amphibolite schist and minor banded iron formation. The Belt is up to 70 kilometres wide and bounded to the west by the Darling Fault (and Perth Basin) and to the east by younger Archaean rocks. Regionally the geological trend is north-westerly with moderate to steep north-easterly dips.</p> <p>NNE and NNW trending, Proterozoic dolerite dykes also intrude the geological sequence.</p> <p>Outcrops are rare and bedrock geology is largely obscured by lateritic duricrust and saprolitic weathering. The clearing of farmland and related agricultural practices have further contributed to the masking of the bedrock.</p> <p>The intrusive mafic/ultramafic units are interpreted to form concordant igneous complexes at least 50m thick; however, the true dimensions are difficult to determine due to the limited outcrop.</p>
Drill hole Information	<p><i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i></p> <ul style="list-style-type: none"> <i>easting and northing of the drill hole collar</i> <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i> <i>dip and azimuth of the hole</i> <i>down hole length and interception depth</i> <i>hole length.</i> 	<p>See diagrams and appendices in attached report.</p>
Data aggregation methods	<p><i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i></p> <p><i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i></p>	<p>See Appendices referred to above.</p> <p>See Appendices referred to above.</p>

Criteria	JORC Code explanation	Commentary
	<i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i>	None reported
Relationship between mineralisation widths and intercept lengths	<p><i>These relationships are particularly important in the reporting of Exploration Results.</i></p> <p><i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i></p> <p><i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</i></p>	<p>At Angepena, true thicknesses estimated to be:</p> <ul style="list-style-type: none"> ▪ 75-80% of down hole length for holes drilled towards SW; and ▪ 20-30% of down hole length for holes drilled towards NE. <p>At Mynt true thicknesses estimated to be:</p> <ul style="list-style-type: none"> • 85-90% of down hole length <p>At Zest true thicknesses estimated to be:</p> <ul style="list-style-type: none"> • 75-80% of down hole length
Diagrams	<i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i>	See Figures in body of report
Balanced reporting	<i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i>	Results for all sampling reported are shown on diagrams included in the ASX report.
Other substantive exploration data	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i>	All meaningful and material data reported
Further work	<i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i>	<ul style="list-style-type: none"> • Process and interpret pending assays from drilling programs. • Plan follow up drilling.