

ASX:DRE

ABN 40 1 19 03 1 864

ASX ANNOUNCEMENT 12 September 2023

Thick Ni-Cu Mineralisation over 400m, Open in all Directions: Mangaroon (Earn-in)

Amendment

Dreadnought Resources Limited ("**Dreadnought**") provides some supplementary information regarding Figure 3 of the announcement released earlier today, noting that the photo of the massive sulphide RC chips from 45-46m comprised of 40-50% pentlandite and chalcopyrite was taken from drillhole REYRC013.

The cautionary statement on page 8 has also been updated to include an additional statement with regards to visual estimates.

The amended version of the release is attached.

For further information please contact:

Dean Tuck Managing Director Dreadnought Resources Limited E:<u>dtuck@dreadnoughtresources.com.au</u> Jessamyn Lyons Company Secretary Dreadnought Resources Limited E:jlyons@dreadnoughtresources.com.au



ASX:DRE

ABN 40 1 19 03 1 864

ASX ANNOUNCEMENT 12 September 2023

Thick Ni-Cu Mineralisation over 400m, Open in all Directions: Mangaroon (Earn-in)

HIGHLIGHTS

- The current RC drill program has been completed at the Bookathanna North and High Range prospects along the 45km Money Intrusion, part of the Mangaroon Ni-Cu-PGE Project (First Quantum Minerals Earn-in). A total of 10 holes (1,074m) were drilled with down hole EM ("DHEM") to commence in September 2023.
- The first hole of the program at Bookathanna North (REYRC013, for 153m) targeting a 37,000S conductor plate, intersected ~14m of Ni-Cu sulphide mineralisation from 37m (ASX 31 August 2023).
- Visual, thick Ni-Cu mineralisation has now been confirmed over 400m strike and remains open in all directions. REYRC019, a 200m step out hole from REYRC013 intersected 27m of Ni-Cu sulphide mineralisation including 2m of semi-massive sulphides with no previously defined geophysical signature. The sulphides appear to be high tenor, comprised of 40-50% combined pentlandite and chalcopyrite in equal proportions.
- Given the tenor, style and thickness of mineralisation, the entire Money Intrusion will be reassessed with work to include Induced Polarization ("IP") surveys to search for deeper, massive sulphides, trap sites.
- Assays from the program are expected throughout September/October 2023. DHEM results are expected in October 2023.
- This and future programs are fully funded by First Quantum Minerals and managed by Dreadnought.

Dreadnought Resources Limited ("Dreadnought") is pleased to announce that RC drilling has intersected further significant visual Ni-Cu sulphides at the Bookathanna North prospect



along the 45km long Money Intrusion part of the Mangaroon Ni-Cu-PGE Project, located in the Gascoyne Region of Western Australia.

Dreadnought's Managing Director, Dean Tuck, commented: "For the past two years, the work programs at the Money Intrusion have focused on confirming the fertility, high tenor and potential to form sulphide accumulations. This program has been a major leap forward confirming massive and semi-massive sulphides within thick halos of disseminated and net textured sulphides at a marginal trap site within the Money Intrusion. There are two key outcomes from this program. Firstly, that the Money Intrusion can form high tenor massive sulphides and that the search for additional trap sites is imperative. Secondly, given the high tenor of mineralisation, massive sulphides are not required for high-grade mineralisation and geophysical techniques used to date may have missed significant targets. We look forward to re-assessing the entire Money Intrusion, including follow up geophysics and drilling at Bookathanna North later in 2023."

Figure 1: Nick Chapman (L) and Chris Manners (R) with semimassive sulphide RC chips from a step out drill hole at the Bookathanna North prospect.





SX:DRE

ABN 40 1 19 03 1 864

SNAPSHOT – MANGAROON Ni-Cu-PGE

Major Miner, First Quantum Minerals, Earning-in

- The potential of the Money Intrusion is underscored by an Earn-In with First Quantum Minerals Ltd (TSE:FM), a ~\$20B TSX listed company (ASX 7 Apr 2021, ASX 30 Aug 2022).
- First Quantum Minerals can earn an initial 51% interest by funding \$12M of expenditure by 1 March 2026. First Quantum Minerals may withdraw at any time during the earn-in phase with 0% interest.
- Upon satisfying the earn-in requirements, a Joint Venture will be formed where First Quantum Minerals may elect to increase its interest to 70% by sole funding expenditure up until a Decision to Mine.
- Once a Decision to Mine has been made, Dreadnought can elect to either:
 - Maintain its 30% by co-contributing.
 - Dilute to 20% and be loan carried by First Quantum Minerals, repaid through revenue.
 - Divest its 30% interest to First Quantum Minerals at fair market value.
- Dreadnought retains gold rights across the earn-in tenements.

Fertile Ni-Cu-PGE System Confirmed

- Fertile Ni-Cu-PGE sulphide systems are rare and the Money Intrusion has already been proven to contain high tenor magmatic Ni-Cu-PGE mineralisation.
- The Money Intrusion is confirmed to be ~800Ma, a fertile time for Ni-Cu-PGE systems globally. Highly prospective keel geometries which are suitable for forming trap sites for magmatic sulphide accumulations have been identified.
- First pass drilling in 2022 at the Bookathanna and High Range prospects intersected magmatic sulphide mineralisation including (ASX 10 Nov 2022). To date, the Ni and Cu have been in ~50:50 proportions.
- Notwithstanding the early-stage drilling, a significant success rate has already been achieved. Out of the 22 RC holes (2,906m) drilled to date, 15 holes have either assayed or shown visual/pXRF evidence of Ni-Cu-PGE sulphides.

No Modern Exploration

- Outcropping Ni sulphides were identified by Alan McDonald, the Pastoralist at Mangaroon in the early 1960s. However, no detailed geophysical, geochemical or mapping programs were ever undertaken.
- The first-ever detailed airborne magnetics, surface geochemical, ground EM and mapping surveys have now confirmed the potential of the 45km long Money Intrusion.

Genuine Camp Scale Potential

- Outcropping blebby sulphides have been confirmed over significant portions of the ~45km long Money Intrusion.
- Multiple plumbing centres have been interpreted, each with the potential for trap sites within the magma pathways.
- Mineralisation has already been confirmed by drilling at three prospects within the Money Intrusion: Bookathanna, Bookathanna North and High Range.

Nickel and Copper are Critical to the Low Carbon Energy Transition

- Nickel is essential to clean energy technologies including being a major cathode material in lithium-ion batteries. Furthermore, nickel sulphide deposits have a much lower carbon footprint when being converted to Class I nickel for battery grade applications.
- Copper is essential for electricity-related technologies with renewable energy systems requiring up to 12x more copper compared to traditional energy systems.





ABN 40 1 19 03 1 864




Figure 2: Plan view image showing the location of recently completed drill holes (red dots) in relation to previous drilling over a magnetics (RTP IVD) and ortho image. The Money Intrusion is outlined in green.



ASX:DRE

+61 (08) 9473 8345 info@dreres.com.au Unit I, 4 Burgay Court Osborne Park WA 6017

ABN 40 1 19 03 1 864

Technical Discussion of Ni-Cu-PGE RC Drilling (REYRC013-22)

The drill program was originally designed as 5 RC holes with DHEM to test 5 EM conductors within the Money Intrusion (2 at Bookathanna North and 3 at High Range). Following the intersection of massive sulphides in the first hole (REYRC013), an additional 5 holes were drilled at Bookathanna North infilling and then stepping out north and south along strike. A total of 10 holes have been drilled (1,074m) with 7 holes at Bookathanna North and 3 at High Range.

Drilling generally collared into the shallow and weakly weathered gabbroic core of the Money Intrusion before passing into the footwall olivine dolerite and finishing in gneissic to granitic country rock. Significantly, the furthest north hole (REYRC017) intersected a thick gabbroic core and did not reach the mineralised footwall olivine dolerite or country rock. REYRC017 highlights the variable geometry of the Money Intrusion and potential to form trap sites for sulphide accumulation.

Importantly, 6 of the 7 holes at Bookathanna North intersected thick (10-50m) disseminated and net textured Ni-Cu sulphides within the footwall olivine dolerite. Of these REYRC013 and REYRC019 each intersected 2m of semi-massive to massive sulphides within the mineralised envelope. Logging details are shown in Table I below. Significantly, REYRC019 was



Figure 3: Photo of massive sulphide RC chips from REYRC013: 45-46m comprised of 40-50% pentlandite and chalcopyrite.

a blind step out hole not targeting a conductive anomaly. REYRC019 intersected semi-massive sulphides emphasising the need for the entire Money Intrusion to be reassessed given the results to date.

All sulphide mineralisation consists of pentlandite $(Fe,Ni)_9S_8$, chalcopyrite $(CuFeS_2)$ and pyrrhotite (Fe(1-x)S) with pentlandite and chalcopyrite making up ~40-50% of the sulphide mix with the remainder being pyrrhotite. In addition to the observed mineralisation, the presence of Ni and Cu was confirmed by handheld XRF.

At High Range, 3 holes were drilled (REYRC020-22, 255m) targeting three conductive plates ranging from 450-900S. These holes intersected sheared metasediments within the Edmund Group explaining the EM conductors. These results will be incorporated into the overall reassessment of the entire Money Intrusion

Assay results are expected throughout September/October 2023. DHEM survey results are expected in October 2023.

Hole ID	From (m)	To (m)	Interval (m)	Mineralisation Style	Sulphide Type	Sulphide %	Prospect
	37	45	8	Disseminated		1-5	
REYRC013	45	47	2	Massive		80-100	
	47	51	4	Net Textured		5-10	
REYRC014	35	61	26	Disseminated		1-10	
REYRC015	28	57	29	Disseminated	Pyrrhotite,	I <i>-</i> 5	
REYRC016	41	73	32	Disseminated	Pentlandite,	1-5	Bookathanna North
REYRC018	5	58	53	Disseminated / Net Textured	Chalcopyrite	I-20	
	59	78	19	Disseminated		1-5	
REYRC019	78	80	2	Semi-Massive		30-40	
	80	86	6	Disseminated		1-10	


Table 1: Significant Sulphide Intervals - Visual Estimates



Technical Discussion of Ni-Cu-PGE Exploration (E08/3274, E09/2384: First Quantum Minerals Earn-in) The confirmation of a fertile magmatic Ni-Cu-PGE system within the 45km long Money Intrusion highlights the potential for multiple deposits and/or deposit styles as outlined below.

- **Jinchuan Ni-Cu-PGE:** The Money Intrusion has been dated to ~800Ma, similar in age and tectonic setting to the Jinchuan Ni-Cu-PGE deposit in China (>500 Mt @ 1.2% Ni, 0.7% Cu, ~0.4 g/t PGE, Lightfoot 2007). Jinchuan contains three main deposits over ~6.5kms of strike, each situated within a sub-chamber of the overall intrusion. Only one of the deposits outcrops at surface. Mineralisation is dominated by net-textured and disseminated sulphides with minor massive sulphide accumulations. The disseminated sulphides form an envelope around the higher-grade, net-textured and massive sulphides.
- Eagle and Eagle East: To date, 15 out of 22 RC holes intersected mineralisation along significant strike showing increasing width and intensity near subtle changes in the walls and base of the intrusion, including the formation of massive and semi-massive mineralisation. These results highlight the potential for massive sulphide mineralisation to concentrate and form at trap sites. This is similar to Eagle and Eagle East (~5Mt @ 3.5% Ni, 2.9% Cu, 1.6g/t PGE, 0.1% Co, Lundin 2013) located in North America.

Drill targeting to date has been dominated by FLEM surveys designed to identify near-surface, massive sulphides along the southwestern edge of the Money Intrusion. Drilling has confirmed high tenor massive, semi-massive sulphides within a halo of net-texture and disseminated sulphides with mineralisation intensifying in trap sites along the edges and base of the intrusion. Drilling at Bookathanna North has confirmed that thick mineralisation occurs over a significant strike length and that net-textured and semi-massive sulphide accumulations have not been identified by the FLEM surveys.



Given the high tenor of the Ni-Cu sulphide system, net-textured and semi-massive sulphides are viable targets in their own right. Additionally, deeper trap sites potential with the to form sulphide significant massive accumulations have not been targeted or assessed.


Targeting going forward will focus on identifying:

- net textured and heavily disseminated sulphide mineralisation using IP surveys: and

- deep trap sites for massive sulphides using geophysical inversions and more powerful EM surveys.

A review reassessment of the Money Intrusion and the targeting completed to date is underway with further drill targets expected to be defined in the December 2023 quarter.

Figure 4: Plan view image showing the location of recently completed drill holes at Bookathanna North in relation to FLEM plates over an orthoimage and interpreted Money Intrusion.



Background on Mangaroon (E08/3274, E8/3178, E09/2384, E09/2433, E09/2473: First Quantum Minerals Earn-in) (E08/3275, E08/3439, E09/2290, E09/2359, E09/2370, E09/2405, E09/2448, E09/2449, E09/2450, E09/2467, E09/2478, E09/2531, E09/2535, E09/2616, M09/91, M09/146, M09/147, M09/174, M09/175: 100%)

Mangaroon (Figure 5) covers >5,200sq kms of the Mangaroon Zone in the Gascoyne Region of Western Australia and is comprised of:

- the ~45km long Money Intrusion (First Quantum Minerals earn-in) which contains high tenor magmatic Ni-Cu-PGE mineralisation;
- the >10km long Mangaroon Au Shear Zone (100%) where fractured, small scale ownership has limited previous gold exploration with only ~200m of the >10km having been drilled notwithstanding the high-grade, camp scale potential;
- the ~43km long Yin REE Ironstone Complex (100%) which already contains: an independent total Resource of 20.06Mt @ 1.03% TREO (ASX 5 Jul 2023) over only ~4km of the ~43km of ironstones including an initial Indicated Resource of 5.52Mt @ 1.23% TREO over only ~250m of strike (ASX 5 Jul 2023); and an Exploration Target of 50-100Mt at 0.9-1.3% TREO (ASX 13 Feb 2023) over 40 kms of strike.
- the ~9km long REE-Nb-Ti-P-Sc C1-C5 carbonatites which contain an initial independent Inferred Resource of 10.84Mt @ 1.00% TREO at C3 (ASX 28 Aug 2023).




Figure 5: Plan view map of Mangaroon showing the location of the First Quantum Minerals Earn-in and 100% Dreadnought ground (Mangaroon Au Shear Zone, Yin REE Ironstone Complex and REE-Nb-Ti-P-Sc CI-C5 carbonatites).



SX:DRE

ABN 40 1 19 03 1 864

For further information please refer to previous ASX announcements:

- 25 November 2020 Mangaroon Ni-Cu-PGE & Au Project
- 7 April 2021
- 14 February 2022
- 10 June 2022
- 30 August 2022
- 10 November 2022
- Mangaroon Ni-Cu-PGE Project advances to \$152M Earn-In Exploration Update Mangaroon Ni-Cu-PGE (FQM Earn-In)

Conductors Defined Along the Money Intrusion

Option/IV Agreement Signed with Global Base Metal Miner

Drilling Successfully Completed at Mangaroon Ni-Cu-PGE

- 24 March 2023 Five Strong EM Conductors at Mangaroon Ni-Cu-PGE Project
- 30 August 2023 Drilling Commenced at Money Intrusion Ni-Cu-PGE
- 31 August 2023 Massive and Disseminated Ni-Cu Sulphides Intersected

UPCOMING NEWSFLOW

September-December: Ongoing drilling results from completed drilling at Mangaroon REE (100%)

12 (Melbourne) & 14 (Sydney) September: New World Metals Conference

September: Results of geophysical surveys at Mangaroon (100%)

September: Commencement of RC drilling at Mangaroon Au (100%)

September: Commencement of drilling at Tarraji-Yampi (80% and 100%)

September: Results of geophysical and geochemical surveys at Central Yilgarn (100%)

September: 2023 Annual Report

October/November: Results from target generation and definition work at Bresnahan (100%)

October/November: Further RC drilling at Mangaroon Ni-Cu-PGE (Earn-in) and Au (100%)

October: Quarterly Activities and Cashflow Report

23 November: Annual General Meeting

December 2023 quarter: REE Resource upgrade (Mangaroon 100%)

~Ends~

For further information please contact: **Dean Tuck** Managing Director Dreadnought Resources Limited E: <u>dtuck@dreres.com.au</u>

Jessamyn Lyons Company Secretary Dreadnought Resources Limited E: <u>ilyons@dreres.com.au</u>

This announcement is authorised for release to the ASX by the Board of Dreadnought.



SX:DRF

ABN 40 1 19 03 1 864

Cautionary Statement

This announcement and information, opinions or conclusions expressed in the course of this announcement contains forecasts and forward-looking information. Such forecasts, projections and information are not a guarantee of future performance, involve unknown risks and uncertainties. Actual results and developments will almost certainly differ materially from those expressed or implied. There are a number of risks, both specific to Dreadnought, and of a general nature which may affect the future operating and financial performance of Dreadnought, and the value of an investment in Dreadnought including and not limited to title risk, renewal risk, economic conditions, stock market fluctuations, commodity demand and price movements, timing of access to infrastructure, timing of environmental approvals, regulatory risks, operational risks, reliance on key personnel, reserve estimations, native title risks, cultural heritage risks, foreign currency fluctuations, and mining development, construction and commissioning risk.

Visual estimates of mineral abundance should never be considered a proxy or substitute for laboratory analyses where concentrations or grades are the factor of principal economic interest. Visual estimates also potentially provide no information regarding impurities or deleterious physical properties relevant to valuations.

Competent Person's Statement – Exploration Results

The information in this announcement that relates to geology, exploration results and planning, and exploration targets was compiled by Mr. Dean Tuck, who is a Member of the AIG, Managing Director, and shareholder of the Company. Mr. Tuck has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr. Tuck consents to the inclusion in the announcement of the matters based on the information in the form and context in which it appears.

The Company confirms that it is not aware of any new information or data that materially affects the information in the original reports, and that the forma and context in which the Competent Person's findings are presented have not been materially modified from the original reports.



ABN 40 1 19 03 1 864

INVESTMENT HIGHLIGHTS

Kimberley Ni-Cu-Au Project (80/100%)

DREADNOUGHT

ESO

The project is located only 85kms from Derby in the West Kimberley region of WA and was locked up as a Defence Reserve since 1978.

The project has outcropping mineralisation and historic workings which have seen no modern exploration.

Results to date indicate that there may be a related, large scale, Proterozoic Cu-Au-Ag-Bi-Sb-Co system at Tarraji-Yampi, similar to Cloncurry/Mt Isa and Tennant Creek.

Mangaroon Ni-Cu-PGE JV & Au/REE 100% Project

Mangaroon covers ~5,200 kms and is located 250kms south-east of Exmouth in the Gascoyne Region of WA. At the Money Ni-Cu-PGE has been identified and is subject to an earn-in by First Quantum Minerals (up to 70%). Dreadnought also has areas of outcropping highgrade gold including the historic Star of Mangaroon and Diamonds gold mines. In addition, Mangaroon has emerged as a globally significant, rapidly growing, potential source of critical minerals. Highlights include:

- An Exploration Target of 50-100Mt at 0.9-1.3% TREO estimated for the top 150m of the ~43km long Yin REE Ironstone Complex (ASX 13 Feb 2023).



- An independent Resource for Yin Ironstones Complex of 20.06Mt @ 1.03% TREO over only ~4kms including an Indicated Resource of 5.52Mt @ 1.23% TREO over just 250m strike (ASX 5 Jul 2023).
- Regional source of rare earths at the CI-C5 carbonatites totaling ~9kms x ~1km (ASX 7 Aug 2023).
- A large, independent initial Resource of 10.84Mt @ 1.00% TREO at C3, containing a range of critical minerals including rare earths, niobium, phosphate, titanium and scandium (ASX 28 Aug 2023).

Bresnahan HREE and Au Project (100%)

Bresnahan is located ~125km southwest of Newman in the Ashburton Basin. The project comprises ~3,700 sq kms covering over 200kms strike along the Bresnahan Basin / Wyloo Group unconformity. Bresnahan is prospective for unconformity related heavy rare earth ("**HREE**") deposits similar to Browns Range HREE deposits and mesothermal lode gold similar to Paulsen's Au-Ag-Sb deposits along strike.

Prior to consolidation by Dreadnought, the Bresnahan Basin had only been explored for unconformity uranium with limited exploration for mesothermal gold. Bresnahan is a first mover opportunity to explore for unconformity HREE.

Central Yilgarn Gold, Base Metals, Critical Minerals & Iron Ore Project (100%)

Central Yilgarn is located ~190km northwest of Kalgoorlie in the Yilgarn Craton. The project comprises ~1,600 sq kms covering ~150km of strike along the majority of the Illaara, Yerilgee and Evanston greenstone belts. Central Yilgarn is prospective for typical Archean mesothermal lode gold deposits, VMS base metals, komatiite hosted nickel sulphides and critical metals including Lithium-Caesium-Tantalum.

Prior to consolidation by Dreadnought, the Central Yilgarn was predominantly held by iron ore explorers and remains highly prospective for iron ore.



ABN 40 1 19 03 1 864

Table 2: Drill Collar Data (GDA94 MGAz50)

DREADNOUGHT

Prospect	Туре	EOH	Azimuth	Dip	RL	Northing	Easting	Hole ID
	RC	153	045	-70	286	7384666	364221	REYRC013
	RC	141	40	-70	288	7384657	364222	REYRC014
	RC	81	215	-85	285	7384670	364192	REYRC015
Bookathanna North	RC	87	15	-75	288	7384710	364245	REYRC016
	RC	177	20	-70	288	7384805	364279	REYRC017
	RC	69	30	-60	288	7384574	364150	REYRC018
	RC	111	215	-80	286	7384456	364136	REYRC019
	RC	57	290	-60	334	7376739	360783	REYRC020
High Range	RC	81	270	-60	333	7376696	360759	REYRC021
	RC	117	260	-60	333	7376672	360725	REYRC022

JORC Code, 2012 Edition – Table 1 report template Section I Sampling Techniques and Data (Criteria in this section apply to all succeeding sections.)

Criteria Sampling techniques	 JORC Code explanation Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement task approximate to the minorale under 	Commentary RC Drilling
	chips, or specific specialised industry standard	-
	measurement tools appropriate to the minerals under	Reverse Circulation (RC) drilling was undertaken to produce samples for assaying.
	 investigation, such as down hole gamma sondes, or handheld XRF instruments, etc.). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any 	Two sampling techniques were utilised for this program, Im metre splits directly from the rig sampling system each metre and 2m composite sampling from spoil piles. Samples submitted to the laboratory were determined by the site geologist.
	measurement tools or systems used.	Im Splits
	• Aspects of the determination of mineralisation that are Material to the Public Report.	Every metre drilled a 2-3kg sample (split) was sub-sampled into a calico bag via a Metzke cone splitter from each metre of drilling.
	 In cases where 'industry standard' work has been done this would be relatively simple (a g 'reverse signalation drilling) 	2m Composites
	would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling	All remaining spoil from the sampling system was collected in buckets from the sampling system and neatly deposited in rows adjacent to the rig. An aluminium scoop was used to then sub-sample each spoil pile to create a 2-3kg 2m composite sample in a calico.
	problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information.	For gold and PGEs, all samples are submitted to the laboratory and pulverised to produce a 50g charge for Fire Assay (ALS Code PGM-ICP24).
		Base Metal and lithological samples are analysed for 48 multi- elements via 4 acid digestion with MS/ICP finish (ALS Code ME-MS61)
Drilling techniques	 Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc.) and details (e.g. core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc.). 	RC Drilling Ausdrill undertook the program utilising a Drill Rigs Australia truck mounted Schramm T685WS drill rig with additional air from an auxiliary compressor and booster. Bit size was 5 ³ /4".
Drill sample recovery	• Method of recording and assessing core and chip sample	RC Drilling
	 recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. 	Drilling was undertaken using a 'best practice' approach to achieve maximum sample recovery and quality through the mineralised zones.
	• Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	Best practice sampling procedure included: suitable usage of dust suppression, suitable shroud, lifting off bottom between each metre, cleaning of sampling equipment, ensuring a dry sample and suitable supervision by the supervising geologist to ensure good sample quality.
ogging	• Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.	RC Drilling RC chips were logged under the supervision of a qualified geologist with sufficient experience in this geological terrane and relevant styles of mineralisation using an industry standard logging system which could eventually be utilised





ABN 40 1 19 03 1 864

 Whether legging is qualitative or quantitative in nature. Circ (or corstant, channel (c) photography). The total length and percentage of the relevant intersections logged. Sub-sampling techniques and sample of the relevant intersections logged. Sub-sampling techniques and sample of the control of the relevant intersections logged. If core, whether cut or som and whether quarter, half are used to an intersection and future relevance. RC pulp material is also analysed on their by pXFR analysis of pulversised and parameter to assist with legging and the identification of mineralisation. Logging is qualitative or semi-quantitative in nature. If core, whether cut or som and whether quarter, half are used to another the generation of the sample generation technique. If core, whether cut or som and whether quarter, half are used to another the generation of the sample generation technique. If core, whether cut or som and whether quarter, quality and the identification or semi-quantitative in nature. If core, whether cut or som and whether quarter, quality and the identification or semi-quantitative in nature. If core, whether cut or som and whether quarter, quality and the identification or semi-quantitative in nature. If core, whether cut or som and whether quarter, quality and the identification or semi-quantitative in nature. If core, whether cut or som and whether quarter, quality and the identification or semi-quantitative in nature. If core core, whether field, to a sample is a port context or percenting perlimitary gan perportation technique. Measures taken to ensure that the sampling is representation of the instance of the sample sample in the identification or semi-quantitation. Measures taken to ensure that the sampling is instance and tasket of concorgenetion or taker and mon	Criteria	JORC Code explanation	Commentary
 The 'total length and percentage of the relevant intersections logged. The 'total length and percentage of the relevant intersections logged. The 'total length and percentage of the relevant intersections logged. Sub-sampling techniques and source and stored in chip trays for preservation and future reference. Sub-sampling techniques and source whether rule to source whether rule to source whether rule (lifed, tube sampler), rotary source and source in the rule of the sample repercention technique. For all sample types, the nature, quality and appropriates to the gran size of the sample perpenditor technique. Quality control procedures of the sampler perpenditor technique. Whether sample sizes are appropriate to the gran size of the matterial collectic, including for instances takes to the sampler and the matterial collectic, including for instances takes to the sampler and a sample types. Whether sample sizes are opporpriate to the gran size of the matterial being sampled. Whether sample sizes are opporpriate to the gran size of the matterial being sampled. Whether sample sizes are opporpriate to the gran size of the matterial being sampled. The nature, quality and appropriates to the gran size of the matterial being sampled. The nature, quality and appropriates of the assign and blocatory technical persons at a rate of the sampler appropriate to the gran size of the analysis of pulses with the rune takes to the sampler and the sampler		• Whether logging is qualitative or quantitative in nature.	
Quality of mosay data and laboratory tests • The nature, quality and appropriateness of the asarphica to the regeneration of significant or fine-register in the significant of minimary packet in the sample in the sample in the sample in the material being sample. • Fif care, whether cut or same and whether quarter, had a regeneration of significant on fine-register in the sample in the material being sample in the sample in the sample in the material being sample. • Pertiminary pRRF analysis pRR analysis of pulverised and partially homogenised reject and whether sample in the sample in the material being sample. • Pertiminary pRRF analysis pRR is a spor reading on raw (inprocessed) RC sample plate with variable grain states and states of homogenisation to appropriateness of the sample in the sampling instructor creature for did dubicotectoron-tool in appropriateness of the sample in the sampling instructor creature for did dubicotectoron-tool in appropriate result for field dubicotectoron-tool in and hobrarony procedures used for determine 48 elements (ME-FKE) (NRE Sandards) were inserted through the re-zones at a rate of a wore inserted through and appropriateness of the assaying and baboratory tracks. • The nature, quality and appropriateness of the assaying and baboratory procedures used a determine 48 elements (ME-FKE) (NRE Sandard baboratory QAQC is undertaken and monitored anapresis including instrument moke and model, reeding in the contra		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	с, с
Sub-sampling techniques and some prephration If core, whether cut or som and whether quarter, hard and core taken. Legging is qualitative, quantitative or semi-quantitative in nature. Performinary pXRF analysis pxRF analysis of pulverised and partally homogenised reject and whether simple vet or dry. Quality control procedures dopted for all sub-sampling techniques for the sample repertoriation technique. Quality control procedures odpet for all sub-sampling instance results for field diplectatisecond-fund stages to machine representiative of the in-situ meterial callectal, including for the material being sampled. Wetainers subset to ensure that the sampling instance results for field diplectatisecond-fund sampling; whether sample size and the dimeter diplectatise cond-fund the material being sampled. Wetainers sample sampled. Wetainers sample sampled. Wetainers sample sampled. Wetainers sample sampled. Wetainer sample size and transmitter difficulties of market cone sample sampled (regit vas sub- sample from the bulk regits and CRM's (OREA Sandard) were inserted through the ore zones and resting and a grab sample from the bulk regits and CRM's (OREA Sandard) were inserted diversed to RSS samples (regit vas sub- sample from the bulk regits and CRM's (OREA Sandard) were inserted diversed to RSS samples (regit vas sub- sample from the bulk regits and CRM's (OREA Sandard bioarcaly, with IC-ASS finitoh or produce a SQ drange for Fire Assay with IC-ASS finitoh and bioarcany procedures used in determining the anal procession flocus apopled and theri derivation, error and precision hore been establis		intersections logged.	
Sub-sampling rechniques and sample preparation • If case, whether cut or sawn and whether quarty split, all care taken. • Preliminary pXFF analysis pXRF analysis of pulverised and partially homogenised reject C sample piles is fit for purpose as a preliminary end advectors adopted for all sub-sampler grants and states of homogenisation. • Preliminary pXFF analysis pXRF is a spot reading on raw (unprocessed) RC sample plants in the context of homogenisation. • For all sample types, the nature, quality and appropriatenes of the sample representity of samplers. • Measures taken to ensure that the sampling instance results of field dipatcels/cont-Mol Sampling. • WRF is a spot reading on raw (unprocessed) RC sample plants with variable grain sizes and states of homogenisations to confirm repetatability. The competent person considers this exceptable within the context of reporting preliminary exploration results. • Whether sample is zes are opporting to the grain sizes the material being sampled. • Work is a spat sample from the bulk reject in more clay-rich material. • Whether sample is a sampled. • Whether sampled into a call co bag via a bahar inserted directly afte instanced adjuctable scarthold is sampled. • Whether sample is a sampled. • The nature, quality and appropriates of the sample. • Preliminary PXEF analysis and laboratory tests • The nature, quality and appropriatenes of the assort material. • Quality of assay data and laboratory tests • The nature, quality and appropriatenes of the assort material. • Preliminary PXEF analysis • The nature, quality			magnetic susceptibility meter to assist with logging and the
etchniques and sample preparation af care token. if non-cre, whether simpled wet or dy. For all sample types, the nature, quality and appropriatenes of the sample reparation technique. Quality control procedures adopted for all sub-samples. Measures taken to ensure that the sampler preparative of the in-situ material calceted, including for instance results for field duplicate/scoothalf sampling. Measures taken to ensure that the sampler preparative of the in-situ material calceted, including for instance results for field duplicate/scoothalf sampling. Whether sample sizes are opporprinte to the grain size of the material being sampled. Whether sample sizes are opporprinte to the grain size of the material being sampled. The nature, quality and opporprinte to the grain size and laboratory tests The nature, quality and opporprintenes of the assiving and laboratory tests The nature, quality and opporprintenes of the assiving and laboratory tests The nature, quality and opporprintenes of the assiving and laboratory tests The nature, quality and opporprintenes of the assiving and laboratory tests The nature, quality and opporprintenes of the assiving and laboratory tests The nature, quality and opporprintenes of the assiving and haboratory tests The nature, quality and opporprintenes of the assiving and haboratory tests The nature, quality and opporprintenes of the assiving and ubboratory tests The nature, quality and opporprintenes of the assiving and laboratory QAQC is undertaken and monitorced. For gregisphical tools, spectrame			
preparation If non-care, whether riffed, tube sampled, ratary split, et and whether simple were of a sample types, the nature, quality and appropriateness of the sample spectra technique. Quality control procedures adopted for all sub-sampling increases taken to ensure that the sampling increase adopted for all sub-samples. Measures taken to ensure that the sampling increases of the duplicates control of sampling. Whether sample sizes are appropriateness of the duplicates control of samples. Measures taken to ensure that the sampling increases and products to the grain size and states of homogenisation. Whether sample sizes are appropriate to the grain size of the material being sampled. Whether sample sizes are appropriate to the grain size of the material being sampled. Whether sample sizes are appropriate to the grain size of the material being sampled. Whether sample sizes are appropriate to the grain size of the compart of products as and comparison results. Contining intermed directly field. Whether sample sizes are appropriate to the grain size of the material being sampled. Control applicates and event whether of the comparison of samples. Whether sample sizes are appropriate to the grain size of the comparison of samples. Standard by event samples and comparison of samples. Standard by event samples and comparison of samples. Whether acceptable within the comparison of samples. Standard by event samples and sample sizes of the assay in a sample form the bubic region to more day. The nature, quolity and appropriateness of the assay in a distance of fine samplesis including for t		• If core, whether cut or sawn and whether quarter, half or	Preliminary pXRF analysis
 For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality of control procedures adopted for all sub-sampling its ease and status even preparation at multiple locations to confirm repeated at molecule configure and abank inserted directly at a 4 Z-3 kg sample from the bulk reject in more clay-rich material. Quellity of assoy data The nature, quelity and appropriateness of the assaying and laboratory procedures used and whether technique is considered partial or total. For geophysici docks, spectrometers, handheid XRF instruments, etc., the parameters, used in determining the analysis including instrument, mole and model, rednig times, colibrations foctors ophiled and model, rednig times, colibrations foctors ophile and model, rednig times, paradimet with inbut ICAQLC All atta vas the conf		• If non-core, whether riffled, tube sampled, rotary split, etc.	
instance results for field duplicate/second-holf sampling. Instance results for field duplicate/second-holf sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. From every metter drilled, a 2-3kg sample (split) was sub-sampled into a calico bag wia Metzke cone splitter or taker as a grab sample from the bulk reject in more clay-rich material. Quality of end to be appropriate to the grain size of the material being sampled. From every metter drilled, a 2-3kg sample (split) was sub-sampled into a calico bag wia Metzke cone splitter or taker as a grab sample from the bulk reject in more clay-rich material. Quality of end to be appropriate to the grain size of the material. Quality of assay data and bank inserved directly after the core of the direct after the class and the class of the discover and the direct after the class of the discover and the direct after the technique is considered partial or total. Quality of assay data and laboratory procedures used and whether the technique is considered partial or total. From requestion took, spectrometers, handheld XRR instruments, etc., the parameters used in determining the analysis instruments, etc., the parameters used in determining the analysis instruments, etc., the parameters used in determining the analysis (and precision have been established. Verification of significant intersections by either independent or alternative company personnel. Preliminary partial sharks and monitored by the laboratory QAC is undertaken and monitored by the laboratory and by the company upon assay result creaking and procision have been established. Verification of significant intersections by either independent or alte		 For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is 	piles with variable grain sizes and states of homogenisation. High grade results were repeated at multiple locations to confirm repeatability. The competent person considers this acceptable within the context of reporting preliminary exploration results.
 Whether sample sizes are appropriate to the grain stee of the material being sampled. Whether sample sizes are appropriate to the grain stee of the material being sampled. Sampled C, and Marker C, and Sample C, and Sample C, Bullitz er at Reize C cone splitter or takes as a grab sample from the bulk reject in more clay-rich material. QAQC in the form of duplicates and CRM's (OREA Standard) were inserted through the ore zones at a rate of duplicate sample was taken and a blank inserted directly after a sag with besubmitted to ALS blaoratories (Perth oven dried to 105° cand pulverised to 85% passing 75um to produce a 50g charge for Fire Assay with IC-PAES finish were reassed with IC-PAES instanding diget to determine 48 elements (ME-MS61) with over arige as required. Standard laboratory pacedures used and whether technique is considered partial or total. For geophysical tooks, spectrometars, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors opplied and their derivation, etc. Nature of quality control procedures used in determining the analysis including instrument make and model, reading times, calibration factors opplied and their derivation, etc. Nature of quality control procedures odoptied (etc. standards, blanks, duplicates, external laboratory chccks) and whether acceltable levels of accuracy (it. lack of bias and errified standard are routinely analysed to monitor pXRF performance. Uverification of significant. intersections by either independent or alternative company personel. The verification of significant intersections by either independent or alternative company personel. The verification of significant intersections by either independent or alternative company personel. The verification of significant intersections by either independent or alter			0
Quality of assay data and laboratory pestore The nature, quality and appropriateness of the assaying and laboratory tests The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical total, spectrometers, handheid XRR, instrument, etc., the parameters used in determining the analysis including instrument, etc., the parameters used in determining the analysis including instrument, etc., the parameters used in determining the analysis including instrument, etc., the parameters used in deterdet (e.g. standard shanks, duplicate, external laboratory clecks) and whether acceptable levels of accuracy (i.e. lack of biars and precision have been established. The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures of the assay data assaying protocols. The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures of the responsible geologist and fiel on the company parameter of an errorade level of the clear assay result receival. 		• Whether sample sizes are appropriate to the grain size of	sampled into a calico bag via a Metzke cone splitter or taken as a grab sample from the bulk reject in more clay-rich
Quality of assoy data and laboratory tests • The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. • The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. • The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. • For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. • Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory clecks) and whether acceptable levels of accuracy (i.e. lack of biass) and precision have been established. • The verification of significant intersections by either independent or alternative company personnel. • The verification of significant intersections by either independent or alternative company personnel. • The verification of significant intersections by either independent or alternative company personnel. • Documentation of primary data, data entry procedures addata was collected directly by the Olympus Vanta M Series pXRF analyses and downloaded by digital transfer to an excel spreadsheet with inbuilt QAQC. All data was checked by the responsible geologist and filed on the company server. Verification of sum primary data, data entry procedures, data was indexed with as and eventually stored in an offsite of procode. • Discuss any adjustment to assay data. • Discuss any adjustment to assay data.			QAQC in the form of duplicates and CRM's (OREAS Standards) were inserted through the ore zones at a rate of 1:50 samples. Additionally, within mineralised zones, a duplicate sample was taken and a blank inserted directly after.
Quality of assay data and laboratory tests The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established. Verification of sampling and assaying The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. Preliminary pXRF analyses Preliminary pXRF analyses			2-3kg samples will be submitted to ALS laboratories (Perth), oven dried to 105°C and pulverised to 85% passing 75um to produce a 50g charge for Fire Assay with ICP-AES finish to determine Au and PGEs (PGM-ICP24) and 0.25g aliquot for four acid digest to determine 48 elements (ME-MS61) with overranges as required.
and laboratory tests and laboratory procedures used and whether the technique is considered partial or total. Olympus Vanta M Series pXRF analyser is used to provide preliminary quantitative measurement of mineralisation. A 3 beam, 35 second reading time was used with a single reading times, calibrations factors applied and their derivation, etc. • For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instruments make and model, reading times, calibrations factors applied and their derivation, etc. Olympus Vanta M Series pXRF analyser is used to provide preliminary quantitative measurement of mineralisation. A 3 beam, 35 second reading time was used with a single reading times, calibrations factors applied and their derivation, etc. • Nature of quality control procedures adopted (eg. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established. Calibration checks of the pXRF are undertaken daily, a silica blank and certified standard are routinely analysed to monitor pXRF performance. Laboratory Analysis Assay technique is Fire Assay which is a 'Total Technique' for Au and PGEs. Four acid digest is considered a 'near total technique for the 48 elements received under ME-MS61. • The verification of significant intersections by either and assaying • The verification of significant intersections by either independent or alternative company personnel. • The use of twinned holes. • Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. • Documentation of primary data,			
 Verification of sampling and assaying The verification of significant intersections by either and assaying The verification of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 			
standards, blanks, duplicates, external laboratory checks) Initiation pXRP performance. and whether acceptable levels of accuracy (i.e. lack of bias) Iaboratory Analysis and precision have been established. Assay technique is Fire Assay which is a 'Total Technique' for Au and PGEs. Four acid digest is considered a 'near total technique for the 48 elements received under ME-MS61. Standard laboratory QAQC is undertaken and monitored by the laboratory and by the company upon assay result receival. Verification of sampling and assaying The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. Discuss any adjustment to as		 technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. 	preliminary quantitative measurement of mineralisation. A 3- beam, 35 second reading time was used with a single reading on unprepared raw RC chip sample piles. High grade samples were repeated to confirm repeatability of grade. Calibration checks of the pXRF are undertaken daily, a silica blank and certified standard are routinely analysed to
and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established. Assay technique is Fire Assay which is a 'Total Technique' for Au and PGEs. Four acid digest is considered a 'near total technique for the 48 elements received under ME-MS61. Verification of sampling and assaying • The verification of significant intersections by either independent or alternative company personnel. • Standard laboratory QAQC is undertaken and monitored by the laboratory and by the company upon assay result receival. Verification of sampling and assaying • The verification of significant intersections by either independent or alternative company personnel. • Preliminary pXRF analysis • The use of twinned holes. • Analytical data was collected directly by the Olympus Vanta M Series pXRF analyser and downloaded by digital transfer to an excel spreadsheet with inbuilt QAQC. All data was checked by the responsible geologist and filed on the company server. • Discuss any adjustment to assay data. Logging and Sampling Logging and sampling were recorded directly into a digital logging system, verified and eventually stored in an offsite			
 Verification of sampling and assaying The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. For Au and PGEs. Four acid digest is considered a 'near total technique for the 48 elements received under ME-MS61. Standard laboratory QAQC is undertaken and monitored by the laboratory and by the company upon assay result receival. Preliminary pXRF analysis Analytical data was collected directly by the Olympus Vanta M Series pXRF analyser and downloaded by digital transfer to an excel spreadsheet with inbuilt QAQC. All data was checked by the responsible geologist and filed on the company server. Logging and Sampling Logging and sampling were recorded directly into a digital logging system, verified and eventually stored in an offsite 		and whether acceptable levels of accuracy (i.e. lack of bias)	
Verification of sampling and assaying • The verification of significant intersections by either independent or alternative company personnel. • Preliminary pXRF analysis • The use of twinned holes. • Analytical data was collected directly by the Olympus Vanta • Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. • Discuss any adjustment to assay data. • Discuss any adjustment to assay data. • Discuss any adjustment to assay data.		and precision have been established.	for Au and PGEs. Four acid digest is considered a 'near total'
 and assaying independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. Analytical data was collected directly by the Olympus Vanta M Series pXRF analyser and downloaded by digital transfer to an excel spreadsheet with inbuilt QAQC. All data was checked by the responsible geologist and filed on the company server. Logging and Sampling Logging and sampling were recorded directly into a digital logging system, verified and eventually stored in an offsite 			
 The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. Many data data was contected directly of the Orympus varial M Series pXRF analyser and downloaded by digital transfer to an excel spreadsheet with inbuilt QAQC. All data was checked by the responsible geologist and filed on the company server. Logging and Sampling Logging and sampling were recorded directly into a digital logging system, verified and eventually stored in an offsite 		· · · · · · · · · · · · · · · · · · ·	Preliminary pXRF analysis
Discuss any adjustment to assay data. Discuss any adjustment to assay data. Logging and Sampling Logging and sampling were recorded directly into a digital logging system, verified and eventually stored in an offsite	and assaying	 The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) 	to an excel spreadsheet with inbuilt QAQC. All data was checked by the responsible geologist and filed on the
Logging and sampling were recorded directly into a digital logging system, verified and eventually stored in an offsite			Logging and Sampling
			logging system, verified and eventually stored in an offsite
Significant intersections are inspected by senior company			



ABN 40 1 19 03 1 864

Criteria	JORC Code explanation	Commentary
		personnel.
		No twinned holes have been completed at this time.
		No adjustments to any assay data have been undertaken.
Location of data points	Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings	Collar position was recorded using a Emlid Reach RS2 RTK GPS system (+/- 0.2m x/y, +/-0.5m z).
	and other locations used in Mineral Resource estimation.	GDA94 Z50s is the grid format for all xyz data reported.
	 Specification of the grid system used. Quality and adequacy of topographic control. 	Azimuth and dip of the drill hole was recorded after the completion of the hole using a Reflex Sprint IQ Gyro. A reading was undertaken every 30 th metre with an accuracy of +/- 1° azimuth and +/-0.3° dip.
Data spacing and	Data spacing for reporting of Exploration Results.	See drill table for hole positions.
distribution	 Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	The drill spacing is not suitable for resource estimation.
Orientation of data in relation to geological	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this 	At this early stage of exploration, mineralisation thickness's, orientation and dips are not known.
structure	is known, considering the deposit type.If the relationship between the drilling orientation and the	Drilling was undertaken at a near perpendicular angle to the interpreted strike and dip of the modelled FLEM plates.
	orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.	No sample bias is known at this time.
Sample security	The measures taken to ensure sample security.	All geochemical samples were collected, bagged, and sealed by Dreadnought staff and delivered directly to ALS Laboratories Perth by Jarrahbar Contracting out of Carnarvon and Exmouth Haulage out of Exmouth.
Audits or reviews	• The results of any audits or reviews of sampling techniques and data.	The program is continuously reviewed by senior company personnel.

Section 2 Reporting of Exploration Results

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence 	The Mangaroon Project consists of 19 granted Exploration License (E08/3178, E08/3274, E08/3275, E08/3439, E09/2290, E09/2359, E09/2370, E09/2384, E09/2405, E09/2433, E09/2448, E09/2449, E09/2450, E09/2467, E09/2473, E09/2478, E09/2531, E09/2535, E09/2616) and 5 granted Mining Licenses (M09/91, M09/146, M09/147, M09/174, M09/175). All tenements are 100% owned by Dreadnought Resources.
	to operate in the area.	E08/3178, E08/3274, E09/2384, E09/2433, E09/2473 are subject to an option agreement with First Quantum Minerals over the base metal rights.
		E08/3178, E09/2370, E09/2384 and E09/2433 are subject to a 2% Gross Revenue Royalty held by Beau Resources.
		E08/3274, E08/3275, E09/2433, E09/2448, E09/2449, E09/2450 are subject to a 1% Gross Revenue Royalty held by Beau Resources.
		E09/2359 is subject to a 1% Gross Revenue Royalty held by Prager Pty Ltd.
		E09/2290, M09/146 and M09/147 are subject to a 1% Gross Revenue Royalty held by STEHN, Anthony Paterson and BROWN, Michael John Barry.
		M09/174 is subject to a 0.5% Gross Revenue Royalty held by STEHN, Anthony Paterson.
		M09/175 is subject to a 0.5% Gross Revenue Royalty held by STEHN, Anthony Paterson and BROWN, Michael John Barry.
		M09/91 is subject to a 1% Gross Royalty held by DOREY, Robert Lionel.



ABN 40 119 031 864

Criteria	JORC Code explanation	Commentary
		The Mangaroon Project covers 4 Native Title Determinations including the Budina (WADI31/2004), Thudgari (WAD6212/1998), Gnulli (WAD22/2019) and the Combined Thiin-Mah, Warriyangka, Tharrkari and Jiwarli (WAD464/2016).
		The Mangaroon Project is located over Lyndon, Mangaroon, Gifford Creek, Maroonah, Minnie Creek, Edmund, Williambury and Towera Stations.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	Historical exploration of a sufficiently high standard was carried out by a few parties which have been outlined and detailed in this ASX announcement including:
		Regional Resources 1986-1988s: WAMEX Reports A23715, 23713
		Peter Cullen 1986: WAMEX Report A36494
		Carpentaria Exploration Company 1980: WAMEX Report A9332
		Newmont 1991: WAMEX Report A32886
		Hallmark Gold 1996: WAMEX Report A49576
		Rodney Drage 2011: WAMEX Report A94155
		Sandfire Resources 2005-2012: WAMEX Report 94826
Geology	• Deposit type, geological setting and style of mineralisation.	The Mangaroon Project is located within Mangaroon Zone of the Gascoyne Province.
		The Mangaroon Project is prospective for orogenic gold, magmatic Ni-Cu-PGE mineralisation and carbonatite hosted REEs.
Drill hole information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	An overview of the drilling program is given within the text and tables within this document.
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	Assay Results are not being reported.
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known'). 	Drilling is undertaken close to perpendicular to the dip and strike of the modelled EM plates. At this early stage, the relation between mineralisation and drill intercepts is unknown.
Diagrams	• Appropriate maps and sections (with scales) and	Refer to figures within this report.
	tabulations of intercepts should be included for any	



ABN 40 119 031 864

Criteria	JORC Code explanation	Commentary
	significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	Refer to figures within this report.
Other substantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	Suitable commentary of the geology encountered is given within the text of this document.
Further work	 The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	Down hole EM Additional RC drilling