

ABN 35 091 542 451

8 Kearns Crescent, Ardross WA 6153 Telephone: 08 9364 3866 Facsimile: 08 9364 4892 Web: www.ausquest.com.au

11 January 2024

Market Announcements Office Australian Securities Exchange Level 40, Central Park 152-158 St Georges Terrace Perth WA 6000

Update: High Priority Targets defined by VTEM Survey at Ballodonia

Dear Sir / Madam

AusQuest Limited (ASX: AQD) advises that further to the ASX announcement "High Priority Targets defined by VTEM Survey at Ballodonia" this morning, a JORC table has been included in the attached announcement.

Yours faithfully

Henko Vos Company Secretary



ASX ANNOUNCEMENT

January 11th, 2024

MULTIPLE HIGH-PRIORITY TARGETS IDENTIFIED BY **VTEM SURVEY AT BALLADONIA, WA**

Extensive survey reveals both base metal and carbonatite targets

Further to its ASX release of December 5th, AusQuest Limited (ASX: AQD) is pleased to advise that the airborne VTEM survey successfully completed last month over the Balladonia Project in the Fraser Range region of WA has identified a number of high-priority EM targets.

The survey, comprising a total of 1,104km, was flown along east-west flight lines spaced 200m apart using the helicopter-mounted VTEM Max system and a base frequency of 25Hz.

Images of the vertical component of the electromagnetic (B) field and calculated time constants (a measure of conductivity) are presented in Figure 1.

Preliminary interpretation of the VTEM data has highlighted several strong EM responses indicative of potential massive sulphide mineralisation (anomalies A to E).

These conductors are generally discrete in nature, extending over 2-5 flight lines (300m to 1,000m in length) and are clearly evident in the late-time channels of the survey data (channel 48) and the 'Time Constant' image, which highlights the stronger conductive responses often associated with sulphide mineralisation.




Figure 1: Balladonia Project: VTEM images of Channel 48 (Vertical B field component) and the B field Time Constant, showing outlines of the interpreted EM targets.

ASX: AQD

WWW.AUSQUEST.COM.AU

JAUSQUEST_LTD in AUSQUEST_LIMITED



Large strike length anomalies such as anomaly F are considered more likely to reflect graphitic source rocks, with conductivity variations along the length of the conductors reflecting the possibility of increased thickness of graphite and/or the addition of sulphide mineralisation.

Moderate conductive responses (anomalies G to J) that coincide with distinct magnetic lows are considered potential carbonatite targets based on comparisons with geophysical responses over the Telegraph carbonatite that was drilled by the Company in 2020 (ASX Release – May 7th 2020).

These EM targets, which occur along a linear trend stretching over ~15km, are thought to represent a series of dyke-like intrusions associated with the NNW trending structures (*Figure 2*).




Figure 2: Balladonia Project: VTEM image of B field Time Constant and Reduced to Pole (RTP) magnetics showing outlines of the interpreted EM targets.

Targets K and L (*Figure 2*), which are localised areas of increased conductivity, are thought to reflect possible alteration associated with the Tea Tree stratigraphy – which is believed to contain prospective host rocks for Broken Hill Type (BHT) mineralisation.

Earlier reconnaissance drilling at Balladonia (as reported on 22nd September 2023) confirmed the presence of widespread prospective host rocks for BHT mineralisation, while also supporting the possibility of carbonatite-related mineralisation (including base metals and/or rare earth elements) within the project area.

Further exploration at Balladonia is currently the subject of discussions under the Strategic Alliance Agreement (SAA) with a wholly-owned subsidiary of South32 Limited.

AusQuest's Managing Director, Graeme Drew, said the VTEM survey had generated a series of compelling targets, further elevating the prospectivity of the Balladonia Project.

"This is an exciting new development for Balladonia and we are looking forward to following the targets generated by this extensive VTEM survey," he said.



"Exploration at Balladonia continues to provide us with encouragement that a new base metal and possibly rare earth element discovery could be made in this area. We are looking forward to continuing our efforts in this area and reporting results as and when they come to hand."

Graeme Drew

Managing Director

COMPETENT PERSON'S STATEMENT

The details contained in this report that pertain to exploration results are based upon information compiled by Mr Graeme Drew, a full-time employee of AusQuest Limited. Mr Drew is a Fellow of the Australasian Institute of Mining and Metallurgy (AUSIMM) and has sufficient experience in the activity which he is undertaking to qualify as a Competent Person as defined in the December 2012 edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves" (JORC Code). Mr Drew consents to the inclusion in the report of the matters based upon his information in the form and context in which it appears.

FORWARD LOOKING STATEMENT

This report contains forward looking statements concerning the projects owned by AusQuest Limited. Statements concerning mining reserves and resources may also be deemed to be forward looking statements in that they involve estimates based on specific assumptions. Forward-looking statements are not statements of historical fact and actual events and results may differ materially from those described in the forward looking statements as a result of a variety of risks, uncertainties and other factors. Forward looking statements are based on management's beliefs, opinions and estimates as of the dates the forward looking statements are made and no obligation is assumed to update forward looking statements if these beliefs, opinions and estimates should change or to reflect other future developments.

JORC Code, 2012 Edition – Table 1 report, Balladonia VTEM Survey Results

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	 A helicopter-borne Versatile Transient Electromagnetic survey (VTEM Max) using a base frequency of 25Hz was completed by UTS Geophysics along E-W flight lines spaced 200m apart with an EM sensor height of ~35m The VTEM Max system uses a transmitter loop diameter of 35m, a peak dipole moment of 700K NIA, a transmitter pulse width of 7ms and a three component receiver coils.
Drilling techniques	• Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	Not applicable
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	Not applicable
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	Not applicable
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation 	Not applicable

Criteria	JORC Code explanation	Commentary
	 Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	Not applicable
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	Not applicable
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 VTEM survey data were located using a Novatel GPS receiver which records the helicopter location in three dimensions to a resolution of 2 to 3 metres. All location data are recorded in GDA94 datum, UTM zone 51.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 Flight lines were flown east west at a nominal 200 metre spacing which was deemed appropriate for the targets being sought. Data points are acquired every 2 to 4 metres along the survey line.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	The VTEM survey lines were oriented approximately perpendicular to geological strike.
Sample security	The measures taken to ensure sample security.	 All data produced by the survey was transmitted electronically from the contractor to the Company's

Criteria	JORC Code explanation	Commentary
		consultant.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	Data quality was reviewed on an ongoing basis by the Company's consultant.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 The Balladonia Project is centered at 6411000N and 515500E (GDA94 Zone 51), approximately 135 km ESE of Norseman in Western Australia. Tenement holdings include six granted Exploration License's (E69/3246, 3825, 3671, 3558, 3932, 3559) and one Exploration License application (E69/3672). The Balladonia Prospect is subject to a Strategic Alliance Agreement whereby South32 have the right to earn a 70% interest by spending US\$4.5M. Aboriginal heritage surveys and fauna – Flora surveys are routinely completed ahead of ground disturbing activities.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	 Limited surface exploration has been completed by other parties. AusQuest is the first exploration company to complete drilling programs within the tenements. The tenements have been covered by regional government geophysical and geological surveys and partly by regional GSWA geochemical sampling.
Geology	Deposit type, geological setting and style of mineralisation.	• The exploration model for the Balladonia Project is based upon copper and nickel sulphides hosted in mafic rocks as is the case within the Fraser Range Belt, and base metal mineralisation in BHT and /or IOCG settings similar to the Eastern Succession in north-west Queensland and at Broken Hill in NSW. Potential for carbonatite related mineralization is also evident.

Criteria	JORC Code explanation	Commentary
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	Not applicable
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	Not applicable
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	Not applicable
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	• Relevant EM data are shown on appropriate plans and included in the ASX release.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	All significant results are reported.
Other substantive exploration data	• Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	The relationship between the EM results and previously reported exploration data is discussed in the report.

Criteria	JORC Code explanation	Commentary
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	Further exploration programs will depend on the full assessment and compilation of the VTEM and other results