



ASX ANNOUNCEMENT

26 June 2024

Stavely Copper-Gold Project – Exploration Update

Drilling Access Agreed for Key Junction Target

Access agreement secured to undertake air-core drilling to confirm the exact location and orientation of historic results from the Junction Prospect

- Access terms have been agreed with the landowner to undertake an air-core drilling program of ~20 drill holes to confirm the orientation of material historic drill intercepts in the eastern zone at the Junction prospect, including:
 - 35m at 3.44% Cu and 26g/t Ag from 24m drill depth to end of hole (EoH) in TGAC078
 - 11m at 1.72% Cu and 26g/t Ag from 33m in TGRC087
 - 10m at 1.09% Cu and 6g/t Ag from 26m in TGRC082
 - 6m at 2.15% Cu and 8g/t Ag from 2m and 6m at 3.90% Cu and 26g/t Ag from 28m to EoH in PENP004
- Diamond drilling at Junction has been postponed pending the completion of a more comprehensive air-core program to confirm the orientation and near-surface extent of the copper mineralisation defined by historic drilling.
- Following the completion of two initial diamond holes, Stavely Minerals has concerns about the locational accuracy of the previously reported historic drill holes in the western zone of the Junction Prospect, with clear evidence that the historic holes are actually located on the eastern side of Stavely Road, not the western side where recent drilling occurred.
- Air-core drilling provides a much cheaper method of confirming the drill targets while conserving the Company's budget for subsequent diamond drilling.
- An air-core rig has been booked to arrive in August, subject to weather and ground conditions.

Stavely Minerals Limited (ASX Code: **SVY** – “Stavely Minerals”) advises that it has reached agreement to gain access to the eastern zone for air-core drilling to verify the location of historic drill intercepts at the Junction Prospect, within the Company's 100%-owned Stavely Project (Figures 1 and 2).

The agreement will enable the Company to drill 20 air-core holes to better define targets for subsequent diamond drilling. This access provides a much improved and more cost-effective method to determine the orientation of the Junction Lode.

The Junction Prospect is defined by two zones of mineralisation – the eastern and western zones located on either side of Stavely Road. Historic drilling (TGAC- and TGRC- pre-fixed drill- holes, drilled in separate campaigns in December 2008 and January 2009) was designed to follow up on the earlier Pennzoil of Australia Ltd drill-hole PENP004 drilled in 1979, which intersected:

- 6m at 2.15% Cu and 8g/t Ag from 2m depth; and
- 6m at 3.90% Cu and 25g/t Ag from 28m depth to the end-of-hole.

Air-core (AC) and Reverse Circulation (RC) drilling completed by Beaconsfield Mining (BCD Resources) in December 2008 to follow-up the results in PENP004 in the eastern zone of the Junction Prospect returned significant intercepts:

- 35m at 3.44% Cu and 26g/t Ag from 24m drill depth to end-of-hole (EoH) in TGAC078;
- 11m at 1.72% Cu and 26g/t Ag from 33m in TGRC087; and
- 10m at 1.09% Cu and 6g/t Ag from 26m in TGRC082.

In January 2009, these initial BCD Resources results were followed-up with drill holes TGAC107 and TGRC108 to TGRC111, with significant results including:

- 6m at 1.65% Cu and 16g/t Ag from 37m in TGRC109
- 6m at 1.52% Cu and 19g/t Ag from 42m, 5m at 1.12% Cu and 10g/t Ag from 62m; and 6m at 1.77% Cu and 21g/t Ag from 72m to EoH in TGRC110




Figure 1. Stavely Project and prospect location map.




Figure 2. Junction prospect drill collar location map with drill traces. Note the revised location for drill holes TGRC109 and TGRC110 to the east of Stavelly Road.

However, TGRC109 and TGRC110 had collar location coordinates recorded as having been drilled on the western side of Stavelly Road with these new results defining the western zone of the Junction Prospect.

The inexplicable nature of this target location on the west side of Stavelly Road for TGRC109 and TGRC110 is that there was no prior copper anomalism in earlier drilling on the western side of Stavelly Road and these holes, drilled in late January 2009 were following-up on pre-Christmas 2008 significant intercepts in TGAC078, TGRC082 and TGRC087.

Stavelly has recently completed two initial diamond drill holes targeting the Junction Prospect (as outlined in recent ASX releases).

The first hole was collared to drill from the Stavelly Road verge to due south, between the eastern and western zones of previous drill intercepts at the Junction Prospect. This hole (SMD189) failed to confirm the east-west orientation of mineralisation linking those two zones – an interpretation based on the incorrect position of TGRC109 and TGRC110.

The diamond rig was subsequently oriented at ~225 degrees (south-west) to establish if the mineralisation hosted by drill holes TGRC109 and TGRC110 (incorrectly recorded as located on the west side of Stavelly Road) could be confirmed with a second diamond drill hole SMD190. Despite passing less than 10m below the recorded end-of-hole position of drill-hole TGRC110, that finished in **6m at 1.77% Cu and 21g/t Ag**, SMD190 did not intersect any material copper mineralisation.

The Company's interpretation is that drill holes TCRC109 and TCRC110, completed in January 2009 in the western zone of the Junction Prospect, have been mis-located and were in fact collared approximately 100m to the east of the recent drilling – a data entry error with the easting of TGRC110 entered as 642788mE rather than 642888mE, with the same 100m west transposition affecting TGRC109 (and for that matter, also TGRC111).

The Stavelly Minerals team has since confirmed this interpretation after reviewing archived historical records. Stavelly Minerals believes the incorrect location for drill holes TGRC109 and TGRC110 has been perpetuated for some 15 years in databases, reports and drill hole location plans, as a data entry error, ever since the drilling of those holes.

The net outcome is that these historic holes are in fact believed to be located on the eastern side of Stavelly Road, shifting by 100m by the historical transposition of one digit in the collar easting of both drill holes and that this location makes perfect sense in the context of following-up the significant copper assay results from pre-Christmas 2008 drill holes TGAC078, TGRC082 and TGRC087. This means that the Junction opportunity is still very much alive, and the recently agreed terms for access for 20 air-core drill holes in the paddock to the east of Stavelly Road will solve this locational issue prior to a resumption of definitive diamond drilling.

Stavelly Minerals Executive Chair and Managing Director, Mr Chris Cairns, said: *“While we are disappointed that the first two diamond holes failed to locate any mineralisation, we are relieved that we now understand the reason why the expected copper mineralisation was not there – because it never was. If anything, the transposition of drill holes TGRC109 and TGRC110 enhances the zone of high-grade copper mineralisation at Junction.*

“We are pleased that we have agreed to terms to secure air-core drill access with the owner of the property to the east of Stavelly Road. This will allow us to better define the known high-grade copper mineralisation with air-core drilling prior to a resumption of more expensive diamond drilling.

“The Junction Lode opportunity has not gone away and we ask shareholders to have patience while we do the work to sort out these locational issues. We are confident we have identified the historic locational issue, and can now move forward with greater certainty.”

When the air-core rig arrives on-site, drill holes TGRC109 and TGRC110 will first be twinned to definitively confirm whether they have been mis-located, then the air-core rig will proceed to better define the orientation of the shallow high-grade mineralisation in the eastern zone at the Junction Prospect where we have recently agreed to terms for drill access.

Yours sincerely,



Chris Cairns
Executive Chair and Managing Director

The information in this report that relates to Exploration Targets, Exploration Results, Mineral Resources or Ore Reserves is based on information compiled by Mr Chris Cairns, a Competent Person who is a Fellow of the Australian Institute of Geoscientists and a Fellow of the Australasian Institute of Mining and Metallurgy. Mr Cairns is a full-time employee of the Company. Mr Cairns is Executive Chair and Managing Director of Stavelly Minerals Limited and is a shareholder and option holder of the Company. Mr Cairns has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Cairns consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

Previously Reported Information: The information in this report that references previously reported exploration results is extracted from the Company's ASX market announcements released on the date noted in the body of the text where that reference appears. The previous market announcements are available to view on the Company's website or on the ASX website (www.asx.com.au). The Company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcements. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcements.

Authorised for lodgement by Chris Cairns, Executive Chair and Managing Director.

For Further Information, please contact:

Stavelly Minerals Limited

Phone: 08 9287 7630

Email: info@stavelly.com.au

Media Inquiries:

Nicholas Read – Read Corporate

Phone: 08 9388 1474

JORC Code, 2012 Edition – Table 1

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<i>Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i>	<p>The Junction Prospect has predominately been evaluated by shallow aircore and reverse circulation drilling to date.</p> <p>For diamond holes drilled by Stavelly Minerals, SMD075 and SMD077 and holes drilled along strike from the Junction Prospect, SMD002 and SMD005 the entire hole has been sampled. PQ quarter core and HQ half core is submitted for analysis. In general 1m samples were sent for analysis.</p> <p>For the historical diamond drill holes drilled by Penzoil, PEND2J and PEND3J samples were only selected where mineralisation was observed, it is unknown whether these were half or full core intervals. PEND4J and PEND5J were not sampled.</p> <p>For the North Limited aircore holes 3m composite samples were taken.</p> <p>For BCD reverse circulation holes TGRC082-88, TGRC108 – 111 and TGRC139-143, 1 or 2m composite samples were collected . 1m samples were collected from the bulk sample using a riffle splitter to collect a representative sample (of unknown proportion).</p> <p>For BCD aircore drilling, 2m composite samples were collected for holes TGAC074, TGAC075, TGAC077, TGAC078, TGAC079 and TGAC107. The sample collection method is unknown.</p> <p>BCD aircore holes TGAC076, TGAC080 and TGAC081 were not sampled.</p>
	<i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i>	For Stavelly drilling sample representivity was ensured by a combination of Company Procedures regarding quality control (QC) and quality assurance/ testing (QA). Certified standards and blanks were inserted into the assay batches.
	<i>Aspects of the determination of mineralisation that are Material to the Public Report - In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m</i>	<p>Diamond Drilling</p> <p>Stavelly Minerals drill sampling techniques are considered industry standard for the Stavelly work program.</p> <p>For Stavelly Minerals diamond, sonic and reverse circulation drill samples were crush to 70% < 2mm, riffle/rotary split off 1kg, pulverize to >85% passing 75 microns to produce a 30g charge for gold analysis and 0.25g charge for multi-element analysis.</p>

Criteria	JORC Code explanation	Commentary																										
	<p><i>samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information.</i></p>																											
<p>Drilling techniques</p>	<p><i>Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g. core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i></p>	<p>A summary of drilling at the Junction Prospect by Company is given below.</p> <table border="1"> <thead> <tr> <th>Company</th> <th>Drill hole type</th> <th>Number of holes</th> <th>Total metres</th> </tr> </thead> <tbody> <tr> <td>Stavelly Minerals</td> <td>DD</td> <td>4</td> <td>1876.5</td> </tr> <tr> <td rowspan="2">BCD</td> <td>RC</td> <td>20</td> <td>1068</td> </tr> <tr> <td>AC</td> <td>9</td> <td>299</td> </tr> <tr> <td>North Limited</td> <td>AC</td> <td>3</td> <td>99.5</td> </tr> <tr> <td rowspan="2">Pennzoil</td> <td>DD</td> <td>4</td> <td>207</td> </tr> <tr> <td>RC</td> <td>4</td> <td>131</td> </tr> </tbody> </table> <p>Diamond core drilled by Titeline Drilling Pty Ltd for Stavelly Minerals (SMD prefix holes) was drilled utilising standard wireline drilling mostly using PQ bits but also with some HQ drilling to produce oriented core. Triple tube core barrels were routinely used to maximise drill core recovery. Core diameter is mostly PQ (85mm) or HQ3 (63.5mm). For diamond tails to RC drilling, HQ diameter core is produced. SMD002 was orientated at -50° towards azimuth 239° to a depth of 530.9m. SMD005 was orientated at -50° towards azimuth 208° to a depth of 696.4m. SMD075 was orientated at -50° towards azimuth 60° to a depth of 244.4m. SMD077 was orientated at -50° towards azimuth 60° to a depth of 404.8m. Historic North Limited aircore drilling was conducted in 1993 by contractor Luhrs Holding using an "Edson 3000 Rig". Historical aircore holes with prefix TGAC were drilled by Beaconsfield Gold Mines Pty Ltd in 2008 and 2009 by Wallis Drilling. Historical reverse circulation holes with prefix TGRC were drilled by BCD in 2009. Drilling was conducted by Budd Exploration Drilling P/L using a Universal drill rig.</p>	Company	Drill hole type	Number of holes	Total metres	Stavelly Minerals	DD	4	1876.5	BCD	RC	20	1068	AC	9	299	North Limited	AC	3	99.5	Pennzoil	DD	4	207	RC	4	131
Company	Drill hole type	Number of holes	Total metres																									
Stavelly Minerals	DD	4	1876.5																									
BCD	RC	20	1068																									
	AC	9	299																									
North Limited	AC	3	99.5																									
Pennzoil	DD	4	207																									
	RC	4	131																									

Criteria	JORC Code explanation	Commentary
Drill sample recovery	<i>Method of recording and assessing core and chip sample recoveries and results assessed.</i>	<p>Diamond core recoveries for Stavely Minerals holes were logged and recorded in the database.</p> <p>Core recovery for SMD002 averaged 98%, SMD005 averaged 99%, SMD075 averaged 97% and SMD077 averaged 99%.</p> <p>Recoveries were not documented for Pennzoil or North Limited holes.</p> <p>For BCD percussion drilling, wet drilling and sampling conditions is often mentioned and is likely to have affected all drill holes. However, data and information is not available.</p>
	<i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i>	<p>Stavely Minerals diamond core is reconstructed into continuous runs on an angle iron cradle for orientation marking. Depths are checked against the depth given on the core blocks and rod counts are routinely carried out by the driller. Triple tube core barrels were routinely used to maximise drill core recovery.</p> <p>No details are available for the historical drill holes.</p>
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	<p>There are no issues with Stavely Minerals diamond core sample recovery at the Junction Prospect.</p> <p>For BCD drilling, wet drilling and sampling conditions is often mentioned and is likely to have affected all drill holes. However, data and information is not available for assessing the effect these conditions have on grade.</p> <p>No details are available for the other historical drill holes.</p>
Logging	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	<p>For Stavely Minerals drilling geological logging of samples followed Company and industry common practice. Qualitative logging of samples including, but not limited to, lithology, mineralogy, alteration, veining and weathering. Diamond core logging included additional fields such as structure and geotechnical parameters.</p> <p>Magnetic Susceptibility measurements were taken for each 1m diamond core interval.</p> <p>All historical drill holes were geologically logged.</p>
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i>	<p>For all diamond drilling by Stavely Minerals, logging is quantitative, based on visual field estimates. Systematic photography of the core in the wet and dry form was completed.</p> <p>For all historic drilling logging is quantitative, based on visual field estimates.</p>
	<i>The total length and percentage of the relevant intersections logged.</i>	<p>For Stavely Minerals diamond Drilling, detailed core logging, with digital capture, was conducted for 100% of the core by Stavely Minerals' on-site geologist at the Company's core shed near Glenthompson.</p> <p>Historical holes have been logged in their entirety.</p>
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	<p>For Stavely Minerals diamond drilling quarter core for the PQ diameter diamond core and half core for the HQ diameter core was sampled on site using a core saw.</p> <p>For historical holes, sub-sampling is not well documented. Holes drilled by BCD and North Limited the majority of the hole was sampled in 1-2m intervals. For Pennzoil diamond holes, samples were only selected where mineralisation was observed, it is unknown whether these were half or full</p>

Criteria	JORC Code explanation	Commentary
		core intervals. For Pennzoil reverse circulation holes 2m composite samples were collected.
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	For BCD holes reverse circulation drill holes, 1-2m composite samples were collected from the bulk sample using a riffle splitter to collect a representative sample (of unknown proportion).
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	For the Stavely Minerals drilling the Company procedures were followed to ensure sub-sampling adequacy and consistency. These included, but were not limited to, daily work place inspections of sampling equipment and practices. No details of sample preparation are given for the historical drilling.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	For diamond drilling by Stavely Minerals, blanks and certified reference materials are submitted with the samples to the laboratory as part of the quality control procedures. Blanks were inserted – 1 per 40 samples outside the strongly mineralised zone and 1 in 10 samples within the strongly mineralised zone. Standards were inserted – 1 per 20 samples outside the strongly mineralised zone and 1 in 10 samples within the strongly mineralised zone. For historical holes no QAQC procedures have been recorded.
	<i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i>	For diamond drilling by Stavely Minerals at the Junction Prospect no second – half core sampling was conducted.
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	For the Stavely Minerals drilling the sample sizes are considered to be appropriate to correctly represent the sought mineralisation.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i>	Stavely Minerals core samples were analysed by multielement ICPAES Analysis - Method ME-ICP61. A 0.25g sample is pre-digested for 10-15 minutes in a mixture of nitric and perchloric acids, then hydrofluoric acid is added and the mixture is evaporated to dense fumes of perchloric (incipient dryness). The residue is leached in a mixture of nitric and hydrochloric acids, the solution is then cooled and diluted to a final volume of 12.5mls. Elemental concentrations are measured simultaneously by ICP Atomic Emission Spectrometry. This technique approaches total dissolution of most minerals and is considered an appropriate assay method for porphyry copper-gold systems. This technique is a four- acid digest with ICP-AES or AAS finish. The drill core was also analysed for gold using Method Au-AA23. Up to a 30g sample is fused at approximately 1,100°C with alkaline fluxes including lead oxide. During the fusion process lead oxide is reduced to molten lead

Criteria	JORC Code explanation	Commentary
		<p>which acts as a collector for gold. When the fused mass is cooled the lead separates from the impurities (slag) and is placed in a cupel in a furnace at approximately 900°C. The lead oxidizes to lead oxide, being absorbed by the cupel, leaving a bead (prill) of gold, silver (which is added as a collector) and other precious metals. The prill is dissolved in aqua regia with a reduced final volume. Gold content is determined by flame AAS using matrix matched standards. For samples which are difficult to fuse a reduced charge may be used to yield full recovery of gold. This technique approaches total dissolution of most minerals and is considered an appropriate assay method for detecting gold mineralisation.</p> <p>Information on assaying details for historic holes are not well documented, the following information was gathered from previous annual technical reports:</p> <ul style="list-style-type: none"> • Pennzoil: A base metal suite was assayed via AAS (digestion not specified) including Ag, Cu, Pb and Zn. Au was assayed via fire assay. • North Limited: A base metal suite (Cu, Ni, Pb & Zn) was assayed via Mixed Acid digest, AAS detection (ICP-OES for CRAE) and Au was assayed via fire assay. • BCD: A base metal suite (Ag, As, Co, Cu, Cr, Fe, Mn, Ni, Pb, S & Zn) by aqua regia digest ICP-OES methods and repeated assays for samples returning greater than 5000ppm Cu by Mixed Acid Digest ICP-OES detection. Au was assayed via fire assay.
	<i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i>	Not applicable to this report.
	<i>Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</i>	<p>Laboratory QAQC for Stavelly Minerals drilling involved insertion of CRM (Certified Reference Materials), duplicates and blanks.</p> <p>The analytical laboratory provides their own routine quality controls within their own practices. The results from their own validations were provided to Stavelly Minerals.</p> <p>Results from the CRM standards and the blanks gives confidence in the accuracy and precision of the assay data returned from ALS.</p> <p>For historical holes no QAQC procedures have been recorded.</p>
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Stavelly Minerals Managing Director, the Technical Director or the Geology Manager – Victoria have visually verified significant intersections in the diamond core for holes drilled by Stavelly Minerals.

Criteria	JORC Code explanation	Commentary
		The chip trays with samples from the BCD AC and RC drilling have also been inspected and the mineralised intervals verified.
	<i>The use of twinned holes.</i>	No twinned holes have been drilled.
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	For Stavely Minerals drilling primary data was collected for drill holes using the OCRIS logging template on Panasonic Toughbook laptop computers using lookup codes. The information was sent to a database consultant for validation and compilation into a SQL database. All primary assay data is received from the laboratory as electronic data files that are imported into the sampling database with verification procedures in place. Digital copies of Certificates of Analysis are stored on the server which is backed up daily. Data is also verified on import into mining related software. No details are available for historical drilling.
	<i>Discuss any adjustment to assay data.</i>	No adjustments or calibrations were made to any assay data used in this report.
Location of data points	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	For the Stavely Minerals diamond drilling, the drill collar location was pegged before drilling and surveyed using Garmin handheld GPS to accuracy of +/- 3m. Collar surveying was performed by Stavely Minerals' personnel. There is no location metadata for historic Pennzoil, North Limited or BCD holes.
	<i>Specification of the grid system used.</i>	The grid system used is GDA94, zone 54.
	<i>Quality and adequacy of topographic control.</i>	For Stavely Minerals exploration, the RL was recorded for each drill hole location from the DGPS. Accuracy of the DGPS is considered to be within 1m.
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	The drill holes are variably spaced. A collar plan with the drill hole locations is presented in the body of the report.
	<i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	The Junction Prospect has not been sufficiently drilled to produce a Mineral Resource.
	<i>Whether sample compositing has been applied.</i>	For Stavely Minerals diamond core for the entire hole is sampled. For diamond core PQ quarter core and HQ half core was submitted for analysis. Sample intervals were in general 1m. Historical Pennzoil diamond holes were selectively sampled with composite samples varying from 1 to 16m. Historical RC drill holes with the prefix PENP were drilled by Pennzoil of Australia and two metre composite samples were assayed for Au, Ag, Cu, Pb and Zn.

Criteria	JORC Code explanation	Commentary
		<p>Historical aircore drill holes with the prefix STAVRA were drilled by North Limited and three metre composite samples were assayed for Au, Cu, Pb and Zn.</p> <p>For historical aircore holes TGAC002 to TGAC125 approximately the top 15 to 16 metres was not sampled, after that one metre intervals samples were taken for the remainder of the holes.</p> <p>For BCD aircore holes two metre composite samples were collected and for the RC holes one meter samples were collected. The aircore and RC was assayed for Au, Ag, As, Co, Cu, Fe, Ni, Pb, S and Zn.</p>
Orientation of data in relation to geological structure	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	The Junction Prospect is still at a reconnaissance drilling stage.
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	There is insufficient drilling data to date at the Junction Prospect to demonstrate continuity of mineralised domains and determine if any orientation sampling bias can be identified in the data.
Sample security	<i>The measures taken to ensure sample security.</i>	For Stavely Minerals drill samples in closed poly-weave bags are delivered by Stavely personnel to Ararat or Ballarat from where the samples were couriered by a reputable transport company to ALS Laboratory in either Orange, NSW or Adelaide, SA. At the laboratory, samples are stored in a locked yard before being processed and tracked through sample preparation and analysis.
Audits or reviews	<i>The results of any audits or reviews of sampling techniques and data.</i>	No review of the sampling technique or data has been conducted for drilling at the Junction Prospect.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i>	<p>Stavely Project</p> <p>The Stavely Project comprises RL2017, EL6870, EL7347, EL7921, EL7922, EL7923 and EL7924. Stavely Minerals hold 100% ownership of the Stavely Project tenements.</p> <p>The mineralisation at Thursday's Gossan is situated within retention licence RL2017.</p> <p>EL4556, which was largely replaced by RL2017 was purchased by Stavely Minerals (formerly Northern Platinum) from BCD Resources Limited in May 2013. RL2017 was granted on the 8th May 2020 and expires on the 7th May 2030. A Section 31 Deed and a Project Consent Deed has been signed between Stavely Minerals Limited and the Eastern Maar Native Title Claim Group for RL2017.</p> <p>EL6870 was granted on the 30 August 2021 and expires on the 29 August 2026. A Section 31 Deed and a Project Consent Deed has been signed between Stavely Minerals Limited and the Eastern Maar Native Title Claim Group for EL6870.</p> <p>EL7347 was granted on the 17th June 2022 for a period of 5 years. EL7921 was granted on the 15th September 2022 for a period of 5 years. EL7922, EL7923 and EL7924 were granted on the 29th September 2022 for a period of 5 years. These 5 tenements do not cover crown land and are not subject to Native Title.</p> <p>Black Range Joint Venture</p> <p>The Black Range Joint Venture comprises exploration licence 5425 and is an earn-in and joint venture agreement with Navarre Minerals Limited. Stavely Minerals earned 83% equity in EL5425 in December 2022. EL5425 was granted on 18 December 2021 and expires on the 17 December 2027.</p>
	<i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i>	All the exploration licences and the retention licence are in good standing and no known impediments exist.
Exploration done by other parties	<i>Acknowledgment and appraisal of exploration by other parties.</i>	<p>Stavely Project & Black Range Joint Venture</p> <p>The Mt Stavely belt has been explored since the late 1960's, including programmes undertaken by mineral exploration companies including WMC, Duval, CRA Exploration, BHP, and North Limited.</p> <p>Exploration activity became focused on Thursday's Gossan and the Junction prospects following their discovery by Pennzoil of Australia Ltd in the late 1970s. North Limited continued to focus on Thursday's Gossan in the 1990s. North's best drill result at Thursday's Gossan came from VICT1D1 which gave 161m of 0.26% Cu from 43m,</p>

Criteria	JORC Code explanation	Commentary
		<p>including 10m of 0.74% Cu from 43m from a supergene-enriched zone containing chalcocite.</p> <p>The tenement was optioned to CRA Exploration between 1995 and 1997. CRAE drilled several deep diamond drill holes into Thursday's Gossan, including DD96WL10, which intersected 186m from 41m of 0.15% Cu and DD96WL11, which intersected 261.7m from 38.3m of 0.13% Cu.</p> <p>EL4556 was further explored by Newcrest Operations Limited under option from New Challenge Resources Ltd between 2002 and 2004. Their main focus was Thursday's Gossan in order to assess its potential as a porphyry copper deposit. One of their better intersections came from drill hole VSTD01 on the northern edge of the deposit which gave 32m at 0.41 g/t Au and 0.73% Cu from 22m in supergene-enriched material.</p> <p>The Stavely Project was optioned to Beaconsfield Gold Mines Pty Ltd in 2006 who flew an airborne survey and undertook an extensive drilling programme focused on several prospects including Thursday's Gossan. One of their diamond drill holes at Thursday's Gossan, SNDD001, encountered zones with quartz-sulphide veins assaying 7.7m at 1.08 g/t Au and 4.14% Cu from 95.3m and 9.5m at 0.44 g/t Au and 2.93% Cu from 154.6m along silicified and sheared contacts between serpentinite and porphyritic intrusive rocks.</p> <p>Once Beaconsfield Gold Mines Pty Ltd had fulfilled their option requirements, title of EL4556 passed to their subsidiary company, BCD Metals Pty Ltd, who undertook a gravity survey and extensive drilling at prospects including Thursday's Gossan. They also commissioned a maiden Mineral Resource estimate for Thursday's Gossan.</p> <p>All work conducted by previous operators at Thursday's Gossan is considered to be of a reasonably high quality.</p> <p>The Junction Prospect forms the largest (1,200m x 500m) and highest tenor soil auger copper anomaly identified in the Stavely Project area. The anomaly is located 3.5km SSE of the Cayley Lode along a sub-cropping portion of the Stavely Volcanic Belt. Pennzoil drilled 5 diamond holes and 4 RC holes in the late 1970's and early 1980's. PENP004 returned 2m @ 5.10% Cu & 6g/t Ag from 2m and 6m @3.90% Cu & 25g/t Ag from 28m to EoH. In 1993 North Limited drilled 3 aircore holes at the vicinity of the Junction Prospect. These holes did not return any anomalous intercepts.</p> <p>In 2008 and 2009 BCD drilled 9 AC holes and 16 RC holes At the Junction Prospect. RC drilling methods were required where the ground conditions were too hard for AC methods. Drilling targeted a sub-circular copper soil anomaly and the previously drilled intersection in PENP004. Drill spacing was on a nominal spacing of 30x60m. Best results include 35m @ 3.69% Cu (TGAC078) and 12m @ 1.61% Cu (TGRC087). Peak results are listed</p>

Criteria	JORC Code explanation	Commentary																																																					
		<p>in the table below. Mineralisation was predominantly observed in the oxide zone as chalcocite & covellite sulphides with minor malachite. Limited drilling in the fresh zone remained a drill target. Drilling by BCD at the Junction Prospect was terminated early due to landholder access issues.</p> <table border="1" data-bbox="743 490 1434 1117"> <thead> <tr> <th>Hole ID</th> <th>MGA East (m)</th> <th>MGA N (m)</th> <th>Depth From (m)</th> <th>Significant Intersections</th> <th>Total Depth (m)</th> </tr> </thead> <tbody> <tr> <td rowspan="2">TGAC078</td> <td rowspan="2">642927</td> <td rowspan="2">5833571</td> <td>2</td> <td>10m @ 2.18% Cu</td> <td rowspan="2">59</td> </tr> <tr> <td>24</td> <td>35m @ 3.69% Cu</td> </tr> <tr> <td>TGRC082</td> <td>642905</td> <td>5833552</td> <td>26</td> <td>13m @ 1.07% Cu</td> <td>61</td> </tr> <tr> <td>TGRC087</td> <td>642882</td> <td>5833535</td> <td>33</td> <td>12m @ 1.61% Cu</td> <td rowspan="2">76</td> </tr> <tr> <td></td> <td></td> <td></td> <td>73</td> <td>1m @ 1.13% Cu</td> </tr> <tr> <td>TGRC109</td> <td>642784</td> <td>5833563</td> <td>37</td> <td>6m @ 1.65% Cu</td> <td>65</td> </tr> <tr> <td rowspan="3">TGRC110</td> <td rowspan="3">642788</td> <td rowspan="3">5833533</td> <td>42</td> <td>6m @ 1.52% Cu</td> <td rowspan="3">78</td> </tr> <tr> <td>60</td> <td>7m @ 0.93% Cu</td> </tr> <tr> <td>71</td> <td>7m @ 1.59% Cu</td> </tr> <tr> <td>TGRC139</td> <td>642750</td> <td>5833600</td> <td>3</td> <td>1m @ 1.26% Cu</td> <td>49</td> </tr> </tbody> </table> <p>In 2014 Stavelly Minerals drilled diamond holes SMD002 and SMD005 approximately 500m along strike from the Junction Prospect. SMD002 was designed to test the northern end of the magnetic high surrounded by a magnetic low annulus and a copper soil/auger geochemical anomaly coincident with the magnetic high. SMD002 intercepted a high-grade zone of 5m @ 1.38% Cu & 0.25 g/t Au from 332m. SMD005 was designed to target the core of the magnetic high which is coincident with the peak/ auger geochemical anomaly. SMD005 intercepted 3m @ 0.21% Cu from 161m.</p> <p>In 2020 Stavelly Minerals drilled diamond holes SMD075 and SMD077 at the Junction Prospect. These holes were drilled at an orientation of 060 degrees and did not explain the presence of the high-grade copper in historical aircore holes. SMD077 intersected 3m @ 0.58% Pb from 275m. From a more recent interpretation it would appear that the holes drilled over and under the mineralised structure.</p>	Hole ID	MGA East (m)	MGA N (m)	Depth From (m)	Significant Intersections	Total Depth (m)	TGAC078	642927	5833571	2	10m @ 2.18% Cu	59	24	35m @ 3.69% Cu	TGRC082	642905	5833552	26	13m @ 1.07% Cu	61	TGRC087	642882	5833535	33	12m @ 1.61% Cu	76				73	1m @ 1.13% Cu	TGRC109	642784	5833563	37	6m @ 1.65% Cu	65	TGRC110	642788	5833533	42	6m @ 1.52% Cu	78	60	7m @ 0.93% Cu	71	7m @ 1.59% Cu	TGRC139	642750	5833600	3	1m @ 1.26% Cu	49
Hole ID	MGA East (m)	MGA N (m)	Depth From (m)	Significant Intersections	Total Depth (m)																																																		
TGAC078	642927	5833571	2	10m @ 2.18% Cu	59																																																		
			24	35m @ 3.69% Cu																																																			
TGRC082	642905	5833552	26	13m @ 1.07% Cu	61																																																		
TGRC087	642882	5833535	33	12m @ 1.61% Cu	76																																																		
			73	1m @ 1.13% Cu																																																			
TGRC109	642784	5833563	37	6m @ 1.65% Cu	65																																																		
TGRC110	642788	5833533	42	6m @ 1.52% Cu	78																																																		
			60	7m @ 0.93% Cu																																																			
			71	7m @ 1.59% Cu																																																			
TGRC139	642750	5833600	3	1m @ 1.26% Cu	49																																																		
Geology	<i>Deposit type, geological setting and style of mineralisation.</i>	<p>Stavelly Project & Black Range Joint Venture</p> <p>The Stavelly Project and Black Range JV are located in the Mount Stavelly Volcanic Complex (MSVC). Intrusion of volcanic arc rocks, such as the Mount Stavelly Volcanic Complex, by shallow level porphyries can lead to the formation of porphyry copper ± gold ± molybdenum deposits.</p>																																																					

Criteria	JORC Code explanation	Commentary																																																								
		<p>EL6870 is interpreted by Cayley et al. (2017) to host structurally dislocated and rotated segments of both the Stavely Belt and the Bunnugal Belt.</p> <p>Stavely Project</p> <p>Thursday's Gossan Prospect</p> <p>The Thursday's Gossan prospect is located in the Mount Stavely Volcanic Complex (MSVC). Intrusion of volcanic arc rocks, such as the Mount Stavely Volcanic Complex, by shallow level porphyries can lead to the formation of porphyry copper ± gold ± molybdenum deposits.</p> <p>The Thursday's Gossan Chalcocite deposit (TGC) is considered to be a supergene enrichment of primary porphyry-style copper mineralisation. Mineralisation is characterised by chalcopyrite, covellite and chalcocite copper sulphide mineralisation within a sericite, illite and kaolin clay alteration assemblage. Copper mineralisation is within a flat lying enriched 'blanket' of overall dimensions of 4 kilometres north-south by up to 1.5 kilometres east-west by up to 60 metres thick with an average thickness of approximately 20 metres commencing at an average depth below surface of approximately 30 metres. The majority (circa 60%) of the Mineral Resources reside within a higher-grade zone of approximate dimensions of 1 kilometre x 300 metres by 35 metres thick.</p> <p>The mineralisation at the Cayley Lode at the Thursday's Gossan prospect is associated with high-grade, structurally controlled copper-gold-silver mineralisation along the ultramafic contact fault.</p> <p>The Thursday's Gossan area hosts a major hydrothermal alteration system with copper-gold mineralisation over a 10 kilometre long corridor.</p> <p>Junction Prospect</p> <p>The Junction Prospect is predominately underlain by a package of sandstone and siltstone with some dacite porphyry. Trace to locally weak quartz+carbonate+sulphide+base metal veining was intersected in SMD077. In the aircore drilling mineralisation was predominantly observed in the oxide zone as chalcocite-covellite sulphides with minor malachite.</p>																																																								
<p>Drill hole Information</p>	<p><i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i></p> <p><i>easting and northing of the drill hole collar</i></p> <p><i>elevation or RL (Reduced Level – elevation above sea</i></p>	<table border="1"> <thead> <tr> <th>Hole ID</th> <th>Hole Type</th> <th>Max Depth</th> <th>Grid</th> <th>East</th> <th>North</th> <th>_RL</th> </tr> </thead> <tbody> <tr> <td>PEND2J</td> <td>DD</td> <td>26</td> <td>MGA94_54</td> <td>642861.1</td> <td>5833657</td> <td>289.21</td> </tr> <tr> <td>PEND3J</td> <td>DD</td> <td>72</td> <td>MGA94_54</td> <td>642885.1</td> <td>5833618</td> <td>290.48</td> </tr> <tr> <td>PEND4J</td> <td>DD</td> <td>60.1</td> <td>MGA94_54</td> <td>642924.1</td> <td>5833658</td> <td>289.94</td> </tr> <tr> <td>PEND5J</td> <td>DD</td> <td>42.6</td> <td>MGA94_54</td> <td>642841.1</td> <td>5833624</td> <td>287.88</td> </tr> <tr> <td>PENP001</td> <td>RC</td> <td>31</td> <td>MGA94_54</td> <td>643088.1</td> <td>5833536</td> <td>286</td> </tr> <tr> <td>PENP002</td> <td>RC</td> <td>28</td> <td>MGA94_54</td> <td>642890.1</td> <td>5833617</td> <td>289.92</td> </tr> <tr> <td>PENP003</td> <td>RC</td> <td>38</td> <td>MGA94_54</td> <td>642850.1</td> <td>5833581</td> <td>288.79</td> </tr> </tbody> </table>	Hole ID	Hole Type	Max Depth	Grid	East	North	_RL	PEND2J	DD	26	MGA94_54	642861.1	5833657	289.21	PEND3J	DD	72	MGA94_54	642885.1	5833618	290.48	PEND4J	DD	60.1	MGA94_54	642924.1	5833658	289.94	PEND5J	DD	42.6	MGA94_54	642841.1	5833624	287.88	PENP001	RC	31	MGA94_54	643088.1	5833536	286	PENP002	RC	28	MGA94_54	642890.1	5833617	289.92	PENP003	RC	38	MGA94_54	642850.1	5833581	288.79
Hole ID	Hole Type	Max Depth	Grid	East	North	_RL																																																				
PEND2J	DD	26	MGA94_54	642861.1	5833657	289.21																																																				
PEND3J	DD	72	MGA94_54	642885.1	5833618	290.48																																																				
PEND4J	DD	60.1	MGA94_54	642924.1	5833658	289.94																																																				
PEND5J	DD	42.6	MGA94_54	642841.1	5833624	287.88																																																				
PENP001	RC	31	MGA94_54	643088.1	5833536	286																																																				
PENP002	RC	28	MGA94_54	642890.1	5833617	289.92																																																				
PENP003	RC	38	MGA94_54	642850.1	5833581	288.79																																																				

Criteria	JORC Code explanation	Commentary						
<p><i>level in metres) of the drill hole collar</i></p> <p><i>dip and azimuth of the hole down hole length and interception depth</i></p> <p><i>hole length.</i></p>		PENP004	RC	34	MGA94_54	642897.1	5833597	288.41
		SMD075	DD	244.4	MGA94_54	642780	5833522	291
		SMD077	DD	404.8	MGA94_54	642762	5833595	288
		STAVRA119	AC	39	MGA94_54	642812.1	5833688	285.8
		STAVRA120	AC	33.5	MGA94_54	642822.1	5833478	288.89
		STAVRA266	AC	27	MGA94_54	642722.1	5833578	284.61
		TGAC074	AC	38	MGA94_54	642878	5833583	288.67
		TGAC075	AC	51	MGA94_54	642912	5833604	288.47
		TGAC076	AC	17	MGA94_54	642944	5833622	288.46
		TGAC077	AC	21	MGA94_54	642986	5833653	285.67
		TGAC078	AC	59	MGA94_54	642927	5833571	289.67
		TGAC079	AC	35	MGA94_54	642890	5833638	290.27
		TGAC080	AC	8	MGA94_54	642996	5833540	287.76
		TGAC081	AC	12	MGA94_54	642893	5833543	288.88
		TGAC107	AC	58	MGA94_54	642790	5833490	288.41
		TGRC082	RC	61	MGA94_54	642905	5833552	289.09
		TGRC083	RC	37	MGA94_54	642965	5833520	288.69
		TGRC084	RC	43	MGA94_54	642932	5833498	288.95
		TGRC085	RC	49	MGA94_54	642894	5833708	288.42
		TGRC086	RC	67	MGA94_54	642849	5833682	288.75
		TGRC087	RC	76	MGA94_54	642882	5833535	289.02
		TGRC088	RC	91	MGA94_54	642914	5833491	288.84
		TGRC108	RC	60	MGA94_54	642789	5833525	287.45
		TGRC109	RC	65	MGA94_54	642784	5833563	285.34
		TGRC110	RC	78	MGA94_54	642788	5833533	287.06
		TGRC111	RC	72	MGA94_54	642749	5833552	285.4
		TGRC139	RC	49	MGA94_54	642750	5833600	283.85
		TGRC140	RC	55	MGA94_54	642790	5833600	284.37
		TGRC141	RC	79	MGA94_54	642750	5833520	287.3
		TGRC142	RC	49	MGA94_54	642960	5833540	289.57
		TGRC143	RC	6	MGA94_54	642870	5833525	288.56
	SMD005	DD	696.4	MGA94_54	643681	5833768	292	
	SMD002	DD	530.9	MGA94_54	643549	5833804	270	
	<p><i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i></p>	<p>No material drill hole information has been excluded.</p>						

Criteria	JORC Code explanation	Commentary
Data aggregation methods	<i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</i>	High-grade mineralisation exploration all copper/ and or gold intervals considered to be significant have been reported with subjective discretion. No top-cutting of high-grade assay results have been applied, nor was it deemed necessary for the reporting of significant intersections.
	<i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i>	In reporting exploration results, length weighted averages are used for any non-uniform intersection sample lengths. Length weighted average is (sum product of interval x corresponding interval grade %) divided by sum of interval length.
	<i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i>	Assumptions used for reporting of metal equivalent values are clearly stated.
Relationship between mineralisation widths and intercept lengths	<i>These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i>	There is insufficient drilling data to date to demonstrate continuity of mineralised domains and determine the relationship between mineralisation widths and intercept lengths.
	<i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known').</i>	Refer to the Tables and Figures in the text.
Diagrams	<i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i>	Refer to Figures in the text. A plan view of the drill hole collar locations is included.

Criteria	JORC Code explanation	Commentary
Balanced reporting	<i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i>	All copper and gold values considered to be significant have been reported. Some subjective judgement has been used.
Other substantive exploration data	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i>	All relevant exploration data is shown on figures and discussed in the text.
Further work	<i>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i>	Diamond drilling has been planned to test the new interpretation of the copper mineralised structure at the Junction Prospect.