

## FURTHER HIGH-GRADE NICKEL-COPPER-COBALT SULPHIDES INTERSECTED AT FRASER LAKE COMPLEX

- **Latest drill hole intersects multiple narrow zones of massive to semi massive nickel-copper bearing sulphide mineralisation**
  - Fourth hole drilled into a large geophysical anomaly - similar strong Ni-Cu-Co sulphide mineralisation as in previous holes
  - Continues to substantiate high grade tenor of FLC nickel mineralisation
  - Indicates long-lived Ni-Cu-Co sulphide rich magmatic plumbing system
- **Downhole electromagnetic geophysics identifies several conductors for follow-up**
- **Drilling on-going**

Corazon Mining Limited (ASX: CZN) ("Corazon" or "the Company") is pleased to provide an update of exploration activities at the Fraser Lake Complex ("FLC"), located just five kilometers south of its 100% owned Lynn Lake Nickel-Copper-Cobalt Mining Centre in Canada.


The Company recently commenced its second phase of drilling at the FLC and reports initial results from the latest completed hole, FLC-2017-010. This hole has intersected multiple zones of magmatic massive sulphide within a gabbro host with strong pervasive levels of sulphide mineralisation. Field-analysis using a hand-held XRF of two fine-grained massive sulphide zones returned results of **5.0% to 12.0%** nickel (at approximately 145m downhole) and **2.0% to 2.5%** nickel (at approximately 82m downhole), substantiating the high nickel tenor of the FLC mineralisation (Figure 1).

Corazon commenced targeted exploration drilling and ground geophysics at the FLC in January, testing what the Company believes is a significant greenfields nickel-copper-cobalt (Ni-Cu-Co) sulphide discovery. Exploration is focused on a high-chargeability Induced Polarisation (IP) geophysical anomaly (the Matrix Trend) coincident with the interpreted extensions of the feeder zone for the FLC. There appears little doubt that this IP anomaly is a result of multiple magmatic Ni-Cu-Co sulphide events.

Corazon Managing Director Brett Smith stated; *"The FLC is an exceptional exploration target. These rocks are exactly what we would expect to see in a long-lived fertile magmatic sulphide system. The sheer volume of sulphide-rich gabbro, along with the high-grade sulphide zones, continues to support and add weight to our belief that this area may host a significant new nickel-copper-cobalt sulphide deposit."*

### Drilling

FLC-2017-010 is the fourth hole drilled into the Matrix trend and exhibits similar strong nickel-copper-cobalt sulphide mineralisation to holes FLC-2017-002, -003 and -008 (Figure 2). This hole is situated 80 metres from hole FLC-2017-003, which hosts massive sulphide mineralisation, as previously announced (ASX announcement 15<sup>th</sup> March, 2017). FLC-2017-010 has been drilled to 475m depth and has intersected significantly more zones of magmatic massive sulphide mineralisation than in the previous drilling. These zones are thin, typically less than 0.5 metres and suggest the injection of multiple pulses of sulphide rich magmatic melt.



**Figure 1 – Fraser Lake Complex Hole FLC-2017-010 - Photos of variable mineralisation styles**

- A. Settling globules of magmatic Ni-Cu-Co sulphides – approximately 68m downhole
- B. Massive sulphide – **2.0% to 2.5% Ni** over 0.5m – approximately 82m downhole
- C. Thin bands of semi-massive to massive magmatic sulphides – approximately 128.6m downhole
- D. Massive sulphide – **5.0% to 12.0% Ni** over 0.3m – approximately 145m downhole

Analysis was completed using a hand-held XRF (Niton) on dry core samples. Such methods provide an indication of the tenor of mineralisation only. They are not considered accurate and cannot be used for the purposes of resource calculations. Assay values were quoted only for the fine-grained matrix material of massive sulphide mineralisation. Results for mineralisation exhibiting coarser sulphides are typically variable and have not been published. Photo Scale = Core Diameter 47.6mm.

Hand-held Niton XRF analysis of the sulphide zones within the core samples substantiates the potential high-grade nature of the FLC mineralisation. While this method of testing can deliver high variability, the analysis of two narrow fine-grained massive sulphide zones at approximately 82m and 145m downhole returned reproducible results of **2.0% to 2.5%** and **5.0% to 12.0%** nickel respectively (Figure 1). The nickel/copper ratio of these zones were in line with the 2.0-2.7/1.0 ratio of the Lynn Lake Mining Centre.

Four holes have provided an initial test of the large Matrix Trend over approximately 400m in strike, at what is interpreted to be the far northeastern extents of a feeder zone of more than 1.5km in length. All holes have reported significant sulphide mineralisation, in what the Company believes is peripheral to the main target, a large sulphide deposit within the feeder zone of a fertile gabbroic complex.

Drilling of hole FLC-2017-012 has commenced. The hole is located north of holes FLC-2017-003 and -010 and will be the first test of the northern margin of the Matrix Trend at a coincident geophysical and geochemical (nickel) anomaly.

### **DHEM Survey**

Downhole electromagnetic (DHEM) geophysical surveys of holes FLC-2017-008 and -010 identified several conductors worthy of follow-up exploration. Some of these anomalies are coincident with strong sulphide mineralisation intersected within the drilling, some pertain to off-hole features.


The Ni-Cu-Co sulphide mineralisation does not display a DHEM conductor as strong as the barren sulphidic sediments that also exist within the FLC, however, the Company believes it is now able to geophysically distinguish between these sulphide deposit types.

Work determining the size and target priority ranking of these anomalies is ongoing.


### **On-going Exploration**

The current phase of drilling is expected to continue into April 2017.

Ground geophysics including IP and magnetics is being completed over the interpreted FLC feeder zone, southwest of the currently identified Matrix Trend (Figure 2). This work will be used to define additional drilling targets. Such drilling would be undertaken in a new area not covered by the existing Work Permits; as such, additional Work Permits will be applied for. It is expected additional permitting will be completed in early April.



**Figure 2 – Geophysical Features and Targets.** Aeromagnetic Total Field image overlain by Gradient Array IP Chargeability image, with the main IP anomaly (Matrix HC IP), IP Survey outline, historical drill hole and current drill hole locations (FLC-2017-\*). A gravity high anomaly to the south of the FLC intrusion is believed to be the source of mantle material that feed the intrusion. The main IP anomaly trends off the IP surveyed area and is in alignment with the interpreted neck/feeder zone of the intrusion.



**Figure 3 – Project Location and Geology.** *Interpreted Geology – Emslie, R.R. and Moore, J.M. 1961. Manitoba Mines Branch, Publication 57-4. Datum UTM Zone 14 (NAD83). Lynn Lake is considered a historically significant nickel mine and remains the fourth largest nickel producing districts in Canada, despite the mine closing in 1976. The Fraser Lake Complex is twice as large as Lynn Lake and in many facets is geologically identical to Lynn Lake.*

END.

For further information visit [www.corazon.com.au](http://www.corazon.com.au) or contact:

**Brett Smith**

Managing Director  
Corazon Mining Limited  
P: +61 (8) 6142 6366  
E: [info@corazonmining.com.au](mailto:info@corazonmining.com.au)

**James Moses**

Media & Investor Relations  
Mandate Corporate  
M: +61 (0) 420 991 574  
E: [james@mandatecorporate.com.au](mailto:james@mandatecorporate.com.au)

### Competent Persons Statement

The information in this report that relates to Exploration Results and Targets is based on information compiled by Mr Brett Smith, B.Sc Hons (Geol), Member AusIMM, Member AIG and an employee of Corazon Mining Limited. Mr Smith has sufficient experience that is relevant to the style of mineralization and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves". Mr Smith consents to the inclusion in the report of the matters based on this information in the form and context in which it appears.

Canadian geologist Dr Larry Hulbert has been engaged by Corazon to manage the collation of past exploration information and the definition of new targets at Lynn Lake. Dr Hulbert has extensive knowledge of the Lynn Lake district and over 40 years' experience in Ni-Cu-PGM exploration and research. Dr Hulbert is one of North America's foremost experts on magmatic sulphide deposits and would qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves".

Dr. Hulbert has authored numerous professional papers, was the recipient of the Barlow Medal from CIM in 1993, a Robinson Distinguished Lecturer for the Geological and Mineralogical Association of Canada for 2001-2002, and in 2003 received the Earth Sciences Sector Merit Award from Natural Resources Canada.

This announcement tables results of a downhole electromagnetic (DHEM) survey completed by Abitibi Geophysics Inc, ("Abitibi") based in Quebec, Canada. Abitibi are an accredited geophysical consultancy with extensive experience in this form of geophysical technique targeting this style of mineralisation.

The results of the BHEM survey have been audited and interpreted by the Company's consultant geophysicist and 'expert', Martin St. Pierre (P. Geophysicist) from St Pierre Geoconsultant Inc., based in British Columbia, Canada.

### Forward Looking Statements

This announcement contains certain statements that may constitute "forward looking statement". Such statements are only predictions and are subject to inherent risks and uncertainties, which could cause actual values, results, performance achievements to differ materially from those expressed, implied or projected in any forward-looking statements.

# Table 1: Checklist of Assessment and Reporting Criteria

27<sup>th</sup> March 2017

## Core Drilling - Fraser Lake Complex - Lynn Lake Project, Canada.

### Section 1 Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
<b>Sampling techniques</b>	<ul style="list-style-type: none"> <li>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</li> <li>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</li> <li>Aspects of the determination of mineralisation that are Material to the Public Report.</li> <li>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</li> </ul>	<p><b>Drill Core Sampling</b></p> <p>Half core is sampled on the basis of geology. Minimum interval 200mm, maximum interval sampled is 1.5m.</p> <p>The drill core is cut using an industry standard core saw. Individual samples are collected in labelled calico bags. Sample weights are typically between 2kg and 5kg.</p> <p><b>"Field-Testing"</b> - a hand-held XRF (Niton) is used for the purposes of assisting with mineral identification and metal content. Analysis is completed by point-testing of the dry, un-processed, core sample. This style of sampling typically un-reliable and can result in large variations in results. Broad ranges for nickel contents have been stated. These results are indicative only and by no means truly representative and should not be used for the purposed of resource calculations.</p>
<b>Drilling techniques</b>	<ul style="list-style-type: none"> <li>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</li> </ul>	<p>NQ drill core is being undertaken by Vital Drilling Services using an Atlas Capco CS 1000. Rod lengths are 3m (NM – Atlas Capco), with core run lengths also of 3m.</p> <p>Depth capacity of this drill rig is approximately 700 metres.</p>
<b>Drill sample recovery</b>	<ul style="list-style-type: none"> <li>Method of recording and assessing core and chip sample recoveries and results assessed.</li> <li>Measures taken to maximise sample recovery and ensure representative nature of the samples.</li> <li>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to</li> </ul>	<p>Recovery of the core drilling is excellent (+99%).</p>

## Table 1: Checklist of Assessment and Reporting Criteria

27<sup>th</sup> March 2017

### Core Drilling - Fraser Lake Complex - Lynn Lake Project, Canada.

Criteria	JORC Code explanation	Commentary
	<i>preferential loss/gain of fine/coarse material.</i>	
<b>Logging</b>	<ul style="list-style-type: none"> <li>• Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</li> <li>• Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</li> <li>• The total length and percentage of the relevant intersections logged.</li> </ul>	<p>Core is geologically logged and tested for magnetic susceptibility &amp; conductivity.</p> <p>A hand-held XRF (Niton) is used for the purposes of assisting with mineral identification and metal content.</p>
<b>Sub-sampling techniques and sample preparation</b>	<ul style="list-style-type: none"> <li>• If core, whether cut or sawn and whether quarter, half or all core taken.</li> <li>• If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</li> <li>• For all sample types, the nature, quality and appropriateness of the sample preparation technique.</li> <li>• Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</li> <li>• Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</li> <li>• Whether sample sizes are appropriate to the grain size of the material being sampled.</li> </ul>	<p>Drill core is cut and typically half core is taken as a sample for analysis.</p> <p>Quality control measures include core duplicates (1/4 core), CANMET certified reference materials (standards) and silica blanks.</p> <p>Samples are transported to TSL Laboratories in Saskatoon for sample preparation, including total sample crushing and pulverising to 80% passing 75 microns.</p> <p>Sample analysis is completed by ACME Laboratories in Vancouver.</p> <p>Sample security is overseen by Aurora Geosciences personnel until shipment from site to the Laboratory. Shipment and transport is overseen by Corazon's Lynn Lake site manager.</p>
<b>Quality of assay data and laboratory tests</b>	<ul style="list-style-type: none"> <li>• The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</li> <li>• For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</li> <li>• Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</li> </ul>	<p>Once sample preparation was completed by TSL Laboratories, they are transported to ACME Laboratories in Vancouver for analysis. A multi-element analysis is completed using ICP-MS with a 4 acid digest (30 gram samples). A total of 37 elements are tested for (ACME method code AQ525).</p> <p>Both TSL and ACME are accredited Canadian laboratories.</p> <p>A hand-held XRF (Niton) is used for the purposes of assisting with mineral identification and metal content. Broad ranges for nickel and copper metal contents have been stated. These results are indicative only and by no means truly representative and should not be used for the purposed of resource calculations.</p>



## Table 1: Checklist of Assessment and Reporting Criteria

27<sup>th</sup> March 2017

### Core Drilling - Fraser Lake Complex - Lynn Lake Project, Canada.

Criteria	JORC Code explanation	Commentary
<b>Verification of sampling and assaying</b>	<ul style="list-style-type: none"> <li>• The verification of significant intersections by either independent or alternative company personnel.</li> <li>• The use of twinned holes.</li> <li>• Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</li> <li>• Discuss any adjustment to assay data.</li> </ul>	<p>Drilling is being managed by experienced geological personnel from Aurora Geosciences and overseen by Corazon's consultant and nickel sulphide expert Dr Larry Hulbert.</p> <p>All data is captured electronically on site and transferred to backup facilities. All paper information is captured electronically and stored digitally and in paper format.</p> <p>No adjustment to primary assaying has been undertaken. All averaging over intervals is calculated on an individual interval weighted average basis.</p>
<b>Location of data points</b>	<ul style="list-style-type: none"> <li>• Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</li> <li>• Specification of the grid system used.</li> <li>• Quality and adequacy of topographic control.</li> </ul>	<p>Drill holes were positioned using a hand-held Trimble GEOXH GPS and Reflex Northfinder APS.</p> <p>The survey data is recorded in real-world grid system NAD 83 Zone 14.</p>
<b>Data spacing and distribution</b>	<ul style="list-style-type: none"> <li>• Data spacing for reporting of Exploration Results.</li> <li>• Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</li> <li>• Whether sample compositing has been applied.</li> </ul>	<p>Drill holes are widely spaced and targeted at individual geophysical anomalies.</p> <p>This exploration is reconnaissance in nature and as such will not result in the immediate definition of a mineral resource estimation.</p>
<b>Orientation of data in relation to geological structure</b>	<ul style="list-style-type: none"> <li>• Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</li> <li>• If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</li> </ul>	<p>Drill holes are widely spaced and targeted at individual geophysical anomalies.</p> <p>Azimuths and dips are variable, dependent on the targets being tested.</p> <p>No bias for the sampling has been established.</p>
<b>Sample security</b>	<ul style="list-style-type: none"> <li>• The measures taken to ensure sample security.</li> </ul>	<p>Sample security is overseen by Aurora Geosciences personnel until shipment to the Laboratory.</p>

## Table 1: Checklist of Assessment and Reporting Criteria

27<sup>th</sup> March 2017

### Core Drilling - Fraser Lake Complex - Lynn Lake Project, Canada.

Criteria	JORC Code explanation	Commentary
		<p>Individual samples are collected in plastic bags, before being bundled together into sealed in large PVC bags and sealed with security tags for transport to the laboratory.</p> <p>Shipment and transport of the samples to TSL Laboratories is overseen by Corazon's Lynn Lake site manager.</p>
<b>Audits or reviews</b>	<ul style="list-style-type: none"> <li><i>The results of any audits or reviews of sampling techniques and data.</i></li> </ul>	<p>Industry standard duplicate sampling and submission of certified blank and standard samples have been undertaken.</p> <p>At this stage, no audits or reviews have been conducted.</p>

### Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
<b>Mineral tenement and land tenure status</b>	<ul style="list-style-type: none"> <li><i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i></li> <li><i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i></li> </ul>	<p>The Fraser Lake Complex (FLC) is predominantly covered in an agreement between Mr Peter Dunlop and Corazon Mining Limited whereby Corazon has the option to acquire 100% of the project by meeting certain conditions. This agreement was originally announced within a Company ASX announcement dated 18 May 2010, with the most recent amendments to this agreement presented in a Company ASX announcement dated 29 July 2015.</p> <p>The tenure includes multiple Mineral Claims as defined by the Provincial Government of Manitoba. All claims are currently in good standing.</p> <p>Corazon Mining works closely with First Nation groups and several government organizations responsible for mining and the environment. Work Permits are currently in place for the FLC and covers activities such as ground geophysics and land-based drilling.</p>
<b>Exploration done by other parties</b>	<ul style="list-style-type: none"> <li><i>Acknowledgment and appraisal of exploration by other parties.</i></li> </ul>	<p>Where exploration has been completed by other parties, those parties have been referenced in this document or within previous ASX announcements by</p>

## Table 1: Checklist of Assessment and Reporting Criteria

27<sup>th</sup> March 2017

### Core Drilling - Fraser Lake Complex - Lynn Lake Project, Canada.

Criteria	JORC Code explanation	Commentary																																																								
		the Company. In particular refer to CZN ASX announcement dated 11 April 2016.																																																								
<b>Geology</b>	<ul style="list-style-type: none"> <li>• <i>Deposit type, geological setting and style of mineralisation.</i></li> </ul>	<p>Magmatic nickel-copper-cobalt sulphide deposits associated within mafic/ultramafic intrusive rock (gabbro related).</p> <p>Volcanogenic massive sulphide (VMS) deposits. Zinc dominant +/- lead, copper, silver and gold.</p>																																																								
<b>Drill hole Information</b>	<ul style="list-style-type: none"> <li>• <i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> <ul style="list-style-type: none"> <li>○ <i>easting and northing of the drill hole collar</i></li> <li>○ <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i></li> <li>○ <i>dip and azimuth of the hole</i></li> <li>○ <i>down hole length and interception depth</i></li> <li>○ <i>hole length.</i></li> </ul> </li> <li>• <i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i></li> </ul>	<p>Drill Hole Survey Data</p> <table border="1"> <thead> <tr> <th>Hole_ID</th> <th>East</th> <th>North</th> <th>RL</th> <th>Dip</th> <th>Azim</th> <th>Depth</th> </tr> </thead> <tbody> <tr> <td>FLC-2017-1</td> <td>370645</td> <td>6295794</td> <td>342.9</td> <td>60</td> <td>10</td> <td>83</td> </tr> <tr> <td>FLC-2017-2</td> <td>370913</td> <td>6296178</td> <td>347.6</td> <td>86</td> <td>334</td> <td>602</td> </tr> <tr> <td>FLC-2017-3</td> <td>370733</td> <td>6296076</td> <td>345.5</td> <td>87</td> <td>334</td> <td>605</td> </tr> <tr> <td>FLC-2017-4</td> <td>371425</td> <td>6295984</td> <td>346.4</td> <td>86</td> <td>156</td> <td>107</td> </tr> <tr> <td>FLC-2017-5</td> <td>372385</td> <td>6295788</td> <td>342.3</td> <td>86</td> <td>156</td> <td>120</td> </tr> <tr> <td>FLC-2017-08</td> <td>370971</td> <td>6296388</td> <td>351.0</td> <td>80</td> <td>190</td> <td>485</td> </tr> <tr> <td>FLC-2017-010</td> <td>370850</td> <td>6296061</td> <td>351.0</td> <td>80</td> <td>323</td> <td>475</td> </tr> </tbody> </table> <p>Survey data presented in real-world grid system NAD 83 Zone 14</p>	Hole_ID	East	North	RL	Dip	Azim	Depth	FLC-2017-1	370645	6295794	342.9	60	10	83	FLC-2017-2	370913	6296178	347.6	86	334	602	FLC-2017-3	370733	6296076	345.5	87	334	605	FLC-2017-4	371425	6295984	346.4	86	156	107	FLC-2017-5	372385	6295788	342.3	86	156	120	FLC-2017-08	370971	6296388	351.0	80	190	485	FLC-2017-010	370850	6296061	351.0	80	323	475
Hole_ID	East	North	RL	Dip	Azim	Depth																																																				
FLC-2017-1	370645	6295794	342.9	60	10	83																																																				
FLC-2017-2	370913	6296178	347.6	86	334	602																																																				
FLC-2017-3	370733	6296076	345.5	87	334	605																																																				
FLC-2017-4	371425	6295984	346.4	86	156	107																																																				
FLC-2017-5	372385	6295788	342.3	86	156	120																																																				
FLC-2017-08	370971	6296388	351.0	80	190	485																																																				
FLC-2017-010	370850	6296061	351.0	80	323	475																																																				
<b>Data aggregation methods</b>	<ul style="list-style-type: none"> <li>• <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i></li> <li>• <i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i></li> <li>• <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i></li> </ul>	No data aggregation has been reported in this announcement.																																																								

## Table 1: Checklist of Assessment and Reporting Criteria

27<sup>th</sup> March 2017

### Core Drilling - Fraser Lake Complex - Lynn Lake Project, Canada.

Criteria	JORC Code explanation	Commentary
<b>Relationship between mineralisation widths and intercept lengths</b>	<ul style="list-style-type: none"> <li>• These relationships are particularly important in the reporting of Exploration Results.</li> <li>• If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</li> <li>• If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</li> </ul>	<p><b>Typical Lynn Lake Ni-Cu-Co Magmatic Sulphide Deposits</b></p> <p>Known nickel-copper-cobalt magmatic sulphide deposits in the Lynn Lake Mining Centre are typically "pipe-like" in form, averaging between 80m and 120m in strike, 30m to 60m in width and with vertical extents of 100's of metres. The historically mined deposits in the Lynn Lake area have been developed to a maximum depth of approximately 1,100 metres.</p> <p>Multiple sulphide pipe-like deposits have been identified and mined in the Lynn Lake area.</p>
<b>Diagrams</b>	<ul style="list-style-type: none"> <li>• Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</li> </ul>	Appropriate diagrams have been included in the announcement.
<b>Balanced reporting</b>	<ul style="list-style-type: none"> <li>• Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</li> </ul>	This report tables early findings with respect to core drilling currently being undertaken within the FLC at Lynn Lake.
<b>Other substantive exploration data</b>	<ul style="list-style-type: none"> <li>• Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</li> </ul>	<p>The announcement contains results of current and past exploration programs including surface sampling, drilling, geophysics and geological mapping.</p> <p>Information regarding this work has been referenced in this document or within previous ASX announcements by the Company.</p>
<b>Further work</b>	<ul style="list-style-type: none"> <li>• The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</li> <li>• Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</li> </ul>	<p>Phase II Drilling at the FLC commenced in March, 2017.</p> <p>Ground geophysics is currently underway on the Project. This work will refine drill targets and test new areas.</p>