

9 December 2017

FURTHER HIGH-GRADE LITHIUM RESULTS AT MORABISI

Highlights

- Latest grab samples from the Turesi Ridge report up to 2.03% Li2O.
- Turesi grab samples continue to increase zone of high-grade Li2O in Trench #1 by over 200m.
- Scintillometer radiometric grid at Turesi indicates a 1500m strike, 500m width and open along strike.
- Consistent grades (albeit weathered) of +1% Li2O. •
- New stream sediment samples indicate two additional LCT pegmatite targets at • Banakaru.
- Over 1,000 outstanding samples (results pending) from Turesi, Robello and Heavy • Creek.
- Results from the additional seven Turesi trenches and Turesi grab samples are • expected within the next 4 weeks.

Greenpower Energy Ltd (ASX: Greenpower, "GPP", "Company") is pleased to provide the following update regarding field activities at the Morabisi Lithium/REE Project ("Project").

Progress Overview

The Morabisi Phase II exploration program is now complete, with all equipment and personnel having been demobilised from all camps for the season. The joint venture successfully completed 10 trenches at Turesi totaling approx. 2,500m and defined a strong radiometric signature related to lithium mineralization. 61 Banka drill holes at Robello and Heavy Creek totaling 211m. And two trenches at Banakaru with additional stream sediment sampling.

Greenpower Executive Chairman, Gerard King:

"The continuing receipt of positive assay results provides further encouragement to Greenpower that Morabisi may in fact be a world-class Lithium discovery which is able to meet the demand currently seen globally. With over 1,000 assay results still to be received, further near-term news flow for shareholders should be expected from this exciting project.

The Company is pleased with the significant amount of work completed in Phase II given the limited budget and looks forward to communicating next steps with shareholders once the final assay results are received."

+61 418 852 700 | +61 299 991 515



PO Box 1664 Fremantle WA 6959 Australia




Image 1. Map of Turesi Ridge sampling data




Image 2. Map of Turesi Ridge grab & stream sediment results

Target	Location	Channel	Grab	Stream	Soil	Total	Analysis
Turesi	TT17-01	39	8			47	Complete
Turesi	TT17-02	20	5			25	Complete
East Camp	East Camp			12		12	Complete
Robello	Tailings			3		3	Complete
Banakaru	TB17-02	31	2			33	Complete
Turesi	TT17-01 & Rd	5	13			18	Complete
Robello	Tailings			3		3	Complete
Robello	Scint grid			28		28	Complete
Banakaru	TB17-02	40				40	Complete
Banakaru	TB17-01	59				59	Complete
Turesi	TT17-04	71	27			98	Pending
Turesi	TT17-05	63				63	Pending
Turesi	TT17-06	15				15	Pending
Turesi	TT17-07	18				18	Pending
Turesi	TT17-08	67	47			114	Pending
Turesi	TT17-09	130	33			163	Pending
Turesi	TT17-10	93	12			105	Pending
Turesi	Grid		79			79	Pending
Robello	Banka			58		58	Pending
Heavy Ck	Banka			185		185	Pending
Heavy Ck Rd	Road		10	50	100	160	Pending

The sample summary for Phase II is as follows - all samples are now with MS Analytical:

Banakaru Trenching and East Camp

Banakaru trenches have been completed on the northern slope of Banakaru Mountain. Banakaru Mountain is capped by a west-northwest striking diabase dyke which has preserved the underlying greenstone rocks. The Banakaru trenches are strategically located to follow up on strong Cs, Rb and Be geochemical anomalies identified in the Phase 1 stream sediment sampling program.

TB17-02 encountered two zones of high kaolinite alteration from 68 – 90 m and 446 – 490 m. After analysis, portions of these two kaolinized zones indicate elevated values in Cs, Nb and Ta relative to background values of the weathered, underlying, greenstone rocks.

Weathered greenstone rocks were mapped over the entire length of TB17-01.

Additional stream sediment sampling was conducted in the East Camp and Banakaru areas during Phase II and successfully identified two new prospective targets with high Rb and Cs anomalies. Rb is proving to be a strong pathfinder for LCT Pegmatites as three samples at Turesi returned values of Rb between 31 – 218 ppm that are directly related to LCT-Pegmatites with high Li values previously reported in trenches. At Banakaru there are three samples that range between 42 – 143 ppm Rb and have corresponding high Cs values. Rb is a highly mobile alkali element, where highly anomalous values tend to be close to the source.

<u>Turesi Ridge Area</u>

Following the encouraging results reported October 25th, 2017 which delivered up to 2.63% Li2O, crews returned to Turesi to continue trenching. GSM excavated an additional seven trenches (1,697 m) for a total of 10 trenches at Turesi totaling 2,496 m.

All samples from Turesi are now being processed by MS Analytical and are summarized as follows:

Trench ID	Length (m)	Channel	Grab
TT17-01	392	39	8
TT17-02	295	20	5
TT17-03	113	0	
TT17-04	159	71	27
TT17-05	218	63	
TT17-06	84	15	
TT17-07	49	18	
TT17-08	248	67	47
TT17-09	755	130	33
TT17-10	184	93	12
Total	2496	516	132

The follow-up Turesi trenching program commenced November 2nd, 2017 and was completed on November 15th, 2017.

During the period GSM also conducted Radiometric sampling using a hand-held scintillometer over a tight grid covering an area of approximately 1 km2. The result of the survey is a strong anomaly striking ~1500m NW-SE and ~500m wide with a strong correlation between high total count and Li-bearing pegmatites. This is understood to possibly be a good indication that an airborne radiometric survey would be successful in identifying LCT pegmatites in the Morabisi area. As such, the Joint Venture is contemplating a radiometric survey as a cost-effective method for further exploration.

In addition to the above, GSM has also had the opportunity to re-examine the first 2 trenches in more detail and spend time collecting additional grab samples. The first batch of grab samples, which are primarily from TT17-01, show results of up to 2.03% Li2O (half of which are above 1.0% Li2O) and extend the footprint of known high grade Li2O in TT17-01. Sample A2021532 returned 1.79% Li2O and is located near the top of TT17-01, over 200m from a previously reported high grade sample at 2.63% Li2O. Highlights are shown in Table 2 and Images 1 & 2.

Sample Id	Туре	Target	Easting	Northing	Li2O
A2021501	Grab	Turesi	234,807	648,758	<u>1.11</u>
A2021507	Grab	Turesi	234,715	648,840	<u>1.10</u>
A2021508	Grab	Turesi	234,698	648,833	<u>1.95</u>
A2021511	Grab	Turesi	234,687	648,823	0.44
A2021512	Grab	Turesi	234,683	648,819	0.73
A2021515	Grab	Turesi	234,242	648,910	0.78
A2021516	Grab	Turesi	234,608	648,770	<u>1.76</u>
A2021518	Grab	Turesi	234,561	648,739	<u>2.03</u>
A2021521	Grab	Turesi	234,463	648,691	0.78
A2021522	Grab	Turesi	234,465	648,687	0.77
A2021523	Grab	Turesi	234,463	648,700	<u>0.91</u>
A2021526	Grab	Turesi	234,483	648,719	<u>1.23</u>
A2021528	Grab	Turesi	234,502	648,722	<u>0.89</u>
A2021529	Grab	Turesi	234,464	648,696	<u>1.00</u>
A2021531	Grab	Turesi	234,469	648,699	<u>1.18</u>
A2021532	Grab	Turesi	234,456	648,689	<u>1.79</u>
A2021541	Grab	Turesi	234,515	648,709	0.57
A2021542	Grab	Turesi	234,516	648,716	<u>1.09</u>

Table 1. Latest Turesi Grab Samples

Photographic Summary

The following is a photographic summary of examples of the sampling work and trenching conducted at the Morabisi Project:





ENDS

For further information: Gerard King Chairman of the Board

Competent Person Statement

I, John Adrian Watts on 9 December 2017 confirm that:

- I have read and understood the requirements of the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves ("2012 JORC Code").
- I am a Competent Person as defined by the 2012 JORC Code, having more than five years' experience which is relevant to the style of mineralisation and type of deposit described in the Report, and to the activity for which I am accepting responsibility.
- I am a Fellow of The Australasian Institute of Mining and Metallurgy and a Fellow of the IOMMM.
- This statement fairly represents documentation prepared by myself on behalf of my employer, Australian Exploration Field Services Pty Ltd.
- I consent to the release of this document to the ASX.

JORC Code, 2012 Edition – Table 1 report template

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	 Excavator-cut Trenching to 3m depth. Channel sampling varying from 1m to 4m channel sample interval; grab sampling. In-trench hand held assaying scintillometer survey using a Radiations Solutions Inc. Super Spec RS125 scintillometer, Ser#2121 Results logged on board the scintillometer, downloaded on completion of survey. Separate log of readings maintained. Location GPS readings recorded independently of scintillometer.
Drilling techniques	• Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- sampling bit or other type, whether core is oriented and if so, by what method, etc).	 Banka Drilling, 125mm (6") hole diameter, 1m sampling interval

Criteria	JORC Code explanation	Commentary
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 Samples collected at 1m interval and weighed Sample recovery maximised by drilling crew's expertise Sample analyses pending so not yet known
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	 Banka Drilling samples logged at 1m interval. Trenching channel sample intervals described. It is too early for a mineral resource estimation to be made All drilling and trenching descriptions are qualitative at this stage. Samples being submitted to laboratory For Turesi Trenching, Turesi Scintillometer Grid Sampling, Turesi Road Sampling, Banakaru Trenching, Robello Banka Drilling, Robello Scintillometer Grid Sampling, Robello Tailings Sampling, Heavy Creek Banka Drilling and Heavy Creek Road Sampling : See Trenching lengths, channel and grab sampling data in body of Report
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all subsampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	 Banka drilling samples riffle split in the field. Split samples stored on site. Sample duplicates collected in the field All samples and duplicate samples checked to ensure they are representative Large sample size to ensure appropriate grain size Reference Samples included in the field for Laboratory submissions Blank Samples included in the field for Laboratory submissions Sample sizes collected are appropriate to grain size of material being sampled
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. 	 Li analysis by Sodium Peroxide Fusion, ICP-ES.REE Analysis by Lithium Metaborate Fusion, ICP-MS External laboratory checks via submission of duplicate samples

Criteria	JORC Code explanation	Commentary
Verification of sampling and	 Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. The verification of significant intersections by either independent or alternative company 	 All samples currently being submitted to MS Analytical
assaying	 personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	Vancouver BC. Check samples of pulps will be submitted from MS Analytical Georgetown to Nagrom Laboratories, Perth, WA
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 Start end and intermediate points of trenches by GPS. UTM projection, Zone 21 North, PSAD56 Datum used. Topographic control by available topographic mapping, checked by GPS
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 Sample compositing on 3m lengths Data acquisition to date is insufficient for Mineral Resource and Ore Reserve estimation at this preliminary exploration phase.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	Pegmatite orientation measured from outcrop in trench TT17-01. Further trenching required to verify orientation
Sample security	The measures taken to ensure sample security.	• Samples are collected at the trench sites, moved to and stored securely at base camp. Samples are shipped to Georgetown by river transport, met by a GSM representative who takes them directly to MS Analytical's Georgetown Laboratory. MS Analytical's security protocols will then apply. Samples currently analysed by MS Analytical in Vancouver BC
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	 Too early to review. Samples include blanks, standards.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 Reconnaissance Geophysical and Geological Survey, Morabisi Area, Mining District#3, Region 7 Guyana. The tenement has an area of 950,810.1 acres Guyana Strategic Metals in Joint Venture with Greenpower Energy Ltd A two year exploration programme has been approved by Guyana Geology and Mining Commission There are no known impediments to obtaining a licence to operate in the area
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	 GGMC – Summary of Geochemistry, Geology and Structure, June 2002
Geology	 Deposit type, geological setting and style of mineralisation. 	LCT type pegmatites associated with granite/basic contact zone
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	Not applicable – no previous drilling
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	 Previous Phase 1 exploration by the Joint Venturers GSM and Greenpower

Criteria	JORC Code explanation	Commentary
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	 Not applicable – no previous drilling
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	 Not applicable - no previous drilling
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	 Currently not applicable – too early in the current exploration programme. All exploration results are being reported.
Other substantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 Further trenching at Turesi as indicated on accompanying plan to more accurately determine pegmatite orientation Drilling contemplated as following step.

Section 3 Estimation and Reporting of Mineral Resources

(Criteria listed in section 1, and where relevant in section 2, also apply to this section.)

Criteria	JORC Code explanation	Commentary
Database integrity	 Measures taken to ensure that data has not been corrupted by, for example, transcription or keying errors, between its initial collection and its use for Mineral Resource estimation purposes. Data validation procedures used. 	Currently not applicable
Site visits	 Comment on any site visits undertaken by the Competent Person and the outcome of those visits. If no site visits have been undertaken indicate why this is the case. 	Competent Person overflew the area 5 July 2017 Ground access at that time not possible because of late wet season flooding. Site inspections of Turesi Banakaru and Robello Creek Old Mine made during a

Criteria	JORC Code explanation	Commentary
		site visit, 23-27 September 2017
Geological interpretation	 Confidence in (or conversely, the uncertainty of) the geological interpretation of the mineral deposit. Nature of the data used and of any assumptions made. The effect, if any, of alternative interpretations on Mineral Resource estimation. The use of geology in guiding and controlling Mineral Resource estimation. The factors affecting continuity both of grade and geology. 	 Reasonable confidence in geological model Historical data, GSM Greenpower JV data used for assumptions No Mineral Resource estimations have been made due to the early stage of exploration
Dimensions	• The extent and variability of the Mineral Resource expressed as length (along strike or otherwise), plan width, and depth below surface to the upper and lower limits of the Mineral Resource.	Not applicable.
Estimation and modelling techniques	 The nature and appropriateness of the estimation technique(s) applied and key assumptions, including treatment of extreme grade values, domaining, interpolation parameters and maximum distance of extrapolation from data points. If a computer assisted estimation method was chosen include a description of computer software and parameters used. The availability of check estimates, previous estimates and/or mine production records and whether the Mineral Resource estimate takes appropriate account of such data. The assumptions made regarding recovery of by-products. Estimation of deleterious elements or other non-grade variables of economic significance (eg sulphur for acid mine drainage characterisation). In the case of block model interpolation, the block size in relation to the average sample spacing and the search employed. Any assumptions about correlation between variables. Description of how the geological interpretation was used to control the resource estimates. Discussion of basis for using or not using grade cutting or capping. The process of validation, the checking process used, the comparison of model data to drill hole data, and use of reconciliation data if available. 	 None of the following in this section are applicable
Moisture	 Whether the tonnages are estimated on a dry basis or with natural moisture, and the method of determination of the moisture content. 	Not applicable
Cut-off parameters	 The basis of the adopted cut-off grade(s) or quality parameters applied. 	Not applicable
Mining factors or assumptions	Assumptions made regarding possible mining methods, minimum mining dimensions and internal (or, if applicable, external) mining	Not applicable

Criteria	JORC Code explanation	Commentary
	dilution. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential mining methods, but the assumptions made regarding mining methods and parameters when estimating Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the mining assumptions made.	
Metallurgical factors or assumptions	• The basis for assumptions or predictions regarding metallurgical amenability. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential metallurgical methods, but the assumptions regarding metallurgical treatment processes and parameters made when reporting Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the metallurgical assumptions made.	Not applicable
Environmen-tal factors or assumptions	 Assumptions made regarding possible waste and process residue disposal options. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider the potential environmental impacts of the mining and processing operation. While at this stage the determination of potential environmental impacts, particularly for a greenfields project, may not always be well advanced, the status of early consideration of these potential environmental impacts should be reported. Where these aspects have not been considered this should be reported with an explanation of the environmental assumptions made. 	Not applicable
Bulk density	 Whether assumed or determined. If assumed, the basis for the assumptions. If determined, the method used, whether wet or dry, the frequency of the measurements, the nature, size and representativeness of the samples. The bulk density for bulk material must have been measured by methods that adequately account for void spaces (vugs, porosity, etc), moisture and differences between rock and alteration zones within the deposit. Discuss assumptions for bulk density estimates used in the evaluation process of the different materials. 	Not applicable
Classification	 The basis for the classification of the Mineral Resources into varying confidence categories. Whether appropriate account has been taken of all relevant factors (ie relative confidence in tonnage/grade estimations, reliability of input data, confidence in continuity of geology and metal values, quality, quantity and distribution of the data). Whether the result appropriately reflects the 	Not applicable

Criteria	JORC Code explanation	Commentary
	Competent Person's view of the deposit.	
Audits or reviews	 The results of any audits or reviews of Mineral Resource estimates. 	Not applicable
Discussion of relative accuracy/ confidence	 Where appropriate a statement of the relative accuracy and confidence level in the Mineral Resource estimate using an approach or procedure deemed appropriate by the Competent Person. For example, the application of statistical or geostatistical procedures to quantify the relative accuracy of the resource within stated confidence limits, or, if such an approach is not deemed appropriate, a qualitative discussion of the factors that could affect the relative accuracy and confidence of the estimate. The statement should specify whether it relates to global or local estimates, and, if local, state the relevant tonnages, which should be relevant to technical and economic evaluation. Documentation should include assumptions made and the procedures used. These statements of relative accuracy and confidence of the estimate should be compared with production data, where available. 	 None of the following in this section are applicable

Section 4 Estimation and Reporting of Ore Reserves

(Criteria listed in section 1, and where relevant in sections 2 and 3, also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral Resource estimate for conversion to Ore Reserves	 Description of the Mineral Resource estimate used as a basis for the conversion to an Ore Reserve. Clear statement as to whether the Mineral Resources are reported additional to, or inclusive of, the Ore Reserves. 	 Not applicable
Site visits	 Comment on any site visits undertaken by the Competent Person and the outcome of those visits. If no site visits have been undertaken indicate why this is the case. 	Competent Person overflew the area 5 July 2017 Ground access at that time not possible because of late wet season flooding.Compenent Person visited Turesi Trenches, Banakarau Trenches, Robello Creek Old Mine,23-27 September 2017
Study status	 The type and level of study undertaken to enable Mineral Resources to be converted to Ore Reserves. The Code requires that a study to at least Pre- Feasibility Study level has been undertaken to convert Mineral Resources to Ore Reserves. Such studies will have been carried out and will have determined a mine plan that is technically achievable and economically viable, and that material Modifying Factors have been considered. 	Not applicable

Criteria	JORC Code explanation	Commentary
Cut-off parameters	 The basis of the cut-off grade(s) or quality parameters applied. 	Not applicable
Mining factors or assumptions	 The method and assumptions used as reported in the Pre-Feasibility or Feasibility Study to convert the Mineral Resource to an Ore Reserve (i.e. either by application of appropriate factors by optimisation or by preliminary or detailed design). The choice, nature and appropriateness of the selected mining method(s) and other mining parameters including associated design issues such as pre-strip, access, etc. The assumptions made regarding geotechnical parameters (eg pit slopes, stope sizes, etc), grade control and pre-production drilling. The major assumptions made and Mineral Resource model used for pit and stope optimisation (if appropriate). The mining dilution factors used. Any minimum mining widths used. The manner in which Inferred Mineral Resources are utilised in mining studies and the sensitivity of the outcome to their inclusion. The infrastructure requirements of the selected mining methods. 	
Metallurgical factors or assumptions	 The metallurgical process proposed and the appropriateness of that process to the style of mineralisation. Whether the metallurgical process is well-tested technology or novel in nature. The nature, amount and representativeness of metallurgical test work undertaken, the nature of the metallurgical domaining applied and the corresponding metallurgical recovery factors applied. Any assumptions or allowances made for deleterious elements. The existence of any bulk sample or pilot scale test work and the degree to which such samples are considered representative of the orebody as a whole. For minerals that are defined by a specification, has the ore reserve estimation been based on the appropriate mineralogy to meet the specifications? 	 None of the following in this section are applicable
Environmental	 The status of studies of potential environmental impacts of the mining and processing operation. Details of waste rock characterisation and the consideration of potential sites, status of design options considered and, where applicable, the status of approvals for process residue storage and waste dumps should be reported. 	• Not applicable
Infrastructure	• The existence of appropriate infrastructure: availability of land for plant development, power, water, transportation (particularly for bulk commodities), labour, accommodation; or the ease with which the infrastructure can be	 Not applicable. All infrastructure relates to preliminary exploration and is supplied by the GSM/ Greenpower Joint Venture

Criteria	JORC Code explanation	Commentary
Costs	 provided, or accessed. The derivation of, or assumptions made, regarding projected capital costs in the study. The methodology used to estimate operating costs. Allowances made for the content of deleterious elements. The source of exchange rates used in the study. Derivation of transportation charges. The basis for forecasting or source of treatment and refining charges, penalties for failure to meet specification, etc. The allowances made for royalties payable, both Government and private. 	None of the following in this section are applicable
Revenue factors	 The derivation of, or assumptions made regarding revenue factors including head grade, metal or commodity price(s) exchange rates, transportation and treatment charges, penalties, net smelter returns, etc. The derivation of assumptions made of metal or commodity price(s), for the principal metals, minerals and co-products. 	Not applicable
Market assessment	 The demand, supply and stock situation for the particular commodity, consumption trends and factors likely to affect supply and demand into the future. A customer and competitor analysis along with the identification of likely market windows for the product. Price and volume forecasts and the basis for these forecasts. For industrial minerals the customer specification, testing and acceptance requirements prior to a supply contract. 	Not applicable
Economic	 The inputs to the economic analysis to produce the net present value (NPV) in the study, the source and confidence of these economic inputs including estimated inflation, discount rate, etc. NPV ranges and sensitivity to variations in the significant assumptions and inputs. 	Not applicable
Social	 The status of agreements with key stakeholders and matters leading to social licence to operate. 	•
Other	 To the extent relevant, the impact of the following on the project and/or on the estimation and classification of the Ore Reserves: Any identified material naturally occurring risks. The status of material legal agreements and marketing arrangements. The status of governmental agreements and approvals critical to the viability of the project, such as mineral tenement status, and government and statutory approvals. There must be reasonable grounds to expect that all necessary Government approvals will be received within the timeframes anticipated in the Pre-Feasibility or Feasibility study. Highlight and discuss the materiality of any unresolved matter 	 None of the following in this section are applicable

Criteria	JORC Code explanation	Commentary
	that is dependent on a third party on which extraction of the reserve is contingent.	
Classification	 The basis for the classification of the Ore Reserves into varying confidence categories. Whether the result appropriately reflects the Competent Person's view of the deposit. The proportion of Probable Ore Reserves that have been derived from Measured Mineral Resources (if any). 	•
Audits or reviews	 The results of any audits or reviews of Ore Reserve estimates. 	Not applicable
Discussion of relative accuracy/ confidence	 Where appropriate a statement of the relative accuracy and confidence level in the Ore Reserve estimate using an approach or procedure deemed appropriate by the Competent Person. For example, the application of statistical or geostatistical procedures to quantify the relative accuracy of the reserve within stated confidence limits, or, if such an approach is not deemed appropriate, a qualitative discussion of the factors which could affect the relative accuracy and confidence of the estimate. The statement should specify whether it relates to global or local estimates, and, if local, state the relevant tonnages, which should be relevant to technical and economic evaluation. Documentation should include assumptions made and the procedures used. Accuracy and confidence discussions should extend to specific discussions of any applied Modifying Factors that may have a material impact on Ore Reserve viability, or for which there are remaining areas of uncertainty at the current study stage. It is recognised that this may not be possible or appropriate in all circumstances. These statements of relative accuracy and confidence of the estimate should be compared with production data, where available. 	None of the following in this section are applicable