

Alderan intersects copper-molybdenum mineralisation and wide intervals of copper at Cactus

HIGHLIGHTS

- Drilling at Cactus Mine has intersected further copper-gold-silver mineralisation and a new zone of copper and molybdenum-bearing quartz-magnetite veins indicative of a proximal copper-bearing porphyry intrusion within the Cactus Corridor, distinct from the Perseverance porphyry prospect
- Drillhole ALCA009 intersected:
 - 49m @ 0.62% Cu, 0.14 g/t Au, 5.9 g/t Ag from 45m including 12m @ 1.37% Cu, 0.28 g/t Au, 10.2 g/t Ag within tourmaline breccia; and
 - 5m @ 0.52% Cu, 0.08% Mo from 169m within a wider 25m zone of copper-molybdenum-bearing magnetite veins
- Hole ALCA008 tested adjacent to the Comet Mine and returned 21.5m @ 0.83% Cu, 0.14 g/t Au, 20.4 g/t Ag from 35.5m
- Alderan has received permits for drilling the recently identified Wasp and Bandit prospects, adjacent to Cactus, with drilling to start at Bandit in coming days
- Work continuing on permitting and road preparation to allow drilling to commence at the Accrington and Perseverance prospects starting in Q2 2018
- Further drilling results from Cactus are expected within the next 2-4 weeks




Figure 1: Copper-molybdenum-bearing quartz-magnetite veins in hole ALCA009 (from 173m) indicative of a proximal porphyry copper system within the Cactus Corridor.

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
 Christopher Wanless | *Chief Executive Officer*
 Bruno Hegner | *Executive Director*
 Tom Eadie | *Non-executive Director*
 Brett Tucker | *Company Secretary*
 Peter Geerdts | *Chief Geologist*

MARKET DATA

ASX Code: AL8
 Share Price: \$1.07
 Shares on Issue: 107,963,908
 Options on Issue: 19,257,454

Drilling intersects copper-molybdenum mineralisation and further breccia-hosted copper

Alderan Resources Limited (ASX: AL8) is pleased to announce drilling has intersected further wide intervals of copper at the Cactus Mine, part of the Company's Frisco Project in Utah, USA.

Results from Alderan's continuing diamond drilling program also discovered a zone of copper and molybdenum-bearing quartz-magnetite veins from approximately 171m to 196m in ALCA009. These are interpreted to be early veins emplaced into wall rocks above or adjacent to a mineralised porphyry intrusive (Figure 1).

Identification of these veins underneath the Cactus Mine substantiates Alderan's belief that a nearby porphyry intrusive caused the mineralisation at Cactus. This intrusive is possibly represented by the Wasp and Bandit prospects which may be distinct from the Perseverance porphyry target (see Figure 3 and ASX announcement dated 19 January 2018).

Table 1: Results from ALCA003 to ALCA005, Cactus Prospect

Hole ID	From (m)	To (m)	Interval (m)	Cu %	Au g/t	Ag g/t	Mo %	
ALCA007	No significant results. Drill hole situated to the north-east of the Cactus Mine to test possible north-eastward extensions							
ALCA008	35.5	57	21.5	0.83	0.14	20.4		Breccia hosted
ALCA009	45	94	49	0.62	0.14	5.9		Breccia hosted
Including	76	88	12	1.37	0.28	10.2		Breccia hosted
And	169	174	5	0.52			0.083	Quartz-magnetite veins

Permitting Update – Bandit and Wasp

Alderan has received permits for drilling at the Bandit and Wasp prospects with drilling expected to begin this week following minor roadworks and drill pad preparation.

The Bandit Prospect is a shallow, flat-lying geophysical target located northwest of the Cactus Mine above a strongly magnetic, pipe-shaped anomaly possibly relating to an intrusive at depth.

Bandit is prospective for porphyry related or skarn-hosted mineralisation, including a supergene enrichment blanket. The target is characterised by:

- A flat-lying high chargeability anomaly (up to >80 mV/V) which occurs over an area of at least 800m by 400m. The anomaly is interpreted to be caused by the presence of either sulphides or skarn-related magnetite;
- A coincident resistivity low (up to <150 Ωm) at depth, indicating a zone of increased conductivity;

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
 Christopher Wanless | *Chief Executive Officer*
 Bruno Hegner | *Executive Director*
 Tom Eadie | *Non-executive Director*
 Brett Tucker | *Company Secretary*
 Peter Geerds | *Chief Geologist*

MARKET DATA

ASX Code: AL8
 Share Price: \$1.07
 Shares on Issue: 107,963,908
 Options on Issue: 19,257,454

- Leached veins at surface with rock-chip sampling returning anomalous copper up to 0.17% and up to 2.9 g/t gold; and
- The location of both chargeability and resistivity anomalies as a blanket on top of a subvertical, highly magnetic body at depth.

The Bandit prospect may represent a large body of sulphides at shallow depths, related to and within an underlying intrusive body.

Alderan will drill 3-5 holes to approximately 200-350m depth to test the Bandit Prospect before moving to the Wasp Prospect.




Figure 2: Target summary for the Bandit target showing a shallow, flat lying chargeability anomaly and a low resistivity anomaly on top of a vertical strongly magnetic body.

The Wasp Prospect is a geophysical anomaly situated several hundred metres northeast of the Cactus Mine within the Cactus structural corridor. It is considered to be prospective for Cactus-style copper-gold-silver or porphyry copper-gold. Key observations include:

- A similar geophysical response to mineralisation intersected by drilling within and adjacent to the Cactus Mine, specifically a low resistivity signature of <60 Ωm; and

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
Christopher Wanless | *Chief Executive Officer*
Bruno Hegner | *Executive Director*
Tom Eadie | *Non-executive Director*
Brett Tucker | *Company Secretary*
Peter Geerds | *Chief Geologist*

MARKET DATA

ASX Code: AL8
Share Price: \$1.07
Shares on Issue: 107,963,908
Options on Issue: 19,257,454

- A medium to strongly magnetic, “pipe” shaped zone along strike of Wasp that also exhibits lower resistivity than surrounding areas suggesting it may form part of an intrusive elongated along the Cactus Corridor.

Mineralisation intersected in recent drilling at the Cactus Mine shows a very good spatial correlation with zones of lower resistivity from the 3D inversion model. The Wasp prospect may represent either a continuation or a primary source of mineralisation at the Cactus Mine to depth.




Figure 3: Wasp prospect shown as a large resistivity low (higher conductivity) to the right (north-east) of the Cactus Mine. The Wasp Prospect occurs within a pipe like structure extending to depth, possibly related to an intrusive body.

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
Christopher Wanless | *Chief Executive Officer*
Bruno Hegner | *Executive Director*
Tom Eadie | *Non-executive Director*
Brett Tucker | *Company Secretary*
Peter Geerdts | *Chief Geologist*

MARKET DATA

ASX Code: AL8
Share Price: \$1.07
Shares on Issue: 107,963,908
Options on Issue: 19,257,454




Figure 4: Map showing the Wasp and Bandit Prospects and hole ALCA009 which intersected copper-molybdenum bearing veins typical of veins emplaced above and adjacent to porphyry copper deposits.

Permitting update – Accrington and Perseverance

Alderan continues drill planning and permitting of Accrington and the Perseverance porphyry prospect. Initial drilling at Accrington will focus on thick copper-bearing skarns which occur from the Imperial Mine to Accrington East. In addition, initial testing of the Perseverance porphyry prospect will occur from near the Imperial Mine.

Whilst extensive roads and tracks occur across Accrington, drilling of outcropping copper bearing skarns and the Perseverance prospect requires further road building and improvements. Completion of permitting, including archeology surveys, and preparatory works is dependent on snow cover. Alderan expects to drill at Accrington and Perseverance in the second quarter of 2018.

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
Christopher Wanless | *Chief Executive Officer*
Bruno Hegner | *Executive Director*
Tom Eadie | *Non-executive Director*
Brett Tucker | *Company Secretary*
Peter Geerdts | *Chief Geologist*

MARKET DATA

ASX Code: AL8
Share Price: \$1.07
Shares on Issue: 107,963,908
Options on Issue: 19,257,454




Figure 5: Cross section of the 3D inversion model for chargeability showing the location of the various prospects within the Frisco system.

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
 Christopher Wanless | *Chief Executive Officer*
 Bruno Hegner | *Executive Director*
 Tom Eadie | *Non-executive Director*
 Brett Tucker | *Company Secretary*
 Peter Geerds | *Chief Geologist*

MARKET DATA

ASX Code: AL8
 Share Price: \$1.07
 Shares on Issue: 107,963,908
 Options on Issue: 19,257,454

Table 2: Drill collar details. Co-ordinates are in WGS84 Zone 12.

Drillhole ID	East	North	Dip	Azimuth	Elevation	Depth (m)	Drill type
ALCA007	299959	4263705	-70	042	1982 asl	396.5	Diamond
ALCA008	300104	4262569	-55	195	1972 asl	297.50	Diamond
ALCA009	299801	4262697	-70	175	1903 asl	327.75	Diamond
ALCA010	299801	4262697	-55	175	1903 asl	158.30	Diamond




Figure 6: Long section through the Cactus and Comet Mine showing ALCA drill holes and historical drilling (refer to announcements on 28 June 2017 and 21 August 2017 for historical drill and channel sample results).

---ENDS---

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
Christopher Wanless | *Chief Executive Officer*
Bruno Hegner | *Executive Director*
Tom Eadie | *Non-executive Director*
Brett Tucker | *Company Secretary*
Peter Geerds | *Chief Geologist*

MARKET DATA

ASX Code: AL8
Share Price: \$1.07
Shares on Issue: 107,963,908
Options on Issue: 19,257,454

ALDERAN RESOURCES LIMITED

Ground Floor, 16 Ord Street, West Perth, 6005, WA

www.alderanresources.com.au

For further information:

e: info@alderanresources.com.au**p:** +61 8 9482 0560

ABN: 55 165 079 201

Please direct enquiries to:

Nathan Ryan

NWR Communications

Mobile: 0420 582 887

Christopher Wanless

Chief Executive Officer

chris@alderanresources.com.au**Stay Connected**

Interested investors and shareholders are encouraged to subscribe to the Company's social media channels using the links below:

**Competent Persons Statement**

The information in this presentation that relates to exploration targets, exploration results, mineral resources or ore reserves is based on information compiled by Peter Geerdts, a competent person who is a member of the Australian Institute of Geoscientists (AIG). Peter Geerdts is the Chief Geologist of Alderan Resources Limited. Peter Geerdts has sufficient experience that is relevant to the style of mineralisation and type of deposits under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 edition of the JORC Code (JORC Code). Peter Geerdts consents to the inclusion of this information in the form and context in which it appears.

Mr Geerdts confirms that that the information provided in this announcement provided under ASX Listing Rules Chapter 5.12.2 to 5.12.7 is an accurate representation of the available data and studies for the proposed exploration programmes that relate to this "material mining project".

The information in this press release that relates to exploration targets, exploration results, mineral resources or ore reserves is based on information compiled by Brian Kay, a competent person who is a member of Engineers and Geoscientists British Columbia (formerly The Association of Professional Engineers and Geoscientists of British Columbia). Brian Kay is the Exploration Manager of Alderan Resources Limited. Brian Kay has sufficient experience that is relevant to the style of mineralisation and type of deposits under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 edition of the JORC Code (JORC Code). Brian Kay consents to the inclusion of this information in the form and context in which it appears. Mr Kay confirms that that the information provided in this announcement provided under ASX Listing Rules Chapter 5.12.2 to 5.12.7 is an accurate representation of the available data and studies for the proposed exploration programmes that relate to this "material mining project".

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
Christopher Wanless | *Chief Executive Officer*
Bruno Hegner | *Executive Director*
Tom Eadie | *Non-executive Director*
Brett Tucker | *Company Secretary*
Peter Geerdts | *Chief Geologist*

MARKET DATA

ASX Code: AL8
Share Price: \$1.07
Shares on Issue: 107,963,908
Options on Issue: 19,257,454

About Alderan Resources Limited

Alderan is a copper explorer with a focus on the Frisco Project, located in Utah, United States of America. The Frisco Project encompasses an area of significant historical mining activity with numerous old mines and workings across an area of approximately 7km by 4km. These include:

- the Cactus copper-gold-silver deposit and breccia pipe, one of several mineralised breccia pipes over an area of approximately 1000 m by up to 400 m.
- the Accrington copper-zinc-silver-gold skarn, which hosts extensive mineralisation across an area of 1.8 km by 1.2 km; and
- the Horn zinc deposit, a historical lead-silver mine, which contains significant amounts of unmined high grade zinc.

The Company believes that these three deposits are genetically related to, and were formed contemporaneously with, underlying mineralised (copper-molybdenum-gold) porphyry intrusion(s). Work undertaken by the Company has identified a likely large mineralised porphyry system beneath and adjacent to the Accrington skarn associated with a 2-3 km diameter chargeability anomaly (Perseverance Prospect).

Forward Looking Statement

Statements contained in this release, particularly those regarding possible or assumed future performance, costs, dividends, production levels or rates, prices, resources, reserves or potential growth of Alderan Resources Limited, are, or may be, forward looking statements. Such statements relate to future events and expectations and, as such, involve known and unknown risks and uncertainties. Actual results and developments may differ materially from those expressed or implied by these forward-looking statements depending on a variety of factors.

BOARD AND MANAGEMENT

Nicolaus Heinen | *Non-executive Chairman*
Christopher Wanless | *Chief Executive Officer*
Bruno Hegner | *Executive Director*
Tom Eadie | *Non-executive Director*
Brett Tucker | *Company Secretary*
Peter Geerds | *Chief Geologist*

MARKET DATA

ASX Code: AL8
Share Price: \$1.07
Shares on Issue: 107,963,908
Options on Issue: 19,257,454

JORC Code, 2012 Edition – Table 1 report template

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	<ul style="list-style-type: none"> All samples collected by diamond drilling, half cut core using core saw, sampled at intervals designated by a geologist. Core was laid out in suitably labelled core trays. A core marker (core block) was placed at the end of each drilled run (nominally 1.5m) and labelled with down hole depth, length of drill run. Core was aligned and measured by tape, comparing back to this down hole depth consistent with industry standards. Mineralisation is determined by the presence of sulphide minerals as logged by a qualified geologist. Chalcopyrite is identified as the mineral of economic interest.
Drilling techniques	<ul style="list-style-type: none"> Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc). 	<ul style="list-style-type: none"> Drilling is by diamond core of HQ (61mm) diameter, using triple tube splits and TruCore orientation device. The Trucore device requires competent core at the core lifter in order to result in a useable orientation line. Sections of core which are broken results in limited or no oriented core in these intervals. There is no known relationship between sample recovery and grade.
Drill sample recovery	<ul style="list-style-type: none"> Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	<ul style="list-style-type: none"> Core is measured by a qualified geologist using downhole marking blocks placed by the driller. Zones of cave or fill are assessed by competence, texture and geologic relationship to surrounding rock, as well as reported cave from drill crew. Drilling through poor ground conditions has resulting in minor zones of poor drill recovery.

Criteria	JORC Code explanation	Commentary																				
		<table border="1"> <thead> <tr> <th>Hole ID</th> <th>Depth (m)</th> <th>Dh casing (m)</th> <th>Recovery % Casing to end of hole</th> </tr> </thead> <tbody> <tr> <td>ALCA006</td> <td>128.36</td> <td>27</td> <td>74</td> </tr> <tr> <td>ALCA007</td> <td>396.5</td> <td>25</td> <td>94</td> </tr> <tr> <td>ALCA008</td> <td>297.6</td> <td>21</td> <td>95</td> </tr> <tr> <td>ALCA009</td> <td>327.75</td> <td>21.4</td> <td>97</td> </tr> </tbody> </table> <ul style="list-style-type: none"> There is no known relationship between sample recovery and grade. 	Hole ID	Depth (m)	Dh casing (m)	Recovery % Casing to end of hole	ALCA006	128.36	27	74	ALCA007	396.5	25	94	ALCA008	297.6	21	95	ALCA009	327.75	21.4	97
Hole ID	Depth (m)	Dh casing (m)	Recovery % Casing to end of hole																			
ALCA006	128.36	27	74																			
ALCA007	396.5	25	94																			
ALCA008	297.6	21	95																			
ALCA009	327.75	21.4	97																			
Logging	<ul style="list-style-type: none"> Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	<ul style="list-style-type: none"> All core has been geologically logged to a level of detail to support future geological modelling and resource estimation. All logging is qualitative with visual estimates of various characteristics conducted by a qualified geologist. Logged characteristics include lithology, alteration veining and mineralisation. Data collection of Specific Gravity, Magnetic Susceptibility is also undertaken at the logging stage All core is photographed by DMT Corescan and photographs recorded in a proprietary database. 																				
Sub-sampling techniques and sample preparation	<ul style="list-style-type: none"> If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material 	<ul style="list-style-type: none"> All in-situ core is sampled and submitted for assay. Sample intervals are defined by a geologist to honor geological, mineralisation or alteration boundaries. Sample intervals are greater than 30cm up to 1.5m in length. Core is cut with an Almonte core saw. Laboratory Preparation procedures – samples are oven dried and crushed to 2mm in two stages, Riffle split to 250gm which is pulverized to 85% passing 75micron. Duplicates are taken at first crushing stage. Sampling techniques are industry standard and considered appropriate 																				

Criteria	JORC Code explanation	Commentary
Quality of assay data and laboratory tests	<p><i>being sampled.</i></p> <ul style="list-style-type: none"> <i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i> <i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i> <i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i> 	<ul style="list-style-type: none"> <i>Gold is determined using a 30g charge fire assay and Atomic Absorption finish</i> <i>Copper, Silver and 46 other elements are determined by Inductively Coupled Plasma Mass Spectroscopy following a 4 acid digest.</i> <i>Samples which exceed the upper detection limit (10,000ppm) are subjected to Ore Grade analysis by ICP Atomic Emission Spectroscopy</i> <i>Commercially prepared Certified Reference Materials (CRM) consisting of High grade, Medium grade, Low grade and Blank were inserted at an average of 2 in 22 samples, with higher frequency in strongly mineralized intervals.</i> <i>Crush duplicate samples were inserted at 1 in 22 samples.</i> <i>Laboratory QAQC sampling includes insertion of CRM samples, and duplicates. This data was reported for each sample submission. Failed standards result in re-assaying of portions of the affected sample batches.</i>
Verification of sampling and assaying	<ul style="list-style-type: none"> <i>The verification of significant intersections by either independent or alternative company personnel.</i> <i>The use of twinned holes.</i> <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> <i>Discuss any adjustment to assay data.</i> 	<ul style="list-style-type: none"> <i>Drill data was compiled and collated, and reviewed by senior staff. External consultants do not routinely verify exploration data until resource estimation procedures are deemed necessary.</i> <i>Twinned holes have not been employed at this early stage of the project</i> <i>Logging is completed in Geobank, an industry standard geological software package. Logging is undertaken on laptops with live uplink to Alderan's proprietary database server.</i> <i>Data validation protocols are run within Geobank</i> <i>Digital assay datafiles are received from ALS and imported into the database</i> <i>Digital copies of Certificate of Analysis are stored in a central database</i> <i>No assay data was adjusted</i>
Location of data points	<ul style="list-style-type: none"> <i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i> <i>Specification of the grid system used.</i> <i>Quality and adequacy of topographic control.</i> 	<ul style="list-style-type: none"> <i>Collar locations are set with handheld GPS with a positional accuracy of +/-3m. Upon completion of drilling, collar locations will be surveyed with DGPS to a positional accuracy of +/-0.1m, to be conducted by a licensed surveyor.</i> <i>Progress downhole surveys are conducted by Boart Longyear personnel at 30m intervals using a Reflex EZshot single shot</i>

Criteria	JORC Code explanation	Commentary
		<p>magnetic survey tool.</p> <ul style="list-style-type: none"> • End of hole downhole surveys are conducted by IDS Drilling Services using a North Seeking Gyro on 10m sample spacing. • Grid coordinate system is WGS84 Zone 12, UTM (m) units. • Upon completion of drilling, topographic control will be provided by DGPS to a positional accuracy of +/-0.1m, to be conducted by a licensed surveyor.
Data spacing and distribution	<ul style="list-style-type: none"> • Data spacing for reporting of Exploration Results. • Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. • Whether sample compositing has been applied. 	<ul style="list-style-type: none"> • At this early exploration stage, the data spacing is variable as the focus is on identifying new zones of mineralisation. • Reconnaissance drilling only, no resource estimation being undertaken at this time. • No sample compositing is applied.
Orientation of data in relation to geological structure	<ul style="list-style-type: none"> • Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. • If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	<ul style="list-style-type: none"> • Drillhole azimuth of approximately 210 degrees intersects the interpreted controlling ESE-WNW structures at an optimal angle. • Other drilling orientations are undertaken to test this interpreted controlling structural orientation. • Insufficient data exists to properly assess degree of structural control or True Width.
Sample security	<ul style="list-style-type: none"> • The measures taken to ensure sample security. 	<ul style="list-style-type: none"> • All logging and sampling is undertaken in a secured facility which is locked when unattended and video monitored at all times. • Samples are bagged in cable-tied plastic bags, and batched into polyweave sacks for transport. • ALS Laboratories personnel receive the samples at Alderan's facility in Milford Utah and perform appropriate chain of custody procedures onsite. ALS then transport the samples in their own trucks to the laboratory in Elko Nevada. • Sample pulps and coarse rejects are returned to site for storage.
Audits or reviews	<ul style="list-style-type: none"> • The results of any audits or reviews of sampling techniques and data. 	<ul style="list-style-type: none"> • No external audits have been undertaken. These would be part of future resource estimation work.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<ul style="list-style-type: none"> Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	<ul style="list-style-type: none"> The Frisco Prospect comprises 275 patented and 252 unpatented claims, which are governed by the Horn, Cactus and Northern Carbonate lease agreements entered into with the private landowner, Horn Silver Mines Inc. The Horn and Cactus lease agreements grant Alderan all rights to access the property and to explore for and mine minerals, subject to a retained royalty of 3% to the landholder. Alderan holds options to reduce the royalty to 1% and to purchase the 231 patented claims. The Northern Carbonate Lease grants Alderan with all rights to access the property and to explore for and mine minerals, subject to a retained royalty of 3% to the landholder. Alderan holds options to reduce the royalty to 1% and to purchase the 231 patented claims. Alderan was in full compliance with both lease agreements and all claims were in good standing at the time of reporting.
Exploration done by other parties	<ul style="list-style-type: none"> Acknowledgment and appraisal of exploration by other parties. 	<ul style="list-style-type: none"> A large amount of historical exploration has been carried out by numerous different parties dating back to the 1800's. Historical mining records including level plans and production records exist for the period between 1905 and 1915 when the vast majority of production occurred Historical drilling has been carried out by multiple parties including Anaconda Company, Rosario Exploration Company, Amax Exploration and Western Utah Copper Corporation/Palladon Ventures Data has been acquired, digitized where indicated, and interpreted by Alderan.
Geology	<ul style="list-style-type: none"> Deposit type, geological setting and style of mineralisation. 	<ul style="list-style-type: none"> Porphyry style mineralised district with several expressions of mineralisation at surface, such as breccia pipes, skarns, structurally-hosted mineralisation, and manto style mineralised zones, including outcropping porphyries. Part of the larger Laramide mineralising event. Overprinted by Basin and Range tectonics.

Criteria	JORC Code explanation	Commentary																																								
Drill hole Information	<ul style="list-style-type: none"> A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: <ul style="list-style-type: none"> easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	<table border="1"> <thead> <tr> <th>Hole ID</th> <th>Azimuth</th> <th>Dip</th> <th>Depth (m)</th> <th>Easting (wgs84 Zone 12S)</th> <th>Northing (wgs84 Zone 12S)</th> <th>Elevation</th> <th>Depth of Mineralisation (m)</th> </tr> </thead> <tbody> <tr> <td>ALCA006</td> <td>220</td> <td>-82</td> <td>128.36</td> <td>299991</td> <td>4262629</td> <td>1987</td> <td>NA</td> </tr> <tr> <td>ALCA007</td> <td>042</td> <td>-70</td> <td>396.5</td> <td>299959</td> <td>4262705</td> <td>1982</td> <td>NA</td> </tr> <tr> <td>ALCA008</td> <td>195</td> <td>-55</td> <td>297.6</td> <td>300104</td> <td>4262569</td> <td>1972</td> <td>35.5</td> </tr> <tr> <td>ALCA009</td> <td>175</td> <td>-70</td> <td>327.75</td> <td>299801</td> <td>4262697</td> <td>1930</td> <td>44</td> </tr> </tbody> </table>	Hole ID	Azimuth	Dip	Depth (m)	Easting (wgs84 Zone 12S)	Northing (wgs84 Zone 12S)	Elevation	Depth of Mineralisation (m)	ALCA006	220	-82	128.36	299991	4262629	1987	NA	ALCA007	042	-70	396.5	299959	4262705	1982	NA	ALCA008	195	-55	297.6	300104	4262569	1972	35.5	ALCA009	175	-70	327.75	299801	4262697	1930	44
Hole ID	Azimuth	Dip	Depth (m)	Easting (wgs84 Zone 12S)	Northing (wgs84 Zone 12S)	Elevation	Depth of Mineralisation (m)																																			
ALCA006	220	-82	128.36	299991	4262629	1987	NA																																			
ALCA007	042	-70	396.5	299959	4262705	1982	NA																																			
ALCA008	195	-55	297.6	300104	4262569	1972	35.5																																			
ALCA009	175	-70	327.75	299801	4262697	1930	44																																			
Data aggregation methods	<ul style="list-style-type: none"> In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	<ul style="list-style-type: none"> No cut off or top cut grades have been applied. Composites reported are calculated by length weighted average grades with internal high grades reported separately. No Metal Equivalent values are presented Where assay result is below detection limit of the assay method, a value is inserted which is less than half the detection limit. For example, $A_{ppm} < 0.005ppm$ is stored as $0.002ppm$. This has negligible effect on calculations as mineralized intercepts do not routinely contain below detection limit assays. 																																								
Relationship between mineralisation widths and intercept lengths	<ul style="list-style-type: none"> These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	<ul style="list-style-type: none"> Reported mineralisation is quoted in downhole depths. True width may be less than downhole intercept width (apparent width), and insufficient work has been completed to enable accurate calculation of true widths. 																																								
Diagrams	<ul style="list-style-type: none"> Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	<ul style="list-style-type: none"> See Figure 6 Section View 																																								
Balanced reporting	<ul style="list-style-type: none"> Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of 	<table border="1"> <thead> <tr> <th></th> <th>Low</th> <th>High</th> </tr> </thead> <tbody> <tr> <td>Cu %</td> <td>0.00015</td> <td>3.95</td> </tr> </tbody> </table>		Low	High	Cu %	0.00015	3.95																																		
	Low	High																																								
Cu %	0.00015	3.95																																								

Criteria	JORC Code explanation	Commentary						
	<i>Exploration Results.</i>	<table border="1"> <tr> <td>Au g/t</td> <td><0.005</td> <td>0.972</td> </tr> <tr> <td>Ag g/t</td> <td>0.01</td> <td>106</td> </tr> </table> <ul style="list-style-type: none"> Standard sampling interval is 1m. In cases of change in geologic character sample interval may be 0.3m>x>1.5m 	Au g/t	<0.005	0.972	Ag g/t	0.01	106
Au g/t	<0.005	0.972						
Ag g/t	0.01	106						
<i>Other substantive exploration data</i>	<ul style="list-style-type: none"> Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	<ul style="list-style-type: none"> Details of other exploration results are recorded in the Independent Geologist's Report, contained in the Prospectus and on the announcements dated 28 June 2017, 15 December 2017. 						
<i>Further work</i>	<ul style="list-style-type: none"> The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	<ul style="list-style-type: none"> Details of intended exploration activities are mentioned in the report above and in previous announcements made by the Company also recorded in the Independent Geologist's Report, contained in the Prospectus. 						

Section 3 Estimation and Reporting of Mineral Resources

(Criteria listed in section 1, and where relevant in section 2, also apply to this section.)

Criteria	JORC Code explanation	Commentary
<i>Database integrity</i>	<ul style="list-style-type: none"> Measures taken to ensure that data has not been corrupted by, for example, transcription or keying errors, between its initial collection and its use for Mineral Resource estimation purposes. Data validation procedures used. 	<ul style="list-style-type: none"> No Resource estimation has been undertaken

Section 4 Estimation and Reporting of Ore Reserves

(Criteria listed in section 1, and where relevant in sections 2 and 3, also apply to this section.)

Criteria	JORC Code explanation	Commentary
<i>Mineral Resource estimate for conversion to Ore Reserves</i>	<ul style="list-style-type: none"> • <i>Description of the Mineral Resource estimate used as a basis for the conversion to an Ore Reserve.</i> • <i>Clear statement as to whether the Mineral Resources are reported additional to, or inclusive of, the Ore Reserves.</i> 	<ul style="list-style-type: none"> • <i>No Reserve estimation has been undertaken</i>