

## Robust September Quarter advances Graphite Project

The September 2015 quarter has been the most robust and successful period to date in Australian-based Kibaran Resources Limited's (ASX:KNL) ('Kibaran' or the 'Company') well enunciated growth strategy to establish its wholly owned flagship graphite projects in Tanzania in East Africa, as the emerging and strategic hub for mainstream natural flake graphite exports into the key direct ship routes to Europe.


The quarter was particularly marked by major project achievements across a suite of feasibility studies, project financing negotiations, sales offtake agreements and technical improvements to outputs for our flagship and lead development project, the wholly owned Epanko Deposit.

Epanko has a JORC 2012 Indicated Mineral Resource Estimate of 12.8Mt at 10% TGC, for 1.28Mt of contained graphite.

Paralleling these positive milestones is increasing market recognition that Kibaran's planned conservative and staged build-up of production and processing capability provides realistic and achievable volume, price entry and project affordability (US\$77 million) into "existing" market demand.

This is in contrast to many of our peers whose current project economics are based on the well forecast and expected, but as yet, unrealised "new demand" from emerging technologies and customers. We would expect that any materialisation of this "new demand" will simply further enhance Kibaran's Tanzanian growth profile.

A detailed summary of the quarter's activities follows:

 <p>Project Locations</p>	<p><b>QUARTERLY HIGHLIGHTS:</b></p> <ul style="list-style-type: none"> <li>Mining and environmental licences secured for Epanko</li> <li>Positive Epanko Bankable Feasibility Study</li> <li>Off-take agreement signed with giant Germany industrial conglomerate, ThyssenKrupp</li> <li>Binding offtakes now cover 75% first production</li> <li>Epanko's graphite production capability lifted</li> <li>Subsequent production stages internally funded from Epanko cash flow</li> <li>Development funding negotiations underway with Germany's KfW IPEX-Bank</li> <li>Resource upgrade for 2<sup>nd</sup> Tanzanian graphite project - Merelani</li> <li>Battery manufacturing facility study undertaken</li> </ul>
--	---

## EPANKO GRAPHITE PROJECT – TANZANIA (100% KNL)

The Epanko Graphite Project (“Epanko”) is located 245km south-west of Morogoro in south-east Tanzania.

During the reporting period, Kibaran made significant progress on advancing the Epanko Graphite Project, achieving a number of key milestones to bring it closer to a decision to mine.

### BANKABLE FEASIBILITY STUDY

Following on from the receipt of the Environmental Impact Assessment Certificate in May from the Ministry of Energy and Minerals of Tanzania, Kibaran was notified during the latest quarter that the Mining Licence for Epanko had also been granted.

This coincided with the completion of the Epanko Bankable Feasibility Study (BFS), (refer announcement 5 August 2015). The study was completed on time, within budget and confirmed that Epanko is technically and financially viable with robust project economics.

The receipt of the environmental certificate and mining licence and completion of the BFS has enabled the Company to commence debt funding discussions with potential financiers and advance discussions with strategic partners in the European, Japanese and US graphite markets.

Key results from the BFS include:

- Conventional open cut mine with conventional flotation processing plant
- Annual concentrate production of 40,000tpa
- Annual EBITDA of US\$33.6m for 15 years
- NPV (pre-tax) of US\$197.4m
- Internal Rate of Return of 41.2%
- OPEX FOB Dar es Salaam US\$570/t
- Payback 2.7 years with 25 year mine life
- Project capital US\$77.5m
- Exceptional final average carbon concentrates of 96.3%
- Demonstrated metallurgical testwork indicated a very high proportion of large flake graphite with 85.7% of flake distribution greater than +106 microns

Work completed under the scope of the BFS was the confirmation a maiden Ore Reserve Estimate at Epanko sufficient to support a 25 year mine life.

### Ore Reserve Statement >5% TGC

JORC Classification	Tonnage (Mt)	TGC Grade (%)	Contained Graphite (t)
Proved	8.0	8.3	659,000
Probable	2.9	9.6	279,000
<b>TOTAL</b>	<b>10.9</b>	<b>8.6</b>	<b>938,000</b>

The Ore Reserve Estimate was based on and inclusive of the Measured and Indicated Mineral Resource which was upgraded during the previous quarter. The Measured and Indicated category now includes 62% of the JORC 2012 Resource Estimate.

**Mineral Resource Estimate for Epanko Deposit >8% TGC, June 2015**

JORC Classification	Tonnage (Mt)	TGC Grade (%)	Contained Graphite (t)
Measured	6.6	9.7	635,800
Indicated	7.9	10.0	785,300
Inferred	8.8	8.7	773,500
<b>TOTAL</b>	<b>23.3</b>	<b>9.4</b>	<b>2,194,600</b>

*Tonnage figures contained within tables have been rounded to nearest 100,000. % TGC grades are rounded to 1 decimal figure. Abbreviations used: Mt = 1,000,000 tonnes. Rounding errors may occur in tables.*

**OFF-TAKE AGREEMENT SECURED WITH THYSSENKRUPP**

The finalisation of the BFS augmented the views of ThyssenKrupp Metallurgical Products GmbH, part of the Materials Services business area of ThyssenKrupp group, a diversified industrial corporation based in Germany, resulting in the execution of an off-take agreement to acquire Kibaran’s natural flake graphite products.

The agreement provides sales for 20,000tpa from the Company’s Epanko Graphite Project. This will account for 50% of Kibaran’s planned 40,000tpa graphite production from Epanko. The exclusive long-term commercial agreement between Kibaran and ThyssenKrupp is for the sale of a minimum of 20,000tpa of refractory grade natural flake graphite and is for the term of 10 years with a 5 year option.

This off-take agreement together with an existing agreement secures 75% of planned graphite production at Epanko in binding off-take and binding sales agreements.

**GERMAN GOVERNMENT LOAN GUARANTEE**

The terms captured in the offtake agreement with ThyssenKrupp enlarged the volume of sales into Germany, supplementing those from the existing European offtake agreement, enabling the Company to be eligible for a Untied Loan Guarantee – *Garantie für Ungebundene Finanzkredite* (‘UFK’).

Kibaran has received “in-principle eligibility cover” for Epanko from the German Government for a UFK Guarantee. The UFK guarantee coverage is in the form of loan guarantees for loans awarded by lenders to the financing of eligible projects. It provides lenders insurance against commercial and political risk.

Kibaran’s Epanko Project has satisfied the initial requirements for eligible projects, being those that contribute to the supply of critical natural resources to Germany in the form of a long-term off-take contract between the borrower and a German off-taker, is economically viable and complies with international environmental and social standards (e.g. Equator Principles). The UFK cover is subject to further due diligence and final approval by the German Government.

**MANDATE LETTER SIGNED**

Kibaran has finalised (refer announcement 7 October 2015) an agreement with German Bank KfW IPEX-Bank (“KfW”) to provide advice and structuring support in relation to obtaining the UFK Guarantee. The UFK Guarantee could provide cover, de-risking up to US\$40 million of the initial senior debt for the development of Epanko.

The agreement also provides for KfW IPEX Bank contributing to this initial senior debt and assisting Kibaran with further debt financing arrangements in order to progress the development of Epanko.

**PRODUCTION TARGET LIFTED**

A study undertaken during the quarter confirmed that Kibaran’s Epanko and Merelani-Arusha graphite projects have the resource potential to increase production to produce a combined 150,000tpa of concentrate, subject to market demand, this is a 50% increase over initial estimates earlier this year of a headline rate of 100,00tpa and represents a 375% increase on initial planned production at Epanko.

The growth strategy was calculated in two stages over 6-7 years with production occurring from both Epanko and Merelani-Arusha. The following table shows the potential ramp up in output from Epanko and Merelani-Arusha under the updated production growth strategy, compared to initial estimates.

#### Staged Production Growth

	Concentrate (tpa)	Timeframe
<b>Initial Start-up</b>	40,000	
<b>Stage 1</b>	84,000	2-4 years
<b>Stage 2</b>	150,000	5-6 years

The update on the growth strategy was modelled utilising the anticipated future increases in global demand for premium quality large flake graphite encompassed in the “Roskill Natural & Synthetic Graphite: Market Outlook to 2020” report.

#### BATTERY MANUFACTURING FACILITY STUDY

The results of a Battery Grade Scoping Study were released during the quarter. The study highlighted robust economics and a compelling case for the development of a Manufacturing Facility to participate in downstream value added processing.

The manufacturing of the first battery grade Spherical Graphite would support expanded production from the Epanko Graphite Project. Current forecasts anticipate exponential growth in graphite demand over the next five years from the Electric Vehicle (EV) and Battery Storage industries.

The study was based on initial Stage 1 production of at 15,000tpa, increasing to 50,000tpa over 3 stages, producing spherical, expanded and other purified graphite products. Testwork conducted has confirmed that Epanko graphite is of superior quality and exceptionally well suited for the production of spherical graphite and other purified graphite products.

#### Key Study Results:

- NPV (pre-tax) of US\$115m
- IRR (pre-tax) of 51%
- Capital Expenditure of US\$35m
- Annual pre-tax cashflow of US\$18mpa based on Stage 1
- Payback period of 1.9 years

#### Manufacturing Facility Staged Growth

Stage	Spherical Graphite	Expandable Graphite	Purification	Total
1	6,000	5,000	4,000	<b>15,000</b>
2	15,000	10,000	5,000	<b>30,000</b>
3	24,000	18,000	8,000	<b>50,000</b>

*Note: Table 1 assumes production of natural graphite from the Epanko deposit is increased to meet this demand. Whilst the Feasibility Study for Epanko was based on 40,000tpa, the deposit has been modelled to produce up to 100,000tpa (ASX: announcement 22 January 2015).*

During the quarter, the Company presented its spherical graphite manufacturing facility concept to the Tanzanian Ministry of Industry and Trade. Following this presentation the Company has received a letter of support from the Permanent Secretary of the Ministry and stated that encouraging value add initiatives and developing the manufacturing sector is a high priority for the Government.

## MERELANI-ARUSHA GRAPHITE PROJECT – TANZANIA (100% KNL)

The Merelani-Arusha Project, located in Tanzania, provides the Company with a potential second source of graphite production to Epanko, from the Merelani East Deposit.

An upgrade of the Mineral Resource Estimate for the Merelani East Deposit was announced during the quarter (refer announcement 8 September 2015). The following table shows the estimate based on recent geological and metallurgical testwork.

### Mineral Resource Estimate for Merelani East Deposit, > 5% TGC

JORC Classification	Tonnage (Mt)	TGC Grade (%)	Contained Graphite (t)
Indicated	7.4	6.7	500,000
Inferred	10.3	6.3	650,000
<b>TOTAL</b>	<b>17.7</b>	<b>6.5</b>	<b>1,140,000</b>

*Notes for Table 1: Tonnage figures contained within Table 1 have been rounded to nearest 100,000. % TGC grades are rounded to 1 decimal figure. Abbreviations used: Mt = 1,000,000 tonnes.*

Recent completion of the Epanko Graphite Project Bankable Feasibility Study, coupled with the upgrade of the Merelani East resource and its metallurgical characteristics, will provide the foundation for a Pre-Feasibility Study ('PFS') on Merelani East.

The Company has commenced the Environmental and Social Impact Assessment (ESIA) process for its Merelani-Arusha Graphite Project by registering the Project with the National Environmental Management Council (NEMC), the first step in obtaining an Environmental Certificate and the key pre-requisite for a Mining Licence application. The environmental and social baseline study, receipt of the Environmental Certificate and subsequent Mining Licence, are all long lead time items in the approval and permitting process.

## SCHEDULE OF TENEMENTS

Mining Tenements Held, Acquired or Disposed of by Kibaran Resource Limited as at 30 September 2015.

Pursuant to ASX Listing Rule 5.3.3 Kibaran Resources Limited (ASX: KNL) (the “Company”) reports as follows in relation to mining tenements held at the end of each quarter and acquired or disposed of during the quarter and their location.

Ministry ID	Area (sq. km)	Project Location
<b>TanzGraphite (TZ) Ltd (100% Owned)</b>		
ML 548/2015	9.499	Mahenge
PL 7906/2012	130.49	Merelani-Arusha
PL 7907/2012	53.78	Merelani-Arusha
PL 7915/2012	92.28	Merelani-Arusha
PL 7918/2012	121.88	Merelani-Arusha
PL 9307/2013	2.80	Mahenge
PL 9344/2013	1.37	Mahenge
PL 10388/2014	2.57	Mahenge
PL 10389/2014	103.56	Mahenge
PL 10390/2014	2.81	Mahenge
PL 10392/2014	133.95	Mahenge
PL 10394/2014	9.74	Mahenge
PL 10396/2014	152.43	Mahenge
PL 10090/2014	44.88	Merelani-Arusha
PL 10091/2014	114.22	Merelani-Arusha
PL 10092/2014	23.23	Merelani-Arusha
PL 9537/2014	84.00	Tanga
<b>Castillian Resources (Tanzania) Ltd (100% Owned)</b>		
PL 4985/2008	30.71	Kagera
PL 5192/2008	23.93	Kagera
PL 5306/2008	44.65	Kagera
PL 8368/2012	157.62	Kagera

### Number disposed during the quarter:

There were no tenements disposed during the quarter.

### Number acquired during the quarter:

There were no tenements acquired during the quarter.



## ABOUT KIBARAN RESOURCES LIMITED

*Kibaran Resources Limited (ASX: KNL) ('Kibaran' or the 'Company') is a graphite focused resource company with world class graphite projects located in Tanzania.*

*The Company's primary focus is to develop its 100%-owned Epanko Graphite Project, located within the Mahenge Graphite Province. A Bankable Feasibility Study has been completed with a Proved & Probable Ore Reserve of 10.9Mt at 8.36%. Both Environmental and Mining Licence approvals are in place for Epanko. This initial estimate only covers 20% of the project area. Metallurgical testwork has found Epanko graphite to be large flake, expandable, ultra-high purity and premium quality from a global perspective.*

*Kibaran also has rights to the Merelani-Arusha Graphite Project, located in the north-east of Tanzania. Merelani-Arusha is also considered to be highly prospective for commercial graphite.*

*Graphite is regarded as a critical material for future global industrial growth, destined for industrial and technology applications including nuclear reactors, lithium-ion battery manufacturing and a raw material of graphene.*

*The Company is positioning itself to participate in the emerging 3D printing market using graphite inks via 3D Graphtech Industries PL, jointly owned with 333D Pty Ltd (formerly 3D Group) which is transacting as OZ Brewing (ASX:OZB).*

*In addition, Kibaran has the Kagera Nickel Project which remains underexplored and is located along strike of the Kabanga nickel deposit, owned by the Glencore – Barrick Gold Joint Venture, which is considered to be the largest undeveloped, high grade nickel sulphide deposit in the world. Kibaran is currently seeking a partner to progress exploration of its highly prospective nickel properties.*

## JORC CODE, 2012 EDITION – TABLE 1

### Section 1 Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
<b>Sampling techniques</b>	<ul style="list-style-type: none"> <li>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</li> <li>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</li> <li>Aspects of the determination of mineralisation that are Material to the Public Report.</li> <li>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</li> </ul>	<p>The Epanko deposit was sampled by reverse circulation (RC) holes, diamond core drilling and trenching.</p> <p>Sampling is guided by Kibaran's protocols and QA/QC procedures</p> <p>RC samples are collected by a riffle splitter using a face sampling hammer diameter approximately 140 mm.</p> <p>All samples were sent SGS laboratory in Johannesburg for preparation and LECO analyses. All samples are crushed using LM2 mill to -4 mm and pulverised to nominal 80% passing -75 µm.</p> <p>Diamond core (if competent) is cut using a core saw. Where the material is too soft it is left in the tray and a knife is used to quarter the core for sampling. Trenches were sampled at 0.5m intervals, these intervals were speared and submitted for analyses.</p>
<b>Drilling techniques</b>	<ul style="list-style-type: none"> <li>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</li> </ul>	<p>RC holes were drilled in a direction so as to hit the mineralisation orthogonally. Face sample hammers were used and all samples collected dry and riffle split after passing through the cyclone.</p> <p>Diamond drilling was drilled as triple Tubed HQ diameter core.</p>
<b>Drill sample recovery</b>	<ul style="list-style-type: none"> <li>Method of recording and assessing core and chip sample recoveries and results assessed.</li> <li>Measures taken to maximise sample recovery and ensure representative nature of the samples.</li> <li>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</li> </ul>	<p>The RC rig sampling systems are routinely cleaned to minimize the opportunity for contamination; drilling methods are focused on sample quality. Diamond drilling ( triple Tubed HQ diameter core) was used to maximise sample recovery when used.</p> <p>The selection of RC drilling company, having a water drilling background enables far greater control on any water present in the system, ensuring wet samples were kept to a minimum.</p> <p>No relationship exists between sample recovery and grade.</p>
<b>Logging</b>	<ul style="list-style-type: none"> <li>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</li> <li>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</li> <li>The total length and percentage of the relevant intersections logged.</li> </ul>	<p>Geological logging is completed for all holes and representative across the deposit. Logged data is both qualitative and quantitative depending on field being logged. All drill holes and all intervals were logged.</p>
<b>Sub-sampling techniques and sample preparation</b>	<ul style="list-style-type: none"> <li>If core, whether cut or sawn and whether quarter, half or all core taken.</li> <li>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</li> <li>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</li> <li>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</li> <li>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</li> <li>Whether sample sizes are appropriate to the grain size of the material being sampled.</li> </ul>	<p>All RC samples are split using a riffle splitter mounted under the cyclone, RC samples are drilled dry.</p> <p>A small fraction of samples returned to the surface wet. All samples were submitted for assay.</p> <p>Diamond core was cut on core saw and quarter core submitted for analyses. Sample preparation at the SGS laboratory involves the original sample being dried at 80° for up to 24 hours and weighed on submission to laboratory. Crushing to nominal -4 mm. Sample is split to less than 2 kg through linear splitter and excess retained. Sample splits are weighed at a frequency of 1/20 and entered into the job results file. Pulverising is completed using LM2 mill to 90% passing -75 µm. QAQC protocols were followed, including the use of field duplicate samples to test the primary sampling step for the RC drilling.</p> <p>Sample sizes are considered appropriate with regard to the grain size of the sampled material.</p> <p>Drill samples were sent to the SGS Laboratory at Mwanza (Tanzania) for sample preparation, with the pulps sent to SGS Johannesburg for assaying. The following methodology is used by SGS for Total Graphitic Carbon (TGC) analyses.</p>
<b>Quality of assay data and laboratory tests</b>	<ul style="list-style-type: none"> <li>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</li> <li>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</li> <li>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</li> </ul>	<p>Total carbon is measured using LECO technique. The sample is combusted in the oxygen atmosphere and the IR used to measure the amount of CO2 produced. The calibration of the LECO instrument is done by using certified reference materials.</p> <p>For the analysis of Graphitic Carbon, a 0.3g sample is weighed and roasted at 550oC to remove any organic carbon. The sample is then heated with diluted hydrochloric acid to remove carbonates. After cooling the sample is filtered and the residue rinsed and dried at 75oC prior to analysis by the LECO instrument. The analyses by LECO are done by total combustion of sample in the oxygen atmosphere and using IR absorption from the resulting CO2 produced.</p> <p>Laboratory certificates were sent via email from the assay laboratory to Kibaran. The assay data was provided to CSA in the form of Microsoft XL files and assay laboratory certificates. The files were imported into Datamine.</p> <p>Standards are inserted at approximately a 10% frequency rate. In addition, field duplicates, laboratory duplicates are collectively inserted at a rate of 10% QAQC data analysis has been completed to industry standards.</p>
<b>Verification of sampling and assaying</b>	<ul style="list-style-type: none"> <li>The verification of significant intersections by either independent or alternative company personnel.</li> <li>The use of twinned holes.</li> <li>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</li> <li>Discuss any adjustment to assay data.</li> </ul>	<p>Senior Kibaran geological personnel supervised the sampling, and alternative personnel verified the sampling locations. Two RC holes were twinned with diamond drill holes.</p> <p>Primary data are captured on paper in the field and then re-entered into spreadsheet format by the supervising geologist, to then be loaded into the company's database. No adjustments are made to any assay data.</p>
<b>Location of data points</b>	<ul style="list-style-type: none"> <li>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</li> <li>Specification of the grid system used.</li> <li>Quality and adequacy of topographic control.</li> </ul>	<p>Sample locations picked up by hand held GPS.</p> <p>UTM Zone 37 South was the grid system used.</p> <p>No coordinate transformation was applied to the data.</p> <p>Downhole surveys collected by multi-shot camera.</p>



Criteria	JORC Code explanation	Commentary
<b>Data spacing and distribution</b>	<ul style="list-style-type: none"> <li>Data spacing for reporting of Exploration Results.</li> <li>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</li> <li>Whether sample compositing has been applied.</li> </ul>	<p>Topographic DTM was from a LIDAR survey flown in 2015.</p> <p>Spacings are sufficient for estimation and reporting of a Mineral Resource. Drill hole locations are at a nominal 50 m (Y) by 25 m (X) spacing. Data spacing and distribution are sufficient to establish the degree of geological and grade continuity. No compositing has been applied to exploration data.</p>
<b>Orientation of data in relation to geological structure</b>	<ul style="list-style-type: none"> <li>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</li> <li>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</li> </ul>	<p>Most holes have been orientated towards an azimuth so as to be able intersect the graphitic mineralisation in a perpendicular manner. Drill pad accessibility has required an adjustment to drill hole orientation to a few holes. RC holes were drilled at variable dips to define the geology and contacts of the deposit. Some holes were drilled vertical to test geological contact positions.</p>
<b>Sample security</b>	<ul style="list-style-type: none"> <li>The measures taken to ensure sample security.</li> </ul>	<p>Samples were stored at the company's secure field camp prior to dispatch to the prep lab by contacted transport company, who maintained security of the samples.</p>
<b>Audits or reviews</b>	<ul style="list-style-type: none"> <li>The results of any audits or reviews of sampling techniques and data.</li> </ul>	<p>Sampling procedures were independently reviewed by CSA Global as part of the preparation of the Mineral Resource estimate. Kibaran senior geological personnel reviewed sampling procedures on a regular basis.</p> <p>All drill hole results were collated and stored within a Datashed database. A random selection of assays from the database was cross referenced against the laboratory certificates.</p>

## Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
<b>Mineral tenement and land tenure status</b>	<ul style="list-style-type: none"> <li>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</li> <li>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</li> </ul>	<p>The tenements are 100% owned by Kibaran wholly owned subsidiary and are within granted and live prospecting licenses. The Mahenge project consists of PL 8204/2012.</p>
<b>Exploration done by other parties</b>	<ul style="list-style-type: none"> <li>Acknowledgment and appraisal of exploration by other parties.</li> </ul>	<p>Historical reports exist for the project area as the region was first recognised for graphite potential in 1914 and 1959. No recent information exists.</p>
<b>Geology</b>	<ul style="list-style-type: none"> <li>Deposit type, geological setting and style of mineralisation.</li> </ul>	<p>The Mahenge Project is hosted within a quartz–feldspar-carbonate graphitic schist, part of a Neoproterozoic metasediment package, including marble and gneissic units. Two zones of graphitic schist have been mapped, named the East Zone and the West Zone.</p>
<b>Drill hole information</b>	<ul style="list-style-type: none"> <li>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: <ul style="list-style-type: none"> <li>eastings and northing of the drill hole collar</li> <li>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</li> <li>dip and azimuth of the hole</li> <li>down hole length and interception depth</li> <li>hole length.</li> </ul> </li> <li>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</li> </ul>	<p>Sample and drill hole coordinates are provided in market announcements dated 14th July and 21st July 2014.</p>
<b>Data aggregation methods</b>	<ul style="list-style-type: none"> <li>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</li> <li>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</li> <li>The assumptions used for any reporting of metal equivalent values should be clearly stated.</li> </ul>	<p>No high-grade cuts were necessary. Aggregating was made for intervals that reported over 1% TGC (Total graphitic carbon). The purpose of this is to report intervals that may be significant to future metallurgical work. There is no implication about economic significance. Intervals reporting above 8% TGC are intended to highlight a significant higher grade component of graphite, there is no implication of economic significance. No equivalents were used.</p>
<b>Relationship between mineralisation widths and intercept lengths</b>	<ul style="list-style-type: none"> <li>These relationships are particularly important in the reporting of Exploration Results.</li> <li>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</li> <li>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</li> </ul>	<p>All RC holes have been orientated towards an azimuth so as to be able intersect the graphitic mineralisation orthogonally. Given dip variations are mapped down hole length are reported, true width not known from the exploration results.</p>
<b>Diagrams</b>	<ul style="list-style-type: none"> <li>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</li> </ul>	<p>See main body of report.</p>
<b>Balanced reporting</b>	<ul style="list-style-type: none"> <li>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</li> </ul>	<p>Results are presented previous announcements, such as 21st July 2014.</p>
<b>Other substantive exploration data</b>	<ul style="list-style-type: none"> <li>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk</li> </ul>	<p>Field mapping was conducted early in the geological assessment of the license area to define the geological boundaries of the graphitic schist with other geological formations. Geological mapping of trenches cut across the strike of the host</p>

Criteria	JORC Code explanation	Commentary
	<p><i>samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i></p>	<p>geological units provided important information used to compile the Mineral Resource estimate.</p> <p>Details of metallurgical testwork are detailed in the body of this report, and in Section 3 of this Table.</p>
<b>Further work</b>	<ul style="list-style-type: none"> <li><i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i></li> <li><i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i></li> </ul>	<p>No further drilling is planned at present although geological fieldwork including further mapping will continue during the next field season.</p> <p>Diagrams are presented in the ASX announcement dated 21 July 2014.</p>

### Section 3 Estimation and Reporting of Mineral Resources

Criteria	JORC Code explanation	Commentary
<b>Database integrity</b>	<ul style="list-style-type: none"> <li><i>Measures taken to ensure that data has not been corrupted by, for example, transcription or keying errors, between its initial collection and its use for Mineral Resource estimation purposes.</i></li> <li><i>Data validation procedures used.</i></li> </ul>	<p>Data used in the Mineral Resource estimate is sourced from a data base dump. Relevant tables from the data base are exported to MS Excel format and converted to csv format for import into CAE Studio 3 (Datamine) software for use in the Mineral Resource estimate.</p> <p>Validation of the data import include checks for overlapping intervals, missing survey data, missing assay data, missing lithological data, and missing collars. Every 10<sup>th</sup> assay value was cross checked against the laboratory certificates.</p>
<b>Site visits</b>	<ul style="list-style-type: none"> <li><i>Comment on any site visits undertaken by the Competent Person and the outcome of those visits.</i></li> <li><i>If no site visits have been undertaken indicate why this is the case.</i></li> </ul>	<p>The Competent Person (Mineral Resources) visited site in March 2014. The RC drilling rig was in operation and the CP was able to review drilling and sampling procedures. Outcrop showing mineralisation was examined and geologically assessed. Planned drill sites were examined and assessed with respect to strike and dip of the interpreted geological model.</p> <p>Trenches were examined and a re-enactment of sampling procedures was presented by the Kibaran geological staff. Sample storage facilities were inspected. There were no negative outcomes from any of the above items, and all samples and geological data were deemed fit for purpose, and could be included in the Mineral Resource estimate.</p>
<b>Geological interpretation</b>	<ul style="list-style-type: none"> <li><i>Confidence in (or conversely, the uncertainty of ) the geological interpretation of the mineral deposit.</i></li> <li><i>Nature of the data used and of any assumptions made.</i></li> <li><i>The effect, if any, of alternative interpretations on Mineral Resource estimation.</i></li> <li><i>The use of geology in guiding and controlling Mineral Resource estimation.</i></li> <li><i>The factors affecting continuity both of grade and geology.</i></li> </ul>	<p>There is a high level of confidence in the geological interpretation within the Measured and Indicated resource areas, based upon lithological logging of diamond drill core, and RC chips. Trenches cut orthogonal to the strike of the geology demonstrated the geometry of the deposit, and clearly showed graphitic mineralisation. Deposit scale geological mapping provide a geological framework for the interpretation.</p> <p>Drill hole intercept logging and assay results (RC and diamond core), structural interpretations from drill core and geological logs of trenches have formed the basis for the geological interpretation. Assumptions were made on depth and strike extension of the graphitic schists, using drill hole and trench sample assays as anchor points at depth and at intervals along strike. Geological mapping also support the geological assumptions built into the Mineral Resource.</p> <p>No alternative interpretations were considered because the exposed geology in outcrop support the current interpretation.</p> <p>Graphitic mineralisation is hosted within a graphitic schist, which is mapped along it's strike continuity within the license area. Grade (total graphitic carbon, TGC) is assumed to be likewise continuous with the host rock unit. Metallurgical characteristics, principally flake size, has been observed to be of a consistent nature when observed in outcrop, trench exposure and diamond drill core at numerous locations within the license area.</p> <p>The interpretation of the mineralisation domains is based upon a pre-determined lower cut-off grade for TGC. A variation to the cut-off grade will affect the volume and average grade of the domains.</p>
<b>Dimensions</b>	<ul style="list-style-type: none"> <li><i>The extent and variability of the Mineral Resource expressed as length (along strike or otherwise), plan width, and depth below surface to the upper and lower limits of the Mineral Resource.</i></li> </ul>	<p>The Epanko Mineral Resource estimate is approximately 1,750 m in strike, 290 m in plan width and reaches 350 m depth below surface.</p>
<b>Estimation and modelling techniques</b>	<ul style="list-style-type: none"> <li><i>The nature and appropriateness of the estimation technique(s) applied and key assumptions, including treatment of extreme grade values, domaining, interpolation parameters and maximum distance of extrapolation from data points. If a computer assisted estimation method was chosen include a description of computer software and parameters used.</i></li> <li><i>The availability of check estimates, previous estimates and/or mine production records and whether the Mineral Resource estimate takes appropriate account of such data.</i></li> <li><i>The assumptions made regarding recovery of by-products.</i></li> <li><i>Estimation of deleterious elements or other non-grade variables of economic significance (eg sulphur for acid mine drainage characterisation).</i></li> <li><i>In the case of block model interpolation, the block size in relation to the average sample spacing and the search employed.</i></li> <li><i>Any assumptions behind modelling of selective mining units.</i></li> <li><i>Any assumptions about correlation between variables.</i></li> <li><i>Description of how the geological interpretation was used to control the resource estimates.</i></li> </ul>	<p>Datamine Studio 3 software was used for all geological modelling, block modelling, grade interpolation, MRE classification and reporting. GeoAccess Professional and Snowden Supervisor were used for geostatistical analyses of data. The TGC interpretations were based upon a lower cut-off of 5% TGC and geological interpretations of mineralised outcrop and trenches, and logging of diamond drill core and RC chips. The Mineral Resource model consists of 13 zones of TGC mineralisation, with 11 zones in the Western Lode and 2 zones in the Eastern lode. Mineralisation domains were encapsulated by means of 3D wireframed envelopes. Domains were extrapolated along strike or down plunge to half a section spacing or if a barren hole cut the plunge extension before this limit. Top cuts were not used to constrain extreme grade values because the TGC grade distribution did not warrant their use. All samples were composited to 1m intervals, following a review of sample length distribution that most sample lengths were 1m. All drill hole data (RC and Diamond) and trench assays were utilised in the grade interpolation. A Quality Assurance study of the RC drilling coupled with a 3 hole due diligence and twin drilling programme confirmed the RC drill holes could be used with the diamond core samples as part of the grade interpolation. A statistical study of the trench assay data similarly demonstrated a similar population to the conventional drilling sample assay results.</p> <p>A block model with parent cell sizes 25m x 25m x 25m was constructed, compared</p>

Criteria	JORC Code explanation	Commentary
	<ul style="list-style-type: none"> <li>Discussion of basis for using or not using grade cutting or capping.</li> <li>The process of validation, the checking process used, the comparison of model data to drill hole data, and use of reconciliation data if available.</li> </ul>	<p>to typical drill spacing of 50m x 25m.</p> <p>Grade estimation was by Ordinary Kriging (OK) with Inverse Distance Squared (IDS) estimation was concurrently run as a check estimate. A minimum of 4 and maximum of 16 composited samples were used in any one block estimate for the Eastern Zone, and 6 – 25 samples for the Eastern Zone. A maximum of 5 composited samples per drill hole were used in any one block estimate. Cell Discretisation of 5 x 5 was used. Grade interpolation was run within the individual mineralisation domains, acting as hard boundaries.</p> <p>The current Mineral Resource was checked against the previously reported Mineral Resource (July 2014) and showed an increase in global tonnage with a slight decrease in TGC % grade. This is due to a refined topographic DTM which has resulted in tonnage changes where the resource model cuts the surface.</p> <p>No depletion of the Mineral Resource due to mining activity was required due to no mining having occurred historically. The Mineral Resource was projected to and truncated at the northern boundary of the license area.</p> <p>No by products were modelled.</p> <p>No selective mining units were assumed in this model.</p> <p>The grade model was validated by 1) creating slices of the model and comparing to drill holes on the same slice; 2) swath plots comparing average block grades with average sample grades on nominated easting, northing and RL slices; and 3) mean grades per domain for estimated blocks and flagged drill hole samples. No reconciliation data exists to test the model.</p>
<b>Moisture</b>	<ul style="list-style-type: none"> <li>Whether the tonnages are estimated on a dry basis or with natural moisture, and the method of determination of the moisture content.</li> </ul>	Tonnages are estimated on a dry basis.
<b>Cut-off parameters</b>	<ul style="list-style-type: none"> <li>The basis of the adopted cut-off grade(s) or quality parameters applied.</li> </ul>	A reporting cut-off grade of 8% TGC was previously used to report the Mineral Resource, and is in line with other reported Mineral Resources in East Africa, and recent economic modelling.
<b>Mining factors or assumptions</b>	<ul style="list-style-type: none"> <li>Assumptions made regarding possible mining methods, minimum mining dimensions and internal (or, if applicable, external) mining dilution. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential mining methods, but the assumptions made regarding mining methods and parameters when estimating Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the mining assumptions made.</li> </ul>	<p>It is assumed the deposit, if mined, will be developed using open pit mining methods. No assumptions have been made to date regarding minimum mining widths or dilution.</p> <p>The largest mineralisation domains in plan view have an apparent width of over 80m which may result in less selective mining methods, as opposed to (for example) mining equipment that would need to be used to mine narrow veins in a gold mine.</p>
<b>Metallurgical factors or assumptions</b>	<ul style="list-style-type: none"> <li>The basis for assumptions or predictions regarding metallurgical amenability. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider potential metallurgical methods, but the assumptions regarding metallurgical treatment processes and parameters made when reporting Mineral Resources may not always be rigorous. Where this is the case, this should be reported with an explanation of the basis of the metallurgical assumptions made.</li> </ul>	<p>Flotation achieved greater than 96% recovery of graphitic carbon, with concentrate grading 93% fixed carbon. Flotation yielded large flake graphite (detailed results in Table 2):</p> <ul style="list-style-type: none"> <li>- 73.8% measured greater than 106 microns (<math>\mu\text{m}</math>)</li> <li>- 21.6% measured in the +300 micron (<math>\mu\text{m}</math>) fraction</li> </ul> <p>The recovered flake graphite is clean, with no visible natural mineral impurities. The graphite concentrate is amenable to standard metallurgical recovery processes. The recovered product is considered marketable, with a binding offtake and partnership agreement with a major European graphite trader announced on 23rd December 2013.</p> <p>As announced on 7th July 2014, metallurgical testwork has yielded results exceeding 99.9% carbon from a simple one step process after flotation, with extremely low levels of impurities also reported.</p> <p>Metallurgical testwork completed on composited samples from 7 diamond drill holes (drilled in 2014) provided further data related to flake distribution and product purity. This is discussed in the body of this announcement.</p>
<b>Environmental factors or assumptions</b>	<ul style="list-style-type: none"> <li>Assumptions made regarding possible waste and process residue disposal options. It is always necessary as part of the process of determining reasonable prospects for eventual economic extraction to consider the potential environmental impacts of the mining and processing operation. While at this stage the determination of potential environmental impacts, particularly for a greenfields project, may not always be well advanced, the status of early consideration of these potential environmental impacts should be reported. Where these aspects have not been considered this should be reported with an explanation of the environmental assumptions made.</li> </ul>	The Environmental and Social Impact Assessment (ESIA) certificate, required for the Mining Licence application has been received
<b>Bulk density</b>	<ul style="list-style-type: none"> <li>Whether assumed or determined. If assumed, the basis for the assumptions. If determined, the method used, whether wet or dry, the frequency of the measurements, the nature, size and representativeness of the samples.</li> <li>The bulk density for bulk material must have been measured by methods that adequately account for void spaces (vugs, porosity, etc), moisture and differences between rock and alteration zones within the deposit.</li> <li>Discuss assumptions for bulk density estimates used in the evaluation process of the different materials.</li> </ul>	Density values based upon weathering profile and location (Eastern or Western Zone) were applied to the Mineral Resource, and were based upon density measurements from samples sourced from several of the diamond drill holes. Density values of 1.86, 2.23 and 2.80 t/m <sup>3</sup> were applied to the oxide, transitional and fresh weathering domains respectively for the Mineral Resource located in the Western Zone. Density values of 1.61, 2.23 and 2.80 t/m <sup>3</sup> were applied to the Eastern Zone.
<b>Classification</b>	<ul style="list-style-type: none"> <li>The basis for the classification of the Mineral Resources into varying confidence categories.</li> <li>Whether appropriate account has been taken of all relevant factors (ie relative confidence in tonnage/grade estimations, reliability of input data, confidence in continuity of geology and metal values, quality, quantity and distribution of the data).</li> </ul>	<p>Classification of the Mineral Resource estimates was carried out taking into account the geological understanding of the deposit, QAQC of the samples, density data and drill hole spacing. Metallurgical results related to flake size and sample purity, as well as marketing agreements in place supported the classification, as per Clause 49 (JORC 2012).</p> <p>The Mineral Resource is classified as Measured, Indicated and Inferred, with</p>

Criteria	JORC Code explanation	Commentary
	<ul style="list-style-type: none"> <li>Whether the result appropriately reflects the Competent Person's view of the deposit.</li> </ul>	<p>geological evidence sufficient to confirm geological and grade (and quality) continuity (for Measured) between points of observation where data and samples are gathered. The Inferred classification level was applied to the volumes where geological evidence is sufficient to imply but not verify geological, grade and quality continuity.</p> <p>All available data was assessed and the competent person's relative confidence in the data was used to assist in the classification of the Mineral Resource.</p> <p>The current classification assignment appropriately reflects the Competent Person's view of the deposit.</p>
<b>Audits or reviews</b>	<ul style="list-style-type: none"> <li>The results of any audits or reviews of Mineral Resource estimates.</li> </ul>	<p>No audits or reviews of the current Mineral Resource estimate have been undertaken, apart from internal reviews carried out by Kibaran technical staff.</p>
<b>Discussion of relative accuracy/ confidence</b>	<ul style="list-style-type: none"> <li>Where appropriate a statement of the relative accuracy and confidence level in the Mineral Resource estimate using an approach or procedure deemed appropriate by the Competent Person. For example, the application of statistical or geostatistical procedures to quantify the relative accuracy of the resource within stated confidence limits, or, if such an approach is not deemed appropriate, a qualitative discussion of the factors that could affect the relative accuracy and confidence of the estimate.</li> <li>The statement should specify whether it relates to global or local estimates, and, if local, state the relevant tonnages, which should be relevant to technical and economic evaluation. Documentation should include assumptions made and the procedures used.</li> <li>These statements of relative accuracy and confidence of the estimate should be compared with production data, where available.</li> </ul>	<p>An inverse distance estimation algorithm was used in parallel with the ordinary Kriged interpolation, with results very similar to the Kriged results.</p> <p>No other estimation method or geostatistical analysis has been performed.</p> <p>The Mineral Resource is a local estimate, whereby the drill hole data was geologically dominated above nominated TGC cut-off grades, resulting in fewer drill hole samples to interpolate the block model than the complete drill hole dataset, which would comprise a global estimate.</p> <p>Relevant tonnages and grade above nominated cut-off grades for TGC are provided in the introduction and body of this report. Tonnages were calculated by filtering all blocks above the cut-off grade and sub-setting the resultant data into bins by mineralisation domain. The volumes of all the collated blocks were multiplied by the dry density value to derive the tonnages. The graphite metal values (g) for each block were calculated by multiplying the TGC grades (%) by the block tonnage. The total sum of all metal for the deposit for the filtered blocks was divided by 100 to derive the reportable tonnages of graphite metal.</p> <p>No production data is available to reconcile results with.</p>

## Section 4 Estimating and Reporting of Ore Reserve

Criteria	JORC Code explanation	Commentary
<b>Mineral Resource estimate for conversion to Ore Reserves</b>	<ul style="list-style-type: none"> <li>Description of the Mineral Resource estimate used as a basis for the conversion to an Ore Reserve.</li> <li>Clear statement as to whether the Mineral Resources are reported additional to, or inclusive of, the Ore Reserves.</li> </ul>	<p>The Mineral Resource model for the Epanko deposits have been developed by David Williams of CSA Global and Associates and the Ore Reserve is based on this model.</p> <p>The stated Mineral Resource is inclusive of the Ore Reserve.</p>
<b>Site visits</b>	<ul style="list-style-type: none"> <li>Comment on any site visits undertaken by the Competent Person and the outcome of those visits.</li> <li>If no site visits have been undertaken indicate why this is the case.</li> </ul>	<p>A site visit was not undertaken by the Competent Person as a site visit would not materially affect the determination of the Reserve</p>
<b>Study status</b>	<ul style="list-style-type: none"> <li>The type and level of study undertaken to enable Mineral Resources to be converted to Ore Reserves.</li> <li>The Code requires that a study to at least Pre-Feasibility Study level has been undertaken to convert Mineral Resources to Ore Reserves. Such studies will have been carried out and will have determined a mine plan that is technically achievable and economically viable, and that material Modifying Factors have been considered.</li> </ul>	<p>Studies undertaken and the modifying factors applied to enable the Mineral Resource to be converted to an Ore Reserve are based on a Feasibility level estimation of costs and parameters.</p>
<b>Cut-off parameters</b>	<ul style="list-style-type: none"> <li>The basis of the cut-off grade(s) or quality parameters applied.</li> </ul>	<p>The cut-off grade applied is based on the profitability of the resource block after modifying factors and the metallurgical and mass recovery are applied to the in situ TGC grade. Processing costs were changed from Year 3 onwards to reflect lower power costs due to the connection to grid power. The cut-off grade for Yrs 1 &amp; 2 is 4.8% TGC and 4.3% for Yr 3 onwards. However a higher grade of 8% TGC has been used to ensure the concentrate production target of 40kt per year is met with a ROM throughput limit of 440kt per year.</p>
<b>Mining factors or assumptions</b>	<ul style="list-style-type: none"> <li>The method and assumptions used as reported in the Pre-Feasibility or Feasibility Study to convert the Mineral Resource to an Ore Reserve (i.e. either by application of appropriate factors by optimisation or by preliminary or detailed design).</li> <li>The choice, nature and appropriateness of the selected mining method(s) and other mining parameters including associated design issues such as pre-strip, access, etc.</li> <li>The assumptions made regarding geotechnical parameters (eg pit slopes, stope sizes, etc), grade control and pre-production drilling.</li> <li>The major assumptions made and Mineral Resource model used for pit and stope optimisation (if appropriate).</li> <li>The mining dilution factors used.</li> <li>The mining recovery factors used.</li> <li>Any minimum mining widths used.</li> <li>The manner in which Inferred Mineral Resources are utilised in mining studies and the sensitivity of the outcome to their inclusion.</li> <li>The infrastructure requirements of the selected mining methods.</li> </ul>	<p>Mining dilution is 3.0% extra tonnes with a dilutant grade of 3% TGC.</p> <p>Ore loss applied is 3.0%.</p> <p>Geotechnical parameters applied to the designs are based on preliminary investigations by Chris Orr and Associates. There will be a requirement for further geotechnical investigations to cover the extent of the walls within the current staged designs.</p> <p>Minimum mining widths have been considered in the staged designs.</p> <p>The Ore Reserve has been determined contained by a LOM pit design.</p> <p>The resource has been estimated into 5m x 5m wide x 5m vertical blocks and is representative of the mining method to be utilised.</p> <p>The optimisation was undertaken using only Measured and Indicated resource categories.</p> <p>Infrastructure consisting of the main haulage roads to access the top of the western ridge and also the start of the eastern mining area have been preliminarily designed. As equipment is mobile other infrastructure is not detrimental in determining the Reserve.</p> <p>The Inferred resource has not been reported in the Ore Reserve.</p>
<b>Metallurgical factors or assumptions</b>	<ul style="list-style-type: none"> <li>The metallurgical process proposed and the appropriateness of that process to the style of mineralisation.</li> <li>Whether the metallurgical process is well-tested technology or novel in nature.</li> <li>The nature, amount and representativeness of metallurgical test work undertaken, the nature of the metallurgical</li> </ul>	<p>Processing will consist of a grinding, flotation and concentrator to produce a high quality product. The process is a proven method for the extraction of the graphene to a concentrate.</p> <p>Metallurgical factors applied are 93.36% for TGC metallurgical recovery with a final concentrate grade of 96.3%.</p>



Criteria	JORC Code explanation	Commentary
	<p>domaining applied and the corresponding metallurgical recovery factors applied.</p> <ul style="list-style-type: none"> <li>Any assumptions or allowances made for deleterious elements.</li> <li>The existence of any bulk sample or pilot scale test work and the degree to which such samples are considered representative of the orebody as a whole.</li> <li>For minerals that are defined by a specification, has the ore reserve estimation been based on the appropriate mineralogy to meet the specifications?</li> </ul>	<p>Met recoveries are based on test work by the study</p> <p>Bulk sample test work and the location of that sample has been reported</p>
<b>Environmental</b>	<ul style="list-style-type: none"> <li>The status of studies of potential environmental impacts of the mining and processing operation. Details of waste rock characterisation and the consideration of potential sites, status of design options considered and, where applicable, the status of approvals for process residue storage and waste dumps should be reported.</li> </ul>	<p>Environmental certificate has been received</p> <p>Waste rock characterisation studies assessed the waste rock is chemically inert.</p> <p>There are two locations where waste rock will be stored. In the western area at the exit from the mining area in the valley floor and in the eastern area the waste dump will be integrated into the TSF.</p> <p>Overall finished slopes of 15 degrees have been used and will be rehabilitated progressively.</p> <p>No fatal flaws with regards the environment have been identified.</p>
<b>Infrastructure</b>	<ul style="list-style-type: none"> <li>The existence of appropriate infrastructure: availability of land for plant development, power, water, transportation (particularly for bulk commodities), labour, accommodation; or the ease with which the infrastructure can be provided, or accessed.</li> </ul>	<p>Land acquisition, purchase and rental agreements for the areas affected by mining and siting of process plant and infrastructure are currently being finalised through the RAP process</p> <p>The concentrate will be transported by a public road before connecting to the main road network at Mahenge</p> <p>Labour and accommodation for the majority of the workforce will be available in the major regional centre of Mahenge. The camp is being built on site for senior staff.</p>
<b>Costs</b>	<ul style="list-style-type: none"> <li>The derivation of, or assumptions made, regarding projected capital costs in the study.</li> <li>The methodology used to estimate operating costs.</li> <li>Allowances made for the content of deleterious elements.</li> <li>The source of exchange rates used in the study.</li> <li>Derivation of transportation charges.</li> <li>The basis for forecasting or source of treatment and refining charges, penalties for failure to meet specification, etc.</li> <li>The allowances made for royalties payable, both Government and private.</li> </ul>	<p>Mining and blasting costs are based on preliminary haulage parameters and monthly total movement targets that were formulated by Ausdrill. The mining costs will need to further refined to accommodate variable haulage distances to the ROM and waste dump locations from the LOM stages.</p> <p>Other costs for mine administration and ancillary costs have been determined by Kibaran.</p> <p>Processing costs include allowances for crushing, beneficiation, processing, administration and transport. These costs have been costed by GRES.</p> <p>Deleterious elements are not a factor.</p> <p>The exchange rate is based on \$US1 = 1,818 TZS.</p> <p>Quotes for transport have been used.</p> <p>Royalties have been included as government takes 3% value of saleable concentrate.</p>
<b>Revenue factors</b>	<ul style="list-style-type: none"> <li>The derivation of, or assumptions made regarding revenue factors including head grade, metal or commodity price(s) exchange rates, transportation and treatment charges, penalties, net smelter returns, etc.</li> <li>The derivation of assumptions made of metal or commodity price(s), for the principal metals, minerals and co-products.</li> </ul>	<p>The concentrate price of US\$1,420/t is based on a basket price as determined by the percentage of size fractions and carbon content.</p>
<b>Market assessment</b>	<ul style="list-style-type: none"> <li>The demand, supply and stock situation for the particular commodity, consumption trends and factors likely to affect supply and demand into the future.</li> <li>A customer and competitor analysis along with the identification of likely market windows for the product.</li> <li>Price and volume forecasts and the basis for these forecasts.</li> <li>For industrial minerals the customer specification, testing and acceptance requirements prior to a supply contract.</li> </ul>	<p>The Study was supported by 2 offtake and sales agreements.</p> <p>Pricing for graphite is determined by flake size and carbon content.</p> <p>Pricing model has been included in the study</p>
<b>Economic</b>	<ul style="list-style-type: none"> <li>The inputs to the economic analysis to produce the net present value (NPV) in the study, the source and confidence of these economic inputs including estimated inflation, discount rate, etc.</li> <li>NPV ranges and sensitivity to variations in the significant assumptions and inputs.</li> </ul>	<p>The optimisation NPV has been calculated using a discount rate of 8%. Inflation has not been included in the optimisation.</p> <p>Kibaran will use the Reserve output and LOM schedule for further financial modelling.</p> <p>Sensitivities of +/- 10% were assessed.</p>
<b>Social</b>	<ul style="list-style-type: none"> <li>The status of agreements with key stakeholders and matters leading to social licence to operate.</li> </ul>	<p>Kibaran has engaged in local stakeholder negotiation and was covered as part of the the ESIA certificate the company received.</p>
<b>Other</b>	<ul style="list-style-type: none"> <li>To the extent relevant, the impact of the following on the project and/or on the estimation and classification of the Ore Reserves: <ul style="list-style-type: none"> <li>Any identified material naturally occurring risks.</li> <li>The status of material legal agreements and marketing arrangements.</li> <li>The status of governmental agreements and approvals critical to the viability of the project, such as mineral tenement status, and government and statutory approvals.</li> </ul> </li> </ul> <p>There must be reasonable grounds to expect that all necessary Government approvals will be received within the timeframes anticipated in the Pre-Feasibility or Feasibility study. Highlight and discuss the materiality of any unresolved matter that is dependent on a third party on which extraction of the reserve is contingent.</p>	<p>No natural occurring risks have been identified that will affect the project operation.</p> <p>A mining licence over the mine area has been granted.</p>
<b>Classification</b>	<ul style="list-style-type: none"> <li>The basis for the classification of the Ore Reserves into varying confidence categories.</li> <li>Whether the result appropriately reflects the Competent Person's view of the deposit.</li> </ul>	<p>Measured and Indicated Resource within the LOM designs have all been converted respectively to a Proved and Probable Ore Reserve.</p> <p>The result appropriately reflects the Competent Person's view of the deposit.</p>

Criteria	JORC Code explanation	Commentary
	<ul style="list-style-type: none"> <li>The proportion of Probable Ore Reserves that have been derived from Measured Mineral Resources (if any).</li> </ul>	No Probable ore reserve has been derived from a Measured Mineral Resource.
<b>Audits or reviews</b>	<ul style="list-style-type: none"> <li>The results of any audits or reviews of Ore Reserve estimates.</li> </ul>	The reserve estimate has been reviewed internally by CSA Global and Kibaran personnel and is considered to appropriately reflect the results of the application of the modifying factors to the Mineral Resource.
<b>Discussion of relative accuracy/confidence</b>	<ul style="list-style-type: none"> <li>Where appropriate a statement of the relative accuracy and confidence level in the Ore Reserve estimate using an approach or procedure deemed appropriate by the Competent Person. For example, the application of statistical or geostatistical procedures to quantify the relative accuracy of the reserve within stated confidence limits, or, if such an approach is not deemed appropriate, a qualitative discussion of the factors which could affect the relative accuracy and confidence of the estimate.</li> <li>The statement should specify whether it relates to global or local estimates, and, if local, state the relevant tonnages, which should be relevant to technical and economic evaluation. Documentation should include assumptions made and the procedures used.</li> <li>Accuracy and confidence discussions should extend to specific discussions of any applied Modifying Factors that may have a material impact on Ore Reserve viability, or for which there are remaining areas of uncertainty at the current study stage.</li> </ul>	<p>The study was undertaken to a +/- 10% accuracy.</p> <p>The Competent Person has a good level of confidence in the Ore Reserve estimate based on the costs and parameters used in the determination of the Reserve.</p> <p>All relevant modifying factors are determined to be acceptable to this method of mining.</p> <p>Further investigation into geotechnical parameters and load and haul profiles and unit costs as a result of the completed as mining progresses over the 16year LOM plans.</p>

**For further information, please contact:**

**Managing Director**

Andrew Spinks

**CFO/Company Secretary**

Robert Hodby

Kibaran Resources Limited | ABN: 15 117 330 757

338 Hay Street Subiaco WA 6008 | PO Box 2106 Subiaco WA 6904

T: +61 8 6380 1003 | E: info@kibaranresources.com | www.kibaranresources.com

The information in this report that relates to Exploration Results is based on information compiled by Mr Andrew Spinks, a Competent Person, who is a Member of The Australasian Institute of Mining and Metallurgy. Andrew Spinks is employed by Kibaran Resources Limited. Mr Spinks has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves". Andrew Spinks consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

The information in this report that relates to Mineral Resources is based on information compiled by Mr David Williams, a Competent Person, who is a Member of The Australasian Institute of Mining and Metallurgy. David Williams is employed by CSA Global Pty Ltd, an independent consulting company. Mr Williams has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves". David Williams consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

The information in this report that relates to the Ore Reserve has been compiled by Mr Steve O'Grady. Mr O'Grady, who is a Member of the Australasian Institute of Mining and Metallurgy, is a full time employee of Intermine Engineering and produced the Mining Reserve estimate based on data and geological information supplied by Mr Williams. Mr O'Grady has sufficient experience that is relevant to the estimation, assessment, evaluation and economic extraction of Ore Reserve that he is undertaking to qualify as a Competent Person as defined in the 2012 edition of the Australasian Code for Reporting of Exploration Results, Minerals Resources and Ore Reserves. Mr O'Grady consents to the inclusion in this report of the matters based on his information in the form and context that the information appears.