

Bligh Resources Limited

ACN 130 964 162

ASX: BGH

ASX Release

23 April 2014

Suite 804 Level 8, 84 Pitt St Sydney New South Wales 2000 Tel: +61 2 9233 4677 Fax: +61 2 9239 0866

Contacts:

Robert Benussi

Email:

info@blighresources.com.au

For the Latest News:

www.blighresources.com.au

Directors:

Robert Benussi

Peiqi Zhang - (Non-Executive Director) Jinle Song - (Non-Executive Director) Eric Chan - (Non-Executive Director)

Zhijie Li -(Alternate Director for Mr Zhang) Bill Richie Yang -(Alternate Director for Mr J Song)

Company Secretary

Anna Sandham

Issued Capital:

Shares: 60,125,720 Unlisted Opts: 16,000,000

(Escrowed)

Currently Exploring and Developing:

- Gold
- Manganese

Current Projects:

- Bundarra Gold Project
- Leonora Gold Project
- Kumarina Manganese
- Bootu Creek Two Manganese

Quarterly Report for period ended 31 March 2014

Exploration Highlights

- Bligh increases holding in Bundarra Gold Project from 42.9 % to 71.9 %
- Mapping and Rock chip sampling program completed at Diorite King, Leonora
- Rock chip sampling continues to show gold anomalism around Diorite King and Little Wonder prospects
- Finalising engagement of local project geologist to complete site reconnaissance for potential drilling program at Bootu Creek
- Research and Development (R&D) Tax Incentive Refund applications being prepared for Bligh and SR Mining
- Miscellaneous Licence application submitted at Bundarra to provide for a road connecting the tenement package

Forward Work Plans

- Field work at Bootu Creek to commence once ground conditions are suitable
- Re-evaluate geophysical datasets to identify and categorise specific geological structures associated with field work interpretations

Gold and manganese exploration company, Bligh Resources Limited, ("Bligh" or "Company") (ASX: BGH) is pleased to report on activities undertaken in the quarter ended 31 March 2014 ("quarter").

Bligh's continued focus on the Bundarra Project has coincided with the company taking an increased stake in the project, with Bligh now holding a 71.9 % share of SR Mining. The remaining equity in SRM is held by minority shareholders, including Aura Capital who advised Bligh on the acquisition of the initial 42.9% in December 2012.

A small scale geological mapping and rock chip sampling program has been completed by BM Geological Services PL ("BMGS"), focused around the Diorite King and Little Wonder areas at the Leonora Project.

Research and development applications are being prepared by Deloitte for work completed on projects for SR Mining and Bligh.

Corporate Activity

In February, Bligh announced that it had signed an agreement to acquire a further 29% in SR Mining Pty Ltd (SRM) from two existing majority shareholders in consideration of releasing the vendors from their personal guarantees to the \$937,000 loan facility owed by SRM.

SRM holds 100% of the Bundarra gold project, and following the transaction, Bligh now holds 71.9% of SRM. The remaining equity in SRM is held by minority shareholders, including Aura Capital who advised Bligh on the acquisition of the initial 42.9% in December 2012.

Exploration Activity

BUNDARRA GOLD PROJECT - SR MINING (71.9% OWNED BLIGH RESOURCES)

As previously mentioned, Bligh has signed an agreement to acquire a further 29% in S R Mining Pty Ltd (SRM) from two existing majority shareholders in consideration of releasing the vendors from their personal guarantees to the \$937k loan facility owed by SRM.

SR Mining has submitted an application for a miscellaneous licence which will give the company the ability to construct a road to join Great Western (M37/054) to the main tenement package.

LEONORA PROJECT

The recent mapping campaign conducted at Leonora was based on previous fieldwork including broad scale geological mapping, soil geochemistry and the presence of historical workings, which will assist with the identification of suitable drill targets within the project area. Field observations noted structural geology aspects similar to those documented at around the Leonora district.

Diorite King:

Seventeen rock chip samples were taken around the Diorite King area. Samples TAR005 – TAR008 were collected from historical workings and confirm the presence of gold mineralisation (Table 1 & Figure 1). Based on field observations from the mapping program, results show that gold mineralisation around Diorite King most likely post-dates the mineralisation events at Tarmoola and Leonora. Although local analogous models are not ruled out for mineralisation styles within the area, this interpretation provides a significant step forward in attempting to locate later stage geological structures and assist with target delineation (Figure 2).

Little Wonder:

Nine rock chip samples were taken from the Little Wonder area, with Sample TAR020 from foliated basalt returning the best result (Table 1 & Figure 1).

Field based observations and geological interpretation suggests a geological model for gold mineralisation at Little Wonder may involve the structural evolution of transform structures, formed at a high angle to the Sons of Gwalia Shear zone (Figure 2). These features are favourable for gold mineralisation within the Southern Yilgarn, being long-lived geological structures and potentially conduits for gold-bearing, orogenic fluids, important for gold mineralisation. Transform structures are interpreted around the Leonora gold deposits (30km southeast of Diorite King) and, in some instances, are associated with gold mineralisation.

Further Work:

Field based observations add to the understanding of the structural setting of the Leonora Project. Further work required is to:

- 1. Determine the nature of the stratigraphic sequence and its importance as part of ore forming processes in the area; and
- 2. Re-evaluate geophysical datasets to assist with identifying and categorizing specific geological structures associated with the interpretations above.



Table 1: Rock chip results from Diorite King and Little Wonder, Leonora Project February 2014 (Coordinates are referenced to Map Grid of Australia (MGA) zone 51.)

Sample ID	Easting	Northing	Area	Assay Result
				(Au ppb)
TAR001	310621.1	6825227	Diorite King	9
TAR002	310299.5	6825490	Diorite King	1
TAR003	310702.4	6825513	Diorite King	8
TAR004	310863.7	6825306	Diorite King	73
TAR005	311000.5	6825198	Diorite King	420
TAR006	311026.9	6825169	Diorite King	214
TAR007	311073.7	6825093	Diorite King	275
TAR008	311098.1	6825075	Diorite King	4440
TAR009	311297.5	6826429	Diorite King	2
TAR010	311329.2	6826458	Diorite King	12
TAR011	310987.6	6826584	Diorite King	2
TAR012	310668.3	6824800	Diorite King	22
TAR013	310621.9	6824856	Diorite King	2
TAR014	310434.9	6825027	Diorite King	52
TAR015	310314.3	6825158	Diorite King	8
TAR016	309935.2	6824589	Diorite King	1
TAR017	310256.8	6824275	Diorite King	106
TAR018	311064.9	6823061	Little Wonder	9
TAR019	311304.2	6823025	Little Wonder	4
TAR020	311285.3	6823007	Little Wonder	619
TAR021	311292.4	6822620	Little Wonder	1
TAR022	311549.1	6823192	Little Wonder	<1
TAR023	310937	6822938	Little Wonder	79
TAR024	311007	6823152	Little Wonder	4
TAR025	310984	6823108	Little Wonder	1
TAR026	310899	6822931	Little Wonder	5






Figure 1: Field areas (in black outline) of the Leonora project and rock chip sample locations over orthophoto. Coordinates are referenced to Map Grid of Australia (MGA) zone 51.




Figure 2: Geological map with structural interpretation and geological areas of interest defined after the mapping program.

Coordinates are referenced to Map Grid of Australia (MGA) zone 51.



GRENFELL PROJECT

EL 7556 is in the final stage of relinquishment and Bligh continuing to monitor climate conditions to progress the rehabilitation of drilling sites at the project. An exceedingly dry summer has prevented adequate revegetation of the drilling sites and the return of the security and environmental bonds.

Following wetter autumn conditions Bligh has planted native grass seed across the disturbed area and Bligh is monitoring conditions and hopes to have the bonds refunded by the end of the next quarter, subject to weather conditions.

About Bligh Resources Limited

Listed in 2011, Bligh (ASX: BGH) is an explorer focused on the near term gold production potential in the Leonora region in W.A and manganese exploration projects in both N.T and W.A.

Bligh holds a strategic 42.9% interest in SR Mining Pty Ltd, which owns the advanced Bundarra Gold Project in Western Australia as well as a 100% interest in the Leonora Gold Project. Bligh also has an 80%-100% interest in the Bootu Two Creek Manganese Project in the Northern Territory.

Bligh also has a 100% interest in the Kumarina Manganese projects in WA.

Further information:

Rob Benussi: 0410 415 335 - CEO

Released through Fergus Ross, Six Degrees Investor Relations: 0420 980 448

Competent Person

The review of exploration activities and results contained in this report is based on information compiled by Mr Bradley Daddow a Member of the Australian Institute of Geoscientists. He is a consultant to Bligh Resources Limited and works for BM Geological Services PL. Bradley Daddow has sufficient experience which is relevant to the style of mineralisation and types of deposits under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves (the JORC Code). Bradley Daddow has consented to the inclusion in the report of the matters based on his information in the form and context in which it appears.



APPENDIX: JORC CODE, 2012 EDITION – TABLE 1

Section 1 Sampling Techniques and Data (Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	• Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.	Samples were collected as rock chips in areas of specific geological interest with a geological hammer raking into a calico bag from area <0.5m in diameter. Samples were taken from breaking in situ rock or rock fragments from float/shaft spoils.
	 Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. 	Sample representivity was not achieved according to Gy's sampling theory. No consideration was made for of fraction size, sample weight or sampling medium.
	• In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.	Sample sizes ranged in weights from 0.5 kg to 2kg & were raked into a calico bag from the field. Sample preparation involved: jaw crushing (where required; >70% passing -6mm) & pulverizing entire sample to >80% passing -75um. A 30g spatula sample was taken from the pulverized bulk sample for fire assay digest & Inductively Couple Plasma — Atomic Emission Spectrometry (ICP-AES) for gold analysis
Drilling techniques	Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	No drilling or drill results reported. Only Rock Chip samples were collected.
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	Sample representivity was not achieved according to Gy's sampling theory. No consideration was made for of fraction size, sample weight or sampling medium.



Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography The total length and percentage of the relevant intersections logged. 	All rock chip samples were logged according to rock type, regolith, alteration & structure. Rock ship samples will not be utilised for any resource estimation. Geological logging is qualitative & quantitative in nature.
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. 	The sample preparation was conducted by a commercial laboratory (Australian Laboratory Services PL)
	 For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise 	The nature, quality & appropriateness of the sample preparation is based on commonly accepted sample preparation techniques but has not been validated against Gy's sampling theory.
	 representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. 	No quality control procedures were adopted for the sub sampling due to the nature of rock chip sampling in the first instance.
	 Whether sample sizes are appropriate to the grain size of the material being sampled. 	No field duplicate samples were collected at the time of sampling due to the nature of rock chip sampling in the first instance.
		No work has been conducted to determine if the sample size is appropriate to the grain size of the material being sampled due to the nature of rock chip sampling in the first instance.
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and 	The assaying & laboratory procedures are designed to measure total gold in the sample. Assay resolution is to 0.001 ppm Au which is considered appropriate when assay results are expected to be of a low concentration.
	model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established	The fire assay technique involved using a 30g sample charge with a lead flux, which is decomposed in a furnace, with the prill being totally digested by 2 acids (HCI & HN03) before measurement of the gold content by an ICP-AES machine.
		A total of 9 internal laboratory standards, 3 internal laboratory standards & 5 internal laboratory duplicates were analysed for 26 rock ship samples



	submitted to the laboratory. All results were within acceptable limits of the laboratory's QC guidelines. BGH accepts these guidelines based on the certification & accreditation of the commercial laboratory. The guidelines can be located at & are the property of Australian Laboratory Services PL)
 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. 	Independent verification of significant intersections not considered material due to the nature of rock chip sampling in the first instance.
 Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. 	Samples are documented in the field & assigned an identity code (sample number). Data is stored electronically in spreadsheets.
Discuss any adjustment to assay data.	No adjustment has been made to the assay data.
• Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.	Sample locations are surveyed utilising a hand held GPS unit with an accuracy of +/- 5m.
 Specification of the grid system used. Quality and adequacy of topographic control. 	Sample co-ordinates are referenced to Map Grid of Australia zone 51 & GDA.
	The quality of the topographic control is relatively in-accurate given the utilisation of the hand help GPS.
 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of aeological and grade continuity appropriate for the Mineral Resource and 	Data spacing was based on selectively sampling geological areas of interest & was not intended to be on a set pattern/grid.
Ore Reserve estimation procedure(s) and classifications applied. • Whether sample compositing has been applied.	The data spacing cannot be used to establish geological or grade continuity due to the nature of the selective sampling.
	No sample compositing was applied.
 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	The nature of the rock chip sampling may show bias towards sampling along a mineralised structure. The extent of which is unknown.
	 company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this



Sample security	The measures taken to ensure sample security	Samples collected by BGH were all under the security and custodial chain of BGH contractors until delivered to the commercial laboratory where they were in a secured fenced compound with restricted entry. Internally, the commercial laboratories operate an audit trail that has access to the samples at all times whilst in their custody.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	No audits or review of the sampling process has been completed and is considered un necessary given the nature and intended purpose of the rock chip sampling results.

Section 2 Reporting of Exploration Results (Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	Diorite King Project is located on the following Prospecting Licences: P37/7782-93, P37/7807-16, P37/7829, P37/8048 and P37/7100. All tenements are held 100% held by BGH except for P37/8048 and P37/7100 which are 50% held by BGH. Heritage sites are located within these tenements.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	The tenements are in good standing and no known impediments exist. The project has been explored by predecessors including, Australian Selection, Esso, Western Mining Corporation, Pacmin, and Sons of Gwalia as well as various academic studies on the geology of the project. Results of exploration & mining activities by the aforementioned companies have assisted BGH during the recent exploration program in the area.



Geology	Deposit type, geological setting and style of mineralisation.	The Diorite King project is located within the Leonora District & is part of the Mt Clifford Greenstone Belt. The stratigraphy comprises Archaean mafic, ultramafic units & inter-bedded sedimentary units that are intruded by the Raeside & Bundarra batholiths. The Diorite King is situated in the Leonora West Domain (LWD) which comprises amphibolite overlain by ultramafic, then dolerite & then basalt rock types. A geological model for Diorite King mineralisation area is later stage, brittle-ductile geological structures, intersecting the geochemically favourable horizons with the dolerite unit, & forming orogenic gold deposits, similar to those in the South Yilgarn. At Little Wonder the formation & reactivation of transform structures during later deformation may be responsible for mineralisation.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	The rock chip sampling results are presented in table 1
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	Exploration results are representative of the rock chips relative to a known point. No data aggregation methods have been utilised.



Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	Rock chip samples are not referenced to an interval due to being spot samples.
Diagrams	Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	See figure 1.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	All results have been reported.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	See figure 2.
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	Further work is based on ground truthing target areas given the rock ship sampling results.