



ASX and Media Release

Tarcoola ML exploration gaining momentum

WPG Resources Ltd (ASX:WPG) is capitalising on a number of exploration opportunities to add further ounces to the Tarcoola operation on the Mining Lease. This is a result of increased understanding of geological controls as mining advances in the Perseverance Pit (Figure 1). Various RC drill programs are currently being prepared.




Figure 1: Exploration Targets on the Tarcoola Mining Lease

9 August 2017



ABN 51 109 426 502
 Level 9, Kyle House
 27-31 Macquarie Place
 Sydney NSW 2000
 Telephone (+612) 9251 1044
 Facsimile (+612) 9247 3434
 info@wpgresources.com.au
 www.wpgresources.com.au

Near pit targets include:

- **Morning Star** - 1,200 tonnes of argillic bearing ore was recently mined and processed at 4.48g/t Au. Whilst it is within the confines of the pit design, mineralisation lies outside of resource. An historical drill hole that lies outside the pit design but along strike of the mineralisation returned **6m @ 13.56g/t Au from 53m**.
- **Forgotten Prince** – lies on the contact between the granite and the Tarcoola Formation sediments and is either related to a basal thrust or the northern limb of the anticline.
- **SW Eclipse** – historical drill logs suggest an argillic zone above the Peela Conglomerate in a position where its contact with the granite is displaced by the Perseverance Shear from WSW to SW, indicating a possible trap for mineralising fluids. This has a number of historical gold intersections which requires closer spaced drilling with the aim of resource inclusion.

Other ML exploration targets with proposed RC drilling include (Figure 1):

- **Wondergraph** – Drilling planned to infill and extend to the SW.
- **Lonely Heart** – Drilling planned to follow up on an historical RAB hole intersection of **4m @ 36g/t from 8m**.
- **Genie Bar** – Conglomerate-Granite contact with elevated gold in soils (>40ppb from -0.16mm mesh completed by WPG earlier in the year) and coincident NW structures interpreted from ground magnetics.
- **Lady Luck** – Conceptual similar setting to Wondergraph, except overlies Lady Jane Diorite, and has coincident interpreted N-S structures.
- **Pirate Patch** – **7m @ 4.21g/t** from 1m trench samples.

Warrigal Prospect Update

A seven-hole RC program designed to test the large Warrigal IP chargeability anomaly has been completed with 1,256m drilled.

Significant quantities (1-5%) of sulphides (pyrite) were encountered in every hole, ranging from 17-53% of the length of the holes, which confirmed the IP anomaly was caused by sulphides. The bulk of these were in black shale, but there were also many in other lithological intervals including sandstone, quartzite, shale, conglomerate and granite.

Assays have been returned for holes 17WARC001-005 with peak result to date returning **3m @ 10.11g/t (including 2m @ 14.84g/t)** in hole 17WARC005 in black shale with an internal quartz vein (Figure 2).

The drilling results are summarised in more detail in Appendix 1.

Pending any significant final results, exploration focus will shift from Warrigal to the many other prospective areas on the Mining Lease.

None of the data reported on herein has been used for resource or reserve estimation.




Figure 2 (inset from Figure 1): Peak results from each recent RC hole drilled at the Warrigal Prospect

Further Information

For further information please contact WPG's Executive Chairman, Bob Duffin or CEO Wayne Rossiter on (02) 9251 1044.

Forward-Looking Statements

This document may include forward-looking statements. Forward-looking statements include, but are not limited to statements concerning WPG's planned activities, including but not limited to mining and exploration programs, and other statements that are not historical facts. When used in this document, the words such as "could", "plan", "estimate", "expect", "intend", "may", "potential", "should" and similar expressions are forward-looking statements. In addition, summaries of Exploration Results and estimates of Mineral Resources and Ore Reserves could also be forward looking statements. Although WPG believes that its expectations reflected in these forward-looking statements are reasonable, such statements involve risks and uncertainties and no assurance can be given that actual results will be consistent with these forward-looking statements.

Competent Person Statement

The Tarcoola exploration activities and results contained in this report are based on information compiled by Mr Paul Wittwer.

Paul Wittwer is a Member of the Australasian Institute of Mining and Metallurgy and the Australian Institute of Geoscientists. He is a Senior Project Geologist and a full time employee of WPG Resources Ltd. He has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the December 2012 edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves (the JORC Code & Guidelines). Paul Wittwer has consented in writing to the inclusion in this report of the matters based on his information in the form and context in which it appears.

Appendix 1 – Drill hole information

Drill collar detail

Exploration RC Drill hole Details (MGA94 Zone 53)						
HOLE ID	MGA94 E	MGA94 N	RL	DIP	AZI (TRUE)	DEPTH
17WARC001	456028	6602806	153	-79	356	199
17WARC002	456027	6602846	155	-60	358	180
17WARC003	456177	6602875	146	-65	3	199
17WARC004	456327	6602929	140	-58	2	180
17WARC005	455870	6602759	148	-74	46	187
17WARC006	455869	6602783	151	-60	355	151
17WARC007	456180	6603051	165	-90	104	160

Drill assay results

Drill Assay results						
Hole ID	(m) From	(m) To	Interval (m)	True Width (m)	Au (g/t)	Prospect
17WARC001	84	85	1	1	1.69	Warrigal
17WARC001	151	154	3	3	1.60	Warrigal
<i>including</i>	152	153	1	1	3.98	Warrigal
17WARC002	93	94	1	1	2.87	Warrigal
17WARC003	32	36	3	3	0.64	Warrigal
17WARC004	88	90	2	2	1.58	Warrigal
17WARC005	87	90	3	3	10.11	Warrigal
<i>including</i>	88	90	2	2	14.84	Warrigal
17WARC005	93	94	1	1	1.50	Warrigal

Drill collar detail (Historical)

HOLE ID	TYPE	MGA94 E	MGA94 N	RL	DIP	AZI (TRUE)	DEPTH
QR208	RC	454997	6602903	162	-55	110	65
TAP242	RAB	455627	6603752	150	-60	77	40
TR008	Trench	456429	6602843	136	0	131	120

Drill assay results (Historical)

Hole ID	(m) From	(m) To	Interval (m)	True Width (m)	Au (g/t)	Prospect
QR208	53	59	6	6	13.56	Morning Star
TAP242	8	12	4	4	36.00	Lonely Heart
TR008	86	93	7	7	4.21	Pirate Patch

JORC Code, 2012 Edition – Table 1

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> • <i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i> • <i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i> • <i>Aspects of the determination of mineralisation that are Material to the Public Report.</i> • <i>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i> 	<ul style="list-style-type: none"> • RC drill holes are 132mm diameter and samples every metre are taken directly off the drill rig cyclone splitter at a 1/8 split • Each sample is crushed to 4mm and pulverised to 75 microns through the PAL (pulverising aggressive leach) process. In the PAL process, each sample is pulverised in an aqueous solution with cyanide bearing assay tabs and a collection of assorted ball bearings. Each sample is processed in the PAL for one hour, resulting in an Au_CN complex bearing liquor and remnant pulverised sample.
Drilling techniques	<ul style="list-style-type: none"> • <i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i> 	<ul style="list-style-type: none"> • Reverse Circulation, 132mm diameter
Drill sample recovery	<ul style="list-style-type: none"> • <i>Method of recording and assessing core and chip sample recoveries and results assessed.</i> • <i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i> • <i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i> 	<ul style="list-style-type: none"> • Cyclone has a cutter to separate samples – drilling is paused at each metre when the sample is taken and recommenced when the new bag is put on • No sample bias is expected.

Criteria	JORC Code explanation	Commentary
Logging	<ul style="list-style-type: none"> • <i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i> • <i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i> • <i>The total length and percentage of the relevant intersections logged.</i> 	<ul style="list-style-type: none"> • Each metre in the program is individually sieved and geologically logged (lithology, mineralisation, alteration) down to m-scale, not just mineralised intervals • The logging is quantitative in nature as lithology percentages and compositions are recorded
Sub-sampling techniques and sample preparation	<ul style="list-style-type: none"> • <i>If core, whether cut or sawn and whether quarter, half or all core taken.</i> • <i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i> • <i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i> • <i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i> • <i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i> • <i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i> 	<ul style="list-style-type: none"> • Samples taken from the cyclone splitter are mostly dry • The sample is submitted to the Challenger Mine site laboratory for analysis. All samples are dried at a maximum temperature of 90 degrees Celsius to drive off moisture that would interfere with splitting the sample. After drying, samples are crushed using a Boyd Crusher to approximately 4mm in size and then split through a rotary sample splitter to produce a sub-sample. The crusher is cleaned regularly, with barren material (bricks) crushed through it to ensure no smearing prior to the sample run being crushed. Each reject sample is retained for resampling if required. • Each sample can be tracked by its sample number through the entire laboratory process and results for the original samples and all QAQC samples are presented in digital form to the Tarcoola and Challenger site geologists.
Quality of assay data and laboratory tests	<ul style="list-style-type: none"> • <i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i> • <i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i> • <i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i> 	<ul style="list-style-type: none"> • Assaying at Challenger is completed using the PAL process (pulverising aggressive leach). This process effectively replicates the process in the Challenger mill. Each sample is pulverised in aqueous solution with cyanide bearing assay tabs and a collection of assorted ball bearings. Each sample is processed in the PAL for one hour, resulting in an Au_CN complex bearing liquor and remnant pulverised sample. The pulverised material is 95% passing 75 microns, the ideal liberation size for gold at Challenger. • Every twentieth sample is duplicated for the original sample bag (re-split) to produce a duplicate. Every sample run (53 samples) will contain at least two duplicates, a blank and a standard (prepared by Gannet Holdings Pty Ltd). These are to ensure that the sub-sampling is representative, that the PAL is correctly cleaned between sample runs and that the PAL is pulverising the samples correctly for full gold extraction. • Following PAL processing, the samples are individually decanted, centrifuged and prepared for analysis in an AAS by solvent separation using DIBK (20 minutes). The sample is then aspirated through the AAS to produce a reading. The AAS is calibrated

Criteria	JORC Code explanation	Commentary
		<p>for each sample run using analytical reagent prepared standards (of 1.0, 5.0, 10.0 and 20.0 g/t Au) from Rowe Scientific. Each sample is adjusted for sample weight in Labman software to produce the gold grade in ppm. These grades are presented to site Geologists in MS Excel .csv spread sheets.</p> <ul style="list-style-type: none"> • For each sample job; blanks, standards and duplicates are examined to ensure that the blanks are below detection (0.01ppm), the standards are within 8% (experimental accuracy) and that the duplicates are 'reasonable' with respect to the nugget effect of the Tarcoola deposit. Any sample jobs that fail these checks will be re-analysed from re-splits of the original samples. In addition, all the blanks, standards and duplicates are examined quarterly to ensure that the laboratory is maintaining overall operating standards. • Soil samples were prepared and analysed by Bureau Veritas laboratories in Wingfield with Fire Assay (40g charge) and a mixed-acid digest and ICP-MS for a multi element suite. • Historical drill samples were submitted to Amdel laboratories in Adelaide and analysed using Aqua Regia and AAS finish.
<p>Verification of sampling and assaying</p>	<ul style="list-style-type: none"> • <i>The verification of significant intersections by either independent or alternative company personnel.</i> • <i>The use of twinned holes.</i> • <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> • <i>Discuss any adjustment to assay data.</i> 	<ul style="list-style-type: none"> • Significant intercepts were verified by the Senior Mine Geologist and Senior Project Geologist. Significant intercepts in Tarcoola exploration drilling (greater than 0.5g/t) are submitted to Genalysis for external analysis. This analysis is undertaken by SP-02 or SP-03 sample preparation followed by partial fire assay using a 50 gram charge (FA50). These results are compared to the original PAL results to ensure that the site analyses are repeatable. While the two analysis processes are different, a reasonable correlation is expected. • No twinned holes were drilled • All logging data is captured digitally on company laptop computers and stored in a dropbox cloud. All sample information is recorded both in the relevant logs and in sample submission forms that are submitted to the laboratory (on and off site). This allows checking that all samples are present and accounted for by laboratory staff. Assay results are generated as MS Excel .csv files that are stored on the site server and are manually merged with the primary logging information. This merged data (logs, collar information and assays) are all imported to the site Diamond Drilling Database in MS Access for use in Surpac. All information imported to the database is checked by the importer in MS Access and Surpac to ensure the correct location/display of data. Ongoing checks are carried out by the entire technical team as the data is used. • The only modification of assay data, following creation by Labman software is altering of results below detection, <0.01g/t Au, to 0.005g/t Au, undertaken using the merged data in MS Excel (using standard forms), prior to importing to MS Access

Criteria	JORC Code explanation	Commentary
Location of data points	<ul style="list-style-type: none"> • Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. • Specification of the grid system used. • Quality and adequacy of topographic control. 	<ul style="list-style-type: none"> • All surveys on site are carried out by qualified personnel using the site Leica C515 DGPS, providing collar co-ordinates to cm-scale accuracy in the same datum (GDA94 zone 53) as the rest of the site. Collar dip and azimuth were surveyed with solid state north seeking ChampGyro tool. The collar surveys are transmitted electronically to the site Geologists who merge this information into the MS Excel logs for each drill hole. • No local Reduced Level (RL) is used, just the Australian Height Datum (AHD) • Topographic control is good with the survey system used
Data spacing and distribution	<ul style="list-style-type: none"> • Data spacing for reporting of Exploration Results. • Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. • Whether sample compositing has been applied. 	<ul style="list-style-type: none"> • Drill spacing at Warrigal is nominally approximately 50m spaced collars. • No sample compositing of RC drilling has been applied
Orientation of data in relation to geological structure	<ul style="list-style-type: none"> • Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. • If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	<ul style="list-style-type: none"> • The orientation of RC drill holes are designed to be as perpendicular to the IP anomaly and stratigraphy as possible.
Sample security	<ul style="list-style-type: none"> • The measures taken to ensure sample security. 	<ul style="list-style-type: none"> • Samples are submitted to the site laboratory as soon as practical after sampling in individually numbered calico sample bags (labelled TRC for RC drilling). Analysis is not undertaken until all descriptive paperwork is correctly submitted for the samples. From acceptance of the samples, each sample is tracked on site through Labman software to ensure that each assay is correctly matched with its sample. Any discrepancy between submitted samples and the paperwork is identified and may result in the entire sample job being resampled from original material prior to analysis. External laboratories utilise their own systems for sample tracking.
Audits or reviews	<ul style="list-style-type: none"> • The results of any audits or reviews of sampling techniques and data. 	<ul style="list-style-type: none"> • Data reviews are undertaken on an ongoing basis by site Geologists while using the data. Any errors identified (either by staff, MS Access or Surpac) is queried and corrected as a part of a program of continual improvement. • Lab audits are done annually, showing that operating procedures for sample management, QAQC and result consistency are being adhered to.

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<ul style="list-style-type: none"> • <i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i> • <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i> 	<ul style="list-style-type: none"> • All exploration was undertaken within the current Tarcoola Mine Lease ML6455. The underlying Exploration Licence EL5355 comprises 1183 square kilometres, on the Wilgena pastoral lease, part of which is within the Woomera Prohibited Area.
Exploration done by other parties	<ul style="list-style-type: none"> • <i>Acknowledgment and appraisal of exploration by other parties.</i> 	<ul style="list-style-type: none"> • Abundant previous exploration and mining activities at Tarcoola have been conducted since discovery of the field in 1893, but more recent work (since 1995) by Mungana Goldmines, Stellar Resources, Anglo Gold and Grenfell Resources was used. Due diligence and resurveying of drill holes etc. was completed by Mungana and all information is considered accurate.
Geology	<ul style="list-style-type: none"> • <i>Deposit type, geological setting and style of mineralisation.</i> 	<ul style="list-style-type: none"> • The Tarcoola Project covers a portion of the north-western Gawler Craton centred over the historic Tarcoola goldfield, where Archaean and Proterozoic rocks form the basement to an extensive cover of Phanerozoic sediments. The Archaean basement has been extensively deformed, whereas the Proterozoic rocks have been weakly to moderately deformed. • At Perseverance (current Tarcoola open pit mine), gold mineralisation is hosted within sedimentary rocks of the Tarcoola Formation and granite, both of Proterozoic age. The granite is variably in fault contact with or unconformably overlain by the sediments, which consists of conglomerate, limestone, sandstone, siltstones, and shale. A suite of later intrusions (Lady Jane Diorite) cut both the sedimentary rocks and the granite. • Mafic high level intrusives associated with the 1590Ma Hiltaba Magmatic Event are considered to control the spatial setting of both gold and base metal mineralisation. • Three deformation events have been recognised in the area. D1 is characterised by open folding and NNW-directed thrusting, responsibly for the southerly dip of the sedimentary package at Perseverance. Steeply dipping NW and NE trending brittle faults developed during D2. These structures host and control the gold mineralisation in the Tarcoola Ridge area. The third deformation event (D3) is represented by the late E-W trending barren quartz veins. • Gold has locally been remobilised and enriched in the weathering profile. The base of complete oxidation occurs typically 10-40m below surface, and the base of partial

Criteria	JORC Code explanation	Commentary
		<p>oxidation occurs at a depth of ~20-60m.</p> <ul style="list-style-type: none"> • Within the primary zone, sericite-quartz-pyrite alteration zones are spatially associated with the mineralisation, and overprint earlier hematite-magnetite alteration. An outer halo of chlorite (+/-leucoxene and pyrite) is developed. Pyrite, galena and sphalerite are the main associated sulphide minerals, with subordinate amounts of chalcopyrite bornite and/or arsenopyrite noted. • Veins can be discrete or form wider stockwork zones, and are surrounded by broader quartz-sericite alteration envelopes which can host lower grade background halos of mineralisation. Dispersed supergene mineralisation in the oxide zone can be largely detached from veining. • For more detail see: Budd, A & Skirrow, R, 2007. The Nature and Origin of Gold Deposits of the Tarcoola Goldfield and Implications for the Central Gawler Gold Province, South Australia. Economic Geology, 2007.
Drill hole Information	<ul style="list-style-type: none"> • <i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> <ul style="list-style-type: none"> ○ <i>easting and northing of the drill hole collar</i> ○ <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i> ○ <i>dip and azimuth of the hole</i> ○ <i>down hole length and interception depth</i> ○ <i>hole length.</i> • <i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i> 	<ul style="list-style-type: none"> • See Appendix 1 to this report.
Data aggregation methods	<ul style="list-style-type: none"> • <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i> • <i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should</i> 	<ul style="list-style-type: none"> • For all results from the Challenger Gold Mine laboratory, a low cut-off of 0.01g/t Au is applied (limit of detection), these results are replaced with 0.005g/t Au in the drilling database to flag that they are below detection. No upper grade truncation is used for significant intercepts. • Reported mineralised intercepts are based on consistent zones of mineralisation greater than 1 g/t x m using 0.25g/t cut off and intervals over 1 metre.

Criteria	JORC Code explanation	Commentary
	<p><i>be stated and some typical examples of such aggregations should be shown in detail.</i></p> <ul style="list-style-type: none"> The assumptions used for any reporting of metal equivalent values should be clearly stated. 	<ul style="list-style-type: none"> No metal equivalent values have been used.
Relationship between mineralisation widths and intercept lengths	<ul style="list-style-type: none"> These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	<ul style="list-style-type: none"> All mineralisation widths are reported as true widths
Diagrams	<ul style="list-style-type: none"> Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	<ul style="list-style-type: none"> Diagrams have been included in the main body of the report.
Balanced reporting	<ul style="list-style-type: none"> Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	<ul style="list-style-type: none"> Assay results at the Warrigal Prospect range from <0.01 to 19.83g/t Au
Other substantive exploration data	<ul style="list-style-type: none"> Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	<ul style="list-style-type: none"> Some copper minerals and fluorite were observed in hole 17WARC004 suggesting an epithermal environment
Further work	<ul style="list-style-type: none"> The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	<ul style="list-style-type: none"> Planned further drilling may be conducted pending assays