
Gold Mountain Limited
(ASX: GMN)

24/589 Stirling Highway
Cottesloe WA 6011
Australia

Directors and Management**David Evans**

Executive Director

Syed Hizam Alsagoff

Non-Executive Director

Aharon Zaetz

Non-Executive Director

Rhys Davies

CFO & Company Secretary

Projects**Lithium Projects (Brazil)**

Cococi region

Custodia

Iguatu region

Jacurici

Juremal region

Salinas region

Salitre

Serido Belt

Copper Projects (Brazil)

Ararenda region

Sao Juliao region

Iguatu region

REE Projects (Brazil)

Jequie

Copper Projects (PNG)

Wabag region

Green River region

ASX Announcement/Press Release | 25 July 2024**Gold Mountain Limited (ASX:GMN)****Strongly Anomalous LCT Pegmatite Assays in Lithium Valley, Salinas Project.**

Gold Mountain Limited (ASX: GMN) ("Gold Mountain" or "the Company" or "GMN") is excited to announce it has received a batch of 55 stream sediment samples from the Agua Boa and Bananal Valley tenements in the Salinas II Project. This area lies along regional strike from Latin Resources Collina Resource.

Highlights**Work Undertaken**

- Assays received from regional stream sediment sampling with peak values of **672 ppm lithium in Bananal Valley and 226 ppm in Agua Boa. 54 anomalous results out of 55 samples.**
- Potential for significantly mineralised LCT pegmatites is considered to be very high.
- Multi element anomalies consisting of Be+Cs+Nb+Rb+Sn+Ta gave a good discrimination of the highest order anomalies and prioritised an area for follow up.
- Future program of mapping and soil sampling is proposed to develop drill targets.

Future Workplan

- Landowner access will be obtained for detailed work to develop drill targets.
- Mapping of exposures in drainages as well as grid soil sampling will be undertaken to define the sources of the high order stream sediment anomalies.

Very high magnitude stream sediment sample results were received on the Agua Boa project. Sample result coverage of the Agua Boa tenement is now complete and two exceptionally high grade results were obtained from the two sample results from the Bananal Valley tenement where we expect a further 38 results shortly.

54 out of 55 samples results received were anomalous, however only the highest order anomalies were plotted to allow for prioritising areas for follow up. As the area of preserved old surface is approached in the NE of the Agua Boa tenement, the anomalies become weaker but are still considered anomalous.

The GMN sampling methods allow for rapid and cost effective coverage at broad spacing of samples. Detailed work is then restricted to much smaller catchment areas within the tenements as a result.

Previous mapping carried out on the tenements had identified pegmatites and an artisanal working as shown on the maps.

ASX:GMN**info@goldmountainltd.com.au****+61 421 903 222**

Catchment areas for each anomalous sample were defined on satellite imagery and coloured to indicate magnitude.

The combination of very highly anomalous lithium results within the known pegmatite bearing tenements is considered to be very encouraging for another discovery within the Lithium Corridor published by Latin Resources. Proximity of GMN tenements to Latin Resources does not guarantee same or similar levels of results however it does help GMN target exploration programmes.

Images & Maps

Figure 1 shows the location of the majority of the Salinas Project tenements in relation to Latin resources Collina deposit and to other pegmatites identified by Latin Resources.




Figure 1. Location of the Agua Boa and Bananal Valley tenements in the GMN Salinas Project. Structures shown in grey were interpreted from topography, magnetics and radiometric data. Red dots are known lithium bearing pegmatites compiled by CPRM.

Using the two most highly anomalous Lithium values as the most important areas for follow up and then plotting a combined sum of lithium correlated LCT associated elements, a further discriminator was developed to prioritise a broader area with the highest priority targets. The approach successfully identified a 4 kilometre long zone of the most anomalous responses that will form the principal initial target zone in the Bananal Valley tenements.

Figure 2 shows the highest priority target zone in the Agua Boa tenement.




Figure 2. Highest priority target zone in the southern part of the Agua Boa tenement. Multi-element LCT mineral anomalies are plotted with the highest order lithium anomalies shown by the green diamonds. The marked working is of unknown type but lies in very close proximity to the tenements boundary so is of significant interest.

Previous mapping on the tenement is shown on figure 3.




Figure 3. Geological mapping carried out on the Agua Boa tenement.

Two extremely high value results of 547 and 672 ppm lithium in stream sediments were obtained from the Bananal Valley tenement, for the only two results received so far from the 40 samples covering the tenement area. These are extremely high values for stream sediment results.

Location of the highly anomalous results is shown on figure 4.




Figure 4. Bananal Valley anomalous catchments for the two sample results received.

Previous mapping was carried out and the high grade anomalies are along regional lithium controlling structural strike from mapped pegmatites within the tenements. Mapping in the tenements is shown on figure 5.




Figure 5. Geological mapping carried out over the Bananal Valley tenements.

Competent Persons Statement

The information in this ASX release is based on information compiled by Peter Temby, a Competent Person who is a Member of Australian Institute of Geoscientists. No exploration results are included in this announcement apart from presenting mapping done as a part of stream sediment sampling. Peter Temby is an independent consultant working currently for Mars Mines Ltd. Peter Temby confirms there is no potential for a conflict of interest in acting as the Competent Person. Peter Temby has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Peter Temby consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

- END -

This ASX announcement has been authorised by the Board of Gold Mountain Limited

For further information, please contact:

Gold Mountain Limited

David Evans

Executive Director M: +61 421 903 222 E: info@goldmountainltd.com.au

About Us

Gold Mountain (ASX:GMN) is a mineral explorer with projects based in Brazil and Papua New Guinea (PNG). These assets, which are highly prospective for a range of metals including rare earth elements, niobium, lithium, nickel, copper and gold, are now actively being explored.

Gold Mountain has gradually diversified its project portfolio. The Company has highly prospective rare earth elements (REE), niobium, copper and lithium licenses located within the eastern Brazilian lithium belt, spread over parts of the Borborema Province and São Francisco craton in north-eastern Brazil including in Salinas, Minas Gerais.

In PNG, Gold Mountain is exploring the Wabag Project, which covers approximately 950km² of highly prospective exploration ground in the Papuan Mobile belt. This project contains three targets, Mt Wipi, Monoyal and Sak Creek, all lying within a northwest-southeast striking structural corridor. The three prospects have significant potential to host a porphyry copper-gold-molybdenum system and, or a copper-gold skarn system. Gold Mountain's current focus is Mongae Creek, which has been subjected to several phases of exploration, and the potential to host a significant copper-gold deposit is high. The current secondary targets are, in order of priority, Mt Wipi, Lombokai and Sak Creek. A new target, potentially another epithermal/porphyry system has been identified and is about to be sampled.

Gold Mountain has also applied for a total of 1048 km² in two exploration licences at Green River where high grade Cu-Au and Pb-Zn float has been found and porphyry style mineralisation was identified by previous explorers. Intrusive float, considered to be equivalent to the hosts of the majority of Cu and Au deposits in mainland PNG, was also previously identified.

List of references

GMN ASX Release 12 July 2024 Technical Presentation Brazil and PNG

GMN ASX Release 7 March 2024 Investor Presentation

GMN ASX Release 11 Dec 2023 Investor Presentation

GMN ASX Release 29 March 2023 Exploration underway at Highly Prospective Salinas II Lithium Project, Brazil

GMN ASX Release 24 January 2023 Gold Mountain Restructures its Brazilian Lithium JV Portfolio

LRS ASX Release 2 March 2023 PDAC Presentation March 2023

LRS ASX Release 30 May 2024 Collina Lithium Deposit MRE Upgrade: Global JORC MRE - 77.7 Mt@1.24%Li₂O 95% of Collina Deposit now in Measured and Indicated Categories – 67.27 Mt @1.27% Li₂O

LRS ASX Release 18 October 2023 Salinas District Scale Resource Continues to Grow Towards a Tier One Lithium Deposit

LRS ASX Release 28 August 2023 Positive High- Grade Lithium Results continue at Colina

Appendix 1 JORC Code, 2012 Edition – Table 1

Section 1 - Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections)

Criteria	JORC Code Explanation	Commentary
<i>Sampling techniques</i>	<p><i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i></p> <p><i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i></p> <p><i>Aspects of the determination of mineralisation that are Material to the Public Report.</i></p> <p><i>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i></p>	<p><i>Stream sediment sampling was carried out in drainages over 500 metres long with spacing planned at approximate 1 km on drainages.</i></p> <p><i>Stream sediment samples weighed approximately 1 kg each. Sample is pre-processed to a -10 micron sample fraction that is submitted to the laboratory.</i></p> <p><i>Samples are not considered representative of the possible grade of mineralisation at depth however they are considered to well represent the metals that are attached to clays, fine iron oxides and micaceous minerals as the fine fraction used is better able to travel in low gradient catchments than coarser fractions.</i></p> <p><i>The size fraction is considered to be representative of the geochemistry of the catchment.</i></p> <p><i>Analytical procedures are industry standard 4 acid digest and ICP analysis.</i></p>
<i>Drilling techniques</i>	<p><i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other</i></p>	<p><i>No drilling undertaken</i></p>

Criteria	JORC Code Explanation	Commentary
	<i>type, whether core is oriented and if so, by what method, etc).</i>	
<i>Drill sample recovery</i>	<p><i>Method of recording and assessing core and chip sample recoveries and results assessed.</i></p> <p><i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i></p> <p><i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i></p>	<p><i>No drilling undertaken</i></p> <p><i>Samples are considered representative due to the fine grain size and taking the sample in active channels.</i></p> <p><i>Sample recovery and grade relationships are not relevant to the type of stream sediment fraction targeted in the stream sediment samples</i></p>
<i>Logging</i>	<p><i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i></p> <p><i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i></p> <p><i>The total length and percentage of the relevant intersections logged.</i></p>	<p><i>No drilling undertaken</i></p> <p><i>Stream sediment sampling is subjective however the fraction sampled and the preparation and analytical procedures used make the samples readily compared and more representative than -80 # samples.</i></p> <p><i>All sample data including stream size and associated lithologies in the stream are recorded on site.</i></p> <p><i>Data recorded is quantitative for location and stream width and qualitative for any percentages of lithologies present as gravel.</i></p>
<i>Sub-sampling techniques and sample preparation</i>	<p><i>If core, whether cut or sawn and whether quarter, half or all core taken.</i></p> <p><i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i></p> <p><i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i></p> <p><i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i></p> <p><i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i></p>	<p><i>No drilling undertaken</i></p> <p><i>All samples were collected at 1 kg bulks in the field, screened at approximately 2.5 mm then securely packaged and taken to the GMN sample preparation laboratory.</i></p> <p><i>Sample preparation undertaken by GMN prior to sample dispatch to ALS at Belo Horizonte was to separate the sample in an apparatus using Stokes Law to produce a nominal -10 micron fraction for dispatch to the lab after drying. Samples are dried in a low temperature drying cabinet.</i></p> <p><i>Sample representativity of the catchment was well represented in the -10 micron samples as this size fraction will travel over low gradient surfaces better than coarser fraction samples. No duplicates are collected in the field however residues from extraction of the clay fraction are</i></p>

Criteria	JORC Code Explanation	Commentary
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	<i>retained to ensure a repeat analysis could be performed if required.</i>
<i>Quality of assay data and laboratory tests</i>	<p><i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i></p> <p><i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i></p> <p><i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i></p>	<p><i>Sample preparation at the ALS lab is to pulverise the -10 micron sample, screen at -80# and analyse by the selected method required.</i></p> <p><i>The analytical techniques used are four acid digest and ICP-MS, the 4 acid digest method is a partial digest technique, compared to fusion digests and then ICP-MS, however differences in the analytical values of certified reference materials by the two methods suggest that 4 acid digests are suitable for non-resource sampling in exploration work. ALS codes used were ME-MS41L.</i></p> <p><i>No standards duplicates or blanks accompany these initial samples that will not be used other than to indicate potentially interesting element contents of the variably weathered samples</i></p> <p><i>Checks of the analytical values of CRM's used by the laboratory against the CRM specification sheets were made to assess whether analyses were within acceptable limits</i></p>
<i>Verification of sampling and assaying</i>	<p><i>The verification of significant intersections by either independent or alternative company personnel.</i></p> <p><i>The use of twinned holes.</i></p> <p><i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i></p> <p><i>Discuss any adjustment to assay data.</i></p>	<p><i>No drilling or drill hole samples analysed</i></p> <p><i>No twin holes drilled</i></p> <p><i>No verification will be undertaken for these initial samples, which will not be used in any resource estimate. The samples are to determine the levels of Li and other valuable elements in stream sediment samples</i></p> <p><i>All field data is checked upon entry into spreadsheets and storage in the company data base.</i></p> <p><i>No adjustments are made to assay data except to plot below detection as half detection limit and over limit as the value of maximum detection.</i></p>
<i>Location of data points</i>	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	<i>Data points are measured by hand held Garmin 65 Multiband instruments with accuracy to 3 metres</i>

Criteria	JORC Code Explanation	Commentary
	<p><i>Specification of the grid system used.</i></p> <p><i>Quality and adequacy of topographic control.</i></p>	<p><i>Grid system used is SIRGAS 2000 which is equivalent to WGS84 for hand held GPS instruments</i></p> <p><i>Elevations are measured by hand held GPS and are sufficiently accurate for this stage of exploration.</i></p> <p><i>Stream sediment sample sites are measured by hand held Garmin 65 multiband instruments with 3 metre accuracy in open conditions.</i></p>
<p><i>Data spacing and distribution</i></p>	<p><i>Data spacing for reporting of Exploration Results.</i></p> <p><i>Whether the data spacing, and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i></p> <p><i>Whether sample compositing has been applied.</i></p>	<p><i>Stream sediment sampling was carried out at approximately 1 km intervals on drainages over 500 metres long.</i></p> <p><i>No sample compositing was undertaken.</i></p> <p><i>Samples are not used for estimation of grade.</i></p>
<p><i>Orientation of data in relation to geological structure</i></p>	<p><i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i></p> <p><i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i></p>	<p><i>No drilling undertaken.</i></p> <p><i>Many streams are controlled by regional structure which may also control mineralisation and may bias results to some degree. The close spacing of samples is thought to have removed much of the potential bias that may be present.</i></p>
<p><i>Sample security</i></p>	<p><i>The measures taken to ensure sample security.</i></p>	<p><i>Stream sediment samples are taken to the GMN laboratory daily and kept under secure conditions.</i></p> <p><i>Prepared samples are securely packed and dispatched to ALS by reliable couriers or hand delivered by GMN personnel.</i></p>
<p><i>Audits or reviews</i></p>	<p><i>The results of any audits or reviews of sampling techniques and data.</i></p>	<p><i>Reviews of stream sediments sampling are undertaken in the field at irregular intervals by senior staff and new employees are trained by</i></p>

Criteria	JORC Code Explanation	Commentary
		<i>field crew in sampling techniques prior to working independently.</i>

Section 2 - Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	ORC Code Explanation	Commentary														
<i>Mineral tenement and land tenure status</i>	<p><i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i></p> <p><i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i></p>	<p><i>GMN holds 7 granted tenements in the Salinas II Project. GMN has 75% ownership of the 7 granted tenements.</i></p> <table><tr><td>Bananal Valley (Água Boa)</td><td>831703/2022</td></tr><tr><td>Bananal Valley</td><td>831702/2022</td></tr><tr><td>Bananal Valley</td><td>831700/2022</td></tr><tr><td>Pedra Grande (Almenara)</td><td>831704/2022</td></tr><tr><td>Salinas</td><td>831697/2022</td></tr><tr><td>Salinas</td><td>831696/2022</td></tr><tr><td>Salinas</td><td>831698/2022</td></tr></table> <p><i>There are no known serious impediments to obtaining a licence to operate in the area.</i></p> <p><i>Access permissions from local landholders is required. No Native title , historical sites, wilderness or national park and environmental settings are known to be present in the tenements.</i></p>	Bananal Valley (Água Boa)	831703/2022	Bananal Valley	831702/2022	Bananal Valley	831700/2022	Pedra Grande (Almenara)	831704/2022	Salinas	831697/2022	Salinas	831696/2022	Salinas	831698/2022
Bananal Valley (Água Boa)	831703/2022															
Bananal Valley	831702/2022															
Bananal Valley	831700/2022															
Pedra Grande (Almenara)	831704/2022															
Salinas	831697/2022															
Salinas	831696/2022															
Salinas	831698/2022															
<i>Exploration done by other parties</i>	<p><i>Acknowledgment and appraisal of exploration by other parties.</i></p>	<p><i>No known exploration for lithium has been carried out on the exploration licence areas. Exploitation of occurrences of other mineral resources is known over the licence areas, mainly artisanal mining for tourmaline, quartz, beryl and tin in pegmatites and granite, sillimanite and aggregate. Clay mining, including illegal operations have also been carried out.</i></p>														
<i>Geology</i>	<p><i>Deposit type, geological setting and style of mineralisation.</i></p>	<p><i>Principal deposit type sought is lithium bearing pegmatites.</i></p> <p><i>LCT pegmatites and the occurrences of gem tourmaline and tin are indicative of evolved pegmatites.</i></p>														

Criteria	ORC Code Explanation	Commentary
<i>Drill hole Information</i>	<p><i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i></p> <ul style="list-style-type: none"> <i>o easting and northing of the drill hole collar</i> <i>o elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i> <i>o dip and azimuth of the hole</i> <i>o down hole length and interception depth</i> <i>o hole length.</i> <p><i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i></p>	<p><i>No drilling undertaken</i></p> <p><i>Locations of all stream sediment samples and of anomalies are shown on maps in this report.</i></p> <p><i>Elevations of all stream sediment samples are recorded together with easting and northing.</i></p>
<i>Data aggregation methods</i>	<p><i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i></p> <p><i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i></p> <p><i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i></p>	<p><i>No drilling undertaken, no cut off grades applied</i></p> <p><i>.</i></p> <p><i>All sample results were included in the interpretations of the stream sediment data and no cut off was applied to results.</i></p> <p><i>No sample aggregation was undertaken</i></p> <p><i>No metal equivalent values reported</i></p>
<i>Relationship between mineralisation widths and</i>	<p><i>These relationships are particularly important in the reporting of Exploration Results.</i></p> <p><i>If the geometry of the mineralisation with respect to the drill hole angle is</i></p>	<p><i>No drilling undertaken</i></p> <p><i>No intersection made to report</i></p> <p><i>Geometry of mineralisation if present is unknown</i></p>

Criteria	ORC Code Explanation	Commentary																																
<i>intercept lengths</i>	<i>known, its nature should be reported.</i> <i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</i>																																	
<i>Diagrams</i>	<i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i>	<i>No drilling undertaken; plan views of tenement surface geochemical sample locations are provided</i> <i>Sectional views are not relevant to surface sample interpretation.</i>																																
<i>Balanced reporting</i>	<i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i>	<i>The range of anomalous results in ppm is given for the principal elements .</i> <table><tr><th>Element</th><th>Highest</th><th>Lowest</th><th>Median</th></tr><tr><td>Li ppm</td><td>672</td><td>16.4</td><td>149</td></tr><tr><td>Be ppm</td><td>14.95</td><td>2.11</td><td>8.12</td></tr><tr><td>Cs ppm</td><td>28.5</td><td>3.24</td><td>18.6</td></tr><tr><td>Nb ppm</td><td>41.8</td><td>16.9</td><td>27.7</td></tr><tr><td>Sn ppm</td><td>21.4</td><td>8.92</td><td>14</td></tr><tr><td>Rb ppm</td><td>434</td><td>20.5</td><td>289</td></tr><tr><td>Ta ppm</td><td>4.31</td><td>1.56</td><td>2.56</td></tr></table>	Element	Highest	Lowest	Median	Li ppm	672	16.4	149	Be ppm	14.95	2.11	8.12	Cs ppm	28.5	3.24	18.6	Nb ppm	41.8	16.9	27.7	Sn ppm	21.4	8.92	14	Rb ppm	434	20.5	289	Ta ppm	4.31	1.56	2.56
Element	Highest	Lowest	Median																															
Li ppm	672	16.4	149																															
Be ppm	14.95	2.11	8.12																															
Cs ppm	28.5	3.24	18.6																															
Nb ppm	41.8	16.9	27.7																															
Sn ppm	21.4	8.92	14																															
Rb ppm	434	20.5	289																															
Ta ppm	4.31	1.56	2.56																															
<i>Other substantive exploration data</i>	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i>	<i>Artisanal mining for tourmaline, quartz, beryl, tin and topaz in pegmatites and marble, talc, asbestos, clay, quartzite, granite, sillimanite and aggregate has been carried out in and adjacent to the GMN tenements.</i> <i>Results from limited traversing are included on maps</i>																																
<i>Further work</i>	<i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i> <i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this</i>	<i>Additional work is continuing regional stream sediment sampling and grid soil sampling and mapping of outcrop to define areas for resource drilling.</i> <i>Diagrams show target areas based on current results which will probably be subject to change as further results are obtained.</i>																																

Criteria	ORC Code Explanation	Commentary
	<i>information is not commercially sensitive.</i>	<i>Interpretation of the major controls of anomalous responses are indicated on plans of the regional location of the tenements.</i>