



21 January 2021

Final Dataset for the Narndee VTEM™ Max Survey Released - JORC Table

In relation to the announcement lodged with ASX on 20 January 2021 titled “*Final Dataset for the Narndee VTEM™ Max Survey Released*”, the Company attaches a revised announcement which includes the JORC table and Competent Person Statement as required by ASX Listing Rule 5.7.

This Announcement has been approved for release by the Board of Aldoro Resources Ltd

21 January 2021

FINAL DATASET FOR THE NARNDÉE VTEM™ MAX SURVEY RELEASED

Aldoro Resources Limited (**Aldoro, The Company**) (ASX:ARN) is pleased to advise that the final data processing and imagery refinement of the helicopter-borne **VTEM™ Max** survey conducted over the Narndee Project, has been completed by UTS Geophysics Pty Ltd (subsidiary of Geotech Airborne Pty Ltd Australia).

During 9th-21st November 2020, Geotech Airborne Pty Ltd Australia and UTS Geophysics Pty Ltd, carried out a helicopter-borne electromagnetic (VTEM) geophysical survey over the Narndee Project area in Western Australia, utilising their **VTEM™ Max** system. The area covered by the survey comprised 155 km² area of the southern area of the greater Narndee Igneous Complex (NIC).

Initial processing of 1035 line/km of data (@ 150 m line-spacing) revealed the location of 16 major targets, comprising 7 type-1 bedrock conductors associated with magnetic features, and 9 deeper anomalies, located in the core area of the NIC (**ASX announcement, 24 November 2020**). The Company noted that many of the anomalies detected corresponded well with areas of historic surface geochemical results, with the rest untested by historic work (Figure 1).




Figure 1. VTEM Max targets shown with historic surface geochemistry around the Milgoon Peak area of the NIC.

The Company presented only the preliminary images of the survey data (**ASX announcement, 24 November 2020**), whilst awaiting final processing of data and refinement of geophysical imagery. The compilation of Resistivity Depth Images (RDI) by UTS, both in 3D format (Figure 2) and resistivity depth slices (Figure 3), will now enable The Company to undertake a more detailed interpretation of the data, which will help dictate future work programs.

3d views of apparent resistivity depth slices:




Figure 2. 3D view of stacked horizontal depth slices. (UTS Geophysics Pty Ltd.)

Apparent Resistivity Depth Slices plans:




Figure 3. Apparent resistivity depth slice plan views. (UTS Geophysics Pty Ltd.).

Whilst the formal interpretation of these VTEM data is yet to be fully completed by Southern Geoscience Consultants (SGC), the refined data and imagery released to date support the presence of conductive zones at depths from 50-300m across the entire property. These zones have the appearance of sub-horizontal layers and lense-like bodies reminiscent of a layered, magnetic ultramafic intrusion.

Follow-up analyses in the form of EM anomaly picking and magnetic vector inversions to enhance the spatial correlation between the bedrock conductors and related magnetic bodies are being considered for the major anomalies of interest. In addition, The Company is considering applying a range of multi-disciplinary ground-based geophysical applications, such as gravity, EM, magnetics, as well as supplementary soil geochemistry programs, to further delineate priority targets for potential drill-testing. To this end, The Company announced a **High-Power Fixed Loop (FLTEM)** ground EM survey scheduled to start mid-late January (**ASX Announcement 21 December 2020**). The FLTEM survey will be carried out by HPEM Geophysical Services, who will incorporate those targets that have been interpreted and selected as high priority by SGC (Figure 4).




Figure 4. The Narndee Project. At right, the recently refined imagery had enabled high priority targets (yellow and red circles) to be identified for the follow-up FLTEM survey scheduled in January. At left, showing detail of inset high priority targets and proposed FLTEM ground survey lines (blue).

The Narndee Project will be a significant focus for Aldoro in 2021, and The Company looks forward to updating its shareholders on the progress of these ongoing exploration activities in due course.

About Aldoro Resources

Aldoro Resources Ltd is an ASX-listed (ASX:ARN) mineral exploration and development company. Aldoro has a collection of gold and nickel focused advanced exploration projects all located in Western Australia. The 'Company's flagship project is the Narndee Igneous Complex, highly prospective for Ni-Cu-PGE mineralisation. Aldoro is also currently exploring the Penny South Gold Project, which is contiguous to Ramelius Resources (ASX:RMS) Penny West Project in the Youanmi Gold Mining District, as well as Unaly Hill South (Au) and Kiabye Well (Au). The 'Company's other projects include the Cathedrals Belt Nickel Project, with a significant tenement holding surround St George 'Mining's (ASX:SGQ) Mt Alexander Project, the Leinster Nickel Project (Ni), Windimurra Igneous Complex (Ni-Cu-PGE, Li) and Ryans Find (Au, Ni-Cu-PGE).

Competent Persons Statement

The information in this announcement that relates to Exploration Results and other technical information complies with the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves (JORC Code) and has been compiled and assessed under the supervision of Luke Marshall, a geological consultant to Aldoro Resources Ltd. Mr Marshall is a Member of the Australasian Institute of Geoscientists and has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the JORC Code. Mr Marshall consents to the inclusion in this announcement of the matters based on his information in the form and context in which it appears.

Disclaimer

Some of the statements appearing in this announcement may be forward-looking statements. You should be aware that such statements are only predictions and are subject to inherent risks and uncertainties. Those risks and uncertainties include factors and risks specific to the industries in which Aldoro operates and proposes to operate as well as general economic conditions, prevailing exchange rates and interest rates and conditions in the financial markets, among other things. Actual events or results may differ materially from the events or results expressed or implied in any forward-looking statement. No forward-looking statement is a guarantee or representation as to future performance or any other future matters, which will be influenced by several factors and subject to various uncertainties and contingencies, many of which will be outside 'Aldoro's control.

Aldoro does not undertake any obligation to update publicly or release any revisions to these forward-looking statements to reflect events or circumstances after today's date or to reflect the occurrence of unanticipated events. No representation or warranty, express or implied, is made as to the fairness, accuracy, completeness or correctness of the information, opinions or conclusions contained in this announcement.

To the maximum extent permitted by law, none of Aldoro, its Directors, employees, advisors, or agents, nor any other person, accepts any liability for any loss arising from the use of the information contained in this announcement. You are cautioned not to place undue reliance on any forward-looking statement. The forward-looking statements in this announcement reflect views held only as at the date of this announcement. This announcement is not an offer, invitation, or recommendation to subscribe for, or purchase securities by Aldoro. Nor does this announcement constitute investment or financial product advice (nor tax, accounting, or legal advice) and is not intended to be used for the basis of making an investment decision. Investors should obtain their own advice before making any investment decision.

This announcement has been approved for release by the Board of Aldoro Resources Ltd

Narndee

JORC Code, 2012 Edition - Table 1

Section 1: Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report.a In cases where 'industry 'standard' work has been done this would be relatively simple (eg' reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire 'assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	<ul style="list-style-type: none"> Historical drill and surface sampling over the project area in the last 50 years listed in ASX announcement 29 October 2020 VTEM™ Max airborne EM survey totalling 1004 line km, completed at 150m line spacing, with lines orientation E-W over the basal predominantly ultramafic portion of the Narndee Igneous Complex by UTS Geophysics/Geotech VTEM™ Max configuration: Flying height: 83m EM sensor height: 35m Magnetic sensor height: 73m Transmitter loop diameter: 35m Transmitter plus width: 7ms Peak dipole moment: 700,000 NIA Base frequency: 25Hz Receiver: Z, X coils VTEM surveys are an industry standard practise in testing for bedrock conductors representing potential mineralised massive sulphide mineralised bodies
Drilling techniques	<ul style="list-style-type: none"> Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc). 	<ul style="list-style-type: none"> Not relevant for VTEM™ Max survey
Drill sample recovery	<ul style="list-style-type: none"> Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	<ul style="list-style-type: none"> Not relevant for VTEM™ Max survey
Logging	<ul style="list-style-type: none"> Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	<ul style="list-style-type: none"> Not relevant for VTEM™ Max survey

Criteria	JORC Code explanation	Commentary
Sub-sampling techniques and sample preparation	<ul style="list-style-type: none"> • <i>If core, whether cut or sawn and whether quarter, half or all core taken.</i> • <i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i> • <i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i> • <i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i> • <i>Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second-half sampling.</i> • <i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i> 	<ul style="list-style-type: none"> • Not relevant for VTEM™ Max survey
Quality of assay data and laboratory tests	<ul style="list-style-type: none"> • <i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i> • <i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i> • <i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</i> 	<ul style="list-style-type: none"> • VTEM™ Max system calibrated before commencement of the survey • All digital data is inspected daily by the Geotech site crew and the 'Company's consultant geophysicist • The Company receives a daily report on production and of any equipment issues • The data is reviewed by the 'sCompany's consultant geophysicist and any lines are re- flown if necessary • The data presented here has undergone a high degree of processing/levelling by Geotech. The Company' 's consultant geophysicist has completed a QA/QC of these data and has considered them suitable for public release. 'The refined data and imagery is of sufficient quality and detail to allow the Company' 's Consulting geophysicist to plan a follow-up FLTEM ground survey over selected high priority targets, initially identified from the previous VTEM airborne survey. •
Verification of sampling and assaying	<ul style="list-style-type: none"> • <i>The verification of significant intersections by either independent or alternative company personnel.</i> • <i>The use of twinned holes.</i> • <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> • <i>Discuss any adjustment to assay data.</i> 	<ul style="list-style-type: none"> • Daily data independently checked by 'Company's consultant geophysicist
Location of data points	<ul style="list-style-type: none"> • <i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i> • <i>Specification of the grid system used.</i> • <i>Quality and adequacy of topographic control.</i> 	<ul style="list-style-type: none"> • Real-time GPS navigation system utilising Novatel WAAS enabled GPS receiver providing in-flight accuracy of 3 metres, and up to 1.5m depending on satellites available. A preliminary flight path map is plotted daily and checked against survey specifications • Coordinates presented are in WGS84 UTM Zone 50S

Data spacing and distribution	<ul style="list-style-type: none"> • Data spacing for reporting of Exploration Results. • Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. • Whether sample compositing has been applied. 	<ul style="list-style-type: none"> • Spacing between flight lines was approximately 150m, with readings taken approximately 2 to 4m along line
Criteria	JORC Code explanation	Commentary
Orientation of data in relation to geological structure	<ul style="list-style-type: none"> • Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. • If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	<ul style="list-style-type: none"> • The flight path is approximately perpendicular to any known strike direction of geological formations and is sufficient to locate discrete conductive anomalies
Sample security	<ul style="list-style-type: none"> • The measures taken to ensure sample security. 	<ul style="list-style-type: none"> • All data acquired by Geotech reported to the 'Company's consultant geophysicist
Audits or reviews	<ul style="list-style-type: none"> • The results of any audits or reviews of sampling techniques and data. 	<ul style="list-style-type: none"> • The data was independently verified by the 'Company's consultant geophysicist Russell Mortimer of Southern Geoscience Consultants

Section 2: Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<ul style="list-style-type: none"> • Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. • The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	<ul style="list-style-type: none"> • Tenements E59/2223, E59/2238 and E59/2258 • Held by Gunex Pty Ltd a 100% owned subsidiary of Altium Metals Pty Ltd which in turn is a 100% owned subsidiary of Aldoro Resources Limited • GSR to original tenement holder • Tenement is in good standing, no native title interests and no known historical or environmentally sensitive areas with the tenement areas
Exploration done by other parties	<ul style="list-style-type: none"> • Acknowledgment and appraisal of exploration by other parties. 	<p>Previous relevant exploration was undertaken by:</p> <ul style="list-style-type: none"> Westralian Nickel-INCO (1960s-70s) BHP-Hunter Resources (1985-90) Wedgetail Resources (2001) Apex Minerals-Mark Creasy (2001-06) Falconbridge-Apex-Mark Creasy (2002-03) Maximus Resources (2005-14)

Geology	<ul style="list-style-type: none"> • <i>Deposit type, geological setting and style of mineralisation.</i> 	<p>The Narndee Project is located within the Youanmi Terrane of the Yilgarn Craton, close to a major structural boundary between the Murchison and Southern Cross Domains. Regional geology is dominated by Archaean granite-greenstone terranes (greenstone 2.8-3.0 billion years, granites 2.6-2.95 billion years) and the Windimurra Group of layered mafic intrusions (2.847 billion +/- 71 million years). These bodies represent the largest layered mafic-ultramafic intrusive complex in Australia. The Narndee Igneous Complex forms the primary component of the Boodanoo Suite and is divided into three broad units of stratigraphy: Ultramafic Zone, Lower Zone and Main Zone. Historic exploration has generally focused on stratiform PGE-reef mineralisation whereas 'Aldoro's focus will be on massive magmatic nickel sulphide deposits</p>
Criteria	JORC Code explanation	Commentary
Drill hole information	<ul style="list-style-type: none"> • <i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> <ul style="list-style-type: none"> • <i>easting and northing of the drill hole collar</i> • <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i> • <i>dip and azimuth of the hole</i> • <i>down hole length and interception depth hole length.</i> • <i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i> 	<ul style="list-style-type: none"> • A listing of the historic Maximus Resources drill hole information material to the understanding of the historic exploration results, along with other historic drilling is provided in the body and appendices of ASX announcement 29 October 2020 • Historic drilling by previous explorers used best practice for that time • The use of any data is recommended for indicative purposes only in terms of potential Ni-Cu-PGE mineralisation and for developing exploration targets.
Data aggregation methods	<ul style="list-style-type: none"> • <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i> • <i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i> • <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i> 	<ul style="list-style-type: none"> • Raw composited sample intervals have been reported and aggregated where appropriate • No metal equivalent values have been quoted
Relationship between mineralisation widths and intercept lengths	<ul style="list-style-type: none"> • <i>These relationships are particularly important in the reporting of Exploration Results.</i> • <i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i> • <i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not 'known').</i> 	<ul style="list-style-type: none"> • All results referenced are based on down-hole lengths and may not reflect true width of mineralisation or thickness of host lithologies which is unknown

Diagrams	<ul style="list-style-type: none"> • <i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i> 	<ul style="list-style-type: none"> • Appropriate maps and tabulations are presented in the body of the announcement
Balanced reporting	<ul style="list-style-type: none"> • <i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i> 	<ul style="list-style-type: none"> • Only selected drill intersections have been mentioned and due to the nature of the drilling and lack of adequate records and survey control, they are considered indicative only and not material
Other substantive exploration data	<ul style="list-style-type: none"> • <i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i> 	<ul style="list-style-type: none"> • Falconbridge completed an airborne magnetic and radiometric survey over the NIC using a fixed wing aircraft and Scintrex Cesium Vapour CS-2 Magnetometer and Exploranium GR 820 Spectrometer. Lines were flown E-W at 100m spacing and 35m sensor height. This survey was reprocessed by Southern Geoscience and forms the base image for a number of figures in this announcement
Criteria	JORC Code explanation	Commentary
Further work	<ul style="list-style-type: none"> • <i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i> • <i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i> 	<ul style="list-style-type: none"> • Targets generated from the VTEM Max survey will be followed up with ground geophysical surveys such as gravity, magnetics and MLEM, and eventually followed by drill testing • Exploration is at an early stage, and future work will depend on results